

Package ‘DBI’

May 2, 2018

Version 1.0.0

Date 2018-05-02

Title R Database Interface

Description A database interface definition for communication between R and relational database management systems. All classes in this package are virtual and need to be extended by the various R/DBMS implementations.

Depends R (>= 3.0.0),
methods

Suggests blob,
covr,
hms,
knitr,
magrittr,
rprojroot,
rmarkdown,
RSQLite (>= 1.1-2),
testthat,
xml2

Encoding UTF-8

License LGPL (>= 2)

URL <http://r-dbi.github.io/DBI>

URLNote <https://github.com/r-dbi/DBI>

BugReports <https://github.com/r-dbi/DBI/issues>

Collate 'hidden.R'
'DBObject.R'
'DBDriver.R'
'table.R'
'DBConnection.R'
'ANSI.R'
'DBI-package.R'
'DBResult.R'

'data-types.R'
 'data.R'
 'deprecated.R'
 'interpolate.R'
 'list-pairs.R'
 'quote.R'
 'rd.R'
 'rownames.R'
 'table-create.R'
 'table-insert.R'
 'transactions.R'

VignetteBuilder knitr

Roxygen list(markdown = TRUE, roclets = c("`collate", "`namespace", "`rd", "`pkgapi::api_roclet"))

RoxygenNote 6.0.1.9000

R topics documented:

DBI-package	3
dbAppendTable	4
dbBind	5
dbCanConnect	8
dbClearResult	9
dbColumnInfo	10
dbConnect	11
dbCreateTable	13
dbDataType	14
dbDisconnect	15
dbDriver	16
dbExecute	18
dbExistsTable	19
dbFetch	20
dbGetException	23
dbGetInfo	23
dbGetQuery	24
dbGetRowCount	26
dbGetRowsAffected	27
dbGetStatement	28
dbHasCompleted	29
DBIConnection-class	30
DBIDriver-class	31
DBIObject-class	31
DBIResult-class	32
dbIsReadOnly	32
dbIsValid	33
dbListConnections	34
dbListFields	35
dbListObjects	36

dbListResults	37
dbListTables	38
dbQuoteIdentifier	39
dbQuoteLiteral	40
dbQuoteString	42
dbReadTable	43
dbRemoveTable	45
dbSendQuery	46
dbSendStatement	48
dbUnquoteIdentifier	50
dbWithTransaction	51
dbWriteTable	53
Id-class	56
make.db.names	56
rownames	58
SQL	59
sqlAppendTable	60
sqlCreateTable	61
sqlData	62
sqlInterpolate	63
transactions	64
Index	66

Description

DBI defines an interface for communication between R and relational database management systems. All classes in this package are virtual and need to be extended by the various R/DBMS implementations (so-called *DBI backends*).

Definition

A DBI backend is an R package which imports the **DBI** and **methods** packages. For better or worse, the names of many existing backends start with ‘R’, e.g., **RSQLite**, **RMySQL**, **RSQLServer**; it is up to the backend author to adopt this convention or not.

DBI classes and methods

A backend defines three classes, which are subclasses of **DBIDriver**, **DBIConnection**, and **DBIResult**. The backend provides implementation for all methods of these base classes that are defined but not implemented by DBI. All methods defined in **DBI** are reexported (so that the package can be used without having to attach **DBI**), and have an ellipsis . . . in their formals for extensibility.

Construction of the DBIDriver object

The backend must support creation of an instance of its `DBIDriver` subclass with a *constructor function*. By default, its name is the package name without the leading ‘R’ (if it exists), e.g., `SQLite` for the **RSQLite** package. However, backend authors may choose a different name. The constructor must be exported, and it must be a function that is callable without arguments. DBI recommends to define a constructor with an empty argument list.

Author(s)

Maintainer: Kirill Müller <krlmlr+r@mailbox.org> (0000-0002-1416-3412)

Authors:

- R Special Interest Group on Databases (R-SIG-DB)
- Hadley Wickham

Other contributors:

- R Consortium [funder]

See Also

Important generics: `dbConnect()`, `dbGetQuery()`, `dbReadTable()`, `dbWriteTable()`, `dbDisconnect()`

Formal specification (currently work in progress and incomplete): `vignette("spec", package = "DBI")`

Examples

```
RSQLite::SQLite()
```

<code>dbAppendTable</code>	<i>Insert rows into a table</i>
----------------------------	---------------------------------

Description

The `dbAppendTable()` method assumes that the table has been created beforehand, e.g. with `dbCreateTable()`. The default implementation calls `sqlAppendTableTemplate()` and then `dbExecute()` with the `param` argument. Backends compliant to ANSI SQL 99 which use `?` as a placeholder for prepared queries don’t need to override it. Backends with a different SQL syntax which use `?` as a placeholder for prepared queries can override `sqlAppendTable()`. Other backends (with different placeholders or with entirely different ways to create tables) need to override the `dbAppendTable()` method.

Usage

```
dbAppendTable(conn, name, value, ..., row.names = NULL)
```

Arguments

conn	A DBIConnection object, as returned by dbConnect() .
name	Name of the table, escaped with dbQuoteIdentifier() .
value	A data frame of values. The column names must be consistent with those in the target table in the database.
...	Other arguments used by individual methods.
row.names	Must be NULL.

Details

The `row.names` argument is not supported by this method. Process the values with [sqlRownamesToColumn\(\)](#) before calling this method.

See Also

Other [DBIConnection](#) generics: [DBIConnection-class](#), [dbCreateTable](#), [dbDataType](#), [dbDisconnect](#), [dbExecute](#), [dbExistsTable](#), [dbGetException](#), [dbGetInfo](#), [dbGetQuery](#), [dbIsReadOnly](#), [dbIsValid](#), [dbListFields](#), [dbListObjects](#), [dbListResults](#), [dbListTables](#), [dbReadTable](#), [dbRemoveTable](#), [dbSendQuery](#), [dbSendStatement](#), [dbWriteTable](#)

Examples

```
con <- dbConnect(RSQLite::SQLite(), ":memory:")
dbCreateTable(con, "iris", iris)
dbAppendTable(con, "iris", iris)
dbReadTable(con, "iris")
dbDisconnect(con)
```

dbBind

Bind values to a parameterized/prepared statement

Description

For parametrized or prepared statements, the [dbSendQuery\(\)](#) and [dbSendStatement\(\)](#) functions can be called with statements that contain placeholders for values. The [dbBind\(\)](#) function binds these placeholders to actual values, and is intended to be called on the result set before calling [dbFetch\(\)](#) or [dbGetRowsAffected\(\)](#).

Usage

```
dbBind(res, params, ...)
```

Arguments

res	An object inheriting from DBIResult .
params	A list of bindings, named or unnamed.
...	Other arguments passed on to methods.

Details

DBI supports parametrized (or prepared) queries and statements via the `dbBind()` generic. Parametrized queries are different from normal queries in that they allow an arbitrary number of placeholders, which are later substituted by actual values. Parametrized queries (and statements) serve two purposes:

- The same query can be executed more than once with different values. The DBMS may cache intermediate information for the query, such as the execution plan, and execute it faster.
- Separation of query syntax and parameters protects against SQL injection.

The placeholder format is currently not specified by **DBI**; in the future, a uniform placeholder syntax may be supported. Consult the backend documentation for the supported formats. For automated testing, backend authors specify the placeholder syntax with the `placeholder_pattern` tweak. Known examples are:

- `?` (positional matching in order of appearance) in **RMySQL** and **RSQLite**
- `$1` (positional matching by index) in **RPostgres** and **RSQLite**
- `:name` and `$name` (named matching) in **RSQLite**

Value

`dbBind()` returns the result set, invisibly, for queries issued by `dbSendQuery()` and also for data manipulation statements issued by `dbSendStatement()`. Calling `dbBind()` for a query without parameters raises an error. Binding too many or not enough values, or parameters with wrong names or unequal length, also raises an error. If the placeholders in the query are named, all parameter values must have names (which must not be empty or `NA`), and vice versa, otherwise an error is raised. The behavior for mixing placeholders of different types (in particular mixing positional and named placeholders) is not specified.

Calling `dbBind()` on a result set already cleared by `dbClearResult()` also raises an error.

Specification

DBI clients execute parametrized statements as follows:

1. Call `dbSendQuery()` or `dbSendStatement()` with a query or statement that contains placeholders, store the returned **DBIResult** object in a variable. Mixing placeholders (in particular, named and unnamed ones) is not recommended. It is good practice to register a call to `dbClearResult()` via `on.exit()` right after calling `dbSendQuery()` or `dbSendStatement()` (see the last enumeration item). Until `dbBind()` has been called, the returned result set object has the following behavior:
 - `dbFetch()` raises an error (for `dbSendQuery()`)
 - `dbGetRowCount()` returns zero (for `dbSendQuery()`)
 - `dbGetRowsAffected()` returns an integer `NA` (for `dbSendStatement()`)
 - `dbIsValid()` returns `TRUE`
 - `dbHasCompleted()` returns `FALSE`

2. Construct a list with parameters that specify actual values for the placeholders. The list must be named or unnamed, depending on the kind of placeholders used. Named values are matched to named parameters, unnamed values are matched by position in the list of parameters. All elements in this list must have the same lengths and contain values supported by the backend; a `data.frame` is internally stored as such a list. The parameter list is passed to a call to `dbBind()` on the `DBIResult` object.
3. Retrieve the data or the number of affected rows from the `DBIResult` object.
 - For queries issued by `dbSendQuery()`, call `dbFetch()`.
 - For statements issued by `dbSendStatements()`, call `dbGetRowsAffected()`. (Execution begins immediately after the `dbBind()` call, the statement is processed entirely before the function returns.)
4. Repeat 2. and 3. as necessary.
5. Close the result set via `dbClearResult()`.

The elements of the `params` argument do not need to be scalars, vectors of arbitrary length (including length 0) are supported. For queries, calling `dbFetch()` binding such parameters returns concatenated results, equivalent to binding and fetching for each set of values and connecting via `rbind()`. For data manipulation statements, `dbGetRowsAffected()` returns the total number of rows affected if binding non-scalar parameters. `dbBind()` also accepts repeated calls on the same result set for both queries and data manipulation statements, even if no results are fetched between calls to `dbBind()`.

If the placeholders in the query are named, their order in the `params` argument is not important.

At least the following data types are accepted on input (including `NA`):

- `integer`
- `numeric`
- `logical` for Boolean values
- `character`
- `factor` (bound as character, with warning)
- `Date`
- `POSIXct` timestamps
- `POSIXlt` timestamps
- lists of `raw` for blobs (with `NULL` entries for SQL `NULL` values)
- objects of type `blob::blob`

See Also

Other `DBIResult` generics: `DBIResult-class`, `dbClearResult`, `dbColumnInfo`, `dbFetch`, `dbGetInfo`, `dbGetRowCount`, `dbGetRowsAffected`, `dbGetStatement`, `dbHasCompleted`, `dbIsReadOnly`, `dbIsValid`, `dbQuoteIdentifier`, `dbQuoteLiteral`, `dbQuoteString`, `dbUnquoteIdentifier`

Examples

```
con <- dbConnect(RSQLite::SQLite(), ":memory:")

dbWriteTable(con, "iris", iris)

# Using the same query for different values
iris_result <- dbSendQuery(con, "SELECT * FROM iris WHERE [Petal.Width] > ?")
dbBind(iris_result, list(2.3))
dbFetch(iris_result)
dbBind(iris_result, list(3))
dbFetch(iris_result)
dbClearResult(iris_result)

# Executing the same statement with different values at once
iris_result <- dbSendStatement(con, "DELETE FROM iris WHERE [Species] = $species")
dbBind(iris_result, list(species = c("setosa", "versicolor", "unknown")))
dbGetRowsAffected(iris_result)
dbClearResult(iris_result)

nrow(dbReadTable(con, "iris"))

dbDisconnect(con)
```

dbCanConnect

Check if a connection to a DBMS can be established

Description

Like `dbConnect()`, but only checks validity without actually returning a connection object. The default implementation opens a connection and disconnects on success, but individual backends might implement a lighter-weight check.

Usage

```
dbCanConnect(drv, ...)
```

Arguments

drv	an object that inherits from <code>DBIDriver</code> , or an existing <code>DBIConnection</code> object (in order to clone an existing connection).
...	authentication arguments needed by the DBMS instance; these typically include user, password, host, port, dbname, etc. For details see the appropriate <code>DBIDriver</code> .

Value

A scalar logical. If FALSE, the "reason" attribute indicates a reason for failure.

See Also

Other DBIDriver generics: [DBIDriver-class](#), [dbConnect](#), [dbDataType](#), [dbDriver](#), [dbGetInfo](#), [dbIsReadOnly](#), [dbIsValid](#), [dbListConnections](#)

Examples

```
# SQLite only needs a path to the database. (Here, ":memory:" is a special
# path that creates an in-memory database.) Other database drivers
# will require more details (like user, password, host, port, etc.)
dbCanConnect(RSQLite::SQLite(), ":memory:")
```

dbClearResult	<i>Clear a result set</i>
---------------	---------------------------

Description

Frees all resources (local and remote) associated with a result set. In some cases (e.g., very large result sets) this can be a critical step to avoid exhausting resources (memory, file descriptors, etc.)

Usage

```
dbClearResult(res, ...)
```

Arguments

res	An object inheriting from DBIResult .
...	Other arguments passed on to methods.

Value

dbClearResult() returns TRUE, invisibly, for result sets obtained from both dbSendQuery() and dbSendStatement(). An attempt to close an already closed result set issues a warning in both cases.

Specification

dbClearResult() frees all resources associated with retrieving the result of a query or update operation. The DBI backend can expect a call to dbClearResult() for each [dbSendQuery\(\)](#) or [dbSendStatement\(\)](#) call.

See Also

Other DBIResult generics: [DBIResult-class](#), [dbBind](#), [dbColumnInfo](#), [dbFetch](#), [dbGetInfo](#), [dbGetRowCount](#), [dbGetRowsAffected](#), [dbGetStatement](#), [dbHasCompleted](#), [dbIsReadOnly](#), [dbIsValid](#), [dbQuoteIdentifier](#), [dbQuoteLiteral](#), [dbQuoteString](#), [dbUnquoteIdentifier](#)

Examples

```

con <- dbConnect(RSQLite::SQLite(), ":memory:")

rs <- dbSendQuery(con, "SELECT 1")
print(dbFetch(rs))

dbClearResult(rs)
dbDisconnect(con)

```

dbColumnInfo	<i>Information about result types</i>
--------------	---------------------------------------

Description

Produces a data.frame that describes the output of a query. The data.frame should have as many rows as there are output fields in the result set, and each column in the data.frame describes an aspect of the result set field (field name, type, etc.)

Usage

```
dbColumnInfo(res, ...)
```

Arguments

res	An object inheriting from DBIResult .
...	Other arguments passed on to methods.

Value

dbColumnInfo() returns a data frame with at least two columns "name" and "type" (in that order) (and optional columns that start with a dot). The "name" and "type" columns contain the names and types of the R columns of the data frame that is returned from [dbFetch\(\)](#). The "type" column is of type character and only for information. Do not compute on the "type" column, instead use [dbFetch\(res, n = 0\)](#) to create a zero-row data frame initialized with the correct data types.

An attempt to query columns for a closed result set raises an error.

Specification

A column named row_names is treated like any other column.

The column names are always consistent with the data returned by [dbFetch\(\)](#). If the query returns unnamed columns, unique non-empty and non-NA names are assigned. In the case of a duplicate column name, the first occurrence retains the original name, and unique names are assigned for the other occurrences. Column names that correspond to SQL or R keywords are left unchanged.

See Also

Other DBIResult generics: [DBIResult-class](#), [dbBind](#), [dbClearResult](#), [dbFetch](#), [dbGetInfo](#), [dbGetRowCount](#), [dbGetRowsAffected](#), [dbGetStatement](#), [dbHasCompleted](#), [dbIsReadOnly](#), [dbIsValid](#), [dbQuoteIdentifier](#), [dbQuoteLiteral](#), [dbQuoteString](#), [dbUnquoteIdentifier](#)

Examples

```
con <- dbConnect(RSQLite::SQLite(), ":memory:")

rs <- dbSendQuery(con, "SELECT 1 AS a, 2 AS b")
dbColumnInfo(rs)
dbFetch(rs)

dbClearResult(rs)
dbDisconnect(con)
```

dbConnect

Create a connection to a DBMS

Description

Connect to a DBMS going through the appropriate authentication procedure. Some implementations may allow you to have multiple connections open, so you may invoke this function repeatedly assigning its output to different objects. The authentication mechanism is left unspecified, so check the documentation of individual drivers for details. Use [dbCanConnect\(\)](#) to check if a connection can be established.

Usage

```
dbConnect(drv, ...)
```

Arguments

drv	an object that inherits from DBIDriver , or an existing DBIConnection object (in order to clone an existing connection).
...	authentication arguments needed by the DBMS instance; these typically include user, password, host, port, dbname, etc. For details see the appropriate DBIDriver .

Value

`dbConnect()` returns an S4 object that inherits from [DBIConnection](#). This object is used to communicate with the database engine.

A [format\(\)](#) method is defined for the connection object. It returns a string that consists of a single line of text.

Specification

DBI recommends using the following argument names for authentication parameters, with NULL default:

- `user` for the user name (default: current user)
- `password` for the password
- `host` for the host name (default: local connection)
- `port` for the port number (default: local connection)
- `dbname` for the name of the database on the host, or the database file name

The defaults should provide reasonable behavior, in particular a local connection for `host = NULL`. For some DBMS (e.g., PostgreSQL), this is different to a TCP/IP connection to `localhost`.

In addition, DBI supports the `bigint` argument that governs how 64-bit integer data is returned. The following values are supported:

- `"integer"`: always return as integer, silently overflow
- `"numeric"`: always return as numeric, silently round
- `"character"`: always return the decimal representation as character
- `"integer64"`: return as a data type that can be coerced using `as.integer()` (with warning on overflow), `as.numeric()` and `as.character()`

See Also

[dbDisconnect\(\)](#) to disconnect from a database.

Other DBIDriver generics: [DBIDriver-class](#), [dbCanConnect](#), [dbDataType](#), [dbDriver](#), [dbGetInfo](#), [dbIsReadOnly](#), [dbIsValid](#), [dbListConnections](#)

Examples

```
# SQLite only needs a path to the database. (Here, ":memory:" is a special
# path that creates an in-memory database.) Other database drivers
# will require more details (like user, password, host, port, etc.)
con <- dbConnect(RSQLite::SQLite(), ":memory:")
con

dbListTables(con)

dbDisconnect(con)
```

dbCreateTable	<i>Create a table in the database</i>
---------------	---------------------------------------

Description

The default `dbCreateTable()` method calls `sqlCreateTable()` and `dbExecute()`. Backends compliant to ANSI SQL 99 don't need to override it. Backends with a different SQL syntax can override `sqlCreateTable()`, backends with entirely different ways to create tables need to override this method.

Usage

```
dbCreateTable(conn, name, fields, ..., row.names = NULL, temporary = FALSE)
```

Arguments

<code>conn</code>	A DBIConnection object, as returned by <code>dbConnect()</code> .
<code>name</code>	Name of the table, escaped with <code>dbQuoteIdentifier()</code> .
<code>fields</code>	Either a character vector or a data frame. A named character vector: Names are column names, values are types. Names are escaped with <code>dbQuoteIdentifier()</code> . Field types are unescaped. A data frame: field types are generated using <code>dbDataType()</code> .
<code>...</code>	Other arguments used by individual methods.
<code>row.names</code>	Must be NULL.
<code>temporary</code>	If TRUE, will generate a temporary table statement.

Details

The `row.names` argument is not supported by this method. Process the values with `sqlRownamesToColumn()` before calling this method.

The argument order is different from the `sqlCreateTable()` method, the latter will be adapted in a later release of DBI.

See Also

Other `DBIConnection` generics: [DBIConnection-class](#), [dbAppendTable](#), [dbDataType](#), [dbDisconnect](#), [dbExecute](#), [dbExistsTable](#), [dbGetException](#), [dbGetInfo](#), [dbGetQuery](#), [dbIsReadOnly](#), [dbIsValid](#), [dbListFields](#), [dbListObjects](#), [dbListResults](#), [dbListTables](#), [dbReadTable](#), [dbRemoveTable](#), [dbSendQuery](#), [dbSendStatement](#), [dbWriteTable](#)

Examples

```
con <- dbConnect(RSQLite::SQLite(), ":memory:")
dbCreateTable(con, "iris", iris)
dbReadTable(con, "iris")
dbDisconnect(con)
```

 dbDataType

Determine the SQL data type of an object

Description

Returns an SQL string that describes the SQL data type to be used for an object. The default implementation of this generic determines the SQL type of an R object according to the SQL 92 specification, which may serve as a starting point for driver implementations. DBI also provides an implementation for `data.frame` which will return a character vector giving the type for each column in the dataframe.

Usage

```
dbDataType(dbObj, obj, ...)
```

Arguments

<code>dbObj</code>	A object inheriting from DBIDriver or DBIConnection
<code>obj</code>	An R object whose SQL type we want to determine.
<code>...</code>	Other arguments passed on to methods.

Details

The data types supported by databases are different than the data types in R, but the mapping between the primitive types is straightforward:

- Any of the many fixed and varying length character types are mapped to character vectors
- Fixed-precision (non-IEEE) numbers are mapped into either numeric or integer vectors.

Notice that many DBMS do not follow IEEE arithmetic, so there are potential problems with under/overflows and loss of precision.

Value

`dbDataType()` returns the SQL type that corresponds to the `obj` argument as a non-empty character string. For data frames, a character vector with one element per column is returned. An error is raised for invalid values for the `obj` argument such as a NULL value.

Specification

The backend can override the `dbDataType()` generic for its driver class.

This generic expects an arbitrary object as second argument. To query the values returned by the default implementation, run `example(dbDataType, package = "DBI")`. If the backend needs to override this generic, it must accept all basic R data types as its second argument, namely [logical](#), [integer](#), [numeric](#), [character](#), dates (see [Dates](#)), date-time (see [DateTimeClasses](#)), and [difftime](#). If the database supports blobs, this method also must accept lists of [raw](#) vectors, and `blob::blob` objects. As-is objects (i.e., wrapped by `I()`) must be supported and return the same results as their

unwrapped counterparts. The SQL data type for `factor` and `ordered` is the same as for character. The behavior for other object types is not specified.

All data types returned by `dbDataType()` are usable in an SQL statement of the form "CREATE TABLE test (a ...)".

See Also

Other DBIDriver generics: [DBIDriver-class](#), [dbCanConnect](#), [dbConnect](#), [dbDriver](#), [dbGetInfo](#), [dbIsReadOnly](#), [dbIsValid](#), [dbListConnections](#)

Other DBIConnection generics: [DBIConnection-class](#), [dbAppendTable](#), [dbCreateTable](#), [dbDisconnect](#), [dbExecute](#), [dbExistsTable](#), [dbGetException](#), [dbGetInfo](#), [dbGetQuery](#), [dbIsReadOnly](#), [dbIsValid](#), [dbListFields](#), [dbListObjects](#), [dbListResults](#), [dbListTables](#), [dbReadTable](#), [dbRemoveTable](#), [dbSendQuery](#), [dbSendStatement](#), [dbWriteTable](#)

Examples

```
dbDataType(ANSI(), 1:5)
dbDataType(ANSI(), 1)
dbDataType(ANSI(), TRUE)
dbDataType(ANSI(), Sys.Date())
dbDataType(ANSI(), Sys.time())
dbDataType(ANSI(), Sys.time() - as.POSIXct(Sys.Date()))
dbDataType(ANSI(), c("x", "abc"))
dbDataType(ANSI(), list(raw(10), raw(20)))
dbDataType(ANSI(), I(3))
```

```
dbDataType(ANSI(), iris)
```

```
con <- dbConnect(RSQLite::SQLite(), ":memory:")
```

```
dbDataType(con, 1:5)
dbDataType(con, 1)
dbDataType(con, TRUE)
dbDataType(con, Sys.Date())
dbDataType(con, Sys.time())
dbDataType(con, Sys.time() - as.POSIXct(Sys.Date()))
dbDataType(con, c("x", "abc"))
dbDataType(con, list(raw(10), raw(20)))
dbDataType(con, I(3))
```

```
dbDataType(con, iris)
```

```
dbDisconnect(con)
```

dbDisconnect

Disconnect (close) a connection

Description

This closes the connection, discards all pending work, and frees resources (e.g., memory, sockets).

Usage

```
dbDisconnect(conn, ...)
```

Arguments

conn	A DBIConnection object, as returned by dbConnect() .
...	Other parameters passed on to methods.

Value

dbDisconnect() returns TRUE, invisibly.

Specification

A warning is issued on garbage collection when a connection has been released without calling dbDisconnect(), but this cannot be tested automatically. A warning is issued immediately when calling dbDisconnect() on an already disconnected or invalid connection.

See Also

Other DBIConnection generics: [DBIConnection-class](#), [dbAppendTable](#), [dbCreateTable](#), [dbDataType](#), [dbExecute](#), [dbExistsTable](#), [dbGetException](#), [dbGetInfo](#), [dbGetQuery](#), [dbIsReadOnly](#), [dbIsValid](#), [dbListFields](#), [dbListObjects](#), [dbListResults](#), [dbListTables](#), [dbReadTable](#), [dbRemoveTable](#), [dbSendQuery](#), [dbSendStatement](#), [dbWriteTable](#)

Examples

```
con <- dbConnect(RSQLite::SQLite(), ":memory:")
dbDisconnect(con)
```

 dbDriver

Load and unload database drivers

Description

These methods are deprecated, please consult the documentation of the individual backends for the construction of driver instances.

dbDriver() is a helper method used to create a new driver object given the name of a database or the corresponding R package. It works through convention: all DBI-extending packages should provide an exported object with the same name as the package. dbDriver() just looks for this object in the right places: if you know what database you are connecting to, you should call the function directly.

dbUnloadDriver() is not implemented for modern backends.

Usage

```
dbDriver(drvName, ...)
```

```
dbUnloadDriver(drv, ...)
```

Arguments

drvName	character name of the driver to instantiate.
...	any other arguments are passed to the driver drvName.
drv	an object that inherits from DBIDriver as created by dbDriver.

Details

The client part of the database communication is initialized (typically dynamically loading C code, etc.) but note that connecting to the database engine itself needs to be done through calls to dbConnect.

Value

In the case of dbDriver, an driver object whose class extends DBIDriver. This object may be used to create connections to the actual DBMS engine.

In the case of dbUnloadDriver, a logical indicating whether the operation succeeded or not.

See Also

Other DBIDriver generics: [DBIDriver-class](#), [dbCanConnect](#), [dbConnect](#), [dbDataType](#), [dbGetInfo](#), [dbIsReadOnly](#), [dbIsValid](#), [dbListConnections](#)

Other DBIDriver generics: [DBIDriver-class](#), [dbCanConnect](#), [dbConnect](#), [dbDataType](#), [dbGetInfo](#), [dbIsReadOnly](#), [dbIsValid](#), [dbListConnections](#)

Examples

```
# Create a RSQLite driver with a string
d <- dbDriver("SQLite")
d

# But better, access the object directly
RSQLite::SQLite()
```

dbExecute	<i>Execute an update statement, query number of rows affected, and then close result set</i>
-----------	--

Description

Executes a statement and returns the number of rows affected. `dbExecute()` comes with a default implementation (which should work with most backends) that calls `dbSendStatement()`, then `dbGetRowsAffected()`, ensuring that the result is always free-d by `dbClearResult()`.

Usage

```
dbExecute(conn, statement, ...)
```

Arguments

<code>conn</code>	A DBIConnection object, as returned by <code>dbConnect()</code> .
<code>statement</code>	a character string containing SQL.
<code>...</code>	Other parameters passed on to methods.

Details

You can also use `dbExecute()` to call a stored procedure that performs data manipulation or other actions that do not return a result set. To execute a stored procedure that returns a result set use `dbGetQuery()` instead.

Value

`dbExecute()` always returns a scalar numeric that specifies the number of rows affected by the statement. An error is raised when issuing a statement over a closed or invalid connection, if the syntax of the statement is invalid, or if the statement is not a non-NA string.

Implementation notes

Subclasses should override this method only if they provide some sort of performance optimization.

Additional arguments

The following argument is not part of the `dbExecute()` generic (to improve compatibility across backends) but is part of the DBI specification:

- `params` (default: `NULL`)

It must be provided as named arguments. See the "Specification" sections for details on its usage.

Specification

The `param` argument allows passing query parameters, see `dbBind()` for details.

See Also

For queries: [dbSendQuery\(\)](#) and [dbGetQuery\(\)](#).

Other DBIConnection generics: [DBIConnection-class](#), [dbAppendTable](#), [dbCreateTable](#), [dbDataType](#), [dbDisconnect](#), [dbExistsTable](#), [dbGetException](#), [dbGetInfo](#), [dbGetQuery](#), [dbIsReadOnly](#), [dbIsValid](#), [dbListFields](#), [dbListObjects](#), [dbListResults](#), [dbListTables](#), [dbReadTable](#), [dbRemoveTable](#), [dbSendQuery](#), [dbSendStatement](#), [dbWriteTable](#)

Examples

```
con <- dbConnect(RSQLite::SQLite(), ":memory:")

dbWriteTable(con, "cars", head(cars, 3))
dbReadTable(con, "cars") # there are 3 rows
dbExecute(
  con,
  "INSERT INTO cars (speed, dist) VALUES (1, 1), (2, 2), (3, 3)"
)
dbReadTable(con, "cars") # there are now 6 rows

# Pass values using the param argument:
dbExecute(
  con,
  "INSERT INTO cars (speed, dist) VALUES (?, ?)",
  param = list(4:7, 5:8)
)
dbReadTable(con, "cars") # there are now 10 rows

dbDisconnect(con)
```

dbExistsTable	<i>Does a table exist?</i>
---------------	----------------------------

Description

Returns if a table given by name exists in the database.

Usage

```
dbExistsTable(conn, name, ...)
```

Arguments

conn	A DBIConnection object, as returned by dbConnect() .
name	A character string specifying a DBMS table name.
...	Other parameters passed on to methods.

Value

dbExistsTable() returns a logical scalar, TRUE if the table or view specified by the name argument exists, FALSE otherwise. This includes temporary tables if supported by the database.

An error is raised when calling this method for a closed or invalid connection. An error is also raised if name cannot be processed with dbQuoteIdentifier() or if this results in a non-scalar.

Specification

The name argument is processed as follows, to support databases that allow non-syntactic names for their objects:

- If an unquoted table name as string: dbExistsTable() will do the quoting, perhaps by calling dbQuoteIdentifier(conn, x = name)
- If the result of a call to dbQuoteIdentifier(): no more quoting is done

For all tables listed by dbListTables(), dbExistsTable() returns TRUE.

See Also

Other DBIConnection generics: [DBIConnection-class](#), [dbAppendTable](#), [dbCreateTable](#), [dbDataType](#), [dbDisconnect](#), [dbExecute](#), [dbGetException](#), [dbGetInfo](#), [dbGetQuery](#), [dbIsReadOnly](#), [dbIsValid](#), [dbListFields](#), [dbListObjects](#), [dbListResults](#), [dbListTables](#), [dbReadTable](#), [dbRemoveTable](#), [dbSendQuery](#), [dbSendStatement](#), [dbWriteTable](#)

Examples

```
con <- dbConnect(RSQLite::SQLite(), ":memory:")

dbExistsTable(con, "iris")
dbWriteTable(con, "iris", iris)
dbExistsTable(con, "iris")

dbDisconnect(con)
```

dbFetch

Fetch records from a previously executed query

Description

Fetch the next n elements (rows) from the result set and return them as a data.frame.

Usage

```
dbFetch(res, n = -1, ...)

fetch(res, n = -1, ...)
```

Arguments

<code>res</code>	An object inheriting from <code>DBIResult</code> , created by <code>dbSendQuery()</code> .
<code>n</code>	maximum number of records to retrieve per fetch. Use <code>n = -1</code> or <code>n = Inf</code> to retrieve all pending records. Some implementations may recognize other special values.
<code>...</code>	Other arguments passed on to methods.

Details

`fetch()` is provided for compatibility with older DBI clients - for all new code you are strongly encouraged to use `dbFetch()`. The default implementation for `dbFetch()` calls `fetch()` so that it is compatible with existing code. Modern backends should implement for `dbFetch()` only.

Value

`dbFetch()` always returns a `data.frame` with as many rows as records were fetched and as many columns as fields in the result set, even if the result is a single value or has one or zero rows. An attempt to fetch from a closed result set raises an error. If the `n` argument is not an atomic whole number greater or equal to `-1` or `Inf`, an error is raised, but a subsequent call to `dbFetch()` with proper `n` argument succeeds. Calling `dbFetch()` on a result set from a data manipulation query created by `dbSendStatement()` can be fetched and return an empty data frame, with a warning.

Specification

Fetching multi-row queries with one or more columns by default returns the entire result. Multi-row queries can also be fetched progressively by passing a whole number (`integer` or `numeric`) as the `n` argument. A value of `Inf` for the `n` argument is supported and also returns the full result. If more rows than available are fetched, the result is returned in full without warning. If fewer rows than requested are returned, further fetches will return a data frame with zero rows. If zero rows are fetched, the columns of the data frame are still fully typed. Fetching fewer rows than available is permitted, no warning is issued when clearing the result set.

A column named `row_names` is treated like any other column.

The column types of the returned data frame depend on the data returned:

- `integer` (or coercible to an integer) for integer values between -2^{31} and $2^{31} - 1$, with `NA` for SQL NULL values
- `numeric` for numbers with a fractional component, with `NA` for SQL NULL values
- `logical` for Boolean values (some backends may return an integer); with `NA` for SQL NULL values
- `character` for text, with `NA` for SQL NULL values
- lists of `raw` for blobs with `NULL` entries for SQL NULL values
- coercible using `as.Date()` for dates, with `NA` for SQL NULL values (also applies to the return value of the SQL function `current_date`)
- coercible using `hms::as.hms()` for times, with `NA` for SQL NULL values (also applies to the return value of the SQL function `current_time`)

- coercible using `as.POSIXct()` for timestamps, with NA for SQL NULL values (also applies to the return value of the SQL function `current_timestamp`)

If dates and timestamps are supported by the backend, the following R types are used:

- `Date` for dates (also applies to the return value of the SQL function `current_date`)
- `POSIXct` for timestamps (also applies to the return value of the SQL function `current_timestamp`)

R has no built-in type with lossless support for the full range of 64-bit or larger integers. If 64-bit integers are returned from a query, the following rules apply:

- Values are returned in a container with support for the full range of valid 64-bit values (such as the `integer64` class of the **bit64** package)
- Coercion to numeric always returns a number that is as close as possible to the true value
- Loss of precision when converting to numeric gives a warning
- Conversion to character always returns a lossless decimal representation of the data

See Also

Close the result set with `dbClearResult()` as soon as you finish retrieving the records you want.

Other DBIResult generics: `DBIResult-class`, `dbBind`, `dbClearResult`, `dbColumnInfo`, `dbGetInfo`, `dbGetRowCount`, `dbGetRowsAffected`, `dbGetStatement`, `dbHasCompleted`, `dbIsReadOnly`, `dbIsValid`, `dbQuoteIdentifier`, `dbQuoteLiteral`, `dbQuoteString`, `dbUnquoteIdentifier`

Examples

```
con <- dbConnect(RSQLite::SQLite(), ":memory:")

dbWriteTable(con, "mtcars", mtcars)

# Fetch all results
rs <- dbSendQuery(con, "SELECT * FROM mtcars WHERE cyl = 4")
dbFetch(rs)
dbClearResult(rs)

# Fetch in chunks
rs <- dbSendQuery(con, "SELECT * FROM mtcars")
while (!dbHasCompleted(rs)) {
  chunk <- dbFetch(rs, 10)
  print(nrow(chunk))
}

dbClearResult(rs)
dbDisconnect(con)
```

dbGetException	<i>Get DBMS exceptions</i>
----------------	----------------------------

Description

DEPRECATED. Backends should use R's condition system to signal errors and warnings.

Usage

```
dbGetException(conn, ...)
```

Arguments

conn	A DBIConnection object, as returned by dbConnect() .
...	Other parameters passed on to methods.

Value

a list with elements `errorNum` (an integer error number) and `errorMsg` (a character string) describing the last error in the connection `conn`.

See Also

Other [DBIConnection](#) generics: [DBIConnection-class](#), [dbAppendTable](#), [dbCreateTable](#), [dbDataType](#), [dbDisconnect](#), [dbExecute](#), [dbExistsTable](#), [dbGetInfo](#), [dbGetQuery](#), [dbIsReadOnly](#), [dbIsValid](#), [dbListFields](#), [dbListObjects](#), [dbListResults](#), [dbListTables](#), [dbReadTable](#), [dbRemoveTable](#), [dbSendQuery](#), [dbSendStatement](#), [dbWriteTable](#)

dbGetInfo	<i>Get DBMS metadata</i>
-----------	--------------------------

Description

Get DBMS metadata

Usage

```
dbGetInfo(dbObj, ...)
```

Arguments

dbObj	An object inheriting from DBIObject , i.e. DBIDriver , DBIConnection , or a DBIResult
...	Other arguments to methods.

Value

a named list

Implementation notes

For DBIDriver subclasses, this should include the version of the package (`driver.version`) and the version of the underlying client library (`client.version`).

For DBIConnection objects this should report the version of the DBMS engine (`db.version`), database name (`dbname`), username (`username`), host (`host`), port (`port`), etc. It MAY also include any other arguments related to the connection (e.g., thread id, socket or TCP connection type). It MUST NOT include the password.

For DBIResult objects, this should include the statement being executed (`statement`), how many rows have been fetched so far (in the case of queries, `row.count`), how many rows were affected (deleted, inserted, changed, (`rows.affected`), and if the query is complete (`has.completed`).

The default implementation for DBIResult objects constructs such a list from the return values of the corresponding methods, `dbGetStatement()`, `dbGetRowCount()`, `dbGetRowsAffected()`, and `dbHasCompleted()`.

See Also

Other DBIDriver generics: [DBIDriver-class](#), [dbCanConnect](#), [dbConnect](#), [dbDataType](#), [dbDriver](#), [dbIsReadOnly](#), [dbIsValid](#), [dbListConnections](#)

Other DBIConnection generics: [DBIConnection-class](#), [dbAppendTable](#), [dbCreateTable](#), [dbDataType](#), [dbDisconnect](#), [dbExecute](#), [dbExistsTable](#), [dbGetException](#), [dbGetQuery](#), [dbIsReadOnly](#), [dbIsValid](#), [dbListFields](#), [dbListObjects](#), [dbListResults](#), [dbListTables](#), [dbReadTable](#), [dbRemoveTable](#), [dbSendQuery](#), [dbSendStatement](#), [dbWriteTable](#)

Other DBIResult generics: [DBIResult-class](#), [dbBind](#), [dbClearResult](#), [dbColumnInfo](#), [dbFetch](#), [dbGetRowCount](#), [dbGetRowsAffected](#), [dbGetStatement](#), [dbHasCompleted](#), [dbIsReadOnly](#), [dbIsValid](#), [dbQuoteIdentifier](#), [dbQuoteLiteral](#), [dbQuoteString](#), [dbUnquoteIdentifier](#)

dbGetQuery

Send query, retrieve results and then clear result set

Description

Returns the result of a query as a data frame. `dbGetQuery()` comes with a default implementation (which should work with most backends) that calls `dbSendQuery()`, then `dbFetch()`, ensuring that the result is always free-d by `dbClearResult()`.

Usage

```
dbGetQuery(conn, statement, ...)
```


Arguments

conn	A DBIConnection object, as returned by dbConnect() .
statement	a character string containing SQL.
...	Other parameters passed on to methods.

Details

This method is for SELECT queries only (incl. other SQL statements that return a SELECT-alike result, e. g. execution of a stored procedure).

To execute a stored procedure that does not return a result set, use [dbExecute\(\)](#).

Some backends may support data manipulation statements through this method for compatibility reasons. However, callers are strongly advised to use [dbExecute\(\)](#) for data manipulation statements.

Value

[dbGetQuery\(\)](#) always returns a [data.frame](#) with as many rows as records were fetched and as many columns as fields in the result set, even if the result is a single value or has one or zero rows. An error is raised when issuing a query over a closed or invalid connection, if the syntax of the query is invalid, or if the query is not a non-NA string. If the `n` argument is not an atomic whole number greater or equal to -1 or `Inf`, an error is raised, but a subsequent call to [dbGetQuery\(\)](#) with proper `n` argument succeeds.

Implementation notes

Subclasses should override this method only if they provide some sort of performance optimization.

Additional arguments

The following arguments are not part of the [dbGetQuery\(\)](#) generic (to improve compatibility across backends) but are part of the DBI specification:

- `n` (default: -1)
- `params` (default: NULL)

They must be provided as named arguments. See the "Specification" and "Value" sections for details on their usage.

Specification

The `n` argument specifies the number of rows to be fetched. If omitted, fetching multi-row queries with one or more columns returns the entire result. A value of `Inf` for the `n` argument is supported and also returns the full result. If more rows than available are fetched (by passing a too large value for `n`), the result is returned in full without warning. If zero rows are requested, the columns of the data frame are still fully typed. Fetching fewer rows than available is permitted, no warning is issued.

The `param` argument allows passing query parameters, see [dbBind\(\)](#) for details.

A column named `row_names` is treated like any other column.

See Also

For updates: [dbSendStatement\(\)](#) and [dbExecute\(\)](#).

Other DBIConnection generics: [DBIConnection-class](#), [dbAppendTable](#), [dbCreateTable](#), [dbDataType](#), [dbDisconnect](#), [dbExecute](#), [dbExistsTable](#), [dbGetException](#), [dbGetInfo](#), [dbIsReadOnly](#), [dbIsValid](#), [dbListFields](#), [dbListObjects](#), [dbListResults](#), [dbListTables](#), [dbReadTable](#), [dbRemoveTable](#), [dbSendQuery](#), [dbSendStatement](#), [dbWriteTable](#)

Examples

```
con <- dbConnect(RSQLite::SQLite(), ":memory:")

dbWriteTable(con, "mtcars", mtcars)
dbGetQuery(con, "SELECT * FROM mtcars")
dbGetQuery(con, "SELECT * FROM mtcars", n = 6)

# Pass values using the param argument:
# (This query runs eight times, once for each different
# parameter. The resulting rows are combined into a single
# data frame.)
dbGetQuery(con, "SELECT COUNT(*) FROM mtcars WHERE cyl = ?", param = list(1:8))

dbDisconnect(con)
```

dbGetRowCount

The number of rows fetched so far

Description

Returns the total number of rows actually fetched with calls to [dbFetch\(\)](#) for this result set.

Usage

```
dbGetRowCount(res, ...)
```

Arguments

`res` An object inheriting from [DBIResult](#).
`...` Other arguments passed on to methods.

Value

`dbGetRowCount()` returns a scalar number (integer or numeric), the number of rows fetched so far. After calling [dbSendQuery\(\)](#), the row count is initially zero. After a call to [dbFetch\(\)](#) without limit, the row count matches the total number of rows returned. Fetching a limited number of rows increases the number of rows by the number of rows returned, even if fetching past the end of the result set. For queries with an empty result set, zero is returned even after fetching. For data manipulation statements issued with [dbSendStatement\(\)](#), zero is returned before and after calling [dbFetch\(\)](#). Attempting to get the row count for a result set cleared with [dbClearResult\(\)](#) gives an error.

See Also

Other DBIResult generics: [DBIResult-class](#), [dbBind](#), [dbClearResult](#), [dbColumnInfo](#), [dbFetch](#), [dbGetInfo](#), [dbGetRowsAffected](#), [dbGetStatement](#), [dbHasCompleted](#), [dbIsReadOnly](#), [dbIsValid](#), [dbQuoteIdentifier](#), [dbQuoteLiteral](#), [dbQuoteString](#), [dbUnquoteIdentifier](#)

Examples

```
con <- dbConnect(RSQLite::SQLite(), ":memory:")

dbWriteTable(con, "mtcars", mtcars)
rs <- dbSendQuery(con, "SELECT * FROM mtcars")

dbGetRowCount(rs)
ret1 <- dbFetch(rs, 10)
dbGetRowCount(rs)
ret2 <- dbFetch(rs)
dbGetRowCount(rs)
nrow(ret1) + nrow(ret2)

dbClearResult(rs)
dbDisconnect(con)
```

dbGetRowsAffected	<i>The number of rows affected</i>
-------------------	------------------------------------

Description

This method returns the number of rows that were added, deleted, or updated by a data manipulation statement.

Usage

```
dbGetRowsAffected(res, ...)
```

Arguments

res	An object inheriting from DBIResult .
...	Other arguments passed on to methods.

Value

`dbGetRowsAffected()` returns a scalar number (integer or numeric), the number of rows affected by a data manipulation statement issued with [dbSendStatement\(\)](#). The value is available directly after the call and does not change after calling [dbFetch\(\)](#). For queries issued with [dbSendQuery\(\)](#), zero is returned before and after the call to [dbFetch\(\)](#). Attempting to get the rows affected for a result set cleared with [dbClearResult\(\)](#) gives an error.

See Also

Other DBIResult generics: [DBIResult-class](#), [dbBind](#), [dbClearResult](#), [dbColumnInfo](#), [dbFetch](#), [dbGetInfo](#), [dbGetRowCount](#), [dbGetStatement](#), [dbHasCompleted](#), [dbIsReadOnly](#), [dbIsValid](#), [dbQuoteIdentifier](#), [dbQuoteLiteral](#), [dbQuoteString](#), [dbUnquoteIdentifier](#)

Examples

```
con <- dbConnect(RSQLite::SQLite(), ":memory:")

dbWriteTable(con, "mtcars", mtcars)
rs <- dbSendStatement(con, "DELETE FROM mtcars")
dbGetRowsAffected(rs)
nrow(mtcars)

dbClearResult(rs)
dbDisconnect(con)
```

dbGetStatement
Get the statement associated with a result set

Description

Returns the statement that was passed to [dbSendQuery\(\)](#) or [dbSendStatement\(\)](#).

Usage

```
dbGetStatement(res, ...)
```

Arguments

res An object inheriting from [DBIResult](#).

... Other arguments passed on to methods.

Value

[dbGetStatement\(\)](#) returns a string, the query used in either [dbSendQuery\(\)](#) or [dbSendStatement\(\)](#). Attempting to query the statement for a result set cleared with [dbClearResult\(\)](#) gives an error.

See Also

Other DBIResult generics: [DBIResult-class](#), [dbBind](#), [dbClearResult](#), [dbColumnInfo](#), [dbFetch](#), [dbGetInfo](#), [dbGetRowCount](#), [dbGetRowsAffected](#), [dbHasCompleted](#), [dbIsReadOnly](#), [dbIsValid](#), [dbQuoteIdentifier](#), [dbQuoteLiteral](#), [dbQuoteString](#), [dbUnquoteIdentifier](#)

Examples

```

con <- dbConnect(RSQLite::SQLite(), ":memory:")

dbWriteTable(con, "mtcars", mtcars)
rs <- dbSendQuery(con, "SELECT * FROM mtcars")
dbGetStatement(rs)

dbClearResult(rs)
dbDisconnect(con)

```

dbHasCompleted	<i>Completion status</i>
----------------	--------------------------

Description

This method returns if the operation has completed. A SELECT query is completed if all rows have been fetched. A data manipulation statement is always completed.

Usage

```
dbHasCompleted(res, ...)
```

Arguments

<code>res</code>	An object inheriting from DBIResult .
<code>...</code>	Other arguments passed on to methods.

Value

`dbHasCompleted()` returns a logical scalar. For a query initiated by [dbSendQuery\(\)](#) with non-empty result set, `dbHasCompleted()` returns FALSE initially and TRUE after calling [dbFetch\(\)](#) without limit. For a query initiated by [dbSendStatement\(\)](#), `dbHasCompleted()` always returns TRUE. Attempting to query completion status for a result set cleared with [dbClearResult\(\)](#) gives an error.

Specification

The completion status for a query is only guaranteed to be set to FALSE after attempting to fetch past the end of the entire result. Therefore, for a query with an empty result set, the initial return value is unspecified, but the result value is TRUE after trying to fetch only one row. Similarly, for a query with a result set of length *n*, the return value is unspecified after fetching *n* rows, but the result value is TRUE after trying to fetch only one more row.

See Also

Other DBIResult generics: [DBIResult-class](#), [dbBind](#), [dbClearResult](#), [dbColumnInfo](#), [dbFetch](#), [dbGetInfo](#), [dbGetRowCount](#), [dbGetRowsAffected](#), [dbGetStatement](#), [dbIsReadOnly](#), [dbIsValid](#), [dbQuoteIdentifier](#), [dbQuoteLiteral](#), [dbQuoteString](#), [dbUnquoteIdentifier](#)

Examples

```

con <- dbConnect(RSQLite::SQLite(), ":memory:")

dbWriteTable(con, "mtcars", mtcars)
rs <- dbSendQuery(con, "SELECT * FROM mtcars")

dbHasCompleted(rs)
ret1 <- dbFetch(rs, 10)
dbHasCompleted(rs)
ret2 <- dbFetch(rs)
dbHasCompleted(rs)

dbClearResult(rs)
dbDisconnect(con)

```

DBIConnection-class *DBIConnection class*

Description

This virtual class encapsulates the connection to a DBMS, and it provides access to dynamic queries, result sets, DBMS session management (transactions), etc.

Implementation note

Individual drivers are free to implement single or multiple simultaneous connections.

See Also

Other DBI classes: [DBIDriver-class](#), [DBIObject-class](#), [DBIResult-class](#)

Other DBIConnection generics: [dbAppendTable](#), [dbCreateTable](#), [dbDataType](#), [dbDisconnect](#), [dbExecute](#), [dbExistsTable](#), [dbGetException](#), [dbGetInfo](#), [dbGetQuery](#), [dbIsReadOnly](#), [dbIsValid](#), [dbListFields](#), [dbListObjects](#), [dbListResults](#), [dbListTables](#), [dbReadTable](#), [dbRemoveTable](#), [dbSendQuery](#), [dbSendStatement](#), [dbWriteTable](#)

Examples

```

con <- dbConnect(RSQLite::SQLite(), ":memory:")
con
dbDisconnect(con)

## Not run:
con <- dbConnect(RPostgreSQL::PostgreSQL(), "username", "password")
con
dbDisconnect(con)

## End(Not run)

```

DBIDriver-class	<i>DBIDriver class</i>
-----------------	------------------------

Description

Base class for all DBMS drivers (e.g., SQLite, MySQL, PostgreSQL). The virtual class `DBIDriver` defines the operations for creating connections and defining data type mappings. Actual driver classes, for instance `RPgSQL`, `RMySQL`, etc. implement these operations in a DBMS-specific manner.

See Also

Other DBI classes: [DBIConnection-class](#), [DBIObject-class](#), [DBIResult-class](#)

Other `DBIDriver` generics: [dbCanConnect](#), [dbConnect](#), [dbDataType](#), [dbDriver](#), [dbGetInfo](#), [dbIsReadOnly](#), [dbIsValid](#), [dbListConnections](#)

DBIObject-class	<i>DBIObject class</i>
-----------------	------------------------

Description

Base class for all other DBI classes (e.g., drivers, connections). This is a virtual Class: No objects may be created from it.

Details

More generally, the DBI defines a very small set of classes and generics that allows users and applications access DBMS with a common interface. The virtual classes are `DBIDriver` that individual drivers extend, `DBIConnection` that represent instances of DBMS connections, and `DBIResult` that represent the result of a DBMS statement. These three classes extend the basic class of `DBIObject`, which serves as the root or parent of the class hierarchy.

Implementation notes

An implementation **MUST** provide methods for the following generics:

- [dbGetInfo\(\)](#).

It **MAY** also provide methods for:

- [summary\(\)](#). Print a concise description of the object. The default method invokes `dbGetInfo(dbObj)` and prints the name-value pairs one per line. Individual implementations may tailor this appropriately.

See Also

Other DBI classes: [DBIConnection-class](#), [DBIDriver-class](#), [DBIResult-class](#)

Examples

```

drv <- RSQLite::SQLite()
con <- dbConnect(drv)

rs <- dbSendQuery(con, "SELECT 1")
is(drv, "DBIObject") ## True
is(con, "DBIObject") ## True
is(rs, "DBIObject")

dbClearResult(rs)
dbDisconnect(con)

```

DBIResult-class	<i>DBIResult class</i>
-----------------	------------------------

Description

This virtual class describes the result and state of execution of a DBMS statement (any statement, query or non-query). The result set keeps track of whether the statement produces output how many rows were affected by the operation, how many rows have been fetched (if statement is a query), whether there are more rows to fetch, etc.

Implementation notes

Individual drivers are free to allow single or multiple active results per connection.
The default show method displays a summary of the query using other DBI generics.

See Also

Other DBI classes: [DBIConnection-class](#), [DBIDriver-class](#), [DBIObject-class](#)

Other DBIResult generics: [dbBind](#), [dbClearResult](#), [dbColumnInfo](#), [dbFetch](#), [dbGetInfo](#), [dbGetRowCount](#), [dbGetRowsAffected](#), [dbGetStatement](#), [dbHasCompleted](#), [dbIsReadOnly](#), [dbIsValid](#), [dbQuoteIdentifier](#), [dbQuoteLiteral](#), [dbQuoteString](#), [dbUnquoteIdentifier](#)

dbIsReadOnly	<i>Is this DBMS object read only?</i>
--------------	---------------------------------------

Description

This generic tests whether a database object is read only.

Usage

```
dbIsReadOnly(dbObj, ...)
```


Arguments

dbObj An object inheriting from [DBIObject](#), i.e. [DBIDriver](#), [DBIConnection](#), or a [DBIResult](#)

... Other arguments to methods.

See Also

Other DBIDriver generics: [DBIDriver-class](#), [dbCanConnect](#), [dbConnect](#), [dbDataType](#), [dbDriver](#), [dbGetInfo](#), [dbIsValid](#), [dbListConnections](#)

Other DBIConnection generics: [DBIConnection-class](#), [dbAppendTable](#), [dbCreateTable](#), [dbDataType](#), [dbDisconnect](#), [dbExecute](#), [dbExistsTable](#), [dbGetException](#), [dbGetInfo](#), [dbGetQuery](#), [dbIsValid](#), [dbListFields](#), [dbListObjects](#), [dbListResults](#), [dbListTables](#), [dbReadTable](#), [dbRemoveTable](#), [dbSendQuery](#), [dbSendStatement](#), [dbWriteTable](#)

Other DBIResult generics: [DBIResult-class](#), [dbBind](#), [dbClearResult](#), [dbColumnInfo](#), [dbFetch](#), [dbGetInfo](#), [dbGetRowCount](#), [dbGetRowsAffected](#), [dbGetStatement](#), [dbHasCompleted](#), [dbIsValid](#), [dbQuoteIdentifier](#), [dbQuoteLiteral](#), [dbQuoteString](#), [dbUnquoteIdentifier](#)

Examples

```
dbIsValid(ANSI())
```

dbIsValid	<i>Is this DBMS object still valid?</i>
-----------	---

Description

This generic tests whether a database object is still valid (i.e. it hasn't been disconnected or cleared).

Usage

```
dbIsValid(dbObj, ...)
```

Arguments

dbObj An object inheriting from [DBIObject](#), i.e. [DBIDriver](#), [DBIConnection](#), or a [DBIResult](#)

... Other arguments to methods.

Value

dbIsValid() returns a logical scalar, TRUE if the object specified by dbObj is valid, FALSE otherwise. A [DBIConnection](#) object is initially valid, and becomes invalid after disconnecting with [dbDisconnect\(\)](#). For an invalid connection object (e.g., for some drivers if the object is saved to a file and then restored), the method also returns FALSE. A [DBIResult](#) object is valid after a call to [dbSendQuery\(\)](#), and stays valid even after all rows have been fetched; only clearing it with [dbClearResult\(\)](#) invalidates it. A [DBIResult](#) object is also valid after a call to [dbSendStatement\(\)](#),

and stays valid after querying the number of rows affected; only clearing it with `dbClearResult()` invalidates it. If the connection to the database system is dropped (e.g., due to connectivity problems, server failure, etc.), `dbIsValid()` should return `FALSE`. This is not tested automatically.

See Also

Other `DBIDriver` generics: `DBIDriver-class`, `dbCanConnect`, `dbConnect`, `dbDataType`, `dbDriver`, `dbGetInfo`, `dbIsReadOnly`, `dbListConnections`

Other `DBIConnection` generics: `DBIConnection-class`, `dbAppendTable`, `dbCreateTable`, `dbDataType`, `dbDisconnect`, `dbExecute`, `dbExistsTable`, `dbGetException`, `dbGetInfo`, `dbGetQuery`, `dbIsReadOnly`, `dbListFields`, `dbListObjects`, `dbListResults`, `dbListTables`, `dbReadTable`, `dbRemoveTable`, `dbSendQuery`, `dbSendStatement`, `dbWriteTable`

Other `DBIResult` generics: `DBIResult-class`, `dbBind`, `dbClearResult`, `dbColumnInfo`, `dbFetch`, `dbGetInfo`, `dbGetRowCount`, `dbGetRowsAffected`, `dbGetStatement`, `dbHasCompleted`, `dbIsReadOnly`, `dbQuoteIdentifier`, `dbQuoteLiteral`, `dbQuoteString`, `dbUnquoteIdentifier`

Examples

```
dbIsValid(RSQLite::SQLite())

con <- dbConnect(RSQLite::SQLite(), ":memory:")
dbIsValid(con)

rs <- dbSendQuery(con, "SELECT 1")
dbIsValid(rs)

dbClearResult(rs)
dbIsValid(rs)

dbDisconnect(con)
dbIsValid(con)
```

<code>dbListConnections</code>	<i>List currently open connections</i>
--------------------------------	--

Description

DEPRECATED, drivers are no longer required to implement this method. Keep track of the connections you opened if you require a list.

Usage

```
dbListConnections(drv, ...)
```

Arguments

<code>drv</code>	A object inheriting from <code>DBIDriver</code>
<code>...</code>	Other arguments passed on to methods.

Value

a list

See Also

Other DBIDriver generics: [DBIDriver-class](#), [dbCanConnect](#), [dbConnect](#), [dbDataType](#), [dbDriver](#), [dbGetInfo](#), [dbIsReadOnly](#), [dbIsValid](#)

dbListFields	<i>List field names of a remote table</i>
--------------	---

Description

List field names of a remote table

Usage

```
dbListFields(conn, name, ...)
```

Arguments

conn	A DBIConnection object, as returned by dbConnect() .
name	a character string with the name of the remote table.
...	Other parameters passed on to methods.

Value

dbListFields() returns a character vector that enumerates all fields in the table in the correct order. This also works for temporary tables if supported by the database. The returned names are suitable for quoting with [dbQuoteIdentifier\(\)](#). If the table does not exist, an error is raised. Invalid types for the name argument (e.g., character of length not equal to one, or numeric) lead to an error. An error is also raised when calling this method for a closed or invalid connection.

Specification

The name argument can be

- a string
- the return value of [dbQuoteIdentifier\(\)](#)
- a value from the table column from the return value of [dbListObjects\(\)](#) where is_prefix is FALSE

A column named row_names is treated like any other column.

See Also

[dbColumnInfo\(\)](#) to get the type of the fields.

Other DBIConnection generics: [DBIConnection-class](#), [dbAppendTable](#), [dbCreateTable](#), [dbDataType](#), [dbDisconnect](#), [dbExecute](#), [dbExistsTable](#), [dbGetException](#), [dbGetInfo](#), [dbGetQuery](#), [dbIsReadOnly](#), [dbIsValid](#), [dbListObjects](#), [dbListResults](#), [dbListTables](#), [dbReadTable](#), [dbRemoveTable](#), [dbSendQuery](#), [dbSendStatement](#), [dbWriteTable](#)

Examples

```
con <- dbConnect(RSQLite::SQLite(), ":memory:")

dbWriteTable(con, "mtcars", mtcars)
dbListFields(con, "mtcars")

dbDisconnect(con)
```

dbListObjects	<i>List remote objects</i>
---------------	----------------------------

Description

Returns the names of remote objects accessible through this connection as a data frame. This should include temporary objects, but not all database backends (in particular **RMariaDB** and **RMySQL**) support this. Compared to [dbListTables\(\)](#), this method also enumerates tables and views in schemas, and returns fully qualified identifiers to access these objects. This allows exploration of all database objects available to the current user, including those that can only be accessed by giving the full namespace.

Usage

```
dbListObjects(conn, prefix = NULL, ...)
```

Arguments

conn	A DBIConnection object, as returned by dbConnect() .
prefix	A fully qualified path in the database's namespace, or NULL. This argument will be processed with dbUnquoteIdentifier() . If given the method will return all objects accessible through this prefix.
...	Other parameters passed on to methods.

Value

[dbListObjects\(\)](#) returns a data frame with columns `table` and `is_prefix` (in that order), optionally with other columns with a dot (.) prefix. The `table` column is of type list. Each object in this list is suitable for use as argument in [dbQuoteIdentifier\(\)](#). The `is_prefix` column is a logical. This data frame contains one row for each object (schema, table and view) accessible from the prefix (if passed) or from the global namespace (if prefix is omitted). Tables added with [dbWriteTable\(\)](#)

are part of the data frame, including temporary objects if supported by the database. As soon a table is removed from the database, it is also removed from the data frame of database objects.

The returned names are suitable for quoting with `dbQuoteIdentifier()`. An error is raised when calling this method for a closed or invalid connection.

Specification

The table object can be quoted with `dbQuoteIdentifier()`. The result of quoting can be passed to `dbUnquoteIdentifier()`. The unquoted results are equal to the original table object. (For backends it may be convenient to use the `Id` class, but this is not required.)

The `prefix` column indicates if the table value refers to a table or a prefix. For a call with the default `prefix = NULL`, the table values that have `is_prefix == FALSE` correspond to the tables returned from `dbListTables()`,

Values in `table` column that have `is_prefix == TRUE` can be passed as the `prefix` argument to another call to `dbListObjects()`. For the data frame returned from a `dbListObject()` call with the `prefix` argument set, all table values where `is_prefix` is `FALSE` can be used in a call to `dbExistsTable()` which returns `TRUE`.

See Also

Other `DBIConnection` generics: [DBIConnection-class](#), [dbAppendTable](#), [dbCreateTable](#), [dbDataType](#), [dbDisconnect](#), [dbExecute](#), [dbExistsTable](#), [dbGetException](#), [dbGetInfo](#), [dbGetQuery](#), [dbIsReadOnly](#), [dbIsValid](#), [dbListFields](#), [dbListResults](#), [dbListTables](#), [dbReadTable](#), [dbRemoveTable](#), [dbSendQuery](#), [dbSendStatement](#), [dbWriteTable](#)

Examples

```
con <- dbConnect(RSQLite::SQLite(), ":memory:")

dbListObjects(con)
dbWriteTable(con, "mtcars", mtcars)
dbListObjects(con)

dbDisconnect(con)
```

dbListResults	<i>A list of all pending results</i>
---------------	--------------------------------------

Description

DEPRECATED. DBI currently supports only one open result set per connection, you need to keep track of the result sets you open if you need this functionality.

Usage

```
dbListResults(conn, ...)
```

Arguments

conn A [DBIConnection](#) object, as returned by [dbConnect\(\)](#).
 ... Other parameters passed on to methods.

Value

a list. If no results are active, an empty list. If only a single result is active, a list with one element.

See Also

Other DBIConnection generics: [DBIConnection-class](#), [dbAppendTable](#), [dbCreateTable](#), [dbDataType](#), [dbDisconnect](#), [dbExecute](#), [dbExistsTable](#), [dbGetException](#), [dbGetInfo](#), [dbGetQuery](#), [dbIsReadOnly](#), [dbIsValid](#), [dbListFields](#), [dbListObjects](#), [dbListTables](#), [dbReadTable](#), [dbRemoveTable](#), [dbSendQuery](#), [dbSendStatement](#), [dbWriteTable](#)

dbListTables	<i>List remote tables</i>
--------------	---------------------------

Description

Returns the unquoted names of remote tables accessible through this connection. This should include views and temporary objects, but not all database backends (in particular **RMariaDB** and **RMySQL**) support this.

Usage

```
dbListTables(conn, ...)
```

Arguments

conn A [DBIConnection](#) object, as returned by [dbConnect\(\)](#).
 ... Other parameters passed on to methods.

Value

dbListTables() returns a character vector that enumerates all tables and views in the database. Tables added with [dbWriteTable\(\)](#) are part of the list, including temporary tables if supported by the database. As soon a table is removed from the database, it is also removed from the list of database tables.

The returned names are suitable for quoting with [dbQuoteIdentifier\(\)](#). An error is raised when calling this method for a closed or invalid connection.

See Also

Other DBIConnection generics: [DBIConnection-class](#), [dbAppendTable](#), [dbCreateTable](#), [dbDataType](#), [dbDisconnect](#), [dbExecute](#), [dbExistsTable](#), [dbGetException](#), [dbGetInfo](#), [dbGetQuery](#), [dbIsReadOnly](#), [dbIsValid](#), [dbListFields](#), [dbListObjects](#), [dbListResults](#), [dbReadTable](#), [dbRemoveTable](#), [dbSendQuery](#), [dbSendStatement](#), [dbWriteTable](#)

Examples

```
con <- dbConnect(RSQLite::SQLite(), ":memory:")

dbListTables(con)
dbWriteTable(con, "mtcars", mtcars)
dbListTables(con)

dbDisconnect(con)
```

dbQuoteIdentifier	<i>Quote identifiers</i>
-------------------	--------------------------

Description

Call this method to generate a string that is suitable for use in a query as a column or table name, to make sure that you generate valid SQL and protect against SQL injection attacks. The inverse operation is [dbUnquoteIdentifier\(\)](#).

Usage

```
dbQuoteIdentifier(conn, x, ...)
```

Arguments

conn	A subclass of DBIConnection , representing an active connection to an DBMS.
x	A character vector, SQL or Id object to quote as identifier.
...	Other arguments passed on to methods.

Value

`dbQuoteIdentifier()` returns an object that can be coerced to [character](#), of the same length as the input. For an empty character vector this function returns a length-0 object. The names of the input argument are preserved in the output. When passing the returned object again in `dbQuoteIdentifier()` as `x` argument, it is returned unchanged. Passing objects of class [SQL](#) should also return them unchanged. (For backends it may be most convenient to return [SQL](#) objects to achieve this behavior, but this is not required.)

An error is raised if the input contains NA, but not for an empty string.

Specification

Calling `dbGetQuery()` for a query of the format `SELECT 1 AS ...` returns a data frame with the identifier, unquoted, as column name. Quoted identifiers can be used as table and column names in SQL queries, in particular in queries like `SELECT 1 AS ...` and `SELECT * FROM (SELECT 1) ...`. The method must use a quoting mechanism that is unambiguously different from the quoting mechanism used for strings, so that a query like `SELECT ... FROM (SELECT 1 AS ...)` throws an error if the column names do not match.

The method can quote column names that contain special characters such as a space, a dot, a comma, or quotes used to mark strings or identifiers, if the database supports this. In any case, checking the validity of the identifier should be performed only when executing a query, and not by `dbQuoteIdentifier()`.

See Also

Other DBIResult generics: [DBIResult-class](#), [dbBind](#), [dbClearResult](#), [dbColumnInfo](#), [dbFetch](#), [dbGetInfo](#), [dbGetRowCount](#), [dbGetRowsAffected](#), [dbGetStatement](#), [dbHasCompleted](#), [dbIsReadOnly](#), [dbIsValid](#), [dbQuoteLiteral](#), [dbQuoteString](#), [dbUnquoteIdentifier](#)

Examples

```
# Quoting ensures that arbitrary input is safe for use in a query
name <- "Robert'); DROP TABLE Students;--"
dbQuoteIdentifier(ANSI(), name)

# SQL vectors are always passed through as is
var_name <- SQL("select")
var_name

dbQuoteIdentifier(ANSI(), var_name)

# This mechanism is used to prevent double escaping
dbQuoteIdentifier(ANSI(), dbQuoteIdentifier(ANSI(), name))
```

dbQuoteLiteral	<i>Quote literal values</i>
----------------	-----------------------------

Description

Call these methods to generate a string that is suitable for use in a query as a literal value of the correct type, to make sure that you generate valid SQL and protect against SQL injection attacks.

Usage

```
dbQuoteLiteral(conn, x, ...)
```

Arguments

conn	A subclass of DBIConnection , representing an active connection to an DBMS.
x	A vector to quote as string.
...	Other arguments passed on to methods.

Value

dbQuoteLiteral() returns an object that can be coerced to [character](#), of the same length as the input. For an empty character vector this function returns a length-0 object.

When passing the returned object again to dbQuoteLiteral() as x argument, it is returned unchanged. Passing objects of class [SQL](#) should also return them unchanged. (For backends it may be most convenient to return [SQL](#) objects to achieve this behavior, but this is not required.)

Specification

The returned expression can be used in a SELECT ... query, and the value of dbGetQuery(paste0("SELECT ", dbQuoteLiteral(x)), ...) must be equal to x for any scalar integer, numeric, string, and logical. If x is NA, the result must merely satisfy [is.na\(\)](#). The literals "NA" or "NULL" are not treated specially.

NA should be translated to an unquoted SQL NULL, so that the query SELECT * FROM (SELECT 1) a WHERE ... IS NULL returns one row.

Passing a list for the x argument raises an error.

See Also

Other DBIResult generics: [DBIResult-class](#), [dbBind](#), [dbClearResult](#), [dbColumnInfo](#), [dbFetch](#), [dbGetInfo](#), [dbGetRowCount](#), [dbGetRowsAffected](#), [dbGetStatement](#), [dbHasCompleted](#), [dbIsReadOnly](#), [dbIsValid](#), [dbQuoteIdentifier](#), [dbQuoteString](#), [dbUnquoteIdentifier](#)

Examples

```
# Quoting ensures that arbitrary input is safe for use in a query
name <- "Robert'); DROP TABLE Students;--"
dbQuoteLiteral(ANSI(), name)

# NAs become NULL
dbQuoteLiteral(ANSI(), c(1:3, NA))

# Logicals become integers by default
dbQuoteLiteral(ANSI(), c(TRUE, FALSE, NA))

# Raw vectors become hex strings by default
dbQuoteLiteral(ANSI(), list(as.raw(1:3), NULL))

# SQL vectors are always passed through as is
var_name <- SQL("select")
var_name
dbQuoteLiteral(ANSI(), var_name)

# This mechanism is used to prevent double escaping
dbQuoteLiteral(ANSI(), dbQuoteLiteral(ANSI(), name))
```

 dbQuoteString

Quote literal strings

Description

Call this method to generate a string that is suitable for use in a query as a string literal, to make sure that you generate valid SQL and protect against SQL injection attacks.

Usage

```
dbQuoteString(conn, x, ...)
```

Arguments

conn	A subclass of DBIConnection , representing an active connection to an DBMS.
x	A character vector to quote as string.
...	Other arguments passed on to methods.

Value

dbQuoteString() returns an object that can be coerced to [character](#), of the same length as the input. For an empty character vector this function returns a length-0 object.

When passing the returned object again to dbQuoteString() as x argument, it is returned unchanged. Passing objects of class [SQL](#) should also return them unchanged. (For backends it may be most convenient to return [SQL](#) objects to achieve this behavior, but this is not required.)

Specification

The returned expression can be used in a SELECT ... query, and for any scalar character x the value of dbGetQuery(paste0("SELECT ", dbQuoteString(x)))[[1]] must be identical to x, even if x contains spaces, tabs, quotes (single or double), backticks, or newlines (in any combination) or is itself the result of a dbQuoteString() call coerced back to character (even repeatedly). If x is NA, the result must merely satisfy [is.na\(\)](#). The strings "NA" or "NULL" are not treated specially.

NA should be translated to an unquoted SQL NULL, so that the query SELECT * FROM (SELECT 1) a WHERE ... IS NULL returns one row.

Passing a numeric, integer, logical, or raw vector, or a list for the x argument raises an error.

See Also

Other DBIResult generics: [DBIResult-class](#), [dbBind](#), [dbClearResult](#), [dbColumnInfo](#), [dbFetch](#), [dbGetInfo](#), [dbGetRowCount](#), [dbGetRowsAffected](#), [dbGetStatement](#), [dbHasCompleted](#), [dbIsReadOnly](#), [dbIsValid](#), [dbQuoteIdentifier](#), [dbQuoteLiteral](#), [dbUnquoteIdentifier](#)

Examples

```
# Quoting ensures that arbitrary input is safe for use in a query
name <- "Robert'); DROP TABLE Students;--"
dbQuoteString(ANSI(), name)

# NAs become NULL
dbQuoteString(ANSI(), c("x", NA))

# SQL vectors are always passed through as is
var_name <- SQL("select")
var_name
dbQuoteString(ANSI(), var_name)

# This mechanism is used to prevent double escaping
dbQuoteString(ANSI(), dbQuoteString(ANSI(), name))
```

dbReadTable	<i>Copy data frames from database tables</i>
-------------	--

Description

Reads a database table to a data frame, optionally converting a column to row names and converting the column names to valid R identifiers.

Usage

```
dbReadTable(conn, name, ...)
```

Arguments

conn	A DBIConnection object, as returned by dbConnect() .
name	A character string specifying the unquoted DBMS table name, or the result of a call to dbQuoteIdentifier() .
...	Other parameters passed on to methods.

Value

`dbReadTable()` returns a data frame that contains the complete data from the remote table, effectively the result of calling [dbGetQuery\(\)](#) with `SELECT * FROM <name>`. An error is raised if the table does not exist. An empty table is returned as a data frame with zero rows.

The presence of [rownames](#) depends on the `row.names` argument, see [sqlColumnToRownames\(\)](#) for details:

- If `FALSE` or `NULL`, the returned data frame doesn't have row names.
- If `TRUE`, a column named "row_names" is converted to row names, an error is raised if no such column exists.

- If NA, a column named "row_names" is converted to row names if it exists, otherwise no translation occurs.
- If a string, this specifies the name of the column in the remote table that contains the row names, an error is raised if no such column exists.

The default is `row.names = FALSE`.

If the database supports identifiers with special characters, the columns in the returned data frame are converted to valid R identifiers if the `check.names` argument is TRUE, otherwise non-syntactic column names can be returned unquoted.

An error is raised when calling this method for a closed or invalid connection. An error is raised if name cannot be processed with `dbQuoteIdentifier()` or if this results in a non-scalar. Unsupported values for `row.names` and `check.names` (non-scalars, unsupported data types, NA for `check.names`) also raise an error.

Additional arguments

The following arguments are not part of the `dbReadTable()` generic (to improve compatibility across backends) but are part of the DBI specification:

- `row.names` (default: FALSE)
- `check.names`

They must be provided as named arguments. See the "Value" section for details on their usage.

Specification

The name argument is processed as follows, to support databases that allow non-syntactic names for their objects:

- If an unquoted table name as string: `dbReadTable()` will do the quoting, perhaps by calling `dbQuoteIdentifier(conn, x = name)`
- If the result of a call to `dbQuoteIdentifier()`: no more quoting is done

See Also

Other DBIConnection generics: [DBIConnection-class](#), [dbAppendTable](#), [dbCreateTable](#), [dbDataType](#), [dbDisconnect](#), [dbExecute](#), [dbExistsTable](#), [dbGetException](#), [dbGetInfo](#), [dbGetQuery](#), [dbIsReadOnly](#), [dbIsValid](#), [dbListFields](#), [dbListObjects](#), [dbListResults](#), [dbListTables](#), [dbRemoveTable](#), [dbSendQuery](#), [dbSendStatement](#), [dbWriteTable](#)

Examples

```
con <- dbConnect(RSQLite::SQLite(), ":memory:")

dbWriteTable(con, "mtcars", mtcars[1:10, ])
dbReadTable(con, "mtcars")

dbDisconnect(con)
```

dbRemoveTable	<i>Remove a table from the database</i>
---------------	---

Description

Remove a remote table (e.g., created by [dbWriteTable\(\)](#)) from the database.

Usage

```
dbRemoveTable(conn, name, ...)
```

Arguments

conn	A DBIConnection object, as returned by dbConnect() .
name	A character string specifying a DBMS table name.
...	Other parameters passed on to methods.

Value

`dbRemoveTable()` returns TRUE, invisibly. If the table does not exist, an error is raised. An attempt to remove a view with this function may result in an error.

An error is raised when calling this method for a closed or invalid connection. An error is also raised if name cannot be processed with [dbQuoteIdentifier\(\)](#) or if this results in a non-scalar.

Additional arguments

The following arguments are not part of the `dbRemoveTable()` generic (to improve compatibility across backends) but are part of the DBI specification:

- `temporary` (default: FALSE)
- `fail_if_missing` (default: TRUE)

These arguments must be provided as named arguments.

If `temporary` is TRUE, the call to `dbRemoveTable()` will consider only temporary tables. Not all backends support this argument. In particular, permanent tables of the same name are left untouched.

If `fail_if_missing` is FALSE, the call to `dbRemoveTable()` succeeds if the table does not exist.

Specification

A table removed by `dbRemoveTable()` doesn't appear in the list of tables returned by [dbListTables\(\)](#), and [dbExistsTable\(\)](#) returns FALSE. The removal propagates immediately to other connections to the same database. This function can also be used to remove a temporary table.

The name argument is processed as follows, to support databases that allow non-syntactic names for their objects:

- If an unquoted table name as string: `dbRemoveTable()` will do the quoting, perhaps by calling `dbQuoteIdentifier(conn, x = name)`
- If the result of a call to `dbQuoteIdentifier()`: no more quoting is done

See Also

Other DBIConnection generics: [DBIConnection-class](#), [dbAppendTable](#), [dbCreateTable](#), [dbDataType](#), [dbDisconnect](#), [dbExecute](#), [dbExistsTable](#), [dbGetException](#), [dbGetInfo](#), [dbGetQuery](#), [dbIsReadOnly](#), [dbIsValid](#), [dbListFields](#), [dbListObjects](#), [dbListResults](#), [dbListTables](#), [dbReadTable](#), [dbSendQuery](#), [dbSendStatement](#), [dbWriteTable](#)

Examples

```
con <- dbConnect(RSQLite::SQLite(), ":memory:")

dbExistsTable(con, "iris")
dbWriteTable(con, "iris", iris)
dbExistsTable(con, "iris")
dbRemoveTable(con, "iris")
dbExistsTable(con, "iris")

dbDisconnect(con)
```

dbSendQuery

Execute a query on a given database connection

Description

The `dbSendQuery()` method only submits and synchronously executes the SQL query to the database engine. It does *not* extract any records — for that you need to use the `dbFetch()` method, and then you must call `dbClearResult()` when you finish fetching the records you need. For interactive use, you should almost always prefer `dbGetQuery()`.

Usage

```
dbSendQuery(conn, statement, ...)
```

Arguments

<code>conn</code>	A DBIConnection object, as returned by <code>dbConnect()</code> .
<code>statement</code>	a character string containing SQL.
<code>...</code>	Other parameters passed on to methods.

Details

This method is for SELECT queries only. Some backends may support data manipulation queries through this method for compatibility reasons. However, callers are strongly encouraged to use [dbSendStatement\(\)](#) for data manipulation statements.

The query is submitted to the database server and the DBMS executes it, possibly generating vast amounts of data. Where these data live is driver-specific: some drivers may choose to leave the output on the server and transfer them piecemeal to R, others may transfer all the data to the client – but not necessarily to the memory that R manages. See individual drivers' [dbSendQuery\(\)](#) documentation for details.

Value

[dbSendQuery\(\)](#) returns an S4 object that inherits from [DBIResult](#). The result set can be used with [dbFetch\(\)](#) to extract records. Once you have finished using a result, make sure to clear it with [dbClearResult\(\)](#). An error is raised when issuing a query over a closed or invalid connection, if the syntax of the query is invalid, or if the query is not a non-NA string.

Additional arguments

The following argument is not part of the [dbSendQuery\(\)](#) generic (to improve compatibility across backends) but is part of the DBI specification:

- `params` (default: `NULL`)

It must be provided as named arguments. See the "Specification" sections for details on its usage.

Specification

No warnings occur under normal conditions. When done, the [DBIResult](#) object must be cleared with a call to [dbClearResult\(\)](#). Failure to clear the result set leads to a warning when the connection is closed.

If the backend supports only one open result set per connection, issuing a second query invalidates an already open result set and raises a warning. The newly opened result set is valid and must be cleared with [dbClearResult\(\)](#).

The `param` argument allows passing query parameters, see [dbBind\(\)](#) for details.

See Also

For updates: [dbSendStatement\(\)](#) and [dbExecute\(\)](#).

Other [DBIConnection](#) generics: [DBIConnection-class](#), [dbAppendTable](#), [dbCreateTable](#), [dbDataType](#), [dbDisconnect](#), [dbExecute](#), [dbExistsTable](#), [dbGetException](#), [dbGetInfo](#), [dbGetQuery](#), [dbIsReadOnly](#), [dbIsValid](#), [dbListFields](#), [dbListObjects](#), [dbListResults](#), [dbListTables](#), [dbReadTable](#), [dbRemoveTable](#), [dbSendStatement](#), [dbWriteTable](#)

Examples

```

con <- dbConnect(RSQLite::SQLite(), ":memory:")

dbWriteTable(con, "mtcars", mtcars)
rs <- dbSendQuery(con, "SELECT * FROM mtcars WHERE cyl = 4")
dbFetch(rs)
dbClearResult(rs)

# Pass one set of values with the param argument:
rs <- dbSendQuery(
  con,
  "SELECT * FROM mtcars WHERE cyl = ?",
  param = list(4L)
)
dbFetch(rs)
dbClearResult(rs)

# Pass multiple sets of values with dbBind():
rs <- dbSendQuery(con, "SELECT * FROM mtcars WHERE cyl = ?")
dbBind(rs, list(6L))
dbFetch(rs)
dbBind(rs, list(8L))
dbFetch(rs)
dbClearResult(rs)

dbDisconnect(con)

```

dbSendStatement	<i>Execute a data manipulation statement on a given database connection</i>
-----------------	---

Description

The `dbSendStatement()` method only submits and synchronously executes the SQL data manipulation statement (e.g., UPDATE, DELETE, INSERT INTO, DROP TABLE, ...) to the database engine. To query the number of affected rows, call `dbGetRowsAffected()` on the returned result object. You must also call `dbClearResult()` after that. For interactive use, you should almost always prefer `dbExecute()`.

Usage

```
dbSendStatement(conn, statement, ...)
```

Arguments

conn	A DBIConnection object, as returned by <code>dbConnect()</code> .
statement	a character string containing SQL.
...	Other parameters passed on to methods.

Details

`dbSendStatement()` comes with a default implementation that simply forwards to `dbSendQuery()`, to support backends that only implement the latter.

Value

`dbSendStatement()` returns an S4 object that inherits from `DBIResult`. The result set can be used with `dbGetRowsAffected()` to determine the number of rows affected by the query. Once you have finished using a result, make sure to clear it with `dbClearResult()`. An error is raised when issuing a statement over a closed or invalid connection, if the syntax of the statement is invalid, or if the statement is not a non-NA string.

Additional arguments

The following argument is not part of the `dbSendStatement()` generic (to improve compatibility across backends) but is part of the DBI specification:

- `params` (default: `NULL`)

It must be provided as named arguments. See the "Specification" sections for details on its usage.

Specification

No warnings occur under normal conditions. When done, the `DBIResult` object must be cleared with a call to `dbClearResult()`. Failure to clear the result set leads to a warning when the connection is closed. If the backend supports only one open result set per connection, issuing a second query invalidates an already open result set and raises a warning. The newly opened result set is valid and must be cleared with `dbClearResult()`.

The `param` argument allows passing query parameters, see `dbBind()` for details.

See Also

For queries: `dbSendQuery()` and `dbGetQuery()`.

Other `DBIConnection` generics: `DBIConnection-class`, `dbAppendTable`, `dbCreateTable`, `dbDataType`, `dbDisconnect`, `dbExecute`, `dbExistsTable`, `dbGetException`, `dbGetInfo`, `dbGetQuery`, `dbIsReadOnly`, `dbIsValid`, `dbListFields`, `dbListObjects`, `dbListResults`, `dbListTables`, `dbReadTable`, `dbRemoveTable`, `dbSendQuery`, `dbWriteTable`

Examples

```
con <- dbConnect(RSQLite::SQLite(), ":memory:")

dbWriteTable(con, "cars", head(cars, 3))

rs <- dbSendStatement(
  con,
  "INSERT INTO cars (speed, dist) VALUES (1, 1), (2, 2), (3, 3)"
)
dbHasCompleted(rs)
dbGetRowsAffected(rs)
```

```

dbClearResult(rs)
dbReadTable(con, "cars") # there are now 6 rows

# Pass one set of values directly using the param argument:
rs <- dbSendStatement(
  con,
  "INSERT INTO cars (speed, dist) VALUES (?, ?)",
  param = list(4L, 5L)
)
dbClearResult(rs)

# Pass multiple sets of values using dbBind():
rs <- dbSendStatement(
  con,
  "INSERT INTO cars (speed, dist) VALUES (?, ?)"
)
dbBind(rs, list(5:6, 6:7))
dbBind(rs, list(7L, 8L))
dbClearResult(rs)
dbReadTable(con, "cars") # there are now 10 rows

dbDisconnect(con)

```

dbUnquoteIdentifier *Unquote identifiers*

Description

Call this method to convert a [SQL](#) object created by [dbQuoteIdentifier\(\)](#) back to a list of [Id](#) objects.

Usage

```
dbUnquoteIdentifier(conn, x, ...)
```

Arguments

conn	A subclass of DBIConnection , representing an active connection to an DBMS.
x	An SQL or Id object or character vector to unquote.
...	Other arguments passed on to methods.

Value

`dbUnquoteIdentifier()` returns a list of objects of the same length as the input. For an empty character vector this function returns a length-0 object. The names of the input argument are preserved in the output. When passing the first element of a returned object again to `dbUnquoteIdentifier()` as `x` argument, it is returned unchanged (but wrapped in a list). Passing objects of class [Id](#) should also return them unchanged (but wrapped in a list). (For backends it may be most convenient to return [Id](#) objects to achieve this behavior, but this is not required.)

An error is raised if plain character vectors are passed as the `x` argument.

Specification

For any character vector of length one, quoting (with `dbQuoteIdentifier()`) then unquoting then quoting the first element is identical to just quoting. This is also true for strings that contain special characters such as a space, a dot, a comma, or quotes used to mark strings or identifiers, if the database supports this.

Unquoting simple strings (consisting of only letters) wrapped with `SQL()` and then quoting gives the same result as just quoting.

See Also

Other DBIResult generics: `DBIResult-class`, `dbBind`, `dbClearResult`, `dbColumnInfo`, `dbFetch`, `dbGetInfo`, `dbGetRowCount`, `dbGetRowsAffected`, `dbGetStatement`, `dbHasCompleted`, `dbIsReadOnly`, `dbIsValid`, `dbQuoteIdentifier`, `dbQuoteLiteral`, `dbQuoteString`

Examples

```
# Unquoting allows to understand the structure of a
# possibly complex quoted identifier
dbUnquoteIdentifier(
  ANSI(),
  SQL(c("Schema"."Table", "UnqualifiedTable")))
)

# The returned object is always a list,
# also for Id objects
dbUnquoteIdentifier(
  ANSI(),
  Id(schema = "Schema", table = "Table")
)

# Quoting is the inverse operation to unquoting the elements
# of the returned list
dbQuoteIdentifier(
  ANSI(),
  dbUnquoteIdentifier(ANSI(), SQL("UnqualifiedTable"))[[1]]
)

dbQuoteIdentifier(
  ANSI(),
  dbUnquoteIdentifier(ANSI(), Id(schema = "Schema", table = "Table"))[[1]]
)
```

Description

Given that [transactions](#) are implemented, this function allows you to pass in code that is run in a transaction. The default method of `dbWithTransaction()` calls `dbBegin()` before executing the code, and `dbCommit()` after successful completion, or `dbRollback()` in case of an error. The advantage is that you don't have to remember to do `dbBegin()` and `dbCommit()` or `dbRollback()` – that is all taken care of. The special function `dbBreak()` allows an early exit with rollback, it can be called only inside `dbWithTransaction()`.

Usage

```
dbWithTransaction(conn, code, ...)
```

```
dbBreak()
```

Arguments

<code>conn</code>	A DBIConnection object, as returned by <code>dbConnect()</code> .
<code>code</code>	An arbitrary block of R code.
<code>...</code>	Other parameters passed on to methods.

Details

DBI implements `dbWithTransaction()`, backends should need to override this generic only if they implement specialized handling.

Value

`dbWithTransaction()` returns the value of the executed code. Failure to initiate the transaction (e.g., if the connection is closed or invalid or if `dbBegin()` has been called already) gives an error.

Specification

`dbWithTransaction()` initiates a transaction with `dbBegin()`, executes the code given in the `code` argument, and commits the transaction with `dbCommit()`. If the code raises an error, the transaction is instead aborted with `dbRollback()`, and the error is propagated. If the code calls `dbBreak()`, execution of the code stops and the transaction is silently aborted. All side effects caused by the code (such as the creation of new variables) propagate to the calling environment.

Examples

```
con <- dbConnect(RSQLite::SQLite(), ":memory:")

dbWriteTable(con, "cash", data.frame(amount = 100))
dbWriteTable(con, "account", data.frame(amount = 2000))

# All operations are carried out as logical unit:
dbWithTransaction(
  con,
  {
```

```

    withdrawal <- 300
    dbExecute(con, "UPDATE cash SET amount = amount + ?", list(withdrawal))
    dbExecute(con, "UPDATE account SET amount = amount - ?", list(withdrawal))
  }
)

# The code is executed as if in the current environment:
withdrawal

# The changes are committed to the database after successful execution:
dbReadTable(con, "cash")
dbReadTable(con, "account")

# Rolling back with dbBreak():
dbWithTransaction(
  con,
  {
    withdrawal <- 5000
    dbExecute(con, "UPDATE cash SET amount = amount + ?", list(withdrawal))
    dbExecute(con, "UPDATE account SET amount = amount - ?", list(withdrawal))
    if (dbReadTable(con, "account")$amount < 0) {
      dbBreak()
    }
  }
)

# These changes were not committed to the database:
dbReadTable(con, "cash")
dbReadTable(con, "account")

dbDisconnect(con)

```

dbWriteTable

Copy data frames to database tables

Description

Writes, overwrites or appends a data frame to a database table, optionally converting row names to a column and specifying SQL data types for fields.

Usage

```
dbWriteTable(conn, name, value, ...)
```

Arguments

conn	A DBIConnection object, as returned by dbConnect() .
name	A character string specifying the unquoted DBMS table name, or the result of a call to dbQuoteIdentifier() .

value a [data.frame](#) (or coercible to data.frame).
 ... Other parameters passed on to methods.

Value

dbWriteTable() returns TRUE, invisibly. If the table exists, and both append and overwrite arguments are unset, or append = TRUE and the data frame with the new data has different column names, an error is raised; the remote table remains unchanged.

An error is raised when calling this method for a closed or invalid connection. An error is also raised if name cannot be processed with [dbQuoteIdentifier\(\)](#) or if this results in a non-scalar. Invalid values for the additional arguments row.names, overwrite, append, field.types, and temporary (non-scalars, unsupported data types, NA, incompatible values, duplicate or missing names, incompatible columns) also raise an error.

Additional arguments

The following arguments are not part of the dbWriteTable() generic (to improve compatibility across backends) but are part of the DBI specification:

- row.names (default: FALSE)
- overwrite (default: FALSE)
- append (default: FALSE)
- field.types (default: NULL)
- temporary (default: FALSE)

They must be provided as named arguments. See the "Specification" and "Value" sections for details on their usage.

Specification

The name argument is processed as follows, to support databases that allow non-syntactic names for their objects:

- If an unquoted table name as string: dbWriteTable() will do the quoting, perhaps by calling [dbQuoteIdentifier\(conn, x = name\)](#)
- If the result of a call to [dbQuoteIdentifier\(\)](#): no more quoting is done

If the overwrite argument is TRUE, an existing table of the same name will be overwritten. This argument doesn't change behavior if the table does not exist yet.

If the append argument is TRUE, the rows in an existing table are preserved, and the new data are appended. If the table doesn't exist yet, it is created.

If the temporary argument is TRUE, the table is not available in a second connection and is gone after reconnecting. Not all backends support this argument. A regular, non-temporary table is visible in a second connection and after reconnecting to the database.

SQL keywords can be used freely in table names, column names, and data. Quotes, commas, and spaces can also be used in the data, and, if the database supports non-syntactic identifiers, also for table names and column names.

The following data types must be supported at least, and be read identically with [dbReadTable\(\)](#):

- integer
- numeric (the behavior for Inf and NaN is not specified)
- logical
- NA as NULL
- 64-bit values (using "bigint" as field type); the result can be
 - converted to a numeric, which may lose precision,
 - converted a character vector, which gives the full decimal representation
 - written to another table and read again unchanged
- character (in both UTF-8 and native encodings), supporting empty strings
- factor (returned as character)
- list of raw (if supported by the database)
- objects of type `blob::blob` (if supported by the database)
- date (if supported by the database; returned as Date)
- time (if supported by the database; returned as objects that inherit from `difftime`)
- timestamp (if supported by the database; returned as `POSIXct` respecting the time zone but not necessarily preserving the input time zone)

Mixing column types in the same table is supported.

The `field.types` argument must be a named character vector with at most one entry for each column. It indicates the SQL data type to be used for a new column. If a column is missed from `field.types`, the type is inferred from the input data with `dbDataType()`.

The interpretation of `rownames` depends on the `row.names` argument, see `sqlRownamesToColumn()` for details:

- If FALSE or NULL, row names are ignored.
- If TRUE, row names are converted to a column named "row_names", even if the input data frame only has natural row names from 1 to `nrow(...)`.
- If NA, a column named "row_names" is created if the data has custom row names, no extra column is created in the case of natural row names.
- If a string, this specifies the name of the column in the remote table that contains the row names, even if the input data frame only has natural row names.

The default is `row.names = FALSE`.

See Also

Other DBIConnection generics: [DBIConnection-class](#), [dbAppendTable](#), [dbCreateTable](#), [dbDataType](#), [dbDisconnect](#), [dbExecute](#), [dbExistsTable](#), [dbGetException](#), [dbGetInfo](#), [dbGetQuery](#), [dbIsReadOnly](#), [dbIsValid](#), [dbListFields](#), [dbListObjects](#), [dbListResults](#), [dbListTables](#), [dbReadTable](#), [dbRemoveTable](#), [dbSendQuery](#), [dbSendStatement](#)

Examples

```

con <- dbConnect(RSQLite::SQLite(), ":memory:")

dbWriteTable(con, "mtcars", mtcars[1:5, ])
dbReadTable(con, "mtcars")

dbWriteTable(con, "mtcars", mtcars[6:10, ], append = TRUE)
dbReadTable(con, "mtcars")

dbWriteTable(con, "mtcars", mtcars[1:10, ], overwrite = TRUE)
dbReadTable(con, "mtcars")

# No row names
dbWriteTable(con, "mtcars", mtcars[1:10, ], overwrite = TRUE, row.names = FALSE)
dbReadTable(con, "mtcars")

```

Id-class	<i>Refer to a table nested in a hierarchy (e.g. within a schema)</i>
----------	--

Description

Objects of class Id have a single slot name, which is a named character vector.

Usage

```
Id(...)
```

Arguments

...	Components of the hierarchy, e.g. schema, table, or cluster, catalog, schema, table. For more on these concepts, see http://stackoverflow.com/questions/7022755/
-----	--

make.db.names	<i>Make R identifiers into legal SQL identifiers</i>
---------------	--

Description

These methods are DEPRECATED. Please use `dbQuoteIdentifier()` (or possibly `dbQuoteString()`) instead.

Usage

```

make.db.names(dbObj, snames, keywords = .SQL92Keywords, unique = TRUE,
  allow.keywords = TRUE, ...)

make.db.names.default(snames, keywords = .SQL92Keywords, unique = TRUE,
  allow.keywords = TRUE)

isSQLKeyword(dbObj, name, keywords = .SQL92Keywords, case = c("lower",
  "upper", "any")[3], ...)

isSQLKeyword.default(name, keywords = .SQL92Keywords, case = c("lower",
  "upper", "any")[3])

```

Arguments

dbObj	any DBI object (e.g., DBIDriver).
snames	a character vector of R identifiers (symbols) from which we need to make SQL identifiers.
keywords	a character vector with SQL keywords, by default it's .SQL92Keywords defined by the DBI.
unique	logical describing whether the resulting set of SQL names should be unique. Its default is TRUE. Following the SQL 92 standard, uniqueness of SQL identifiers is determined regardless of whether letters are upper or lower case.
allow.keywords	logical describing whether SQL keywords should be allowed in the resulting set of SQL names. Its default is TRUE
...	any other argument are passed to the driver implementation.
name	a character vector with database identifier candidates we need to determine whether they are legal SQL identifiers or not.
case	a character string specifying whether to make the comparison as lower case, upper case, or any of the two. it defaults to any.

Details

The algorithm in `make.db.names` first invokes `make.names` and then replaces each occurrence of a dot `.` by an underscore `_`. If `allow.keywords` is FALSE and identifiers collide with SQL keywords, a small integer is appended to the identifier in the form of `"_n"`.

The set of SQL keywords is stored in the character vector `.SQL92Keywords` and reflects the SQL ANSI/ISO standard as documented in "X/Open SQL and RDA", 1994, ISBN 1-872630-68-8. Users can easily override or update this vector.

Value

`make.db.names` returns a character vector of legal SQL identifiers corresponding to its `snames` argument.

`SQLKeywords` returns a character vector of all known keywords for the database-engine associated with `dbObj`.

`isSQLKeyword` returns a logical vector parallel to `name`.

Bugs

The current mapping is not guaranteed to be fully reversible: some SQL identifiers that get mapped into R identifiers with `make.names` and then back to SQL with `make.db.names()` will not be equal to the original SQL identifiers (e.g., compound SQL identifiers of the form `username.tablename` will lose the dot “.”).

References

The set of SQL keywords is stored in the character vector `.SQL92Keywords` and reflects the SQL ANSI/ISO standard as documented in "X/Open SQL and RDA", 1994, ISBN 1-872630-68-8. Users can easily override or update this vector.

rownames

Convert row names back and forth between columns

Description

These functions provide a reasonably automatic way of preserving the row names of data frame during back-and-forth translation to an SQL table. By default, row names will be converted to an explicit column called "row_names", and any query returning a column called "row_names" will have those automatically set as row names. These methods are mostly useful for backend implementers.

Usage

```
sqlRownamesToColumn(df, row.names = NA)
```

```
sqlColumnToRownames(df, row.names = NA)
```

Arguments

`df` A data frame

`row.names` Either TRUE, FALSE, NA or a string.

If TRUE, always translate row names to a column called "row_names". If FALSE, never translate row names. If NA, translate rownames only if they're a character vector.

A string is equivalent to TRUE, but allows you to override the default name.

For backward compatibility, NULL is equivalent to FALSE.

Examples

```
# If have row names
sqlRownamesToColumn(head(mtcars))
sqlRownamesToColumn(head(mtcars), FALSE)
sqlRownamesToColumn(head(mtcars), "ROWNAMES")
```

```
# If don't have
```

```
sqlRownamesToColumn(head(iris))
sqlRownamesToColumn(head(iris), TRUE)
sqlRownamesToColumn(head(iris), "ROWNAMES")
```

SQL

SQL quoting

Description

This set of classes and generics make it possible to flexibly deal with SQL escaping needs. By default, any user supplied input to a query should be escaped using either `dbQuoteIdentifier()` or `dbQuoteString()` depending on whether it refers to a table or variable name, or is a literal string. These functions may return an object of the SQL class, which tells DBI functions that a character string does not need to be escaped anymore, to prevent double escaping. The SQL class has associated the `SQL()` constructor function.

Usage

```
SQL(x, ..., names = NULL)
```

Arguments

<code>x</code>	A character vector to label as being escaped SQL.
<code>...</code>	Other arguments passed on to methods. Not otherwise used.
<code>names</code>	Names for the returned object, must have the same length as <code>x</code> .

Value

An object of class SQL.

Implementation notes

DBI provides default generics for SQL-92 compatible quoting. If the database uses a different convention, you will need to provide your own methods. Note that because of the way that S4 dispatch finds methods and because SQL inherits from character, if you implement (e.g.) a method for `dbQuoteString(MyConnection, character)`, you will also need to implement `dbQuoteString(MyConnection, SQL)` - this should simply return `x` unchanged.

Examples

```
dbQuoteIdentifier(ANSI(), "SELECT")
dbQuoteString(ANSI(), "SELECT")

# SQL vectors are always passed through as is
var_name <- SQL("SELECT")
var_name
```

```

dbQuoteIdentifier(ANSI(), var_name)
dbQuoteString(ANSI(), var_name)

# This mechanism is used to prevent double escaping
dbQuoteString(ANSI(), dbQuoteString(ANSI(), "SELECT"))

```

sqlAppendTable	<i>Compose query to insert rows into a table</i>
----------------	--

Description

sqlAppendTable() generates a single SQL string that inserts a data frame into an existing table. sqlAppendTableTemplate() generates a template suitable for use with dbBind(). The default methods are ANSI SQL 99 compliant. These methods are mostly useful for backend implementers.

Usage

```

sqlAppendTable(con, table, values, row.names = NA, ...)

sqlAppendTableTemplate(con, table, values, row.names = NA, prefix = "?",
  ..., pattern = "")

```

Arguments

con	A database connection.
table	Name of the table. Escaped with dbQuoteIdentifier().
values	A data frame. Factors will be converted to character vectors. Character vectors will be escaped with dbQuoteString().
row.names	Either TRUE, FALSE, NA or a string. If TRUE, always translate row names to a column called "row_names". If FALSE, never translate row names. If NA, translate rownames only if they're a character vector. A string is equivalent to TRUE, but allows you to override the default name. For backward compatibility, NULL is equivalent to FALSE.
...	Other arguments used by individual methods.
prefix	Parameter prefix to use for placeholders.
pattern	Parameter pattern to use for placeholders: <ul style="list-style-type: none"> • "": no pattern • "1": position • anything else: field name

Details

The row.names argument must be passed explicitly in order to avoid a compatibility warning. The default will be changed in a later release.

Examples

```
sqlAppendTable(ANSI(), "iris", head(iris))

sqlAppendTable(ANSI(), "mtcars", head(mtcars))
sqlAppendTable(ANSI(), "mtcars", head(mtcars), row.names = FALSE)
sqlAppendTableTemplate(ANSI(), "iris", iris)

sqlAppendTableTemplate(ANSI(), "mtcars", mtcars)
sqlAppendTableTemplate(ANSI(), "mtcars", mtcars, row.names = FALSE)
```

sqlCreateTable	<i>Compose query to create a simple table</i>
----------------	---

Description

Exposes an interface to simple CREATE TABLE commands. The default method is ANSI SQL 99 compliant. This method is mostly useful for backend implementers.

Usage

```
sqlCreateTable(con, table, fields, row.names = NA, temporary = FALSE, ...)
```

Arguments

con	A database connection.
table	Name of the table. Escaped with <code>dbQuoteIdentifier()</code> .
fields	Either a character vector or a data frame. A named character vector: Names are column names, values are types. Names are escaped with <code>dbQuoteIdentifier()</code> . Field types are unescaped. A data frame: field types are generated using <code>dbDataType()</code> .
row.names	Either TRUE, FALSE, NA or a string. If TRUE, always translate row names to a column called "row_names". If FALSE, never translate row names. If NA, translate rownames only if they're a character vector. A string is equivalent to TRUE, but allows you to override the default name. For backward compatibility, NULL is equivalent to FALSE.
temporary	If TRUE, will generate a temporary table statement.
...	Other arguments used by individual methods.

Details

The row.names argument must be passed explicitly in order to avoid a compatibility warning. The default will be changed in a later release.

Examples

```
sqlCreateTable(ANSI(), "my-table", c(a = "integer", b = "text"))
sqlCreateTable(ANSI(), "my-table", iris)

# By default, character row names are converted to a row_names column
sqlCreateTable(ANSI(), "mtcars", mtcars[, 1:5])
sqlCreateTable(ANSI(), "mtcars", mtcars[, 1:5], row.names = FALSE)
```

sqlData

Convert a data frame into form suitable for upload to an SQL database

Description

This is a generic method that coerces R objects into vectors suitable for upload to the database. The output will vary a little from method to method depending on whether the main upload device is through a single SQL string or multiple parameterized queries. This method is mostly useful for backend implementers.

Usage

```
sqlData(con, value, row.names = NA, ...)
```

Arguments

con	A database connection.
value	A data frame
row.names	Either TRUE, FALSE, NA or a string. If TRUE, always translate row names to a column called "row_names". If FALSE, never translate row names. If NA, translate rownames only if they're a character vector. A string is equivalent to TRUE, but allows you to override the default name. For backward compatibility, NULL is equivalent to FALSE.
...	Other arguments used by individual methods.

Details

The default method:

- Converts factors to characters
- Quotes all strings
- Converts all columns to strings
- Replaces NA with NULL

Examples

```
con <- dbConnect(RSQLite::SQLite(), ":memory:")

sqlData(con, head(iris))
sqlData(con, head(mtcars))

dbDisconnect(con)
```

sqlInterpolate	<i>Safely interpolate values into an SQL string</i>
----------------	---

Description

Safely interpolate values into an SQL string

Usage

```
sqlInterpolate(conn, sql, ..., .dots = list())
```

Arguments

conn	A database connection.
sql	A SQL string containing variables to interpolate. Variables must start with a question mark and can be any valid R identifier, i.e. it must start with a letter or ., and be followed by a letter, digit, . or _.
..., .dots	Named values (for ...) or a named list (for .dots) to interpolate into a string. All strings will be first escaped with <code>dbQuoteString()</code> prior to interpolation to protect against SQL injection attacks.

Backend authors

If you are implementing an SQL backend with non-ANSI quoting rules, you'll need to implement a method for `sqlParseVariables()`. Failure to do so does not expose you to SQL injection attacks, but will (rarely) result in errors matching supplied and interpolated variables.

Examples

```
sql <- "SELECT * FROM X WHERE name = ?name"
sqlInterpolate(ANSI(), sql, name = "Hadley")

# This is safe because the single quote has been double escaped
sqlInterpolate(ANSI(), sql, name = "H'); DROP TABLE--;")
```

transactions

Begin/commit/rollback SQL transactions

Description

A transaction encapsulates several SQL statements in an atomic unit. It is initiated with `dbBegin()` and either made persistent with `dbCommit()` or undone with `dbRollback()`. In any case, the DBMS guarantees that either all or none of the statements have a permanent effect. This helps ensuring consistency of write operations to multiple tables.

Usage

```
dbBegin(conn, ...)
```

```
dbCommit(conn, ...)
```

```
dbRollback(conn, ...)
```

Arguments

<code>conn</code>	A DBIConnection object, as returned by <code>dbConnect()</code> .
<code>...</code>	Other parameters passed on to methods.

Details

Not all database engines implement transaction management, in which case these methods should not be implemented for the specific [DBIConnection](#) subclass.

Value

`dbBegin()`, `dbCommit()` and `dbRollback()` return `TRUE`, invisibly. The implementations are expected to raise an error in case of failure, but this is not tested. In any way, all generics throw an error with a closed or invalid connection. In addition, a call to `dbCommit()` or `dbRollback()` without a prior call to `dbBegin()` raises an error. Nested transactions are not supported by DBI, an attempt to call `dbBegin()` twice yields an error.

Specification

Actual support for transactions may vary between backends. A transaction is initiated by a call to `dbBegin()` and committed by a call to `dbCommit()`. Data written in a transaction must persist after the transaction is committed. For example, a record that is missing when the transaction is started but is created during the transaction must exist both during and after the transaction, and also in a new connection.

A transaction can also be aborted with `dbRollback()`. All data written in such a transaction must be removed after the transaction is rolled back. For example, a record that is missing when the transaction is started but is created during the transaction must not exist anymore after the rollback.

Disconnection from a connection with an open transaction effectively rolls back the transaction. All data written in such a transaction must be removed after the transaction is rolled back.

The behavior is not specified if other arguments are passed to these functions. In particular, **RSQLite** issues named transactions with support for nesting if the name argument is set.

The transaction isolation level is not specified by DBI.

See Also

Self-contained transactions: [dbWithTransaction\(\)](#)

Examples

```
con <- dbConnect(RSQLite::SQLite(), ":memory:")

dbWriteTable(con, "cash", data.frame(amount = 100))
dbWriteTable(con, "account", data.frame(amount = 2000))

# All operations are carried out as logical unit:
dbBegin(con)
withdrawal <- 300
dbExecute(con, "UPDATE cash SET amount = amount + ?", list(withdrawal))
dbExecute(con, "UPDATE account SET amount = amount - ?", list(withdrawal))
dbCommit(con)

dbReadTable(con, "cash")
dbReadTable(con, "account")

# Rolling back after detecting negative value on account:
dbBegin(con)
withdrawal <- 5000
dbExecute(con, "UPDATE cash SET amount = amount + ?", list(withdrawal))
dbExecute(con, "UPDATE account SET amount = amount - ?", list(withdrawal))
if (dbReadTable(con, "account")$amount >= 0) {
  dbCommit(con)
} else {
  dbRollback(con)
}

dbReadTable(con, "cash")
dbReadTable(con, "account")

dbDisconnect(con)
```

Index

- as.character(), [12](#)
- as.Date(), [21](#)
- as.integer(), [12](#)
- as.numeric(), [12](#)
- as.POSIXct(), [22](#)

- blob::blob, [7](#), [14](#), [55](#)

- character, [7](#), [14](#), [21](#), [39](#), [41](#), [42](#)

- data.frame, [7](#), [21](#), [25](#), [54](#)
- Date, [7](#), [22](#)
- Dates, [14](#)
- DateTimeClasses, [14](#)
- dbAppendTable, [4](#), [13](#), [15](#), [16](#), [19](#), [20](#), [23](#), [24](#),
[26](#), [30](#), [33](#), [34](#), [36–38](#), [44](#), [46](#), [47](#), [49](#),
[55](#)
- dbBegin (transactions), [64](#)
- dbBegin(), [52](#)
- dbBind, [5](#), [9](#), [11](#), [22](#), [24](#), [27–29](#), [32–34](#), [40–42](#),
[51](#)
- dbBind(), [18](#), [25](#), [47](#), [49](#), [60](#)
- dbBreak (dbWithTransaction), [51](#)
- dbCanConnect, [8](#), [12](#), [15](#), [17](#), [24](#), [31](#), [33–35](#)
- dbCanConnect(), [11](#)
- dbClearResult, [7](#), [9](#), [11](#), [22](#), [24](#), [27–29](#),
[32–34](#), [40–42](#), [51](#)
- dbClearResult(), [6](#), [7](#), [18](#), [22](#), [24](#), [26–29](#), [33](#),
[34](#), [46–49](#)
- dbColumnInfo, [7](#), [9](#), [10](#), [22](#), [24](#), [27–29](#), [32–34](#),
[40–42](#), [51](#)
- dbColumnInfo(), [36](#)
- dbCommit (transactions), [64](#)
- dbCommit(), [52](#)
- dbConnect, [9](#), [11](#), [15](#), [17](#), [24](#), [31](#), [33–35](#)
- dbConnect(), [4](#), [5](#), [8](#), [13](#), [16](#), [18](#), [19](#), [23](#), [25](#),
[35](#), [36](#), [38](#), [43](#), [45](#), [46](#), [48](#), [52](#), [53](#), [64](#)
- dbCreateTable, [5](#), [13](#), [15](#), [16](#), [19](#), [20](#), [23](#), [24](#),
[26](#), [30](#), [33](#), [34](#), [36–38](#), [44](#), [46](#), [47](#), [49](#),
[55](#)
- dbCreateTable(), [4](#)
- dbDataType, [5](#), [9](#), [12](#), [13](#), [14](#), [16](#), [17](#), [19](#), [20](#),
[23](#), [24](#), [26](#), [30](#), [31](#), [33–38](#), [44](#), [46](#), [47](#),
[49](#), [55](#)
- dbDataType(), [13](#), [14](#), [55](#), [61](#)
- dbDisconnect, [5](#), [13](#), [15](#), [15](#), [19](#), [20](#), [23](#), [24](#),
[26](#), [30](#), [33](#), [34](#), [36–38](#), [44](#), [46](#), [47](#), [49](#),
[55](#)
- dbDisconnect(), [4](#), [12](#), [33](#)
- dbDriver, [9](#), [12](#), [15](#), [16](#), [24](#), [31](#), [33–35](#)
- dbExecute, [5](#), [13](#), [15](#), [16](#), [18](#), [20](#), [23](#), [24](#), [26](#),
[30](#), [33](#), [34](#), [36–38](#), [44](#), [46](#), [47](#), [49](#), [55](#)
- dbExecute(), [4](#), [13](#), [25](#), [26](#), [47](#), [48](#)
- dbExistsTable, [5](#), [13](#), [15](#), [16](#), [19](#), [19](#), [23](#), [24](#),
[26](#), [30](#), [33](#), [34](#), [36–38](#), [44](#), [46](#), [47](#), [49](#),
[55](#)
- dbExistsTable(), [37](#), [45](#)
- dbFetch, [7](#), [9](#), [11](#), [20](#), [24](#), [27–29](#), [32–34](#),
[40–42](#), [51](#)
- dbFetch(), [5–7](#), [10](#), [24](#), [26](#), [27](#), [29](#), [46](#), [47](#)
- dbGetException, [5](#), [13](#), [15](#), [16](#), [19](#), [20](#), [23](#), [24](#),
[26](#), [30](#), [33](#), [34](#), [36–38](#), [44](#), [46](#), [47](#), [49](#),
[55](#)
- dbGetInfo, [5](#), [7](#), [9](#), [11–13](#), [15–17](#), [19](#), [20](#), [22](#),
[23](#), [23](#), [26–38](#), [40–42](#), [44](#), [46](#), [47](#), [49](#),
[51](#), [55](#)
- dbGetInfo(), [31](#)
- dbGetQuery, [5](#), [13](#), [15](#), [16](#), [19](#), [20](#), [23](#), [24](#), [24](#),
[30](#), [33](#), [34](#), [36–38](#), [44](#), [46](#), [47](#), [49](#), [55](#)
- dbGetQuery(), [4](#), [18](#), [19](#), [39](#), [43](#), [46](#), [49](#)
- dbGetRowCount, [7](#), [9](#), [11](#), [22](#), [24](#), [26](#), [28](#), [29](#),
[32–34](#), [40–42](#), [51](#)
- dbGetRowCount(), [6](#), [24](#)
- dbGetRowsAffected, [7](#), [9](#), [11](#), [22](#), [24](#), [27](#), [27](#),
[28](#), [29](#), [32–34](#), [40–42](#), [51](#)
- dbGetRowsAffected(), [5–7](#), [18](#), [24](#), [48](#), [49](#)
- dbGetStatement, [7](#), [9](#), [11](#), [22](#), [24](#), [27](#), [28](#), [28](#),
[29](#), [32–34](#), [40–42](#), [51](#)
- dbGetStatement(), [24](#)

- dbHasCompleted, 7, 9, 11, 22, 24, 27, 28, 29, 32–34, 40–42, 51
- dbHasCompleted(), 6, 24
- DBI (DBI-package), 3
- DBI-package, 3
- DBIConnection, 3, 5, 8, 11, 13, 14, 16, 18, 19, 23, 25, 33, 35, 36, 38–40, 42, 43, 45, 46, 48, 50, 52, 53, 64
- DBIConnection-class, 30
- DBIDriver, 3, 4, 8, 11, 14, 23, 33, 34
- DBIDriver-class, 31
- DBIObject, 23, 33
- DBIObject-class, 31
- DBIResult, 3, 5, 6, 9, 10, 21, 23, 26–29, 33, 47, 49
- DBIResult-class, 32
- dbIsReadOnly, 5, 7, 9, 11–13, 15–17, 19, 20, 22–24, 26–32, 32, 34–38, 40–42, 44, 46, 47, 49, 51, 55
- dbIsValid, 5, 7, 9, 11–13, 15–17, 19, 20, 22–24, 26–33, 33, 35–38, 40–42, 44, 46, 47, 49, 51, 55
- dbIsValid(), 6
- dbListConnections, 9, 12, 15, 17, 24, 31, 33, 34, 34
- dbListFields, 5, 13, 15, 16, 19, 20, 23, 24, 26, 30, 33, 34, 35, 37, 38, 44, 46, 47, 49, 55
- dbListObjects, 5, 13, 15, 16, 19, 20, 23, 24, 26, 30, 33, 34, 36, 36, 38, 44, 46, 47, 49, 55
- dbListObjects(), 35
- dbListResults, 5, 13, 15, 16, 19, 20, 23, 24, 26, 30, 33, 34, 36, 37, 37, 38, 44, 46, 47, 49, 55
- dbListTables, 5, 13, 15, 16, 19, 20, 23, 24, 26, 30, 33, 34, 36–38, 38, 44, 46, 47, 49, 55
- dbListTables(), 20, 36, 37, 45
- dbQuoteIdentifier, 7, 9, 11, 22, 24, 27–29, 32–34, 39, 41, 42, 51
- dbQuoteIdentifier(), 5, 13, 20, 35–37, 43–46, 50, 51, 53, 54, 56, 59–61
- dbQuoteLiteral, 7, 9, 11, 22, 24, 27–29, 32–34, 40, 40, 42, 51
- dbQuoteString, 7, 9, 11, 22, 24, 27–29, 32–34, 40, 41, 42, 51
- dbQuoteString(), 56, 59, 60, 63
- dbReadTable, 5, 13, 15, 16, 19, 20, 23, 24, 26, 30, 33, 34, 36–38, 43, 46, 47, 49, 55
- dbReadTable(), 4, 54
- dbRemoveTable, 5, 13, 15, 16, 19, 20, 23, 24, 26, 30, 33, 34, 36–38, 44, 45, 47, 49, 55
- dbRollback (transactions), 64
- dbRollback(), 52
- dbSendQuery, 5, 13, 15, 16, 19, 20, 23, 24, 26, 30, 33, 34, 36–38, 44, 46, 46, 49, 55
- dbSendQuery(), 5, 6, 9, 19, 21, 24, 26–29, 33, 49
- dbSendStatement, 5, 13, 15, 16, 19, 20, 23, 24, 26, 30, 33, 34, 36–38, 44, 46, 47, 48, 55
- dbSendStatement(), 5, 6, 9, 18, 21, 26–29, 33, 47, 49
- dbUnloadDriver (dbDriver), 16
- dbUnquoteIdentifier, 7, 9, 11, 22, 24, 27–29, 32–34, 40–42, 50
- dbUnquoteIdentifier(), 36, 37, 39
- dbWithTransaction, 51
- dbWithTransaction(), 65
- dbWriteTable, 5, 13, 15, 16, 19, 20, 23, 24, 26, 30, 33, 34, 36–38, 44, 46, 47, 49, 53
- dbWriteTable(), 4, 36, 38, 45
- difftime, 14
- factor, 7, 15
- fetch (dbFetch), 20
- format(), 11
- hms::as.hms(), 21
- I(), 14
- Id, 37, 39, 50
- Id (Id-class), 56
- Id-class, 56
- Inf, 21, 25
- integer, 7, 14, 21
- is.na(), 41, 42
- isSQLKeyword (make.db.names), 56
- logical, 7, 14, 21
- make.db.names, 56
- make.db.names(), 58
- NA, 7, 21

NULL, [21](#)
numeric, [7](#), [14](#), [21](#)

on.exit(), [6](#)
ordered, [15](#)

POSIXct, [7](#), [22](#)
POSIXlt, [7](#)

raw, [7](#), [14](#), [21](#)
rbind(), [7](#)
rownames, [43](#), [55](#), [58](#)

SQL, [39](#), [41](#), [42](#), [50](#), [59](#)
SQL(), [51](#)
SQL-class (SQL), [59](#)
sqlAppendTable, [60](#)
sqlAppendTable(), [4](#)
sqlAppendTableTemplate
 (sqlAppendTable), [60](#)
sqlAppendTableTemplate(), [4](#)
sqlColumnToRownames (rownames), [58](#)
sqlColumnToRownames(), [43](#)
sqlCreateTable, [61](#)
sqlCreateTable(), [13](#)
sqlData, [62](#)
sqlInterpolate, [63](#)
SQLKeywords (make.db.names), [56](#)
sqlParseVariables(), [63](#)
sqlRownamesToColumn (rownames), [58](#)
sqlRownamesToColumn(), [5](#), [13](#), [55](#)
summary(), [31](#)

transactions, [52](#), [64](#)