

Package ‘MCMC.qpcr’

February 4, 2019

Type Package

Title Bayesian Analysis of qRT-PCR Data

Version 1.2.3

Date 2016-11-07

Author Mikhail V. Matz

Maintainer Mikhail V. Matz <matz@utexas.edu>

Description Quantitative RT-PCR data are analyzed using generalized linear mixed models based on lognormal-Poisson error distribution, fitted using MCMC. Control genes are not required but can be incorporated as Bayesian priors or, when template abundances correlate with conditions, as trackers of global effects (common to all genes). The package also implements a lognormal model for higher-abundance data and a “classic” model involving multi-gene normalization on a by-sample basis. Several plotting functions are included to extract and visualize results. The detailed tutorial is available here: <<http://bit.ly/1Nwo4CB>>.

License GPL-3

Depends MCMCglmm,ggplot2,coda

NeedsCompilation no

Repository CRAN

Date/Publication 2016-11-09 23:56:55

R topics documented:

MCMC.qpcr-package	2
amp.eff	3
beckham.data	4
beckham.eff	5
coral.stress	6
cq2counts	7
cq2genorm	8
cq2log	9
diagnostic.mcmc	10
dilutions	11
getNormalizedData	12

HPDplot	13
HPDplotBygene	16
HPDplotBygeneBygroup	18
HPDpoints	19
HPDsummary	21
mcmc.converge.check	23
mcmc.pval	24
mcmc.qpcr	24
mcmc.qpcr.classic	27
mcmc.qpcr.lognormal	29
normalize.qpcr	30
outlierSamples	31
padj.qpcr	32
PrimEff	33
softNorm	34
summaryPlot	35
trellisByGene	36

Index	38
--------------	-----------

MCMC.qpcr-package

Bayesian analysis of qRT-PCR data

Description

This package implements generalized linear mixed model analysis of qRT-PCR data so that the increase of variance towards higher Ct values is properly dealt with, and the lack of amplification is informative (function `mcmc.qpcr`). Sample-loading effects, gene-specific variances, and responses of all genes to each factor combination are all jointly estimated within a single model. The control genes can be specified as priors, with adjustable degree of expected stability. The analysis also works well without any control gene specifications.

For higher-abundance datasets, a lognormal model is implemented that does not require Cq to counts conversion (function `mcmc.qpcr.lognormal`).

For higher-abundance datasets in which the quality and/or quantity of RNA samples varies systematically (rather than randomly) across conditions, the analysis based on multigene normalization is implemented (function `mcmc.qpcr.classic`).

The package includes several functions for plotting the results and calculating statistical significance (HPDplot, HPDplotBygene, HPDplotBygeneBygroup).

The detailed step-by-step tutorial is here: http://www.bio.utexas.edu/research/matz_lab/matzlab/Methods_files/mcmc.qpcr.tu

Details

Package: MCMC.qpcr

Type: Package

Version: 1.2.3

Date: 2016-11-07

License: GPL-3

Author(s)

Mikhail V. Matz, University of Texas at Austin <matz@utexas.edu>

References

Matz MV, Wright RM, Scott JG (2013) No Control Genes Required: Bayesian Analysis of qRT-PCR Data. PLoS ONE 8(8): e71448. doi:10.1371/journal.pone.0071448

Examples

```

data(beckham.data)
data(beckham.eff)

# analysing the first 5 genes
# (to try it with all 10 genes, change the line below to gcol=4:13)
gcol=4:8
ccol=1:3 # columns containing experimental conditions

# recalculating into molecule counts, reformatting
qs=cq2counts(data=beckham.data,genecols=gcol,
condcols=ccol,effic=beckham.eff,Cq1=37)

# creating a single factor, 'treatment.time', out of 'tr' and 'time'
qs$treatment.time=as.factor(paste(qs$tr,qs$time,sep="."))

# fitting a naive model
naive=mcmc.qpcr(
fixed="treatment.time",
data=qs,
nitt=3000,burnin=2000 # remove this line in actual analysis!
)

#summary plot of inferred abundances
#s1=HPDsummary(model=naive,data=qs)

#summary plot of fold-changes relative to the global control
s0=HPDsummary(model=naive,data=qs,relative=TRUE)

# pairwise differences and their significances for each gene:
s0$geneWise

```

Description

Fold-amplification within each PCR cycle for each qRT-PCR assay. Determined by qPCR of serial dilutions of the template (see Pfaffl 2001, Nucleic Acids Res 29:00)

Usage

```
data(amp.eff)
```

Format

A data frame with 17 observations on the following 3 variables.

gene a factor with levels actin adk c3 chrom clect eif3h g3pdh gsp2 hsp16 hsp60 hsp90 nd5
r18s rp111 spon2 tgo1n ubl3

efficiency a numeric vector

Cq1 a numeric vector

Examples

```
data(amp.eff)
```

beckham.data

Cellular heat stress response data.

Description

A typical qRT-PCR dataset where a series of treatments are compared to the global control.

Usage

```
data(beckham.data)
```

Format

A data frame with 45 observations on the following 13 variables.

sample cDNA sample (biological replicate): a factor with levels a b c d e f g h i j k l m n o

tr treatment: a factor with levels ct1:control hs:heat stress pshs:pre-stress followed by heat stress

time hours of heat stress exposure: a numeric vector

gapdh a numeric vector

hsp110 a numeric vector

hspb a numeric vector

egr a numeric vector

gadd a numeric vector

dnajb1 a numeric vector

dnajb4 a numeric vector
atf a numeric vector
dnaja4 a numeric vector
fos a numeric vector

Details

Includes global control (ctl), heat stressed cells (hs), and cells pre-stressed by mild heating prior to heat stress (pshs). Two time points: one hour and three hours.

Source

data for Figure 6 in Beckham et al. Microarray analysis of cellular thermotolerance. Lasers Surg Med. 2010 Dec;42(10):752-65. doi: 10.1002/lsm.20983

Examples

```
data(beckham.data)
```

beckham.eff

amplification efficiencies for beckham.data

Description

amplification efficiencies for beckham.data

Usage

```
data(beckham.eff)
```

Format

A data frame with 11 observations on the following 2 variables.

gene a factor with levels atf dnaja4 dnajb1 dnajb4 egr fos gadd gapdh hsp110 hspb r18s
eficiency a numeric vector

Source

Beckham et al. Microarray analysis of cellular thermotolerance. Lasers Surg Med. 2010 Dec;42(10):752-65. doi: 10.1002/lsm.20983

Examples

```
data(beckham.eff)
```

`coral.stress`*RT-qPCR of stress response in coral *Porites astreoides**

Description

Timepoint one is one day of heat-light stress; timepoint two is recovery from it the next day. Controls are the fragments never exposed to stress. Individual denotes a coral colony that yielded several fragments for different treatments.

Usage

```
data(coral.stress)
```

Format

A data frame with 64 observations on the following 19 variables.

`sample` a numeric vector

`individual` a factor with levels s1 s12 s13 s15 s2 s4 s5 s8

`condition` a factor with levels control heat

`timepoint` a factor with levels one two

`hsp16` a numeric vector

`actin` a numeric vector

`adk` a numeric vector

`c3` a numeric vector

`chrom` a numeric vector

`clect` a numeric vector

`EIF3H` a numeric vector

`G3PDH` a numeric vector

`GSP2` a numeric vector

`HSP60` a numeric vector

`HSP90` a numeric vector

`ND5` a numeric vector

`RP111` a numeric vector

`SPON2` a numeric vector

`UB13` a numeric vector

Examples

```
data(coral.stress)
```

cq2counts	<i>Prepares qRT-PCR data for mcmc.qpcr analysis</i>
-----------	---

Description

Converts Cq values into molecule counts, and stacks the dataset

Usage

```
cq2counts(data, genecols, condcols, effc, Cq1 = NULL)
```

Arguments

data	Raw qRT-PCR dataset, one Cq column per gene, plus columns containing factors. The Cq columns, in addition to the proper Cq values, may contain NA (missing data) and -1, which means no amplification observed (i.e., zero target molecules at the start of qPCR reaction). Column headers are either gene names or factor names. Any number of fixed factors is allowed; any number of random factors that are gene-specific scalars (such as effect of genotype, or block) Must have a column called "sample", denoting individual cDNA preps. Technical replicates should not be averaged, they should be represented as independent rows with the same sample ID.
genecols	columns that contain Cq data
condcols	columns corresponding to factors, including "sample" factor
effc	The PCR efficiency data for each of the analyzed genes. This is data frame with two columns: gene name (must exactly match the headers of gene columns in Cq data table!) and efficiency (fold- amplification per PCR cycle, determined from qPCR of serial dilutions; see PrimEff() function)
Cq1	The Cq of a single molecule. If left unspecified, it will be calculated from the efficiency (E) using approximate formula $Cq1=51.6-7.56 * E$, derived empirically for Roche's LightCycler 480. Cq1 does not seem to have much effect on relative quantification results unless it is wildly off (by 2-3 cycles). For an unknown qPCR instrument a single $Cq1=37$ could be assumed for all genes. Note: If all experimental Cq values are less than 30, Cq1 variation (within a reasonable range, 35-39) will not have any effect on the results whatsoever, so just go for $Cq1=37$.

Value

Returns a dataframe with a single response variable column ("count"), gene column ("gene") and several columns containing factors.

Note: The purpose of Cq to counts conversion is to enable generalized linear model analysis, which would take care of the heteroscedasticity and occasional 'empty' amplification trials for low-abundant targets. Although this works well, the absolute values of molecule counts returned by cq2counts are still approximate, so they should not be relied upon for true single-molecule analysis.

Author(s)

Mikhail V. Matz, UT Austin <matz@utexas.edu>

References

Matz MV, Wright RM, Scott JG (2013) No Control Genes Required: Bayesian Analysis of qRT-PCR Data. PLoS ONE 8(8): e71448. doi:10.1371/journal.pone.0071448

Examples

```
data(coral.stress)
data(amp.eff)
genecolumns=c(5:19) # specifying where the Ct data are in the data table
conditions=c(1:4) # specifying data table columns containing factors
# calculating molecule counts and reformatting:
dd=cq2counts(data=coral.stress,genecols=genecolumns,
condcols=conditions,effic=amp.eff,Cq1=37)
```

cq2genorm

Reformats raw Ct data for geNorm analysis (non-parametric selection of stable control genes) as implemented in selectHKgenes function (package SLqPCR)

Description

Does similar procedures as cq2log, but in the end converts the data into relative expression values, leaves it unstacked, and removes factor columns.

Usage

```
cq2genorm(data, genes, effic, noamp=38)
```

Arguments

data	raw qRT-PCR data; see help for cq2counts for details on formatting
genes	Vector of names of the potential control genes. Make sure you select only the potential control genes for this analysis, otherwise geNorm might prefer actual responsive genes if they co-vary and have very low variance.
effic	PCR efficiency data for each of the analyzed genes; see help for cq2counts for details on formatting.
noamp	what to do about Ct values '-1', denoting no amplification. By default, these will be assigned an arbitrarily low expression value corresponding to slightly less than one molecule. Specify 'noamp=NA' if you want to skip samples containing any of these.

Details

See cq2counts help page for details.

Value

A dataset to be fed into the function selectHKgenes (package SLqPCR).

Author(s)

Mikhail V. Matz, UT Austin

References

Matz MV, Wright RM, Scott JG (2013) No Control Genes Required: Bayesian Analysis of qRT-PCR Data. PLoS ONE 8(8): e71448. doi:10.1371/journal.pone.0071448

cq2log	<i>Prepares qRT-PCR data for mcmc.qpcr analysis using lognormal and "classic" (normalization-based) models</i>
--------	--

Description

Log-transforms and efficiency-corrects Cq values, converting them to natural logs fo relative abundances, and stacks the dataset

Usage

```
cq2log(data, genecols, condcols, effic, noamp = 38)
```

Arguments

data	Raw qRT-PCR dataset, one Cq column per gene, plus columns containing factors. The Cq columns, in addition to the proper Cq values, may contain NA (missing data) and -1, which means no amplification observed (i.e., zero target molecules at the start of qPCR reaction). Column headers are either gene names or factor names. Any number of fixed factors is allowed; any number of random factors that are gene-specific scalars (such as effect of genotype, or block) Must have a column called "sample", denoting individual cDNA preps. Technical replicates should not be averaged, they should be represented as independent rows with the same sample ID.
genecols	columns containing Cq data
condcols	columns corresponding to factors, including "sample" factor
effic	The PCR efficiency data for each of the analyzed genes. This is data frame with two columns: gene name (must exactly match the headers of gene columns in Cq data table!) and efficiency (fold- amplification per PCR cycle, determined from qPCR of serial dilutions; see PrimEff() function)

noamp Value to replace instances of no amplification with. These instances would be coded by -1 in the data table. Specify 'noamp=NA' if you want to disregard them, but by default they will be converted into an arbitrarily low value, 38

Details

The models that process cq2log output are expected to work well for datasets that don't have too many Cq values above 30 and don't have instances of no amplification. For examples, see cq2counts function.

Value

Returns a dataframe with a single response variable column ("count", even though it is actually a log-transformed relative abundance value), gene column ("gene") and several columns containing factors.

Author(s)

Mikhail V. Matz, UT Austin

References

Matz MV, Wright RM, Scott JG (2013) No Control Genes Required: Bayesian Analysis of qRT-PCR Data. PLoS ONE 8(8): e71448. doi:10.1371/journal.pone.0071448

diagnostic.mcmc	<i>Plots three diagnostic plots to check the validity of the assumptions of linear model analysis.</i>
-----------------	--

Description

Predicted vs observed plot tests for linearity, Scale-location plot tests for homoscedasticity, and Normal QQ plot tests for normality of the residuals.

Usage

```
diagnostic.mcmc(model, ...)
```

Arguments

model	MCMCglmm object (a model fitted by mcmc.qpcr or mcmc.qpcr.gauss), obtained with additional options, 'pl=T, pr=T'
...	Various plot() options to modify color, shape and size of the plotted points.

Value

A plot with three panels.

Author(s)

Mikhail V. Matz, UT Austin <matz@utexas.edu>

References

Matz MV, Wright RM, Scott JG (2013) No Control Genes Required: Bayesian Analysis of qRT-PCR Data. PLoS ONE 8(8): e71448. doi:10.1371/journal.pone.0071448

Examples

```
# loading Cq data and amplification efficiencies
data(coral.stress)
data(amp.eff)
# extracting a subset of data
cs.short=subset(coral.stress, timepoint=="one")

genecolumns=c(5,6,16,17) # specifying columns corresponding to genes of interest
conditions=c(1:4) # specifying columns containing factors

# calculating molecule counts and reformatting:
dd=cq2counts(data=cs.short,genecols=genecolumns,
condcols=conditions,effic=amp.eff,Cq1=37)

# fitting the model
mm=mcmc.qpcr(
fixed="condition",
data=dd,
controls=c("nd5","rpl11"),
pr=TRUE,pl=TRUE, # these flags are necessary for diagnostics
nitt=4000 # remove this line when analyzing real data!
)
diagnostic.mcmc(mm)
```

dilutions

Data to determine amplification efficiency

Description

Cq data for a series of four-fold dilutions for two targets; the input for PrimEff()

Usage

```
data(dilutions)
```

Format

A data frame with 76 observations on the following 3 variables.

dna a numeric vector

cq a numeric vector

gene a factor with levels chrom eif3h

Examples

```
data(dilutions)
PrimEff(dilutions)
```

getNormalizedData	<i>Extracts qPCR model predictions</i>
-------------------	--

Description

Generates a table of model-derived log₂-transformed transcript abundances without global sample effects (i.e., corresponding to efficiency-corrected and normalized qPCR data)

Usage

```
getNormalizedData(model, data, controls=NULL)
```

Arguments

model	qPCR model: the output of <code>mcmc.qpcr</code> or <code>mcmc.qpcr.lognormal</code> function fitted with two additional options: <code>random="sample"</code> , <code>pr=TRUE</code> . These options do not change the inferences of main effects but make it possible to retain among-sample variation of expression for each gene while still subtracting the global sample effects (i.e., perform "normalization")
data	The dataset that was analysed to generate the model (output of <code>cq2counts</code> or <code>cq2log</code> functions)
controls	List of control genes; required if the <code>mcmc.qpcr</code> model was fit with the option <code>normalize=TRUE</code>

Value

The function returns a list of two data frames. The first one, `normData`, is the model-predicted log₂-transformed transcript abundances table. It has one column per gene and one row per sample. The second data frame, `conditions`, is a table of experimental conditions corresponding to the `normData` table.

Author(s)

Mikhail V. Matz, University of Texas at Austin <matz@utexas.edu>

References

Matz MV, Wright RM, Scott JG (2013) No Control Genes Required: Bayesian Analysis of qRT-PCR Data. PLoS ONE 8(8): e71448. doi:10.1371/journal.pone.0071448

Examples

```
library(MCMC.qpcr)

# loading Cq data and amplification efficiencies
data(coral.stress)
data(amp.eff)

genecolumns=c(5,6,16,17) # specifying columns corresponding to genes of interest
conditions=c(1:4) # specifying columns containing factors

# calculating molecule counts and reformatting:
dd=cq2counts(data=coral.stress,genecols=genecolumns,
condcols=conditions,effic=amp.eff,Cq1=37)

# fitting the model (must include random="sample", pr=TRUE options)
mm=mcmc.qpcr(
fixed="condition",
data=dd,
controls=c("nd5","rp111"),
nitt=4000,
pr=TRUE,
random="sample"
)

# extracting model predictions
pp=getNormalizedData(mm,dd)

# here is the normalized data:
pp$normData

# and here are the corresponding conditions:
pp$conditions

# putting them together for plotting:
ppcombo=cbind(stack(pp$normData),rep(pp$conditions))
names(ppcombo)[1:2]=c("expression","gene")

# plotting boxplots of normalized data:
ggplot(ppcombo,aes(condition,expression,colour=timepoint))+
geom_boxplot()+
facet_wrap(~gene,scales="free")+
theme_bw()
```

Description

Calculates and plots posterior means with 95% credible intervals for specified fixed effects (or their combination) for all genes

Usage

```
HPDplot(model, factors, factors2 = NULL, ylimits = NULL,
         hpdtype = "w", inverse = FALSE, jitter = 0, plot = TRUE, grid = TRUE,
         zero = TRUE, ...)
```

Arguments

model	The output of mcmc.qpcr function.
factors	A vector of names of fixed effects of interest; see details.
factors2	A second vector of fixed effect names to be subtracted from the first; see details.
ylimits	Y-limits for the plot such as c(-3,6); autoscale by default.
hpdtype	Specify hpdtype="l" to plot the upper and lower 95% credible limits as a continuous dashed line across all genes. This is useful to compare credible intervals among several models on the same plot. By default (hpdtype="w") the limits are plotted as whiskers around each point.
inverse	Plot the inverse of the result.
jitter	For hpdtype="w", shifts the plotted values and whiskers by the specified distance along the x axis (reasonable jitter values are 0.15 or -0.15, for example). This helps plot several results (different models or factor combinations) on the same plot (use HPDpoints to add to existing plot)
plot	if plot = FALSE the function returns a table of calculated posterior modes, means, upper and lower 95% credible limits (all on log(2) scale), and two types of p-values: derived from Bayesian z-scores, and derived directly from MCMC sample. All such outputs for a given experiment should be concatenated with rbind and processed by padj.qpcr() function to adjust the p-values for multiple comparisons (disregarding the entries corresponding to control genes)
grid	Whether to draw vertical grid lines to separate genes.
zero	Whether to draw a horizontal line at 0.
...	Various plot() options; such as col (color of lines and symbols), pch (type of symbol), main (plot title) etc.

Details

Use summary(MCMCgImm object) first to see what fixed effect names are actually used in the output. For example, if summary shows:

```
gene1:conditionheat
gene2:conditionheat
....
gene1:timepointtwo
```

```
gene2:timepointtwo
....
gene1:conditionheat:timepointtwo
gene2:conditionheat:timepointtwo
```

, it is possible to specify `factors="conditionheat"` to plot only the effects of the heat.

If a vector of several fixed effect names is given, for example: `factors=c("timepointtwo","treatmentheat:timepointtwo")` the function will plot the posterior mean and credible interval for the sum of these effects.

If a second vector is also given, for example,
`factors=c("f1","f2")`, `factors2=c("f3","f4")`

the function will plot the difference between the sums of these two groups of factors. This is useful for pairwise analysis of differences in complicated designs.

Value

A plot or a table (`plot = F`).

Use the function `HPDpoints()` if you need to add graphs to already existing plot.

Author(s)

Mikhail V. Matz, UT Austin <matz@utexas.edu>

References

Matz MV, Wright RM, Scott JG (2013) No Control Genes Required: Bayesian Analysis of qRT-PCR Data. PLoS ONE 8(8): e71448. doi:10.1371/journal.pone.0071448

Examples

```
# loading Cq data and amplification efficiencies
data(coral.stress)
data(amp.eff)
# extracting a subset of data
cs.short=subset(coral.stress, timepoint=="one")

genecolumns=c(5,6,16,17) # specifying columns corresponding to genes of interest
conditions=c(1:4) # specifying columns containing factors

# calculating molecule counts and reformatting:
dd=cq2counts(data=cs.short,genecols=genecolumns,
condcols=conditions,effic=amp.eff,Cq1=37)

# fitting the model
mm=mcmc.qpcr(
fixed="condition",
data=dd,
controls=c("nd5","rpl11"),
nitt=3000,burnin=2000 # remove this line when analyzing real data!
)
```

```
# plotting log2(fold change) in response to heat stress for all genes
HPDplot(model=mm,factors="conditionheat",main="response to heat stress")
```

HPDplotBygene

Plots qPCR analysis results for individual genes.

Description

For a particular gene, plots model-predicted values (and credible intervals) for a series of specified fixed effect combinations ("conditions").

Usage

```
HPDplotBygene(model, gene, conditions, pval = "mcmc", newplot = T,
ylimits = NULL, inverse = F, jitter = 0, plot = T, yscale = "log2",
interval = "ci", grid = F, zero = F, ...)
```

Arguments

model	model object produced by MCMC.qpcr()
gene	name of the gene to plot
conditions	A list naming the conditions to plot and defining them as combination of fixed effects (See example below). '0' denotes gene-specific intercept.
pval	Type of p-value to report: 'mcmc' - MCMC-based (default), 'z' - based on Bayesian z-score. Use 'z' to approximate p-values lower than 2/[MCMC sample size] (with default MCMC.qpcr settings, this comes to 0.002)
newplot	When TRUE, a new plot should be created. When FALSE, or a graph will be added to an existing plot.
ylimits	Y-limits for the plot such as c(-3,6); autoscale by default.
inverse	When TRUE, the inverse of the data will be plotted.
jitter	Shifts the plotted values and whiskers by the specified distance along the x axis (reasonable jitter values are 0.15 or -0.15, for example). This helps plot several graphs on the same plot without overlapping.
plot	When FALSE, no plot will be generated; the function will just list mean pairwise differences and p-values.
yscale	Scale on which to represent the data. In all mcmc.qpcr models the model scale is natural logarithm, which I prefer to translate into log2 or log10 (if the differences are orders of magnitude) for better human readability. The default is 'log2'; other options are 'log10' and 'native' (no rescaling of the model data). There is also a beta-option 'proportion', which is not useful for qPCR. It was added to cannibalize HPDplotBygene function for plotting results of the model operating with arcsin-square root transformed proportions. With yscale="proportions", the plot will be on the original proportion scale but the tukey-like differences will still be reported on the asin(sqrt()) transformed scale.

interval	'ci' (default) will plot 95% credible limits of the posterior distribution, 'sd' will plot the mean plus/minus one standard deviation of the posterior.
grid	When TRUE, a vertical grid separating conditions will be added
zero	When TRUE, a y=0 line will be added.
...	Various plot() options.

Value

Generates a point-whiskers plot, lists pairwise mean differences between all conditions, calculates and lists pairwise p-values (not corrected for multiple testing).

Author(s)

Mikhail V. Matz, UT Austin, matz@utexas.edu

References

Matz MV, Wright RM, Scott JG (2013) No Control Genes Required: Bayesian Analysis of qRT-PCR Data. PLoS ONE 8(8): e71448. doi:10.1371/journal.pone.0071448

Examples

```
# loading Cq data and amplification efficiencies
data(coral.stress)
data(amp.eff)
# extracting a subset of data
cs.short=subset(coral.stress, timepoint=="one")

genecolumns=c(5,6,16,17) # specifying columns corresponding to genes of interest
conditions=c(1:4) # specifying columns containing factors

# calculating molecule counts and reformatting:
dd=cq2counts(data=cs.short,genecols=genecolumns,
condcols=conditions,effic=amp.eff,Cq1=37)

# fitting the model
mm=mcmc.qpcr(
fixed="condition",
data=dd,
controls=c("nd5","rpl11"),
nitt=3000,burnin=2000 # remove this line when analyzing real data!
)

# plotting abundances of individual genes across all conditions
# step 1: defining conditions
cds=list(
control=list(factors=0), # gene-specific intercept
stress=list(factors=c(0,"conditionheat")) # multiple effects will be summed up
)
```

```
# step 2: plotting gene after gene on the same panel
HPDplotBygene(model=mm, gene="actin", conditions=cds, col="cyan3",
pch=17, jitter=-0.1, ylim=c(-3.5, 15), pval="z")
HPDplotBygene(model=mm, gene="hsp16", conditions=cds,
newplot=FALSE, col="coral", pch=19, jitter=0.1, pval="z")

# step 3: adding legend
legend(0.5, 10, "actin", lty=1, col="cyan3", pch=17, bty="n")
legend(0.5, 7, "hsp16", lty=1, col="coral", pch=19, bty="n")
```

HPDplotBygeneBygroup *Plots qPCR analysis results for individual genes*

Description

For a specified gene, makes overlaid plots such as produced by HPDplotBygene()

Usage

```
HPDplotBygeneBygroup(model, gene, group1, group2, group3 = NULL,
interval = "ci", colors = c("coral", "cyan3", "grey50"),
symbols = c(19, 17, 15), jitter = 0.16, yscale = "log2", ...)
```

Arguments

model	model object produced by mcmc.qpcr()
gene	name of the gene to plot
group1	Combination of factors defining the first group (see HPDplotBygene() for details).
group2	Combination of factors defining the second group.
group3	(optional) Combination of factors defining the third group.
interval	'ci' (default) will plot 95% credible limits of the posterior distribution, 'sd' will plot the mean plus/minus one standard deviation of the posterior.
colors	Colors to use for different groups (see ?par -> col).
symbols	Symbols to use for different groups (see ?par -> pch).
jitter	Jitter distance between groups.
yscale	Scale on which to represent the data. In all mcmc.qpcr models the model scale is natural logarithm, which I prefer to translate into log2 or log10 (if the differences are orders of magnitude) for better human readability. The default is 'log2'; other options are 'log10' and 'native' (no rescaling of the model data). There is also a beta-option 'proportion', which is not useful for qPCR. It was added to cannibalize HPDplotBygene function for plotting results of the model operating with arcsin-square root transformed proportions. With yscale="proportions", the plot will be on the original proportion scale but the tukey-like differences will still be reported on the asin(sqrt()) transformed scale.

... additional parameters for HPDplotBygene() function, such as pval (see HPDplotBygene() help)

Value

Generates a point-whiskers plot, lists pairwise mean differences between all conditions, calculates and lists pairwise p-values (not corrected for multiple testing).

Author(s)

Mikhail V. Matz, UT Austin <matz@utexas.edu>

References

Matz MV, Wright RM, Scott JG (2013) No Control Genes Required: Bayesian Analysis of qRT-PCR Data. PLoS ONE 8(8): e71448. doi:10.1371/journal.pone.0071448

HPDpoints *HPDplot, HPDpoints*

Description

Calculates and plots posterior means with 95% credible intervals for specified fixed effects (or their combination) for all genes. HPDpoints only adds graphs to an existing plot.

Usage

```
HPDpoints(model, factors, factors2 = NULL, ylimits = NULL,
hpdtype = "w", inverse = F, jitter = 0, ...)
```

Arguments

model	The output of mcmc.qpcr function.
factors	A vector of names of fixed effects of interest; see details.
factors2	A second vector of fixed effect names to be subtracted from the first; see details.
ylimits	Y-limits for the plot such as c(-3,6); autoscale by default.
hpdtype	Specify hpdtype="l" to plot the upper and lower 95% credible limits as a continuous dashed line across all genes. By default (hpdtype="w") the limits are plotted as whiskers around each point.
inverse	Plot the inverse of the result.
jitter	For hpdtype="w", shifts the plotted values and whiskers by the specified distance along the x axis (reasonable jitter values are 0.15 or -0.15, for example).
...	Various plot() options; such as col (color of lines and symbols), pch (type of symbol), main (plot title) etc.

Details

See details in HPDplot()

Value

A graph added to a plot.

Author(s)

Mikhail V. Matz, UT Austin <matz@utexas.edu>

References

Matz MV, Wright RM, Scott JG (2013) No Control Genes Required: Bayesian Analysis of qRT-PCR Data. PLoS ONE 8(8): e71448. doi:10.1371/journal.pone.0071448

Examples

```
# loading Cq data and amplification efficiencies
data(coral.stress)
data(amp.eff)
# extracting a subset of data
cs.short=subset(coral.stress, timepoint=="one")

genecolumns=c(5,6,16,17) # specifying columns corresponding to genes of interest
conditions=c(1:4) # specifying columns containing factors

# calculating molecule counts and reformatting:
dd=cq2counts(data=cs.short,genecols=genecolumns,
condcols=conditions,effic=amp.eff,Cq1=37)

# fitting the model
mm=mcmc.qpcr(
fixed="condition",
data=dd,
controls=c("nd5","rpl11"),
nitt=4000 # remove this line when analyzing real data!
)

# plotting log2(fold change) in response to heat stress for all genes
HPDplot(model=mm,factors="conditionheat",main="response to heat stress")
```

HPDsummary

Summarizes and plots results of mcmc.qpcr function series.

Description

Calculates abundances of each gene across factor combinations; calculates pairwise differences between all factor combinations and their significances for each gene; plots results as bar or line graphs with credible intervals (ggplot2) NOTE: only works for experiments involving a single multi-level fixed factor or two fully crossed multi-level fixed factors.

Usage

```
HPDsummary(model, data, xgroup=NULL, genes = NA, relative = FALSE,
log.base = 2, summ.plot = TRUE, ptype="z", ...)
```

Arguments

model	Model generated by <code>mcmc.qpcr()</code> , <code>mcmc.qpcr.lognormal()</code> or <code>mcmc.qpcr.classic()</code>
data	Dataset used to build the model (returned by <code>cq2counts()</code> or <code>cq2log()</code>)
xgroup	The factor to form the x-axis of the plot. By default the first factor in the model will be used.
genes	A vector of gene names to summarize and plot. If left unspecified, all genes will be summarized.
relative	Whether to plot absolute transcript abundances (<code>relative = FALSE</code>) or fold-changes relative to the sample that is considered to be "global control" (<code>relative = TRUE</code>). The "global control" is the combination of factors that served as a reference during model fitting, either because it is alphanumerically first (that happens by default) or because it has been explicitly designated as such using <code>relevel()</code> function (see tutorial).
log.base	Base of the logarithm to use.
summ.plot	By default, the function generates a summary plot, which is a line-points-95% credible intervals plot of $\log(\text{absolute abundances})$ with <code>'relative=FALSE'</code> and a more typical bar graph of $\log(\text{fold change relative to the control})$, again with 95% credible intervals, with <code>'relative=TRUE'</code> . Specify <code>'summ.plot=FALSE'</code> if you don't want the summary plot.
ptype	Which type of p-values to use. By default p-values based on the Bayesian z-score are used. Specify <code>'ptype="mcmc"'</code> to output more conventional p-values based on MCMC sampling (these will be limited on the lower end by the size of MCMC sample).
...	Additional options for <code>summaryPlot()</code> function. Among those, <code>'x.order'</code> can be a vector specifying the order of factor levels on the x-axis.

Value

A list of three items:

summary	Summary table containing calculated abundances, their SD and 95% credible limits
geneWise	A series of matrices listing pairwise differences between factor combinations (upper triangle) and corresponding p-values (lower triangle)
ggPlot	the ggplot2 object for plotting. See http://docs.ggplot2.org/0.9.2.1/theme.html for ways to modify it, such as add text, rotate labels, change fonts, etc.

Author(s)

Mikhail V. Matz, University of Texas at Austin <matz@utexas.edu>

References

Matz MV, Wright RM, Scott JG (2013) No Control Genes Required: Bayesian Analysis of qRT-PCR Data. PLoS ONE 8(8): e71448. doi:10.1371/journal.pone.0071448

See Also

See function `summaryPlot()` for plotting the summary table in other ways.

Examples

```

data(beckham.data)
data(beckham.eff)

# analysing the first 5 genes
# (to try it with all 10 genes, change the line below to gcol=4:13)
gcol=4:8
ccol=1:3 # columns containing experimental conditions

# recalculating into molecule counts, reformatting
qs=cq2counts(data=beckham.data,genecols=gcol,
condcols=ccol,effic=beckham.eff,Cq1=37)

# creating a single factor, 'treatment.time', out of 'tr' and 'time'
qs$treatment.time=as.factor(paste(qs$tr,qs$time,sep="."))

# fitting a naive model
naive=mcmc.qpcr(
fixed="treatment.time",
data=qs,
nitt=3000,burnin=2000 # remove this line in actual analysis!
)

#summary plot of inferred abundances
# s1=HPDsummary(model=naive,data=qs)

```

```
#summary plot of fold-changes relative to the global control
s0=HPDsummary(model=naive,data=qs,relative=TRUE)

# pairwise differences and their significances for each gene:
s0$geneWise
```

mcmc.converge.check *MCMC diagnostic plots*

Description

A wrapper function for plot.MCMCglmm to plot diagnostic convergence plots for selected fixed effects

Usage

```
mcmc.converge.check(model, factors, ...)
```

Arguments

model	output of mcmc.qpcr (or any MCMCglmm class object)
factors	A vector of names of fixed effects of interest; see details in HPDplot help page.
...	other options to pass to plot.MCMCglmm

Value

A series of plots for each gene-specific fixed effect.

The MCMC trace plot is on the left, to see if there is convergence (lack of systematic trend) and no autocorrelation (no low-frequency waves). If lack of convergence is suspected, try increasing number of iterations and burnin by specifying, for example, nitt=50000, burnin=5000, as additional options for mcmc.qpcr. If autocorrelation is present, increase thinning interval by specifying thin=20 in mcmc.qpcr (you might wish to increase the number of iterations, nitt, to keep the size of MCMC sample the same)

The right plot is posterior density distribution.

Author(s)

Mikhail V. Matz, UT Austin

References

Matz MV, Wright RM, Scott JG (2013) No Control Genes Required: Bayesian Analysis of qRT-PCR Data. PLoS ONE 8(8): e71448. doi:10.1371/journal.pone.0071448

mcmc.pval	<i>calculates p-value based on Bayesian z-score or MCMC sampling</i>
-----------	--

Description

Accessory function to HPD... function series

Usage

```
mcmc.pval(dat, testlim = 0, sided = 2, ptype="z")
```

Arguments

dat	a table of MCMC samples
testlim	positive value to test whether the posterior crosses it (for variance components)
sided	sidedness of the test
ptype	'z' for z-score based p-values, 'mcmc' for standard sampling based p-values

Value

A vector of calculated Bayesian p-values. For standard 'mcmc' p-values, the minimal possible value is 1/(MCMC sample size). z-score based p-values are useful to approximate very low p-values with limited MCMC sample sizes.

Author(s)

Mikhail Matz, UT Austin <matz@utexas.edu>

mcmc.qpcr	<i>Analyzes qRT-PCR data using generalized linear mixed model</i>
-----------	---

Description

Wrapper function for MCMCglmm by Jarrod Hadfield, designed for qRT-PCR data analysis.

Usage

```
mcmc.qpcr(fixed=NULL, globalFixed=NULL, random = NULL, globalRandom=NULL, data,
controls = NULL, normalize=FALSE, include = NULL, m.fix = 1.2, v.fix = NULL,
geneSpecRes=TRUE, Covar=FALSE, vprior="uninf", ...)
```


Arguments

fixed	desired combination of fixed effects, as a text string. Do not use "*" symbol, list it fully, such as: 'factor1+factor2+factor1:factor2'.
globalFixed	Vector of fixed covariates (categorical or continuous) that are expected to affect all genes in the sample in the same way. These would be typically related to quality and/or quantity of RNA, such as RIN value.
random	A vector of names for gene-specific scalar random effects, such as 'c("effect1","effect2")'.
globalRandom	Random covariates (categorical only) affecting all genes, similar to globalFixed.
data	output of the cq2counts() function
controls	Vector of control gene names. These will be pushed to the back of the gene list during model fitting, in the reverse order. Controls are NOT NECESSARY for the analysis.
normalize	If controls are specified, requiring 'normalize=TRUE' will perform "soft normalization": the geometric mean of control genes will be used to infer global effects (common to all genes) across conditions; these will be subtracted when summarizing the data with HPDsummary(). Use this option when template abundances are correlated with conditions. Note that this is different from normalizing data within each sample, as per Vandesompele et al 2002; this would be "hard normalization" (use mcmc.qpcr.classic() if you want it).
include	How many of the control genes ('controls') to actually incorporate as priors during model fitting. If left unspecified, all the 'controls' will be used. If 'include=0', the model will be fitted without using any of the control genes as priors. If 'include' equals some number less than the number of 'controls', only the first 'include' of them will be used as priors. In all these cases, the 'controls' will appear in the same order in the output, in the end of the gene list rather than according to their alphabetical position among other genes. This is useful when visually comparing the results of models fitted with different number of control genes, using HPDplot and HPDpoints functions.
m.fix	Allowed average fold-change of the control genes in response to any fixed factor combination.
v.fix	Allowed residual fold-change deviation of the control genes. Applies to the residual variation term.
geneSpecRes	Whether the model should include gene-specific residuals. Keep it TRUE unless the model fails to converge.
Covar	Whether the random effects should be fitted with covariances. This option might require setting vprior="iw" or vprior="iw01" (see below)
vprior	The default prior is an uninformative inverse Wishart with assumed variance (V) at 1 and the degree of belief parameter (nu) at 0. With 'prior="iw"' and 'prior="iw01"' nu is equal [number of genes]-0.998, resulting in a weakly informative prior that is commonly used in this type of inference. vprior="iw" will assume large prior variance (1), vprior="iw01" will assume small prior variance (0.1).
...	other options for MCMCglmm function, such as nitt (number of iterations), thin (tinning interval), and burnin (number of initial iterations to disregard). For a

more precise inference specify 'nitt=45000, thin=20, burnin=5000'. See MCMCglmm documentation for more details.

Details

This function constructs priors and runs an MCMC chain to fit a Poisson-lognormal generalized linear mixed model to the counts data.

The fixed effects for the model by default assume a gene-specific intercept, and gene-specific effect for each of the listed fixed factors.

The user-specified random effects are all assumed to be gene-specific with no covariances.

There is also a universal random factor: the scalar random effect of sample, which accounts for the unequal template loading.

Residual variances are assumed to be gene-specific with no covariances, with weakly informative inverse Wishart prior (variance=1, nu=[number of genes]-0.998).

The priors for fixed effects are diffuse gaussians with a mean at 0 and very large variances (1e+8), except for control genes, for which the prior variances are defined by the m.fix parameter. For the gene-specific random effects and residual variation, non-informative priors are used to achieve results equivalent to ML estimation. For control genes, when v.fix parameter is specified, it will be used to restrict residual variance.

Both m.fix and v.fix parameters should be specified as allowed average fold-change, so the lowest they can go is 1 (no variation).

All control genes share the same m.fix and v.fix parameters.

Value

An MCMCglmm object. HPDsummary() function within this package summarizes these data, calculates all gene-wise credible intervals and p-values, and plots the results either as line-point-whiskers graph or a bar-whiskers graph using ggplot2 functions.

HPDsummary() only works for experiments with a single multilevel factor or two fully crossed multilevel factors. Use functions HPDplot(), HPDplotBygene() and HPDplotBygeneBygroup() to summarize and plot more complicated designs.

For more useful operations on MCMCglmm objects, such as posterior.mode(), HPDinterval(), and plot(), see documentation for MCMCglmm package.

Author(s)

Mikhail V. Matz, University of Texas at Austin <matz@utexas.edu>

References

Matz MV, Wright RM, Scott JG (2013) No Control Genes Required: Bayesian Analysis of qRT-PCR Data. PLoS ONE 8(8): e71448. doi:10.1371/journal.pone.0071448

Examples

```

data(beckham.data)
data(beckham.eff)

# analysing the first 5 genes
# (to try it with all 10 genes, change the line below to gcol=4:13)
gcol=4:8
ccol=1:3 # columns containing experimental conditions

# recalculating into molecule counts, reformatting
qs=cq2counts(data=beckham.data,genecols=gcol,
condcols=ccol,effic=beckham.eff,Cq1=37)

# creating a single factor, 'treatment.time', out of 'tr' and 'time'
qs$treatment.time=as.factor(paste(qs$str,qs$time,sep="."))

# fitting a naive model
naive=mcmc.qpcr(
fixed="treatment.time",
data=qs,
nitt=3000,burnin=2000 # remove this line in actual analysis!
)

#summary plot of inferred abundances
#s1=HPDsummary(model=naive,data=qs)

#summary plot of fold-changes relative to the global control
s0=HPDsummary(model=naive,data=qs,relative=TRUE)

# pairwise differences and their significances for each gene:
s0$geneWise

```

mcmc.qpcr.classic	<i>Analyzes qRT-PCR data using "classic" model, based on multigene normalization.</i>
-------------------	---

Description

Normalizes the data using specified control genes, fits a single model to estimate changes at all genes. Use for datasets with not too many Cq values above 30.

Usage

```

mcmc.qpcr.classic(fixed = NULL, globalFixed = NULL, random = NULL, globalRandom = NULL,
data, controls, genebysample = TRUE, geneSpecRes=FALSE, center = TRUE, ...)

```

Arguments

fixed	desired combination of fixed effects, as a text string. Do not use "*" symbol, list it fully, such as: 'factor1+factor2+factor1:factor2'.
globalFixed	Vector of fixed covariates (categorical or continuous) that are expected to affect all genes in the sample in the same way. These would be typically related to quality and/or quantity of RNA, such as RIN value.
random	A vector of names for gene-specific scalar random effects, such as 'c("effect1","effect2")'.
globalRandom	Random covariates (categorical only) affecting all genes, similar to globalFixed.
data	output of the cq2log() function
controls	Vector of control gene names. These will be pushed to the back of the gene list during model fitting, in the reverse order.
genebysample	Whether random gene by sample interactions should be modeled as an additional random effect. If the model fails to converge, specify 'genebysample=F'.
geneSpecRes	Whether the model should include gene-specific residuals. This was the default in MCMC.qpcr v.1.0; now it is switched off since it does not have any visible effect on the results (as long as genebysample=TRUE), and only makes the model converge slower or fail to converge.
center	Whether to center the normalized log-transformed Cq values around the mean for each gene. Centering does not affect the inference; it only makes the plots of the results more comprehensible (in my opinion).
...	other options for MCMCglmm function, such as nitt (number of iterations), thin (tinning interval), and burnin (number of initial iterations to disregard). For a more precise inference (but longer runs) specify 'nitt=45000, thin=20, burnin=5000'. See MCMCglmm documentation for more details.

Details

This function takes as input the log-transformed relative abundance values, performs multigene normalization as per Vandesompele et al 2002, and runs an MCMC chain to fit a lognormal linear mixed model to estimate gene expression changes jointly at all genes. It is very powerful, as long as the average stability of control genes can be trusted.

This function requires data prepared by cq2log function and must have the control genes specified; otherwise the arguments and syntax are similar to the mcmc.qpcr function.

Value

An MCMCglmm object. See mcmc.qpcr function for details and examples.

Author(s)

Mikhail V. Matz, University of Texas at Austin

References

Matz MV, Wright RM, Scott JG (2013) No Control Genes Required: Bayesian Analysis of qRT-PCR Data. PLoS ONE 8(8): e71448. doi:10.1371/journal.pone.0071448

mcmc.qpcr.lognormal *Fits a lognormal linear mixed model to qRT-PCR data.*

Description

Use in combination with cq2log(), on datasets without too many Cq values above 30.

Usage

```
mcmc.qpcr.lognormal(fixed=NULL, globalFixed=NULL, random = NULL, globalRandom=NULL, data,
controls = NULL, normalize=FALSE, include = NULL, m.fix = 1.2, v.fix = NULL,
geneSpecRes=TRUE, Covar=FALSE, vprior="uninf", ...)
```

Arguments

fixed	desired combination of fixed effects, as a text string. Do not use "*" symbol, list it fully, such as: 'factor1+factor2+factor1:factor2'.
globalFixed	Vector of fixed covariates (categorical or continuous) that are expected to affect all genes in the sample in the same way. These would be typically related to quality and/or quantity of RNA, such as RIN value.
random	A vector of names for gene-specific scalar random effects, such as 'c("effect1","effect2")'.
globalRandom	Random covariates (categorical only) affecting all genes, similar to globalFixed.
data	output of the cq2counts() function
controls	Vector of control gene names. These will be pushed to the back of the gene list during model fitting, in the reverse order. Controls are NOT NECESSARY for the analysis.
normalize	If controls are specified, requiring 'normalize=TRUE' will perform "soft normalization": the geometric mean of control genes will be used to infer global effects (common to all genes) across conditions; these will be subtracted when summarizing the data with HPDsummary(). Use this option when template abundances are correlated with conditions. Note that this is different from normalizing data within each sample, as per Vandesompele et al 2002; this would be "hard normalization" (use mcmc.qpcr.classic() if you want it).
include	How many of the control genes ('controls') to actually incorporate as priors during model fitting. If left unspecified, all the 'controls' will be used. If 'include=0', the model will be fitted without using any of the control genes as priors. If 'include' equals some number less than the number of 'controls', only the first 'include' of them will be used as priors. In all these cases, the 'controls' will appear in the same order in the output, in the end of the gene list rather than according to their alphabetical position among other genes. This is useful when visually comparing the results of models fitted with different number of control genes, using HPDplot and HPDpoints functions.
m.fix	Allowed average fold-change of the control genes in response to any fixed factor combination.

v.fix	Allowed residual fold-change deviation of the control genes. Applies to the residual variation term.
geneSpecRes	Whether the model should include gene-specific residuals. Keep it TRUE unless the model fails to converge.
Covar	Whether the random effects should be fitted with covariances. This option might require setting vprior="iw" or vprior="iw01" (see below)
vprior	The default prior is an uninformative inverse Wishart with assumed variance (V) at 1 and the degree of belief parameter (nu) at 0. With 'prior="iw"' and 'prior="iw01"' nu is equal [number of genes]-0.998, resulting in a weakly informative prior that is commonly used in this type of inference. vprior="iw" will assume large prior variance (1), vprior="iw01" will assume small prior variance (0.1).
...	other options for MCMCglmm function, such as nitt (number of iterations), thin (tinning interval), and burnin (number of initial iterations to disregard). For a more precise inference specify 'nitt=45000, thin=20, burnin=5000'. See MCMCglmm documentation for more details.

Details

This function constructs priors and runs an MCMC chain to fit a lognormal linear mixed model to the log-transformed relative abundances data. The data for this function must be prepared by cq2log instead of cq2counts function; otherwise, the arguments and syntax are identical to mcmc.qpcr function.

Value

An MCMCglmm object. See mcmc.qpcr function for details and examples.

Author(s)

Mikhail V. Matz, University of Texas at Austin

References

Matz MV, Wright RM, Scott JG (2013) No Control Genes Required: Bayesian Analysis of qRT-PCR Data. PLoS ONE 8(8): e71448. doi:10.1371/journal.pone.0071448

normalize.qpcr

Internal function called by mcmc.qpcr.classic

Description

Performs multigene normalization as per Vandesompele et al 2002, centers the resulting gene expression values around the gene's means

Usage

```
normalize.qpcr(data, controls, center = T)
```

Arguments

data	The output of <code>cq2log()</code>
controls	Vector of control genes, such as <code>'controls=c("eif3h","nd5","rp111")'</code>
center	Whether to perform centering around mean or not.

Value

normalized dataset

Author(s)

Mikhail Matz, UT Austin

References

Matz MV, Wright RM, Scott JG (2013) No Control Genes Required: Bayesian Analysis of qRT-PCR Data. *PLoS ONE* 8(8): e71448. doi:10.1371/journal.pone.0071448

outlierSamples	<i>detects outlier samples in qPCR data</i>
----------------	---

Description

reports samples that have too little starting material relative to others (by default, less by two standard deviations)

Usage

```
outlierSamples(model, data, z.cutoff = -2)
```

Arguments

model	qPCR model: the output of <code>mcmc.qpcr</code> or <code>mcmc.qpcr.lognormal</code> function fitted with <code>pr=TRUE</code> option
data	The dataset that was analysed to generate the model (output of <code>cq2counts</code> or <code>cq2log</code> functions)
z.cutoff	z-score cutoff to report an outlier sample.

Value

A vector containing outlier sample names.

Author(s)

Mikhail V. Matz, University of Texas at Austin <matz@utexas.edu>

References

Matz MV, Wright RM, Scott JG (2013) No Control Genes Required: Bayesian Analysis of qRT-PCR Data. PLoS ONE 8(8): e71448. doi:10.1371/journal.pone.0071448

Examples

```
# loading Cq data and amplification efficiencies
data(coral.stress)
data(amp.eff)
# extracting a subset of data
cs.short=subset(coral.stress, timepoint=="one")

genecolumns=c(5,6,16,17) # specifying columns corresponding to genes of interest
conditions=c(1:4) # specifying columns containing factors

# calculating molecule counts and reformatting:
dd=cq2counts(data=cs.short,genecols=genecolumns,
condcols=conditions,effic=amp.eff,Cq1=37)

# fitting the model
mm=mcmc.qpcr(
fixed="condition",
data=dd,
controls=c("nd5","rpl11"),
nitt=4000, # remove this line when analyzing real data!
pr=TRUE
)

# detecting outliers
outliers=outlierSamples(mm,dd)

# removing outliers
dd=dd[!(dd$sample %in% outliers),]
```

padj.qpcr

Calculates adjusted p-values corrected for multiple comparisons

Description

Takes the output of HPDplot(...,plot=FALSE), adds two columns of adjusted p-values (z and mcmc)
Disregards the entries corresponding to control genes

Usage

```
padj.qpcr(data, controls = NULL, method = "BH")
```


Arguments

data	Output of HPDplot(...,plot=FALSE); may be several several such outputs concatenated with rbind
controls	A vector of control gene names
method	p-value correction method (see function p.adjust), default is Benjamini-Hochberg

Value

The dataframe derived from the input, with added columns "padj.z" and "padj.mcmc". See tutorial for examples.

Author(s)

Mikhail V. Matz, matz@mail.utexas.edu

References

Matz MV, Wright RM, Scott JG (2013) No Control Genes Required: Bayesian Analysis of qRT-PCR Data. PLoS ONE 8(8): e71448. doi:10.1371/journal.pone.0071448

PrimEff

Determines qPCR amplification efficiencies from dilution series

Description

Runs linear regression on Cq versus log₂(RNA concentration), plots graph, reports slope (ideally should be -1), and efficiency (with 95 percent credible limits)

Usage

```
PrimEff(data, plot = TRUE)
```

Arguments

data	a dataframe containing three columns. First is RNA concentration. This could be absolute as well as relative concentration (1/dilution factor). Second is the Cq value. Third is gene name. Replicate the same name across all the corresponding RNA concentrations. The dataframe may contain data for multiple genes.
plot	set plot=FALSE if the plot is not required

Details

Run with at least 8 2-fold dilutions per gene

Value

Plots the regression and under it, the values of slope and efficiency (plus and minus one SD). The dataframe may contain data for multiple genes, which will all be plotted together (so the reasonable limit is something like 25 genes)

Also returns a dataframe with columns: gene, efficiency, plus one SD, minus one SD, and intercept.

Author(s)

Mikhail V. Matz, UT Austin <matz@utexas.edu>

References

Matz MV, Wright RM, Scott JG (2013) No Control Genes Required: Bayesian Analysis of qRT-PCR Data. PLoS ONE 8(8): e71448. doi:10.1371/journal.pone.0071448

Examples

```
data(dilutions)
PrimEff(dilutions)
```

softNorm

Accessory function to mcmc.qpcr() to perform soft normalization

Description

adds a fake NORM gene with counts equal to geometric mean of control genes, removes control genes from the dataset

Usage

```
softNorm(data, controls)
```

Arguments

data	The dataset; output of cq2counts()
controls	Vector fo control gene names

Value

A modified dataset with NORM gene set as the reference, and no control genes

Author(s)

Mikhail Matz, UT Austin <matz@utexas.edu>

summaryPlot	<i>Wrapper function for ggplot2 to make bar and line graphs of mcmc.qpcr() results</i>
-------------	--

Description

This function is called automatically by HPDsummary() and also can be used separately to plot the results produced by HPDsummary() with more plotting options

Usage

```
summaryPlot(data, xgroup, facet = NA, type = "bar", x.order = NA,  
whiskers = "ci", genes = NA, log.base=2)
```

Arguments

data	A summary table generated by HPDplot(), it is the first element in the returned list.
xgroup	Which factor will be used to form the x axis (for 2-way designs).
facet	The factor by which the plot will be split into facets (for 2-way designs).
type	Two types are supported: "bar" and "line" ("line" also has points). "bar" is more useful to plot fold-changes returned when HPDsummary() is run with the option 'relative=TRUE'. "line" is better for plotting actual inferred transcript abundances across factor levels; it is particularly good for time courses and other cases when multiple factor levels must be compared to each other. "bar" is good to plot log(fold-changes) relative to global control.
x.order	A vector giving the order of factor levels on the x-axis. If unspecified, an alphanumeric order will be used.
whiskers	The interval indicated by the whiskers. Default is "ci", the 95% credible interval; another option is "sd" - standard deviation of the posterior.
genes	Vector of gene names to plot. By default, all genes in the summary will be plotted.
log.base	Base of the logarithm to indicate on y-axis (does not affect plotting).

Details

The function invokes ggplot() function from the ggplot2 package to plot the results either as a single panel (one-way designs) or a multi-panel (2-way designs, one panel per level of the factor specified by 'facet' argument).

Value

A ggplot object. See <http://docs.ggplot2.org/0.9.2.1/theme.html> for ways to modify it, such as add text, rotate labels, change fonts, etc.

Author(s)

Mikhail V. Matz, University of Texas at Austin <matz@utexas.edu>

References

Matz MV, Wright RM, Scott JG (2013) No Control Genes Required: Bayesian Analysis of qRT-PCR Data. PLoS ONE 8(8): e71448. doi:10.1371/journal.pone.0071448

trellisByGene

For two-way designs, plots mcmc.qpcr model predictions gene by gene

Description

For each gene, plots model-predicted values and 95% credible intervals.

Usage

```
trellisByGene(modelSummary, xFactor, groupFactor,
  nrow=2, lineWidth=0.4, whiskerWidth=0.2, pointSize=2.5,
  facetScales="free_y", ylab="log(abundance)",
  legendPos="bottom", posDodge=0.3)
```

Arguments

modelSummary	two-way design model summary produced by HPDsummary()
xFactor	factor to form the x-axis
groupFactor	factor to form separate lines on the plot
nrow	number of rows in the resulting trellis plot
lineWidth	line width, passed as 'lwd' to geom_errorbar function (ggplot2)
whiskerWidth	width of the line denoting 95% CI margin, passed as 'width' to geom_errorbar function (ggplot2)
pointSize	passed as 'size' to geom_point function of ggplot2
facetScales	passed as 'scales' to facet_wrap function of ggplot2
ylab	y-axis label
legendPos	passed as 'legend.position' to theme function of ggplot2
posDodge	position dodge, increase for more jitter

Value

A ggplot2 type object

Author(s)

Mikhail V. Matz, UT Austin, matz@utexas.edu

References

Matz MV, Wright RM, Scott JG (2013) No Control Genes Required: Bayesian Analysis of qRT-PCR Data. PLoS ONE 8(8): e71448. doi:10.1371/journal.pone.0071448

Examples

```
# loading Cq data and amplification efficiencies
data(coral.stress)
data(amp.eff)

genecolumns=c(5,6,16,17) # specifying columns corresponding to genes of interest
conditions=c(1:4) # specifying columns containing factors

# calculating molecule counts and reformatting:
dd=cq2counts(data=coral.stress,genecols=genecolumns,
condcols=conditions,effic=amp.eff,Cq1=37)

# fitting the 2-way model
mm=mcnc.qpcr(
fixed="condition+timepoint+condition:timepoint",
data=dd,
nitt=4000 # remark this line to analyze real data!
)

# summarizing results
ss=HPDsummary(mm,data=dd,summ.plot=FALSE)

# plotting predicted means and 95% CIs gene by gene
trellisByGene(ss,xFactor="condition",groupFactor="timepoint")
```

Index

*Topic **datasets**

amp.eff, [3](#)
coral.stress, [6](#)
dilutions, [11](#)

*Topic **package**

MCMC.qpcr-package, [2](#)

amp.eff, [3](#)

beckham.data, [4](#)
beckham.eff, [5](#)

coral.stress, [6](#)
cq2counts, [7](#)
cq2genorm, [8](#)
cq2log, [9](#)

diagnostic.mcmc, [10](#)
dilutions, [11](#)

getNormalizedData, [12](#)

HPDplot, [13](#)
HPDplotBygene, [16](#)
HPDplotBygeneBygroup, [18](#)
HPDpoints, [19](#)
HPDsummary, [21](#)

mcmc.converge.check, [23](#)
mcmc.pval, [24](#)
MCMC.qpcr (MCMC.qpcr-package), [2](#)
mcmc.qpcr, [24](#)
MCMC.qpcr-package, [2](#)
mcmc.qpcr.classic, [27](#)
mcmc.qpcr.lognormal, [29](#)

normalize.qpcr, [30](#)

outlierSamples, [31](#)

padj.qpcr, [32](#)

PrimEff, [33](#)

softNorm, [34](#)
summaryPlot, [35](#)

trellisByGene, [36](#)