

Package ‘easyr’

October 13, 2020

Type Package

Title Helpful Functions from Oliver Wyman Actuarial Consulting

Version 0.5-2

Maintainer Bryce Chamberlain <bryce.chamberlain@oliverwyman.com>

Description Makes difficult operations easy. Includes these types of functions: shorthand, type conversion, data wrangling, and work flow.
Also includes some helpful data objects: NA strings, U.S. state list, color blind charting colors.
Built and shared by Oliver Wyman Actuarial Consulting. Accepting proposed contributions through GitHub.

License GPL (>= 2)

LazyData true

URL <https://github.com/oliver-wyman-actuarial/easyr>

BugReports <https://github.com/oliver-wyman-actuarial/easyr/issues>

Depends R (>= 3.4.0)

Imports data.table, digest, dplyr, foreign, glue, Hmisc, lubridate, stringr, openssl, readxl, rlang, rprojroot, XML

RoxygenNote 6.1.1

Suggests pdftools, qs, rstudioapi, testthat

NeedsCompilation no

Author Oliver Wyman Actuarial Consulting [aut, cph],
Bryce Chamberlain [aut, cre],
Scott Sobel [ctb],
Rajesh Sahasrabuddhe [ctb]

Repository CRAN

Date/Publication 2020-10-13 12:40:02 UTC

R topics documented:

astext	3
atype	4

begin	5
binbyvol	6
bindf	6
cache.init	7
cache.ok	8
cblind	9
cc	9
char2fac	10
charnum	11
checkeq	12
clear.cache	12
coalf	13
crun	14
ddiff	14
dict	15
drows	16
ecopy	16
eq	17
fac2char	18
fjoinf	18
fldict	19
fmat	20
getbetterint	21
getinfo	22
gr	23
hashfiles	23
headers_row	24
ijoinf	24
ischar	25
isdate	26
isfac	27
isnum	27
isval	28
jrepl	29
left	30
likedate	30
ljoinf	31
match.factors	32
mdiff	33
mid	34
na	35
namesx	35
nan	36
nanull	36
nastrings	37
null	38
pad0	38
qdiff	39

rany_fixColNames	39
read.any	40
read.txt	42
right	43
runfolder	44
rx	44
save.cache	45
sch	46
spl	47
states	47
strx	48
sumnum	48
tcmmsg	49
tcol	50
tcwarn	50
tobool	51
tochar	52
todate	52
tonum	54
usepkg	55
validate.equal	55
w	57
xldate	57
ydiff	58
%ni%	59
Index	60

astext	<i>As Text</i>
--------	----------------

Description

Prints a vector as text you can copy and paste back into the code. Helpful for copying vectors into code for testing and validation. Author: Bryce Chamberlain.

Usage

```
astext(x)
```

Arguments

x	Vector to represent as text.
---	------------------------------

Value

Vector represented as a character.

Examples

```
astext( c( 1, 2, 4 ) )
astext( c( 'a', 'b', 'c' ) )
```

atype	<i>Auto-Type</i>
-------	------------------

Description

Use easy date and number and conversion functions to automatically convert data to the most useful type available.

Usage

```
atype(x, auto_convert_dates = TRUE, allow_times = FALSE,
      check_numbers = TRUE, nzero = FALSE, check_logical = TRUE,
      isexcel = TRUE, stringsAsFactors = FALSE,
      nastrings = easyr::nastrings, exclude = NULL)
```

Arguments

x	Data to auto-type.
auto_convert_dates	Choose to convert dates.
allow_times	Choose if you want to get times. Only use this if your data has times, otherwise there is a small chance it will prevent proper date conversion.
check_numbers	Choose to convert numbers.
nzero	Convert NAs in numeric columns to 0.
check_logical	Choose to convert numbers.
isexcel	By default, we assume this data may have come from excel. This is to assist in date conversion from excel integers. If you know it didn't and are having issues with data conversion, set this to FALSE.
stringsAsFactors	Convert strings/characters to factors to save compute time, RAM/memory, and storage space.
nastrings	Strings to consider NA.
exclude	Column name(s) to exclude.

Details

Author: Bryce Chamberlain.

Value

Data frame with column types automatically converted.

Examples

```
# create some data in all-characters.
x = data.frame(
  char = c( 'abc', 'def' ),
  num = c( '1', '2' ),
  date = c( '1/1/2018', '2018-2-01' ),
  na = c( NA, NA ),
  bool = c( 'TRUE', 'FALSE' ),
  stringsAsFactors = FALSE
)

# different atype options. Note how the output types change.
str( atype( x ) )
str( atype( x, exclude = 'date' ) )
str( atype( x, auto_convert_dates = FALSE ) )
str( atype( x, check_logical = FALSE ) )
```

begin

Begin

Description

Perform common operations before running a script. Includes clearing environment variables, disabling scientific notation, loading common packages, and setting the working directory to the location of the current file.

Usage

```
begin(wd = NULL, load = c("magrittr", "dplyr"), scipen = FALSE,
      verbose = TRUE, repos = "http://cran.us.r-project.org")
```

Arguments

wd	Path to set as working directory. If blank, the location of the current file open in RStudio will be used if available. If FALSE, the working directory will not be changed.
load	Packages to load. If not available, they'll be installed.
scipen	Do scientific notation in output?
verbose	Print information about what the function is doing?
repos	choose the URL to install from.

Examples

```
begin()
```

binbyvol

Bin by Volume

Description

Bins a numerical column according to another numerical column's volume. For example if I want to bin a column "Age" (of people) into 10 deciles according to "CountofPeople" then I will get Age breakpoints returned by my function such that there is 10 This function handles NA's as their own separate bin, and handles any special values you want to separate out. Author: Scott Sobel. Tech Review: Bryce Chamberlain.

Usage

```
binbyvol(df, groupby, vol, numbins)
```

Arguments

df	(Data Frame) Your data.
groupby	(Character) Name of the column you'll create cuts in. Must be the character name of a numeric column.
vol	(Character) Name of the column for which which each cut will have an equal percentage of volume.
numbins	Number of bins to use.

Value

Age breakpoints returned by my function such that there is 10

Examples

```
# bin Sepal.Width according to Sepal.Length.
iris$bin <- binbyvol(iris, 'Sepal.Width', 'Sepal.Length', 5)

# check the binning success.
aggregate( Sepal.Length ~ bin, data = iris, sum )
```

bindf

Bind Rows with Factors

Description

Matches factor levels before binding rows. Author: Bryce Chamberlain.

Usage

```
bindf(..., sort.levels = TRUE)
```

Arguments

... data to be binded
 sort.levels Sort the factor levels after combining them.

Value

Binded data, with any factors modified to contain all levels in the binded data.

Examples

```
# create data where factors have different levels.
df1 = data.frame(
  factor1 = c( 'a', 'b', 'c' ),
  factor2 = c( 'high', 'medium', 'low' ),
  factor.join = c( '0349038u093843', '304359867893753', '3409783509735' ),
  numeric = c( 1, 2, 3 ),
  logical = c( TRUE, TRUE, TRUE )
)#'
df2 = data.frame(
  factor1 = c( 'd', 'e', 'f' ),
  factor2 = c( 'low', 'medium', 'high' ),
  factor.join = c( '32532532536', '304359867893753', '32534745876' ),
  numeric = c( 4, 5, 6 ),
  logical = c( FALSE, FALSE, FALSE )
)

# bindf preserves factors but combines levels.
# factor-friendly functions default to ordered levels.
str( df1 )
str( bindf( df1, df2 ) )
```

 cache.init

Initialize cache.

Description

Set cache info so easyr can manage the cache.

Usage

```
cache.init(caches, at.path, verbose = TRUE, save.only = FALSE,
  skip.missing = TRUE, n_processes = 2)
```

Arguments

cache	List of lists with properties name, depends.on. See example.
at.path	Where to save the cache. If NULL, a cache/ folder will be created in the current working directory.
verbose	Print via cat() information about cache operations.
save.only	Choose not to load the cache. Use this if you need to check cache validity in multiple spots but only want to load at the last check.
skip.missing	Passed to hashfiles, choose if an error occurs if a depends.on file isn't found.
n_processes	Passed to qs to determine how many cores/workers to use when reading/saving data.

Examples

```
# initialize a cache with 1 cache which depends on files in the current working directory.
# this will create a cache folder in your current working directory.
# then, you call functions to check and build the cache.
cache.init(

# Initial file read (raw except for renaming).
caches = list(
  list(
    name = 'prep-files',
    depends.on = c( '.' )
  )
),

at.path = tempdir()

)
```

cache.ok

Check Cache Status

Description

Check a cache and if necessary clear it to trigger a re-cache.

Usage

```
cache.ok(cache.num, do.load = TRUE)
```

Arguments

cache.num	The index/number for the cache we are checking in the cache.info list.
do.load	Load the cache if it is found.

Value

Boolean indicating if the cache is acceptable. FALSE indicates the cache doesn't exist or is invalid so code should be run again.

Examples

```
# check the first cache to see if it exists and dependent files haven't changed.
# if this is TRUE, code in brackets will get skipped and the cache will be loaded instead.
# set do.load = FALSE if you have multiple files that build a cache,
#   to prevent multiple cache loads.
# output will be printed to the console to tell you if the cache was loaded or re-built.
if( ! cache.ok(1) ){

  # do stuff

  # if this is the final file for this cache, end with save.cache to save passed objects as a cache.
  save.cache(iris)
}
```

cblind

cblind

Description

Color palette that is effective for color-blind clients.

Usage

```
cblind
```

Format

Named vector of hex colors.

cc

Concatenate.

Description

Shorthand function for paste. Author: Bryce Chamberlain.

Usage

```
cc(..., sep = "")
```

Arguments

... Arguments to be passed to `paste0`. Typically a list of vectors or values to be concatenated.

sep (Optional) Separator between concatenated items.

Value

Vector of pasted/concatenated values.

Examples

```
cc( 1, 2, 4 )
x = data.frame( c1 = c( 1, 2, 4 ), c2 = c( 3, 5, 7 ) )
cc( x$c1, x$c2 )
cc( x$c1, x$c2, sep = '-' )
```

char2fac

Characters to Factors

Description

Convert all character columns in a data frame to factors. Author: Bryce Chamberlain.

Usage

```
char2fac(x, sortlevels = FALSE, na_level = "(Missing)")
```

Arguments

x Data frame to modify.

sortlevels Choose whether to sort levels. This is the default R behavior and is therefore likely faster, but it may change the order of the data and this can be problematic so the default is FALSE.

na_level some functions don't like factors to have NAs so we replace NAs with this value for factors only. Set NULL to skip.

Value

Data frame with converted factors.

Examples

```
char2fac( iris )
```

charnum	<i>Check for Number Formatted as Character.</i>
---------	-------------------------------------------------

Description

Checks a vector or value to see if it is a number formatted as a character. Useful for checking columns formatted with \$ or commas, etc. Author: Bryce Chamberlain. Tech review: Dominic Dillingham.

Usage

```
charnum(x, na_strings = easyr::nastrings, run_unique = TRUE,  
        check_date = TRUE)
```

Arguments

x	Vector to check.
na_strings	Strings to consider NA.
run_unique	Convert to unique variables before checking. In some cases, this can make it take longer than necessary. In most, it will make it faster.
check_date	Check for a date, in which case it isn't a number. If you have already checked a date and know it isn't, set this to FALSE to run faster.

Value

True/false value indicating if the vector is a number formatted as a character. Helpful for checking before calling `easyr:tonum()`.

Examples

```
charnum( c(  
  '123', '$50.02', '30%', '(300.01)', '-10', '1 230.4', NA, '-', ' ', "3.799999999999999E-2"  
))  
charnum( c( '123', 'abc', '30%', NA) )  
# returns FALSE since this can be converted to a date:  
charnum( c( '20180101' ) )
```

checkeq	<i>Check Value or Control Total</i>
---------	-------------------------------------

Description

Check actual versus expected values and get helpful metrics back. Author: Bryce Chamberlain.
Tech review: Lindsay Smeltzer.

Usage

```
checkeq(expected, actual, desc = "", acceptable_pct_diff = 0.00000001,
        digits = 2)
```

Arguments

expected	The expected value of the metric.
actual	The actual value of the metric.
desc	(Optional) Description of the metric being checked.
acceptable_pct_diff	(Optional) Acceptable percentage difference when checking values. Checked as an absolute value.
digits	(Optional) Digits to round to. Without rounding you get errors from floating values. Set to NA to avoid rounding.

Value

Message (via cat) indicating success or errors out in case of failure.

Examples

```
checkeq(expected=100,actual=100,desc='A Match')
```

clear.cache	<i>Clear Cache</i>
-------------	--------------------

Description

Clears all caches or the cache related to the passed cache info list.

Usage

```
clear.cache(cache = NULL)
```

Arguments

cache	The cache list to clear.
-------	--------------------------

Value

FALSE if a cache info list item is passed in order to assist other functions in returning this value, otherwise NULL.

Examples

```
# this will only have an effect if a current cache exists.  
clear.cache()
```

coalf

Factor-friendly Coalesce

Description

Coalesce function that matches and updates factor levels appropriately. Checks each argument vector starting with the first until a non-NA value is found. Author: Bryce Chamberlain.

Usage

```
coalf(...)
```

Arguments

... Source vectors.

Value

Vector of values.

Examples

```
x <- sample(c(1:5, NA, NA, NA))  
coalf(x, 0L)
```

`crun` *Concatenate and run.*

Description

Concatenate arguments and run them as a command. Shorthand for `eval(parse(text = paste0(...)))`. Consider also using `base::get()` which can be used to get an object from a string, but only if it already exists. Author: Bryce Chamberlain.

Usage

```
crun(...)
```

Arguments

... Character(s) to be concatenated and run as a command.

Examples

```
crun( 'print(', '"hello world!"', ')' )
crun('T', 'RUE')
```

`ddiff` *Date difference (or difference in days).*

Description

Date difference (or difference in days).

Usage

```
ddiff(x, y, unit = "day", do.date.convert = TRUE, do.numeric = TRUE)
```

Arguments

`x` Vector of starting dates or items that can be converted to dates by `todate`.

`y` Vector of ending dates or items that can be converted to dates by `todate`.

`unit` Character indicating what to use as the unit of difference. Values like `d`, `y`, `m` or `day`, `year`, `month` will work. Takes just the first letter in lower-case to determine unit.

`do.date.convert` Convert to dates before running the difference. If you know your columns are already dates, setting to `FALSE` will make your code run faster.

`do.numeric` Convert the output to a number instead of a date difference object.

Value

Vector of differences.

Examples

```
ddiff( lubridate::mdy( '1/1/2018' ), lubridate::mdy( '3/4/2018' ) )
```

dict

Get Data Dictionary

Description

Get information about a Data Frame or Data Table. Use `getinfo` to explore a single column instead. If you like, use `ecopy` function or argument to copy to the clipboard so that it can be pasted into Excel. Otherwise it returns a data frame. Author: Scott Sobel. Tech Review & Modifications: Bryce Chamberlain.

Usage

```
dict(x, topn = 5, botn = 5, na.strings = easyr::nastrings,  
     do.atype = TRUE, ecopy = FALSE)
```

Arguments

<code>x</code>	Data Frame or Data Table.
<code>topn</code>	Number of top values to print.
<code>botn</code>	Number of bottom values to print.
<code>na.strings</code>	Strings to consider NA.
<code>do.atype</code>	Auto-determine variable types. If your data already has types set, skip this to speed up the code.
<code>ecopy</code>	Use <code>ecopy</code> function or argument to copy to the clipboard so that it can be pasted into Excel.

Examples

```
dict(iris)
```

drows

Get Rows with Duplicates

Description

Pulls all rows with duplicates in a column, not just the duplicate row. Author: Bryce Chamberlain.

Usage

```
drows(x, c, na = FALSE)
```

Arguments

x	Data frame.
c	Column as vector or string.
na	Consider multiple NAs as duplicates?

Value

Rows from the data frame in which the column is duplicated.

Examples

```
ddt = bindf( cars, utils::head( cars, 10 ) )
drows( ddt, 'speed' )
```

ecopy

Copy to Clipboard

Description

Copies a data.frame or anything that can be converted into a data.frame. After running this, you can use ctrl+v or Edit > Paste to paste it to another program, typically Excel. A simple use case would be ecopy(names(df)) to copy the names of a data frame to the clipboard to paste to Excel or Outlook. Author: Scott Sobel. Tech Review: Bryce Chamberlain.

Usage

```
ecopy(x, showrowcolnames = c("cols", "rows", "both", "none"),
      show = FALSE)
```


Arguments

x	Object you'd like to copy to the clipboard.
showrowcolnames	(Optional) Show row and column names. Choose 'none', 'cols', 'rows', or 'both'.
show	(Optional Boolean) Set to 'show' if you want to also print the object to the console.

Examples

```
ecopy( iris, showrowcolnames = "cols", show = 'show' )
ecopy(iris)
```

eq *NA-Friendly Equality Comparison*

Description

Vectorized flexible equality comparison which considers NAs as a value. Returns TRUE if both values are NA, and FALSE when only one is NA. The standard == comparison returns NA in both of these cases and sometimes this is interpreted unexpectedly. Author: Bryce Chamberlain. Tech Review: Maria Gonzalez.

Usage

```
eq(x, y, do.nanull.equal = TRUE)
```

Arguments

x	First vector/value for comparison.
y	Second vector/value for comparison.
do.nanull.equal	Return TRUE if both inputs are NA or NULL (tested via easyr::nanull).

Value

Boolean vector/value of comparisons.

Examples

```
c(NA, 'NA', 1, 2, 'c') == c(NA, NA, 1, 2, 'a') # regular equality check.
eq(c(NA, 'NA', 1, 2, 'c'), c(NA, NA, 1, 2, 'a')) # check with eq.
```

fac2char *Factors to Characters*

Description

Convert all factor columns in a data frame to characters. Author: Bryce Chamberlain.

Usage

```
fac2char(x)
```

Arguments

x Data frame to modify.

Value

Data frame with converted characters.

Examples

```
char2fac( iris )
```

fjoinf *Full Join with Factors*

Description

Matches factor levels before full join via merge. Author: Bryce Chamberlain.

Usage

```
fjoinf(data.left, data.right, by, sort.levels = TRUE,
       restrict.levels = FALSE, na_level = "(Missing)")
```

Arguments

data.left	Left data. Only rows that matche the join will be included (may still result in duplication).
data.right	Right data. All of this data will be preservered in the join (may also result in duplication).
by	Columns to join on.
sort.levels	Sort the factor levels after combining them.
restrict.levels	Often the joined data won't use all the levels in both datasets. Set to TRUE to remove factor levels that aren't in the joined data.
na_level	some functions don't like factors to have NAs so we replace NAs with this value for factors only. Set NULL to skip.

Value

Joined data, with any factors modified to contain all levels in the joined data.

Examples

```
df1 = data.frame(
  factor1 = c( 'a', 'b', 'c' ),
  factor2 = c( 'high', 'medium', 'low' ),
  factor.join = c( '0349038u093843', '304359867893753', '3409783509735' ),
  numeric = c( 1, 2, 3 ),
  logical = c( TRUE, TRUE, TRUE )
)

df2 = data.frame(
  factor1 = c( 'd', 'e', 'f' ),
  factor2 = c( 'low', 'medium', 'high' ),
  factor.join = c( '32532532536', '304359867893753', '32534745876' ),
  numeric = c( 4, 5, 6 ),
  logical = c( FALSE, FALSE, FALSE )
)

fjoinf( df1, df2, by = 'factor.join' )
```

fdict

Get Data Dictionary for Files in Folder

Description

Get information about data files in a folder path. Use dict() on a single data frame or getinfo(0) to explore a single column. Author: Bryce Chamberlain.

Usage

```
fdict(folder = NULL, file.list = NULL,
      pattern = "^[^~]+[.](xls|xmb)?|csv|rds|xml)", ignore.case = TRUE,
      recursive = TRUE, ...)
```

Arguments

folder	File path of the folder to create a dictionary for. Pass either this or file.list. file.list will override this argument.
file.list	List of files to create a combined dictionary for. Pass either this or folder. This will override folder.
pattern	Pattern to match files in the folder. By default we use a pattern that matches read.any-compatible data files and skips temporary Office files. Passed to list.files.
ignore.case	Ignore case when checking pattern. Passed to list.files.

recursive	Check files recursively. Passed to list.files.
...	Other arguments to read.any for reading in files. Consider using a first_column_name vector, etc.

Value

List with the properties:

s	Summary data of each dataset.
l	Line data with a row for each column in each dataset.

Examples

```
folder = system.file('extdata', package = 'easyr')
fl = fldict(folder)
names(fl)

fl$sheets
fl$columns
```

fmat

Number Formatter

Description

Flexible number formatter for easier formatting from numbers and dates into characters for display.

Usage

```
fmat(x = NULL, type = c("auto", ",", "$", "%", ".", "mdy", "ymd",
  "date", "dollar", "dollars", "count", "percentage", "decimal"),
  do.return = c("formatted", "highcharter"), digits = NULL,
  with.unit = FALSE, do.date.sep = "/", do.remove.spaces = FALSE,
  digits.cutoff = NULL)
```

Arguments

x	Vector of values to convert. If retu
type	Type of format to return. If do.return == 'highcharter' this is not required.
do.return	Information to return. "formatted" returns a vector of formatted values.
digits	Number of digits for rounding. If left blank, the funtion will guess at the best digits.
with.unit	For large numbers, choose to add a suffix for fewer characters, like M for million, etc.
do.date.sep	Separator for date formatting.

`do.remove.spaces`

Remove extra spaces in return.

`digits.cutoff` Amount at which to show 0 digits. Allows for flexibility of rounding.

Value

Information requested via `do.return`.

Examples

```
fmat( 1000, 'dollar', digits = 2 )
```

`getbetterint` *Get better Int*

Description

Takes bucket names of binned values such as [1e3,2e3) or [0.1234567, 0.2) and formats the values nicely into values such as 1,000-2,000 or 0.12-0.20 Author: Scott Sobel. Tech Review: Bryce Chamberlain.

Usage

```
getbetterint(int)
```

Arguments

`int` Vector of character bucket names to transform.

Value

Vector of transformed values.

Examples

```
iris$bin <- binbyvol( iris, 'Sepal.Width', 'Sepal.Length', 5 )  
getbetterint( iris$bin )
```

`getinfo`*Get Info*

Description

Get information about a Column in a Data Frame or Data Table. Use `getdatadict` to explore all columns in a dataset instead. Author: Scott Sobel. Tech Review: Bryce Chamberlain.

Usage

```
getinfo(df, colname, topn = 5, botn = 5, graph = TRUE,
        ordered = TRUE, display = TRUE, cutoff = 20, main = NULL,
        cex = 0.9, xcex = 0.9, bins = 50, col = "light blue")
```

Arguments

<code>df</code>	Data Frame or Data Table.
<code>colname</code>	(Character) Name of the column to get information about.
<code>topn</code>	(Optional) Number of top values to print.
<code>botn</code>	(Optional) Number of bottom values to print.
<code>graph</code>	(Boolean Optional) Output a chart of the column.
<code>ordered</code>	(Optional)
<code>display</code>	(Optional)
<code>cutoff</code>	(Optional)
<code>main</code>	(Optional)
<code>cex</code>	(Optional)
<code>xcex</code>	(Optional)
<code>bins</code>	(Optional)
<code>col</code>	(Optional)

Value

Only if `display = FALSE`, returns information about the column. Otherwise information comes through the graphing pane and the console (via `cat/print`).

Examples

```
getinfo(iris, 'Sepal.Width')
getinfo(iris, 'Species')
```

gr *Golden Ratio*

Description

Get the golden ratio. Author: Bryce Chamberlain. Tech Review: Maria Gonzalez.

Usage

```
gr()
```

Value

The golden ratio: $(1+\sqrt{5})/2$

Examples

```
gr()
```

hashfiles *Hash Files*

Description

Get a hash value representing a list of files. Useful for determining if files have changed in order to reset dependent caches.

Usage

```
hashfiles(x, skip.missing = FALSE, full.hash = FALSE,
          verbose = FALSE)
```

Arguments

x	Input which specifies which files to hash. This can be a vector mix of paths and files.
skip.missing	Skip missing files. Default is to throw an error if a file isn't found.
full.hash	By default we just hash the file info (name, size, created/modified time). Set this to TRUE to read the file and hash the contents.
verbose	Print helpful messages from code.

Value

String representing hash of files.

Examples

```
hashfiles( '.' )
```

headers_row	<i>Identify headers row.</i>
-------------	------------------------------

Description

Identify the row with headers in a data frame. It should NOT be used directly (that's why it isn't exported), but will be called by function [read.any] as necessary, with the applicable defaults set by that function.

Usage

```
headers_row(x, headers_on_row = NA, first_column_name = NA,
            field_name_map = NA)
```

Arguments

`x` Data frame to work with.

`headers_on_row` The specific row with headers on it.

`first_column_name` A known column(s) that can be used to find the header row. This is more flexible, but only used if `headers_on_row` is not available. If multiple are possible, use a vector argument here.

`field_name_map` `field_name_map` from `read.any`.

Value

List with `headers_already_column_names` (TRUE/FALSE); `headers_on_row` (1-indexed number of the to match standard R indexing).

ijoinf	<i>Inner Join with Factors</i>
--------	--------------------------------

Description

Matches factor levels before inner join via merge. Author: Bryce Chamberlain.

Usage

```
ijoinf(data.left, data.right, by, sort.levels = TRUE,
        restrict.levels = FALSE, na_level = "(Missing)")
```


Arguments

<code>data.left</code>	Left data. Only rows that matche the join will be included (may still result in duplication).
<code>data.right</code>	Right data. Only rows that matche the join will be included (may also result in duplication).
<code>by</code>	Columns to join on.
<code>sort.levels</code>	Sort the factor levels after combining them.
<code>restrict.levels</code>	Often the joined data won't use all the levels in both datasets. Set to TRUE to remove factor levels that aren't in the joined data.
<code>na_level</code>	some functions don't like factors to have NAs so we replace NAs with this value for factors only. Set NULL to skip.

Value

Joined data, with any factors modified to contain all levels in the joined data.

Examples

```
df1 = data.frame(
  factor1 = c( 'a', 'b', 'c' ),
  factor2 = c( 'high', 'medium', 'low' ),
  factor.join = c( '0349038u093843', '304359867893753', '3409783509735' ),
  numeric = c( 1, 2, 3 ),
  logical = c( TRUE, TRUE, TRUE )
)

df2 = data.frame(
  factor1 = c( 'd', 'e', 'f' ),
  factor2 = c( 'low', 'medium', 'high' ),
  factor.join = c( '32532532536', '304359867893753', '32534745876' ),
  numeric = c( 4, 5, 6 ),
  logical = c( FALSE, FALSE, FALSE )
)

ljoinf( df1, df2, by = 'factor.join' )
```

ischar

Shorthand for is.character

Description

Shorthand for `is.character`

Usage

```
ischar(x)
```

Arguments

x Value to check.

Value

logical indicator

Examples

```
ischar( 'a character' )  
ischar(1)
```

isdate

Shorthand for lubridate::is.Date

Description

Shorthand for lubridate::is.Date

Usage

```
isdate(x)
```

Arguments

x Value to check.

Value

logical indicator

Examples

```
isdate( lubridate::mdy( '10/1/2014' ) )  
isdate(1)
```

isfac	<i>Shorthand for is.factor</i>
-------	--------------------------------

Description

Shorthand for is.factor

Usage

```
isfac(x)
```

Arguments

x Value to check.

Value

logical indicator

Examples

```
isfac( factor( c( 'a', 'b', 'c' ) ) )  
isfac(1)
```

isnum	<i>Shorthand for is.numeric</i>
-------	---------------------------------

Description

Shorthand for is.numeric

Usage

```
isnum(x)
```

Arguments

x Value to check.

Value

logical indicator

Examples

```
isnum(1)  
isnum( factor( c( 'a', 'b', 'c' ) ) )
```

`isval`*Is Valid / Is a Value / NA NULL Check*

Description

Facilitates checking for missing values which may cause errors later in code. NULL values can cause errors on `is.na` checks, and `is.na` can cause warnings if it is inside `if()` and is passed multiple values. This function makes it easier to check for missing values before trying to operate on a variable. It will NOT check for strings like "" or "NA". Only NULL and NA values will return TRUE. Author: Bryce Chamberlain. Tech Review: Maria Gonzalez.

Usage

```
isval(x, na_strings = easyr::nastrings, do.test.each = FALSE)
```

Arguments

<code>x</code>	Object to check. In the case of a data frame or vector, it will check the first (non-NULL) value.
<code>na_strings</code>	(Optional) Set the strings you want to consider NA. These will be applied after <code>stringr::str_trim</code> on <code>x</code> .
<code>do.test.each</code>	Return a vector of results to check each element instead of checking the entire object.

Value

True/false indicating if the argument is NA, NULL, or an empty/NA string/vector. For speed, only the first value is checked.

Examples

```
isval( NULL )
isval( NA )
isval( c( NA , NULL ) )
isval( c( 1, 2, 3 ) )
isval( c( NA, 2, 3 ) )
isval( c( 1, 2, NA ) ) # only the first values is checked, so this will come back FALSE.
isval( c( NULL, 2, 3 ) ) # NULL values get skipped in a vector.
isval( data.frame() )
isval( dplyr::group_by( dplyr::select( cars, speed, dist ), speed ) ) # test a tibble.
isval( "#VALUE!" ) # test an excel error code.
```

jrepl *Join and Replace Values.*

Description

Replace a columns values with matches in a different dataset. Author: Bryce Chamberlain.

Usage

```
jrepl(x, y, by, replace.cols, na.only = FALSE, only.rows = NULL,  
      verbose = FALSE)
```

Arguments

x	Main dataset which will have new values. This data set will be returned with new values.
y	Supporting dataset which has the id and new values.
by	Vector of join column names. A character vector if the names match. A named character vector if they don't.
replace.cols	Vector of replacement column names, similar format as by.
na.only	Only replace values that are NA.
only.rows	Select rows to be affected. Default checks all rows.
verbose	Print via cat information about the replacement.

Value

x with new values.

Examples

```
df1 = utils::head( sleep )  
group.reassign = data.frame(  
  id.num = factor( c( 1, 3, 4 ) ),  
  group.replace = factor( c( 99, 99, 99 ) )  
)  
  
jrepl(  
  x = df1,  
  y = group.reassign,  
  by = c( 'ID' = 'id.num' ),  
  replace.cols = c( 'group' = 'group.replace' )  
)  
  
# doesn't affect since there are no NAs in group.  
jrepl(  
  x = df1,
```

```

y = group.reassign,
by = c( 'ID' = 'id.num' ),
replace.cols = c( 'group' = 'group.replace' ),
na.only = TRUE
)

```

left	<i>left</i>
------	-------------

Description

Behaves like Excel's LEFT, RIGHT, and MID functions Author: Dave. Tech review: Bryce Chamberlain.

Usage

```
left(string, char)
```

Arguments

string	String to process.
char	Number of characters.

Examples

```
left( "leftmidright", 4 )
```

likedate	<i>Like Date</i>
----------	------------------

Description

Check if a column can be converted to a date. Helpful for checking a column before actually converting it. Author: Bryce Chamberlain. Tech review: Dominic Dillingham.

Usage

```
likedate(x, na_strings = easyr::nastrings, run_unique = TRUE,
  aggressive.extraction = TRUE)
```

Arguments

x	Value or vector to check.
na_strings	Vector of characters to consider NA. Like Date will treat these values like NA.
run_unique	Convert to unique variables before checking. In some cases, this can make it take longer than necessary. In most, it will make it faster.
aggressive.extraction	todate will take dates inside long strings (like filenames) and convert them to dates. This seems to be the preferred outcome, so we leave it as default (TRUE). However, if you want to avoid this you can do so via this option (FALSE).

Value

Boolean indicating if the entire vector can be converted to a date.

Examples

```
x <- c('20171124', '2017/12/24', NA, '12/24/2017', 'March 3rd, 2015', 'Mar 3, 2016')
likedate(x)
likedate(c(123, 456, NA))
if(likedate(x)) t <- todate(x)
likedate(lubridate::mdy('1-1-2014'))
likedate('3312019')
likedate('2019.1.3')
```

ljoinf

Left Join with Factors

Description

Matches factor levels before left join via merge. Author: Bryce Chamberlain.

Usage

```
ljoinf(data.left, data.right, by, sort.levels = TRUE,
       restrict.levels = FALSE, na_level = "(Missing)")
```

Arguments

data.left	Left data. All of this data will be preserved in the join (may still result in duplication).
data.right	Right data. Only rows that matche the join will be included (may also result in duplication).
by	Columns to join on.
sort.levels	Sort the factor levels after combining them.

`restrict.levels` Often the joined data won't use all the levels in both datasets. Set to TRUE to remove factor levels that aren't in the joined data.

`na_level` some functions don't like factors to have NAs so we replace NAs with this value for factors only. Set NULL to skip.

Value

Joined data, with any factors modified to contain all levels in the joined data.

Examples

```
df1 = data.frame(
  factor1 = c( 'a', 'b', 'c' ),
  factor2 = c( 'high', 'medium', 'low' ),
  factor.join = c( '0349038u093843', '304359867893753', '3409783509735' ),
  numeric = c( 1, 2, 3 ),
  logical = c( TRUE, TRUE, TRUE )
)

df2 = data.frame(
  factor1 = c( 'd', 'e', 'f' ),
  factor2 = c( 'low', 'medium', 'high' ),
  factor.join = c( '32532532536', '304359867893753', '32534745876' ),
  numeric = c( 4, 5, 6 ),
  logical = c( FALSE, FALSE, FALSE )
)

ljoinf( df1, df2, by = 'factor.join' )
```

`match.factors` *Match Factors.*

Description

Modifies two datasets so matching factor columns have the same levels. Typically this is used prior to joining or `bind_rows` in the easyr functions `bindf`, `ljoinf`, `lfjoinf`.

Usage

```
match.factors(df1, df2, by = NA, sort.levels = TRUE)
```

Arguments

`df1` First data set.

`df2` Second data set.

`by` Columns to join on, comes from the function using `match.factors` (`ljoinf`, `fjoinf`, `ijoinf`).

`sort.levels` Sort the factor levels after combining them.

Value

List of the same data but with factors modified as applicable. All factors are checked if no `'by'` argument is passed. Otherwise only the `'by'` argument is checked.

Examples

```
df1 = data.frame(
  factor1 = c( 'a', 'b', 'c' ),
  factor2 = c( 'high', 'medium', 'low' ),
  factor.join = c( '0349038u093843', '304359867893753', '3409783509735' ),
  numeric = c( 1, 2, 3 ),
  logical = c( TRUE, TRUE, TRUE )
)

df2 = data.frame(
  factor1 = c( 'd', 'e', 'f' ),
  factor2 = c( 'low', 'medium', 'high' ),
  factor.join = c( '32532532536', '304359867893753', '32534745876' ),
  numeric = c( 4, 5, 6 ),
  logical = c( FALSE, FALSE, FALSE )
)

t = match.factors( df1, df2 )
levels( df1$factor1 )
levels( t[[1]]$factor1 )
levels( t[[2]]$factor1 )
```

 mdiff

Date Difference in Months

Description

Date Difference in Months

Usage

```
mdiff(x, y, do.date.convert = TRUE, do.numeric = TRUE)
```

Arguments

<code>x</code>	Vector of starting dates or items that can be converted to dates by <code>today</code> .
<code>y</code>	Vector of ending dates or items that can be converted to dates by <code>today</code> .
<code>do.date.convert</code>	Convert to dates before running the difference. If you know your columns are already dates, setting to <code>FALSE</code> will make your code run faster.
<code>do.numeric</code>	Convert the output to a number instead of a date difference object.

Value

Vector of differences.

Examples

```
mdiff( lubridate::mdy( '1/1/2018' ), lubridate::mdy( '3/4/2018' ) )
```

`mid`

mid

Description

Behaves like Excel's `LEFT`, `RIGHT`, and `MID` functions Author: Bryce Chamberlain.

Usage

```
mid(string, start, nchars)
```

Arguments

<code>string</code>	String to process.
<code>start</code>	Index (1-index) to start at.
<code>nchars</code>	Number of characters to read in from start.

Examples

```
mid( "leftmidright", 5, 3 )
```

na	<i>Shorthand for is.na</i>
----	----------------------------

Description

Shorthand for is.na

Usage

```
na(x)
```

Arguments

x	Value to check.
---	-----------------

Value

logical indicator

Examples

```
na(NA)
na(1)
```

namesx	<i>Names Like</i>
--------	-------------------

Description

Get column names that match a pattern. Author: Scott Sobel. Tech review: Bryce Chamberlain.

Usage

```
namesx(df, char, fixed = TRUE, ignore.case = TRUE)
```

Arguments

df	Object with names you'd like to search.
char	Regex chracter to match to columns.
fixed	Match as a string, not a regular expression.
ignore.case	Ignore case in matches.

Value

Vector of matched names.

Examples

```
namesx( iris, 'len' )
namesx( iris, 'Len' )
```

nan	<i>Shorthand for is.nan</i>
-----	-----------------------------

Description

Shorthand for is.nan

Usage

```
nan(x)
```

Arguments

x	Value to check.
---	-----------------

Value

logical indicator

Examples

```
nan( NaN )
nan(1)
```

nanull	<i>NA / NULL Check</i>
--------	------------------------

Description

Facilitates checking for missing values which may cause errors later in code. NULL values can cause errors on is.na checks, and is.na can cause warnings if it is inside if() and is passed multiple values. This function makes it easier to check for missing values before trying to operate on a variable. It will NOT check for strings like "" or "NA". Only NULL and NA values will return TRUE. Author: Bryce Chamberlain. Tech Review: Maria Gonzalez.

Usage

```
nanull(x, na_strings = easyr::nastrings, do.test.each = FALSE)
```

Arguments

<code>x</code>	Vector to check. In the case of a data frame or vector, it will check the first (non-NULL) value.
<code>na_strings</code>	(Optional) Set the strings you want to consider NA. These will be applied after <code>stringr::str_trim</code> on <code>x</code> .
<code>do.test.each</code>	Return a vector of results to check each element instead of checking the entire object.

Value

True/false indicating if the argument is NA, NULL, or an empty/NA string/vector. For `speect`, only the first value is checked.

Examples

```
nanull( NULL )
nanull( NA )
nanull( c( NA , NULL ) )
nanull( c( 1, 2, 3 ) )
nanull( c( NA, 2, 3 ) )
nanull( c( 1, 2, NA ) ) # only the first values is checked, so this will come back FALSE.
nanull( c( NULL, 2, 3 ) ) # NULL values get skipped in a vector.
nanull( data.frame() )
nanull( dplyr::group_by( dplyr::select( cars, speed, dist ), speed ) ) # test a tibble.
```

nastrings

NA Strings

Description

A list of strings to consider NA. Includes blank string, "NA", excel errors, etc. Used throughout `easyr` for checking NA.

Usage

```
nastrings
```

Format

A vector of values.

`null` *Shorthand for is.null*

Description

Shorthand for `is.null`

Usage

```
null(x)
```

Arguments

`x` Value to check.

Value

logical indicator

Examples

```
null( NULL )  
null(1)
```

`pad0` *Pad with Zeros*

Description

Adds leading zeros to a numeric vector to make each value a specific length. For values shorter than length passed, leading zeros are removed. Author: Scott Sobel. Tech Review: Bryce Chamberlain.

Usage

```
pad0(x, len)
```

Arguments

`x` Vector.
`len` Number of characters you want in each value.

Value

Character vector with padded values.

Examples

```
pad0( c(123,00123,5), len = 5 )
pad0( c(123,00123,5), len = 2 )
pad0( '1234', 5 )
```

qdiff

Date Difference in Quarters

Description

Date Difference in Quarters

Usage

```
qdiff(x, y, do.date.convert = TRUE, do.numeric = TRUE)
```

Arguments

x	Vector of starting dates or items that can be converted to dates by todote.
y	Vector of ending dates or items that can be converted to dates by todote.
do.date.convert	Convert to dates before running the difference. If you know your columns are already dates, setting to FALSE will make your code run faster.
do.numeric	Convert the output to a number instead of a date difference object.

Value

Vector of differences.

Examples

```
qdiff( lubridate::mdy( '1/1/2018' ), lubridate::mdy( '3/4/2018' ) )
```

rany_fixColNames

Fix column names.

Description

Code to fix column names, since this has to be done up to twice will reading in files. It should NOT be used directly (that's why it isn't exported), but will be called by function [read.any] as necessary, with the applicable defaults set by that function.

Usage

```
rany_fixColNames(col_names, fix.dup.column.names, nastrings)
```

Arguments

col_names	Vector/value of column names/name.
fix.dup.column.names	Adds 'DUPLICATE #' to duplicated column names to avoid errors with duplicate names.
nastrings	Characters/strings to read as NA.

Value

Fixed names.

read.any	<i>Read Any File</i>
----------	----------------------

Description

Flexible read function to handle many types of files. Currently handles CSV, TSV, DBF, RDS, XLS (incl. when formatted as HTML), and XLSX. Also handles common issues like strings being read in as factors (strings are NOT read in as factors by this function, you'd need to convert them later). Author: Bryce Chamberlain. Tech Review: Dominic Dillingham.

Usage

```
read.any(filename = NA, folder = NA, sheet = 1, file_type = "",
  first_column_name = NA, header = TRUE, headers_on_row = NA,
  nrows = -1L, row.names.column = NA, row.names.remove = TRUE,
  make.names = FALSE, field_name_map = NA, require_columns = NA,
  all_chars = FALSE, auto_convert_dates = TRUE, allow_times = FALSE,
  check_numbers = TRUE, nzero = FALSE, check_logical = TRUE,
  stringsAsFactors = FALSE, na_strings = easyr::nastrings,
  na_level = "(Missing)", ignore_rows_with_na_at = NA,
  drop.na.cols = TRUE, drop.na.rows = TRUE,
  fix.dup.column.names = TRUE, do.trim.sheetname = TRUE, x = NULL,
  isexcel = FALSE, encoding = "unknown", verbose = TRUE)
```

Arguments

filename	File path and name for the file to be read in.
folder	Folder path to look for the file in.
sheet	The sheet to read in.
file_type	Specify the file type (CSV, TSV, DBF). If not provided, R will use the file extension to determine the file type. Useful when the file extension doesn't indicate the file type, like .rpt, etc.
first_column_name	Define headers location by providing the name of the left-most column. Alternatively, you can choose the row via the [headers_on_row] argument.

header	Choose if your file contains headers.
headers_on_row	Choose a specific row number to use as headers. Use this when you want to tell read.any exactly where the headers are.
nrows	Number of rows to read. Leave blank/NA to read all rows. This only speeds up file reads (CSV, XLSX, etc.), not compressed data that must be read all at once. This is applied BEFORE headers_on_row or first_column_name removes top rows, so it should be greater than those values if headers aren't in the first row.
row.names.column	Specify the column (by character name) to use for row names. This drops the columns and lets rows be referenced directly with this id. Must be unique values.
row.names.remove	If you move a column to row names, it is removed from the data by default. If you'd like to keep it, set this to FALSE.
make.names	Apply make.names function to make column names R-friendly (replaces non-characters with ., starting numbers with x, etc.)
field_name_map	Rename fields for consistency. Provide as a named vector where the names are the file's names and the vector values are the output names desired. See examples for how to create this input.
require_columns	List of required columns to check for. Calls stop() with helpful message if any aren't found.
all_chars	Keep all column types as characters. This makes using bind_rows easier, then you can use atype() later to set types.
auto_convert_dates	Identify date fields and automatically convert them to dates
allow_times	imes are not allowed in reading data in to facilitate easy binding. If you need times though, set this to TRUE.
check_numbers	Identify numbers formatted as characters and convert them as such.
nazero	Convert NAs in numeric columns to 0.
check_logical	Identify logical columns formatted as characters (Yes/No, etc) or numbers (0,1) and convert them as such.
stringsAsFactors	Convert characters to factors to increase processing speed and reduce file size.
na_strings	Strings to treat like NA. By default we use the easyr NA strings.
na_level	dplyr doesn't like factors to have NAs so we replace NAs with this value for factors only. Set NULL to skip.
ignore_rows_with_na_at	Vector or value, numeric or character, identifying column(s) that require a value. read.any will remove these rows after colname swaps and read, before type conversion. Especially helpful for removing things like page numbers at the bottom of an excel report that break type discovery. Suggest using the claim number column here.
drop.na.cols	Drop columns with only NA values.

drop.na.rows	Drop rows with only NA values.
fix.dup.column.names	Adds 'DUPLICATE #' to duplicated column names to avoid issues with multiple columns having the same name.
do.trim.sheetname	read.any will trim sheet names to get better matches. This will cause an error if the actual sheet name has spaces on the left or right side. Disable this functionality here.
x	If you want to use read.any functionality on an existing data frame, pass it with this argument.
isexcel	If you want to use read.any functionality on an existing data frame, you can tell read.any that this data came from excel using isexcel manually. This comes in handy when excel-integer date conversions are necessary.
encoding	Encoding passed to fread and read.csv.
verbose	Print helpful information via cat.

Value

Data frame with the data that was read.

Examples

```
folder = system.file('extdata', package = 'easyr')
read.any('date-time.csv', folder = folder)

# if dates are being converted incorrectly, disable date conversion:
read.any('date-time.csv', folder = folder, auto_convert_dates = FALSE)

# to handle type conversions manually:
read.any('date-time.csv', folder = folder, all_chars = TRUE)
```

read.txt

Read File as Text

Description

Read File as Text

Usage

```
read.txt(filename, folder = NA)
```

Arguments

filename	File path and name for the file to be read in.
folder	Folder path to look for the file in.

Value

Character variable containing the text in the file.

Examples

```
# write a files.
path = tempfile()
cat( "some text", file = path )

# read the file.
read.txt( path )

# cleanum.
file.remove( path )
```

right

right

Description

Behaves like Excel's LEFT, RIGHT, and MID functions Author: Dave. Tech review: Bryce Chamberlain.

Usage

```
right(string, char)
```

Arguments

string	String to process.
char	Number of characters.

Examples

```
right( "leftmidright",5 )
```

runfolder

Run Folder

Description

Run all the R scripts in a folder. Author: Bryce Chamberlain.

Usage

```
runfolder(path, recursive = FALSE, is.local = TRUE, check.fn = NULL,
  run.files = NULL, verbose = TRUE, edit.on.err = TRUE,
  pattern = "[.][Rr]$")
```

Arguments

path	Folder to run.
recursive	Run all folder children also.
is.local	Code is running on a local machine, not a Shiny server. Helpful for skipping items that can be problematic on the server. In this case, printing to the log.
check.fn	Function to run after reach file is read-in.
run.files	Optionally pass the list of files to run. Otherwise, list.files will be run on the folder.
verbose	Print names of files and run-time via cat.
edit.on.err	Open the running file if an error occurs.
pattern	Passed to list.files. Pattern to match/filter files.

Examples

```
# runfolder( 'R' )
```

rx

Read Excel

Description

This gets a bit complex since many errors can occur when reading in excel files. We've done our best to handle common ones. Requires packages: openxlsx, readxl, XML (these are required by easyr). It should NOT be used directly (that's why it isn't exported), but will be called by function [read.any] as necessary, with the applicable defaults set by that function.

Usage

```
rx(filename, sheet, first_column_name, nrow, verbose)
```

Arguments

filename	File path and name for the file to be read in.
sheet	The sheet to read in.
first_column_name	Pass a column name to help the function find the header row.
nrows	Number of rows to read in.
verbose	Print helpful messages via cat().

Value

Data object

save.cache	<i>Save Cache Saves the arguments to a cache file, using the cache.num last checked with cache.ok.</i>
------------	--------------------------------------------------------------------------------------------------------

Description

Save Cache

Saves the arguments to a cache file, using the cache.num last checked with cache.ok.

Usage

```
save.cache(...)
```

Arguments

... Objects to save.

Examples

```
# check the first cache to see if it exists and dependent files haven't changed.
# if this check is TRUE, code in brackets will get skipped and the cache will be loaded instead.
# set do.load = FALSE if you have multiple files that build a cache,
#   to prevent multiple cache loads.
# output will be printed to the console to tell you if the cache was loaded or re-built.
if( ! cache.ok(1) ){

  # do stuff

  # if this is the final file for this cache, end with save.cache to save passed objects as a cache.
  save.cache(iris)
}

# delete the cache folder to close out the example.
system( "rm -r cache" )
```

sch

*Search a Data Frame.***Description**

Searches all columns for a term and returns all rows with at least one match. Author: Bryce Chamberlain.

Usage

```
sch(x, pattern, ignore.case = FALSE, fixed = FALSE, pluscols = NULL,
    exact = FALSE, trim = TRUE, spln = NULL)
```

Arguments

x	Data to search.
pattern	Regex patter to search. Most normal search terms will work fine, too.
ignore.case	Ignore case in search (uses grepl).
fixed	Passed to grepl to match string as-is instead of using regex. See ?grepl.
pluscols	choose columns to return in addition to those where matches are found. Can be a name, number or 'all' to bring back all columns.
exact	Find exact matches intead of pattern matching.
trim	Use trimws to trim columns before exact matching.
spln	Sample data use easyr::spl() before searching. This will speed up searching in large datasets when you only need to identify columns, not all data that matches. See ?spl n argument for more info.

Value

Matching rows.

Examples

```
sch( iris, 'seto' )
sch( iris, 'seto', pluscols='all' )
sch( iris, 'seto', pluscols='Sepal.Width' )
sch( iris, 'seto', exact = TRUE ) # message no matches and return NULL
```

spl	<i>Sample</i>
-----	---------------

Description

Extracts a uniform random sample from a dataset or vector. Provides a simpler API than base R.
 Author: Bryce Chamberlain. Tech Review: Maria Gonzalez.

Usage

```
spl(x, n = 10, warn = TRUE, replace = FALSE, ...)
```

Arguments

x	Data to sample from.
n	Number or percentage of rows/values to return. If less than 1 it will be interpreted as a percentage.
warn	Warn if sampling more than the size of the data.
replace	Whether or not to sample with replacement.
...	Other parameters passed to sample()

Value

Sample dataframe/vector.

Examples

```
spl( c(1:100) )
spl( c(1:100), n = 50 )
spl( iris )
```

states	<i>states</i>
--------	---------------

Description

Helpful info for states. Right now, just a mapping of abbreviations to names.

Usage

```
states
```

Format

Data frame.

strx	<i>Structure with Like</i>
------	----------------------------

Description

Runs str function but only for names matching a character value (regex). Author: Scott Sobel. Tech Review: Bryce Chamberlain.

Usage

```
strx(df, char, ignore.case = T)
```

Arguments

df	Object with names you'd like to search.
char	Regex (character value) to match.
ignore.case	(Optional) Ignore case when matching.

Examples

```
strx(iris, 'length')
```

sumnum	<i>Summarize All Numeric Columns</i>
--------	--------------------------------------

Description

Easily summarize at all numeric variables. Helpful for flexibly summarizing without knowing the columns. Defaults to sum but you can send a custom function through also. Typically pass in a data frame after group_by.

Usage

```
sumnum(x, do.fun = NULL, except = c(), do.ungroup = TRUE, ...)
```

Arguments

x	Grouped tibble to summarize.
do.fun	Function to use for the summary. Passed to dplyr::summarize(). Can be a custom function. Defaults to sum().
except	Columns names, numbers, or a logical vector indicating columns NOT to summarize.
do.ungroup	Run dplyr::ungroup() after summarizing the prevent future issues with grouping.
...	Extra args passed to dplyr::summarize() which are applied as arguments to the function passed in do.fun.

Value

Summarized data frame or tibble.

Examples

```
require(dplyr)
require(easyr)

sumnum( group_by( cars, speed ) )
sumnum( group_by( cars, speed ), mean )
sumnum( cars )
```

tcmsg

tryCatch with Message

Description

Easy Try/Catch implementation to return the same message on error or warning. Makes it easier to write tryCatches. Author: Bryce Chamberlain. Tech review: Lindsay Smelzter.

Usage

```
tcmsg(code_block, ...)
```

Arguments

`code_block` Code to run in Try Catch.
`...` Strings to concatenate to form the message that is returned.

Examples

```
tryCatch({
  tcmsg({ NULL = 1 }, 'Cannot assign to NULL','variable' )
},
error = function(e) print( e )
)

tryCatch({
  tcmsg({ as.numeric('abc') }, 'Issue in as.numeric()')
},
warning = function(e) print( e )
)
```

tccol *Transpose at Column.*

Description

Transpose operation that sets column names equal to a column in the original data. Author: Bryce Chamberlain.

Usage

```
tccol(x, header, cols.colname = "col", do.atype = TRUE)
```

Arguments

x	Data frame to be transposed.
header	Column name/number to be used as column names of transposed data.
cols.colname	Name to use for the column of column names in the transposed data.
do.atype	Transpose convertes to strings, since data types are uncertain. Run atype to automatically correct variable typing where possible. This will slow the result a bit.

Value

Transposed data frame.

Examples

```
# create a summary dataset from iris.
x = dplyr::summarize_at(
  dplyr::group_by( iris, Species ),
  dplyr::vars( Sepal.Length, Sepal.Width ), list(sum)
)
# run tccol
tccol( x, 'Species' )
```

tcwarn *tryCatch with warning*

Description

Easy Try/Catch implementation to return the same message as a warning on error or warning. Makes it easier to write tryCatches. Author: Bryce Chamberlain. Tech review: Lindsay Smelzter.

Usage

```
tcwarn(code_block, ...)
```

Arguments

code_block Code to run in Try Catch.
 ... Strings to concatenate to form the message that is returned.

Examples

```
tryCatch({
  tcwarn({ NULL = 1 }, 'Cannot assign to NULL', 'variable')
},
warning = function(e) print( e )
)

tryCatch({
  tcwarn({ as.numeric('abc') }, 'Issue in as.numeric()')
},
warning = function(e) print( e )
)
```

tobool	<i>Convert to Logical/Boolean</i>
--------	-----------------------------------

Description

Flexible boolean conversion. Author: Bryce Chamberlain.

Usage

```
tobool(x, preprocessed.values = NULL, nastrings = easyr::nastrings,
  ifna = c("return-unchanged", "error", "warning", "return-na"),
  verbose = TRUE, true.vals = c("true", "1", "t", "yes"),
  false.vals = c("false", "0", "f", "no"))
```

Arguments

x	Value or vector to be converted.
preprocessed.values	Strings need to have NAs set, lowercase and be trimmed before they can be checked. To avoid doing this multiple times, you can pass these processed values to the function.
nastrings	Vector of characters to be considered NAs. todate will treat these like NAs. Defaults to the easyr::nastrings list.
ifna	Action to take if NAs are created. 'return-unchanged' returns the sent vector unchanged; 'warning' results in a warning and returns the converted vector with new NAs; 'error' results in an error.
verbose	Choose to view messaging.
true.vals	Values to consider as TRUE.
false.vals	Values to consider as FALSE.

Value

Converted logical vector.

Examples

```
tobool( c( 'true', 'FALSE', 0, 1, NA, 'yes', 'NO' ) )
```

tochar	<i>Shorthand for as.character</i>
--------	-----------------------------------

Description

Shorthand for as.character

Usage

```
tochar(x)
```

Arguments

x Value to check.

Value

as.character result

Examples

```
tochar(NA)
tochar(1)
```

todate	<i>Convert to Date</i>
--------	------------------------

Description

Flexible date conversion function using lubridate. Works with dates in many formats, without needing to know the format in advance. Only use this if you don't know the format of the dates before hand. Otherwise, lubridate functions parse_date_time, mdy, etc. should be used. Author: Bryce Chamberlain. Tech review: Dominic Dillingham.

Usage

```
todate(x, nastrings = easyr::nastrings, aggressive.extraction = TRUE,
       preprocessed.values = NULL, ifna = c("return-unchanged", "error",
       "warning", "return-na"), verbose = TRUE, allow_times = FALSE,
       do.month.char = TRUE, do.excel = TRUE,
       min.acceptable = lubridate::ymd("1920-01-01"),
       max.acceptable = lubridate::ymd("2050-01-01"))
```

Arguments

x	Value or vector to be converted.
nastrings	Vector of characters to be considered NAs. todate will treat these like NAs. Defaults to the easyr::nastrings list.
aggressive.extraction	todate will take dates inside long strings (like filenames) and convert them to dates. This seems to be the preferred outcome, so we leave it as default (TRUE). However, if you want to avoid this you can do so via this option (FALSE).
preprocessed.values	Strings need to have NAs set, lowercase and be trimmed before they can be checked. To avoid doing this multiple times, you can pass these processed values to the function.
ifna	Action to take if NAs are created. 'return-unchanged' returns the sent vector unchanged; 'warning' results in a warning and returns the converted vector with new NAs; 'error' results in an error; 'return-na' returns new NAs without a warning.
verbose	Choose to view messaging.
allow_times	Set to TRUE to allow DateTimes as output, otherwise this will always convert to Dates (losing time information). This is better for binding data, hence the default FALSE.
do.month.char	Attempt to convert month names in text. lubridate does this by default, but sometimes it can result in inaccurate dates. For example, "Feb 2017" is converted to 2-20-2017 even though no day was given.
do.excel	Check for excel-formatted numbers.
min.acceptable	Set NA if converted value is less than this value. Helps to prevent numbers from being assumed as dates. Set NULL to skip this check. Does not affect character conversions.
max.acceptable	Set NA if converted value is greater than this value. Helps to prevent numbers from being assumed as dates. Set NULL to skip this check. Does not affect character conversions.

Value

Converted vector using `lubridate::parse_date_time(x,c('mdy','ymd','dmy'))`

Examples

```
x <- c( '20171124', '2017/12/24', NA, '12/24/2017', '5/11/2017 1:51PM' )
x2 <- todate(x)
x2
```

tonum

*Convert to Number***Description**

Flexible number conversion for converting strings to numbers. Handles \$, ' and spaces. Author: Bryce Chamberlain. Tech review: Dominic Dillingham.

Usage

```
tonum(x, preprocessed.values = NULL, nastrings = easyr::nastrings,
      ifna = c("return-unchanged", "error", "warning", "return-na"),
      verbose = TRUE, nazero = FALSE, checkdate = TRUE,
      remove.chars = FALSE, do.logical = TRUE, do.try.integer = TRUE,
      multipliers = c(`%` = 1/100, K = 1000, M = 1000^2, B = 1000^3))
```

Arguments

x	Vector to convert.
preprocessed.values	Strings need to have NAs set, lowercase and be trimmed before they can be checked. To avoid doing this multiple times, you can pass these processed values to the function.
nastrings	Vector of characters to be considered NAs. todate will treat these like NAs. Defaults to the easyr::nastrings list.
ifna	Action to take if NAs are created. 'return-unchanged' returns the sent vector unchanged; 'warning' results in a warning and returns the converted vector with new NAs; 'error' results in an error; return-na returns data with new NAs and prints via cat if verbose.
verbose	Choose to view messaging.
nazero	(Optional) Convert NAs to 0. Defaults to TRUE, if FALSE NAs will stay NA.
checkdate	Check if the column is a date first. If this has already been done, set this to FALSE so it doesn't run again.
remove.chars	Remove characters for aggressive conversion to numbers.
do.logical	Check for logical-form vectors.
do.try.integer	Return an integer if possible. Integers are a more compact data type and should be used whenever possible.
multipliers	Named vector of factor symbols and values to check. Setting to NULL may speed up operations.

Value

Converted vector.

Examples

```
tonum( c('123', '$50.02', '30%', '(300.01)', NA, '-', '') )
tonum( c('123', '$50.02', '30%', '(300.01)', NA, '-', ''), nazer0 = FALSE )
tonum( c( '$(3,891)M', '4B', '3.41K', '30', '40K' ) )
```

usepkg

Use Package

Description

Installs a package if it needs to be installed, and calls require to load the package. Author: Scott Sobel. Tech Review: Bryce Chamberlain.

Usage

```
usepkg(packages, noCache = FALSE,
       repos = "http://cran.us.r-project.org")
```

Arguments

packages	Character or character vector with names of the packages you want to use.
noCache	When checking packages, you can choose to ignore the cached list, which will increase accuracy but decrease speed.
repos	choose the URL to install from.

Examples

```
# packages shouldn't be installed during tests or examples according to CRAN.
# therefore, examples cannot be provided because CRAN now runs donttest examples.
```

validate.equal

Validate Equal

Description

Check various properties of 2 data frames to ensure they are equivalent.

Usage

```
validate.equal(df1, df2, id.column = NULL,
  regex.remove = "[^A-z0-9.+\\/, -]", do.set.NA = TRUE,
  nastrings = easyr::nastrings, match.round.to.digits = 4,
  do.all.columns.before.err = FALSE, check.column.order = FALSE,
  sort.by.id = TRUE, acceptable.pct.rows.diff = 0,
  acceptable.pct.vals.diff = 0, return.summary = FALSE,
  verbose = TRUE)
```

Arguments

<code>df1</code>	First data frame to compare.
<code>df2</code>	Second data frame to compare.
<code>id.column</code>	If available, a column to use as an ID. Helpful in various checks and output.
<code>regex.remove</code>	Pattern to remove from strings. Used in <code>gsub</code> to remove characters we don't want to consider when comparing values. Set to <code>NULL</code> , <code>NA</code> , or <code>""</code> to leave strings unchanged.
<code>do.set.NA</code>	Remove NA strings.
<code>nastrings</code>	Strings to consider NA.
<code>match.round.to.digits</code>	Round numbers to these digits before checking equality.
<code>do.all.columns.before.err</code>	Check all columns before returning an error. Takes longer but returns more detail. If <code>FALSE</code> , stops at first column that doesn't match and returns mismatches.
<code>check.column.order</code>	Enforce same column order.
<code>sort.by.id</code>	Sort by the id column before making comparisons.
<code>acceptable.pct.rows.diff</code>	If you are OK with differences in a few rows, set this value. If fewer rows in a column don't match, the function will consider the columns equivalent. Interpreted as a percentage (it gets divided by 100).
<code>acceptable.pct.vals.diff</code>	If you are OK with small differences in values, set this value. If the difference in numeric values is less, the function will consider the values equivalent. Interpreted as a percentage (it gets divided by 100) and compared to absolute value of percentage difference.
<code>return.summary</code>	Return 2 items in a list, the row mismatches and a summary of row mismatches.
<code>verbose</code>	Print helpful information via <code>cat()</code> .

Value

May return information about mismatches. Otherwise doesn't return anything (`NULL`).

Examples

```
validate.equal( iris, iris )
```


w

*Write***Description**

Improved write function. Writes to csv without row names and automatically adds .csv to the file name if it isn't there already. Changes to .csv if another extension is passed. Easier to type than write.csv(row.names=F). Author: Bryce Chamberlain. Tech review: Maria Gonzalez.

Usage

```
w(x, filename = "out", row.names = FALSE, na = "")
```

Arguments

x	Data frame to write to file.
filename	(Optional) Filename to use.
row.names	(Optional) Specify if you want to include row names/numbers in the output file.
na	(Optional) String to print for NAs. Defaults to an empty/blank string.

Examples

```
# write the cars dataset.
path = paste0( tempdir(), '/out.csv' )
w( cars, path )

# cleanup.
file.remove( path )
```

xldate

*Convert Excel Number to Date***Description**

Converts dates formatted as long integers from Excel to Date format in R, accounting for known Excel leap year errors. Author: Bryce Chamberlain. Tech review: Dominic Dillingham.

Usage

```
xldate(x, origin = "1899-12-30", nastrings = easyr::nastrings,
preprocessed.values = NULL, ifna = c("return-unchanged", "error",
"warning", "return-na"), verbose = TRUE, allow_times = FALSE,
do.month.char = TRUE, min.acceptable = lubridate::ymd("1920-01-01"),
max.acceptable = lubridate::ymd("2050-01-01"))
```

Arguments

x	Vector of values.
origin	Zero value to use in date conversion. Older version of excel might use a different value.
nastrings	Vector of characters to be considered NAs. todate will treat these like NAs. Defaults to the easyr::nastrings list.
preprocessed.values	Strings need to have NAs set, lowercase and be trimmed before they can be checked. To avoid doing this twice, you can tell the function that it has already been done.
ifna	Action to take if NAs are created. 'return-unchanged' returns the sent vector unchanged; 'warning' results in a warning and returns the converted vector with new NAs; 'error' results in an error.
verbose	Choose to view messaging.
allow_times	Return values with time, not just the date.
do.month.char	Convert month character names like Feb, March, etc.
min.acceptable	Set NA if converted value is less than this value. Helps to prevent numbers from being assumed as dates. Set NULL to skip this check.
max.acceptable	Set NA if converted value is greater than this value. Helps to prevent numbers from being assumed as dates. Set NULL to skip this check.

Value

Vector of converted values.

Examples

```
xldate( c('7597', '42769', '47545', NA ) )
```

ydiff

Date Difference in Years

Description

Date Difference in Years

Usage

```
ydiff(x, y, do.date.convert = TRUE, do.numeric = TRUE)
```

Arguments

- x Vector of starting dates or items that can be converted to dates by todate.
- y Vector of ending dates or items that can be converted to dates by todate.
- do.date.convert Convert to dates before running the difference. If you know your columns are already dates, setting to FALSE will make your code run faster.
- do.numeric Convert the output to a number instead of a date difference object.

Value

Vector of differences.

Examples

```
ydifff( lubridate::mdy( '1/1/2018' ), lubridate::mdy( '3/4/2018' ) )
```

%ni%	<i>Not-In</i>
------	---------------

Description

Opposite of Author: Bryce Chamberlain.

Usage

```
needle %ni% haystack
```

Arguments

- needle Vector to search for.
- haystack Vector to search in.

Value

Boolean vector/value of comparisons.

Examples

```
c(1,3,11) %ni% 1:10
```

Index

- * **datasets**
 - cblind, 9
 - nastrings, 37
 - states, 47
- %ni%, 59
- astext, 3
- atype, 4

- begin, 5
- binbyvol, 6
- bindf, 6

- cache.init, 7
- cache.ok, 8
- cblind, 9
- cc, 9
- char2fac, 10
- charnum, 11
- checked, 12
- clear.cache, 12
- coalf, 13
- crun, 14

- ddiff, 14
- dict, 15
- drows, 16

- ecopy, 16
- eq, 17

- fac2char, 18
- fjoinf, 18
- fldict, 19
- fmat, 20

- getbetterint, 21
- getinfo, 22
- gr, 23

- hashfiles, 23

- headers_row, 24

- ijoinf, 24
- ischar, 25
- isdate, 26
- isfac, 27
- isnum, 27
- isval, 28

- jrepl, 29

- left, 30
- likedate, 30
- ljoinf, 31

- match.factors, 32
- mdiff, 33
- mid, 34

- na, 35
- namesx, 35
- nan, 36
- nanull, 36
- nastrings, 37
- null, 38

- pad0, 38

- qdiff, 39

- rany_fixColNames, 39
- read.any, 40
- read.txt, 42
- right, 43
- runfolder, 44
- rx, 44

- save.cache, 45
- sch, 46
- spl, 47
- states, 47

strx, [48](#)
sumnum, [48](#)

tcmmsg, [49](#)
tcol, [50](#)
tcwarn, [50](#)
tobool, [51](#)
tochar, [52](#)
todate, [52](#)
tonum, [54](#)

usepkg, [55](#)

validate.equal, [55](#)

w, [57](#)

xldate, [57](#)

ydiff, [58](#)