

Package ‘fitPS’

June 10, 2023

Type Package

Title Fit Zeta Distributions to Forensic Data

Version 0.2-6

Date 2023-06-07

Description Fits Zeta distributions (discrete power laws) to data that arises from forensic surveys of clothing on the presence of glass and paint in various populations. The general method is described to some extent in Coulson, S.A., Buckleton, J.S., Gummer, A.B., and Triggs, C.M. (2001) <[doi:10.1016/S1355-0306\(01\)71847-3](https://doi.org/10.1016/S1355-0306(01)71847-3)>, although the implementation differs.

License GPL (>= 2)

Encoding UTF-8

LazyData true

Depends foreach, R (>= 4.0.0)

Imports doParallel, dplyr, Hmisc, iterators, knitr, ks, methods, pbapply, Rdpack, readxl, VGAM

RdMacros Rdpack

RoxygenNote 7.2.3

URL <https://github.com/jmcurran/fitPS>

BugReports <https://github.com/jmcurran/fitPS/issues>

Suggests rmarkdown, sp

VignetteBuilder knitr

NeedsCompilation no

Author James Curran [aut, cre]

Maintainer James Curran <j.curran@auckland.ac.nz>

Repository CRAN

Date/Publication 2023-06-10 11:50:02 UTC

R topics documented:

==.psData	2
as.data.frame.psData	3
bootCI	4
confint.psFit	6
fitDist	7
fitted.psData	9
fitZIDist	9
makePSData	11
mean.psData	12
plot.psFit	13
predict.psFit	14
print.psData	15
print.psFit	15
probfun	16
Psurveys	16
readData	17
rZizeta	18
Ssurveys	19
var	20
var.psData	21

Index	22
--------------	-----------

==.psData	<i>S3 method for objects of class psData</i>
-----------	--

Description

Tests to see if two objects of class `psData` are equal. That is their type is the same, and the data contained in data is the same. See [readData](#) for a description of the `psData` class.

Usage

```
## S3 method for class 'psData'
lhs == rhs
```

Arguments

lhs	an object of class <code>psData</code> .
rhs	an object of class <code>psData</code> .

Details

NOTE: the notes member variable is ignored in this function as it is unlikely that a user would want to see if the notes are the same.

Value

TRUE if the two objects are equal

Examples

```
p = readData(system.file("extdata", "p.xlsx", package = "fitPS"))
p1 = makePSData(n = 0:2, count = c(98, 1, 1), type = "P")
p2 = makePSData(n = 0:2, count = c(97, 2, 1), type = "P")
p == p1 ## TRUE
p == p2 ## FALSE
p1 == p2 ## FALSE
```

as.data.frame.psData *Converts an object of class psData to a data.frame*

Description

Converts an object of class psData—see [readData](#)—to a data.frame that can be used with in functions in other packages such as [vglm](#) to fit more complicated models.

Usage

```
## S3 method for class 'psData'
as.data.frame(x, ...)
```

Arguments

x an object of class psData—see [readData](#) for more details.
 ... any other arguments passed to data.frame.

Details

If x is a psData object of type "P", i.e. it relates to numbers of groups of glass, then a data.frame with a single variable count will be return where count = rep(x\$data[n + 1, x\$data\$rn]). The counts have one added to them because the Zeta distribution requires that the counts are greater than or equal to one. If x is a psData object of type "P", i.e. it relates to group sizes, then a data.frame with a single variable count will be return where count = rep(x\$data[n, x\$data\$rn]).

Value

a data.frame with a single variable count. The number of rows in the data.frame is equal to sum(x\$data\$rn).

Examples

```
p = readData(system.file("extdata", "p.xlsx", package = "fitPS"))
p.df = as.data.frame(p)
table(p.df$count)
p$data
```

bootCI

*Bootstrap confidence intervals or regions***Description**

Use bootstrapping to generate confidence intervals, or confidence regions in the case of the zero-inflated model.

Usage

```
bootCI(x, ...)

## Default S3 method:
bootCI(
  x,
  level = 0.95,
  B = 2000,
  model = c("zeta", "zi.zeta"),
  returnBootValues = FALSE,
  silent = FALSE,
  plot = FALSE,
  parallel = TRUE,
  progressBar = FALSE,
  pbopts = list(type = "txt"),
  ...
)

## S3 method for class 'psData'
bootCI(x, ...)

## S3 method for class 'psFit'
bootCI(x, model = ifelse(!x$zeroInflated, "zeta", "zi.zeta"), ...)
```

Arguments

x	a object of class psFit—see readData for more details.
...	other arguments.
level	the confidence level required—restricted to [0.75, 1). This may be a vector, in which case multiple intervals, or confidence regions will be returned.
B	the number of bootstrap samples to take.
model	which model to fit to the data, either "zeta" or "zi.zeta". Maybe abbreviated to "z" and "zi". Default is "zeta".
returnBootValues	if TRUE then the vector (or data.frame) of bootstrapped values is returned. This can be useful for debugging or understanding the results. Default is FALSE.

<code>silent</code>	if TRUE, then no output will be displayed whilst the bootstrapping is being undertaken. <code>plot</code> if TRUE then the contours for the confidence region will be plotted. This only works if <code>model = "zi.zeta"</code> . It is ignored otherwise. <code>parallel</code> if TRUE then the bootstrapping is performed in parallel.
<code>plot</code>	if TRUE and <code>model == "zi.zeta"</code> , then a plot of the bootstrapped values will be produced and confidence contour lines will be drawn for each value in <code>level</code> .
<code>parallel</code>	if TRUE, then the package will attempt to use multiple cores to speed up computation.
<code>progressBar</code>	if TRUE, then progress bars will be displayed to show progress on the bootstrapping.
<code>pbopts</code>	a list of arguments for the <code>pboptions</code> function that affect the progress bars. Ignored if <code>progressBar = FALSE</code> .

Details

This function uses bootstrapping to compute a confidence interval for the shape parameter in the case of the zeta model and a confidence region in the case of the zero-inflated zeta model. A smoothed bootstrap approach is taken rather than a simple percentile method. The kernel density estimation is performed by the `ks` package using a smoothed cross-validated bandwidth selection procedure.

Value

If `returnBootVals == TRUE` then the results are returned in a list with elements named `ci` and `bootVals` for the zeta model and `confRegion` and `bootVals` for the zero-inflated zeta model. The structure of `ci` and `confRegion` is described below. If `model == "zeta"`, then either a vector or a `data.frame` with elements/columns named "lower" and "upper" representing the lower and upper bounds of the confidence interval(s). Multiple bounds are returned in a `data.frame` when `level` has more than one value. If `model == "zi.zeta"`, then a list with length equal to the length of `level` is returned. The name of each element in the list is the level with list has a single element named "95%". It is possible for there to be multiple contours for the confidence region for a given level. If there is only one contour for each value of `level`, then each element of the list consists of a list with elements named `pi` and `shape` which specify the coordinates of the contour(s) for that level. There is a third element named `level` which gives the height of the kernel density estimate at that contour. If there are multiple contours for a given value of `level` then each list element is a list of lists with the structure given above (`level`, `pi`, and `shape`). NOTE: it is quite possible that there are multiple contours for a given height. If you want a way of thinking about this consider a mountain range with two mountains of equal height. If you draw the contours for (almost) any elevation, then you would expect to capture a region from each mountain.

Methods (by class)

- `bootCI(default)`: Bootstrap confidence intervals or regions
- `bootCI(psData)`: Bootstrap confidence intervals or regions
- `bootCI(psFit)`: Bootstrap confidence intervals or regions

Examples

```
## Not run:
data(Psurveys)
roux = Psurveys$roux
confRegion = bootCI(roux, model = "zi.zeta", parallel = FALSE, plot = TRUE)

## This will not work unless you have the sp package installed
## Count how many of the points lie within the 95% confidence region
lapply(confRegion, function(cr){
  table(sp::point.in.polygon(fit$pi,fit$shape, cr$pi, cr$shape))
. })

## End(Not run)
```

confint.psFit

S3 confint method for objects of class psFit

Description

S3 confint method for objects of class psFit

Usage

```
## S3 method for class 'psFit'
confint(object, parm, level = 0.95, ...)
```

Arguments

object	an object of class psFit—see fitDist for more details
parm	added for compatibility. Should be left empty as it is ignored.
level	the confidence level required—restricted to [0.75, 1)
...	in theory other parameters to be passed to confint, but in reality passed as extra parameters to the internal function plZIZ.

Details

NOTE: the method for ZIZ model is a little computationally intensive and possibly (almost certainly) unstable.

Value

if the Zeta model is used (i.e object comes from a call to `fitDist`), then a list with two items: `wald` and `prof` containing the Wald and profile likelihood confidence intervals respectively for the shape parameter of the fitted Zeta distribution is returned. In general these should be relatively close to each other. ****NOTE**** These values are for the **VGAM** parameterisation of the Zeta distribution which uses $s' = s - 1$. This means they can be used without alteration in `dzeta`. If a Zero-Inflated Zeta model is used (i.e. object comes from a call to `fitZIDist`) then list of a confidence regions is returned with an element for each value of `level`. The confidence regions are `data.frames` with variables `pi` and `shape` which can be used with `lines` or `polygon` to draw a the confidence region.

Examples

```

data(Psurveys)
roux = Psurveys$roux
fit = fitDist(roux)
confint(fit)

## Not run:
fit.zi = fitZIDist(roux)
cr = confint(fit.zi, level = c(0.80, 0.95))
plot(cr[["0.95"]], type = "l")
polygon(cr[["0.8"]])

## End(Not run)

```

fitDist

*Fit a Zeta Distribution to Forensic Data***Description**

This function uses maximum likelihood estimation (MLE) to estimate the shape parameter of a Zeta distribution from a set of observed counts for either the number of groups/sources of forensically interesting material (mostly glass or paint) recovered from clothing, or the number of fragments/particles in each group. This, in turn, allows the estimation of the P and S probabilities, as described by Evett and Buckleton (1990), which used in computing the likelihood ratio (LR) for activity level propositions. The data itself arises from clothing surveys. The general method is described in Coulson et al. (2001), although poor typesetting, and a lack of definition of terms makes it hard to see. This package improves on the estimation in that linear interpolation is not required, and standard numerical optimisation is used instead. The Zeta distribution has probability mass function

$$p(k) = \frac{k^{-s}}{\zeta(s)}$$

where $\zeta(s)$ is the Reimann Zeta function. Coulson et al. (2001) did not have an easy way to rapidly compute this quantity, hence their use of linear interpolation.

Usage

```
fitDist(x, nterms = 10, start = 1, ...)
```

```
fitdist(x, nterms = 10, start = 1, ...)
```

Arguments

x	an object of type psData, usually obtained from readData .
nterms	the number of terms to compute the probability distribution for.
start	a starting value for the optimiser.
...	other parameters - not currently used.

Details

The function returns an object of class `psFit` which is a list contains four elements:

- `psData` – an object of class `psData`—see [readData](#),
- `fit` – the fitted object from [optim](#),
- `shape` – the maximum likelihood estimate of the shape parameter,
- `var.shape` - the maximum likelihood estimate of the shape parameter,
- `fitted` - a named vector containing the first `n` terms of the fitted distribution.
- `zeroInflated` - set to `FALSE` for this model

. The output can be used in a variety of ways. If the interest is just in the shape parameter estimate, then the `shape` member of the `psFit` object contains this information. It is also displayed along with a number of fitted probabilities by the [print.psFit](#) method. The fitted object can also be plotted using the plot method [plot.psFit](#), and to create a probability function with [probfun](#). ****NOTE**** The value of the shape parameter that is printed (if you print the fitted object) is different from that value that is stored in `shape`. The stored value is for the **VGAM** parameterisation of the Zeta distribution which uses $s' = s - 1$. Therefore the printed value is $s = s' + 1$. If you intend to use the fitted value with [dzeta](#), then you should use the stored value s' .

If `start` is not specified, then it is chosen randomly from (0.5, 1). The reason the lower value is not zero is that small starting values seem to cause instability in the likelihood. If you specify your own starting value, it would be sensible to keep it above 0.5.

Value

an object of class `psFit`—see Details.

Functions

- `fitdist()`: Fit a Zeta Distribution to Forensic Data export

References

Coulson, S. A., Buckleton, J. S., Gummer, A. B., and Triggs, C.M., "Glass on clothing and shoes of members of the general population and people suspected of breaking crimes", *Science & Justice* 2001: 41(1): 39–48.

Evet, I. W. and Buckleton, J. S., "The interpretation of glass evidence. A practical approach", *Journal of the Forensic Science Society* 1990: 30(4): 215–223.

See Also

[plot.psFit](#), [print.psFit](#), [probfun](#).

Examples

```
p = readData(system.file("extdata", "p.xlsx", package = "fitPS"))
fit = fitDist(p)
fit
```

fitted.psData	<i>S3 fitted method for an object of class psFit</i>
---------------	--

Description

S3 fitted method for an object of class psFit

Usage

```
## S3 method for class 'psData'
fitted(object, ...)
```

Arguments

object	an object of class psFit, usually from <code>fitDist</code> or <code>fitZIDist</code> .
...	other arguments passed to <code>fittedf</code> —not used.

Value

a named vector of fitted probabilities

fitZIDist	<i>Fit a Zero-Inflated Zeta Distribution to Forensic Data</i>
-----------	---

Description

This function uses maximum likelihood estimation (MLE) to estimate mixing parameter and the shape parameter of a Zero-Inflated Zeta distribution from a set of observed counts for either the number of groups/sources of forensically interesting material (mostly glass or paint) recovered from clothing, or the number of fragments/particles in each group. This, in turn, allows the estimation of the P and S probabilities, as described by Evett and Buckleton (1990), which used in computing the likelihood ratio (LR) for activity level propositions. The data itself arises from clothing surveys. The Zero-Inflated Zeta distribution has probability mass function

$$p(k) = \begin{cases} \pi + \frac{(1-\pi)}{\zeta(s)} & , k = 0, \\ \frac{(1-\pi)k^{-s}}{\zeta(s)} & , k = 1, 2, \dots \end{cases}$$

where $\zeta(s)$ is the Reimann Zeta function.

Usage

```
fitZIDist(x, nterms = 10, start = c(0.5, 1), ...)
```

```
fitZIdist(x, nterms = 10, start = c(0.5, 1), ...)
```

```
fitzidist(x, nterms = 10, start = c(0.5, 1), ...)
```

Arguments

x	an object of type psData, usually obtained from readData .
nterms	the number of terms to compute the probability distribution for.
start	a starting value for the optimiser.
...	other parameters - not currently used.

Details

The function returns an object of class psFit which is a list contains seven elements:

- psData – an object of class psData—see [readData](#),
- fit – the fitted object from [optim](#),
- pi - the maximum likelihood estimate of the mixing parameter,
- shape – the maximum likelihood estimate of the shape parameter,
- var.cov – the estimated variance-covariance matrix for the parameters,
- fitted – a named vector containing the first nterms of the fitted distribution.
- zeroInflated – set to TRUE for this model.

The output can be used in a variety of ways. If the interest is just in the mixing and shape parameter estimates, then the pi and shape member of the psFit object contains this information. It is also displayed along with a number of fitted probabilities by the [print.psFit](#) method. The fitted object can also be plotted using the plot method [plot.psFit](#), and to create a probability function with [probfun](#). ****NOTE**** The value of the shape parameter that is printed (if you print the fitted object) is different from that value that is stored in shape. The stored value is for the **VGAM** parameterisation of the Zeta distribution which uses $s' = s - 1$. Therefore the printed value is $s = s' + 1$. If you intend to use the fitted value with [dzeta](#), then you should use the stored value s' .

If start is not specified, then it is set to (0.5, 1). The reason the starting values are not zero is that small starting values seem to cause instability in the likelihood. If you specify your own starting value, it would be sensible to keep both above 0.5.

Value

an object of class psFit—see Details.

References

Evelt, I. W. and Buckleton, J. S., "The interpretation of glass evidence. A practical approach", Journal of the Forensic Science Society 1990: 30(4): 215–223.

See Also

[plot.psFit](#), [print.psFit](#), [probfun](#).

Examples

```
data(Psurveys)
roux = Psurveys$roux
fit = fitZIDist(roux)
fit
```

makePSData

Create a survey data set manually

Description

Create a survey data set from the command line rather than reading data in from a file. This function is likely to be only useful where there are a very small number of group sizes, or sizes of groups of glass.

Usage

```
makePSData(n, count = NULL, type = c("P", "S"), notes = NULL)
```

```
makeData(n, count = NULL, type = c("P", "S"), notes = NULL)
```

```
createPSData(n, count = NULL, type = c("P", "S"), notes = NULL)
```

Arguments

n	Either the number of groups of glass or the size of different groups of glass, or a vector of observed groups of glass, or group sizes. See details for a longer explanation.
count	Either the number of people in the survey sample who had n groups of glass on their clothing, or the number of people who had a group of glass of size n .
type	either "P" or "S"
notes	a bibentry or a character string which allows extra information about the data to be stored, such as the source, or reference. NULL by default.

Details

If count is NULL, then it is assumed that n consists of actual observed group sizes or numbers of groups of glass found on a survey of N individuals. That is, one could provide $n = \text{rep}(0:1, 98, 1)$ or $n = 0:1$, $\text{count} = \text{c}(98, 1)$. The former is more useful when performing simulation studies.

Value

an object of type psData—see [readData](#) for more details.

See Also

[readData](#)

Examples

```
## recreate the data read in the readData example
p1 = makePSData(n = c(0, 1, 2), count = c(98, 1, 1), type = "P")
s1 = makePSData(n = 1:3, count = c(1, 1, 1), type = "S")
p1
s1
```

mean.psData

An S3 method for computing the mean of clothing survey for the number of groups or size of groups

Description

An S3 method for computing the mean of clothing survey for the number of groups or size of groups

Usage

```
## S3 method for class 'psData'
mean(x, ...)
```

Arguments

x an object of class psData—[readData](#) for more details.
 ... other arguments which are passed to [sum](#)

Value

the mean of the data. If there are r_i observations of the value n_i then the mean is given by

$$\sum_i \frac{r_i \times n_i}{\sum_i r_i}$$

Examples

```
data(Psurveys)
mean(Psurveys$rroux)
```

plot.psFit

*S3 plot method for an object of class psFit***Description**

S3 plot method for an object of class psFit

Usage

```
## S3 method for class 'psFit'
plot(
  x,
  ylim = c(0, 1),
  conf = FALSE,
  conf.level = 0.95,
  ci.type = c("wald", "prof"),
  log.scale = FALSE,
  ...
)
```

Arguments

<code>x</code>	an object of class psFit, usually from <code>fitDist</code> or <code>fitZIDist</code> .
<code>ylim</code>	the limits of the y-axis.
<code>conf</code>	if TRUE, and the model is the the Zeta model (as opposed to the Zero-Inflated Zeta (ZIZ), then confidence intervals (based on the standard error of the shape parameter) are drawn on the plot. If the ZIZ model has been used, then this is ignored.
<code>conf.level</code>	the confidence level for the confidence intervals. Must be between 0.75 and 0.99.
<code>ci.type</code>	Specifies the type of confidence interval. If <code>conf == TRUE</code> , then then <code>ci.type</code> can be either "wald" "prof" (or an abbreviation), depending on whether the Wald interval or the profile likelihood interval should be used. Note that these are intervals on the shape parameter and not the density heights. Therefore the intervals around the probabilities should not really be thought of as confidence intervals but rather something more similar to a "sensitivity" interval.
<code>log.scale</code>	if TRUE the <i>y</i> -axis is changed to a logarithmic (base 10) axis.
<code>...</code>	other arguments passed to plot.

Value

No return value, called for side effects

Examples

```
p = readData(system.file("extdata", "p.xlsx", package = "fitPS"))
fit = fitDist(p)
plot(fit)

## An example with Wald generated intervals
plot(fit, conf = TRUE)

plot(fit, conf = TRUE, ci.type = "p")
```

predict.psFit *S3 predict method for an object of class psFit*

Description

S3 predict method for an object of class psFit

Usage

```
## S3 method for class 'psFit'
predict(
  object,
  newdata,
  interval = c("none", "prof", "wald"),
  level = 0.95,
  ...
)
```

Arguments

object	an object of class psFit, usually from <code>fitDist</code> or <code>fitZIDist</code> .
newdata	an optional vector of integers at which to calculate $\Pr(X = x)$.
interval	either "none", "prof", or "wald" and can be abbreviated. If "prof" or "wald" AND the Zeta model has been used then an interval, based on the bounds of a $100 * \text{level}$ confidence interval for the shape parameter, is given for each predicted probability. The interval is provided based on either a Profile Likelihood, or a Wald, confidence interval for the shape, and therefore cannot really be regarded as a confidence interval for the probabilities. The intervals might be more sensibly regarded as a measure of how sensitive the probabilities are to the choice of shape parameter. NOTE: this parameter is ignored if the Zero-inflated (ZIZ) model has been used.
level	the level of a confidence interval. Ignored if <code>interval == "none"</code> .
...	other arguments passed to <code>predict</code> —not used

Value

either a named vector of fitted probabilities, or a data.frame with columns predicted, lower, and upper and the row names set to show what terms are being calculated

Examples

```
data(Psurveys)
roux = Psurveys$roux
fit = fitDist(roux)
predict(fit, interval = "prof")
```

print.psData	<i>S3 print method for an object of class psData</i>
--------------	--

Description

S3 print method for an object of class psData

Usage

```
## S3 method for class 'psData'
print(x, ...)
```

Arguments

x	an object of class psData, usually from readData or makePSData
...	other arguments passed to print

Value

No return value, called for side effects

print.psFit	<i>S3 print method for an object of class psFit</i>
-------------	---

Description

S3 print method for an object of class psFit

Usage

```
## S3 method for class 'psFit'
print(x, ...)
```

Arguments

x	an object of class psFit, usually from fitDist or #' fitZIDist .
...	other arguments passed to print.

Value

No return value, called for side effects.

 probfun

Probability Functions

Description

Creates a probability function that allows the computation of any P or S term.

Usage

```
probfun(psFitobj)
```

Arguments

psFitobj an object of class psFit—see [fitDist](#) and [fitZIDist](#).

Value

a function that can be used to calculate any P or S term.

Examples

```
p = readData(system.file("extdata", "p.xlsx", package = "fitPS"))
fit = fitDist(p)
P = probfun(fit)
P(0:5)
```

 Psurveys

Number of Groups of Glass Data

Description

Count data from five different surveys looking at the number of sources/groups of glass found on the upper surfaces of clothing taken from the general public.

Usage

```
data(Psurveys)
```

Format

A list with six objects of class psData—see [readData](#) for more details. The elements of the list are named: coulson, jackson, lau, pettard, ross, and roux, corresponding to the lead author in each of the references given below. lau, pettard, and ross were taken from Coulson et al. (2001) rather than the original source.

Source

Coulson, S. A., Buckleton, J. S., Gummer, A. B., and Triggs, C. M. (2001) [doi:10.1016/S1355-0306\(01\)718473](https://doi.org/10.1016/S1355-0306(01)718473) Glass on clothing and shoes of members of the general population and people suspected of breaking crimes, *Science & Justice*, 41(1):39–48.

References

Lau L, Beveridge AD, Callowhill BC, Conners N, Foster K, Groves RJ, Ohashi KN, Sumner AM, Wong H (1997). “The Frequency of Occurrence of Paint and Glass on the Clothing of High School Students.” *Canadian Society of Forensic Science Journal*, **30**(4), 233-240. [doi:10.1080/00085030.1997.10757103](https://doi.org/10.1080/00085030.1997.10757103).

Petterd CI, McCallum I, Bradford L, Brinch K, Stewart S (1998). “Glass particles in the clothing of the general population in Canberra—a survey.” In *Proceedings of the 14th International Symposium on the Forensic Sciences*.

Ross P, Nguyen H (1998). “A survey of clothing for the presence of glass fragments.” In *Proceedings of the 14th International Symposium on the Forensic Sciences*.

Roux C, Kirk R, Benson S, Van Haren T, Petterd CI (2001). “Glass particles in footwear of members of the public in south-eastern Australia—a survey.” *Forensic Science International*, **116**(2), 149–156. [doi:10.1016/S03790738\(00\)003558](https://doi.org/10.1016/S03790738(00)003558).

Jackson F, Maynard P, Cavanagh-Steer K, Dusting T, Roux C (2013). “A survey of glass found on the headwear and head hair of a random population vs. people working with glass.” *Forensic Science International*, **226**(1), 125–131. [doi:10.1016/j.forsciint.2012.12.017](https://doi.org/10.1016/j.forsciint.2012.12.017).

readData

Read count data from file

Description

Reads observed counts of either the number of groups or the size of the groups. The file must have only two columns. One of the columns must be labelled P or S and the other count. It does not matter if the column names are in upper case or not. The P column can have labels 0, 1, 2, ... representing the observation of 0, 1, 2, or more groups. The corresponding count column should contain a positive (non-zero) count for each number of groups. Similarly, if the file contains S counts, then the S column can contain labels 1, 2, ... representing the observation of 1, 2, ... fragments in a group. Note that zeros are neither allowed, or useful, in the file as they both simply result in log-likelihood terms of zero, and therefore make no difference.

Usage

```
readData(fileName, notes = NULL, ...)
```

Arguments

fileName	the name of the file to be read. Must be either a modern (xlsx) Excel file or a csv file.
notes	any additional information about the data, such as the source or a reference.
...	any additional parameters which will be passed to either read_excel or read.csv depending on the extension of your input file.

Value

an object of class psData which is a list containing member variables:

- type – either "P" or "S"
- data – a data.frame which contains columns n and rn, representing the number of groups/fragments, and the number of times that was seen, respectively.
- notes — either a [bibentry](#) or a character string which allows extra information about the data to be stored, such as the source, or reference.

Examples

```
p = readData(system.file("extdata", "p.xlsx", package = "fitPS"))
p
s = readData(system.file("extdata", "s.xlsx", package = "fitPS"))
s
```

rZIzeta

Generate zero inflated zeta random variates

Description

Generate zero inflated zeta random variates

Usage

```
rZIzeta(n, pi = 0.5, shape = 1, offset = 0)
```

```
rzizeta(n, pi = 0.5, shape = 1, offset = 0)
```

```
rzizeta(n, pi = 0.5, shape = 1, offset = 0)
```

Arguments

n	the number of observations.
pi	the mixing parameter for the zero-inflated zeta model—must be in (0, 1).
shape	the shape parameter for the zero-inflated zeta. Must be greater than zero.
offset	the zeta distribution returns random variates that are greater than, or equal to one. If the offset is greater than 0, then the distribution is anchored on (has minimum value of) 1 - offset.

Details

Technically this function returns values from the one-inflated zeta distribution. However, if `offset` is greater than zero (and typically we expect it to be 1), then the minimum random variate value is $1 - \text{offset}$. We chose the name "zero-inflated zeta" as more people are familiar with zero-inflated models.

Value

a vector of random variates from a zero-inflated zeta model

Examples

```
data(Psurveys)
roux = Psurveys$roux
fit.zi = fitZIDist(roux)
x = rZIZeta(n = sum(roux$data$rn), pi = fit.zi$pi, shape = fit.zi$shape)
table(x)
```

Ssurveys

Size of Groups of Glass Data

Description

Count data from six different surveys looking at the number of sources/groups of glass found on the upper surfaces of clothing taken from the general public.

Usage

```
data(Psurveys)
```

Format

A list with five objects of class `psData`—see [readData](#) for more details. The elements of the list are named: `jackson`, `lau`, `pettard`, `ross`, and `roux`, corresponding to the lead author in each of the references given below. `lau`, `pettard`, and `ross` were taken from Coulson et al. (2001) rather than the original source.

Source

Coulson, S. A., Buckleton, J. S., Gummer, A. B., and Triggs, C. M. (2001) [doi:10.1016/S1355-0306\(01\)718473](https://doi.org/10.1016/S1355-0306(01)718473) Glass on clothing and shoes of members of the general population and people suspected of breaking crimes, *Science & Justice*, 41(1):39–48.

References

- Lau L, Beveridge AD, Callowhill BC, Conners N, Foster K, Groves RJ, Ohashi KN, Sumner AM, Wong H (1997). “The Frequency of Occurrence of Paint and Glass on the Clothing of High School Students.” *Canadian Society of Forensic Science Journal*, **30**(4), 233-240. doi:10.1080/00085030.1997.10757103.
- Petterd CI, McCallum I, Bradford L, Brinch K, Stewart S (1998). “Glass particles in the clothing of the general population in Canberra—a survey.” In *Proceedings of the 14th International Symposium on the Forensic Sciences*.
- Ross P, Nguyen H (1998). “A survey of clothing for the presence of glass fragments.” In *Proceedings of the 14th International Symposium on the Forensic Sciences*.
- Coulson SA, Buckleton JS, Gummer AB, Triggs CM (2001). “Glass on clothing and shoes of members of the general population and people suspected of breaking crimes.” *Science & Justice*, **41**(1), 39–48. doi:10.1016/S13550306(01)718473.
- Roux C, Kirk R, Benson S, Van Haren T, Petterd CI (2001). “Glass particles in footwear of members of the public in south-eastern Australia—a survey.” *Forensic Science International*, **116**(2), 149–156. doi:10.1016/S03790738(00)003558.
- Jackson F, Maynard P, Cavanagh-Steer K, Dusting T, Roux C (2013). “A survey of glass found on the headwear and head hair of a random population vs. people working with glass.” *Forensic Science International*, **226**(1), 125–131. doi:10.1016/j.forsciint.2012.12.017.

 var

Variance generic

Description

Variance generic

Usage

var(x, ...)

Arguments

- x an object for which we want to compute the sample variance.
- ... Any additional arguments to be passed to var.

var.psData	<i>An S3 method for computing the variance of clothing survey for the number of groups or size of groups</i>
------------	--

Description

An S3 method for computing the variance of clothing survey for the number of groups or size of groups

Usage

```
## S3 method for class 'psData'
var(x, ...)
```

Arguments

x an object of class psData—[readData](#) for more details.
 ... other arguments which are passed to [sum](#)

Value

the mean of the data. If there are r_i observations of the value n_i then the variance is computed by $E[X^2] - E[X]^2$, where $E[X]$ is computed using

$$\sum_i \frac{r_i \times n_i}{\sum_i r_i}$$

, and $E[X^2]$ is computed by

$$\sum_i \frac{r_i \times n_i^2}{\sum_i r_i}$$

. We realise that the computational formula, $E[X^2] - E[X]^2$, is usually not regarded as computationally stable, but the magnitude of the numbers involved is such that, that this is not likely to cause an issue.

Examples

```
data(Psurveys)
var(Psurveys$roux)
```

Index

- * **datasets**
 - Psurveys, [16](#)
 - Ssurveys, [19](#)
- ==.psData, [2](#)

- as.data.frame.psData, [3](#)

- bibentry, [11](#), [18](#)
- bootCI, [4](#)

- confint.psFit, [6](#)
- createPSData (makePSData), [11](#)

- dzeta, [6](#), [8](#), [10](#)

- fitDist, [6](#), [7](#), [9](#), [13–16](#)
- fitdist (fitDist), [7](#)
- fitted.psData, [9](#)
- fitZIDist, [6](#), [9](#), [9](#), [13–16](#)
- fitZIdist (fitZIDist), [9](#)
- fitzidist (fitZIDist), [9](#)

- lines, [6](#)

- makeData (makePSData), [11](#)
- makePSData, [11](#), [15](#)
- mean.psData, [12](#)

- optim, [8](#), [10](#)

- pboptions, [5](#)
- plot.psFit, [8](#), [10](#), [13](#)
- polygon, [6](#)
- predict.psFit, [14](#)
- print.psData, [15](#)
- print.psFit, [8](#), [10](#), [15](#)
- probfun, [8](#), [10](#), [16](#)
- Psurveys, [16](#)

- readData, [2–4](#), [7](#), [8](#), [10–12](#), [15](#), [16](#), [17](#), [19](#), [21](#)
- rZIZeta, [18](#)

- rzizeta (rZIZeta), [18](#)

- Ssurveys, [19](#)
- sum, [12](#), [21](#)

- var, [20](#)
- var.psData, [21](#)
- vglm, [3](#)