

Package ‘flextable’

April 2, 2019

Type Package

Title Functions for Tabular Reporting

Version 0.5.2

Description Create pretty tables for 'HTML', 'Microsoft Word' and 'Microsoft PowerPoint' documents. Functions are provided to let users create tables, modify and format their content. It extends package 'officer' that does not contain any feature for customized tabular reporting and can be used within R markdown documents.

License GPL-3

LazyData TRUE

Imports stats, utils, grDevices, officer (>= 0.2.0), rmarkdown, knitr, htmltools, xml2, data.table, gdtools (>= 0.1.6), rlang, base64enc

RoxygenNote 6.1.1

Suggests testthat, xtable, magrittr

Encoding UTF-8

URL <https://davidgohe1.github.io/flextable>

BugReports <https://github.com/davidgohe1/flextable/issues>

VignetteBuilder knitr

NeedsCompilation no

Author David Gohe1 [aut, cre],
Quentin Fazilleau [ctb],
Maxim Nazarov [ctb] (rmarkdown for docx output),
Titouan Robert [ctb]

Maintainer David Gohe1 <david.gohe1@ardata.fr>

Repository CRAN

Date/Publication 2019-04-02 17:40:09 UTC

R topics documented:

flextable-package	3
add_header_footer	4
align	5
as_chunk	6
as_flextable	7
as_grouped_data	8
as_image	9
as_paragraph	10
autofit	11
bg	11
body_add_flextable	12
bold	13
border	14
border_inner	15
border_inner_h	15
border_inner_v	16
border_outer	17
border_remove	18
colformat_char	18
colformat_int	19
colformat_lgl	20
colformat_num	21
color	22
compose	22
delete_part	23
dim.flextable	24
dim_pretty	24
display	25
empty_blanks	26
fix_border_issues	27
flextable	27
font	28
fontsize	29
footers_flextable_at_bkm	30
format.flextable	30
headers_flextable_at_bkm	31
height	31
hline	32
hline_bottom	33
hline_top	33
htmltools_value	34
hyperlink_text	35
italic	36
knit_print.flextable	36
linerange	37
merge_at	38

merge_h	39
merge_h_range	40
merge_none	40
merge_v	41
minibar	42
padding	43
ph_with_flextable	44
print.flextable	45
proc_freq	45
rotate	46
save_as_html	47
set_caption	48
set_formatter	48
set_header_footer_df	49
set_header_labels	50
style	51
theme_alafoli	52
theme_booktabs	52
theme_box	53
theme_tron	53
theme_tron_legacy	54
theme_vader	55
theme_vanilla	55
theme_zebra	56
valign	56
vline	57
vline_left	58
vline_right	59
void	59
width	60
xtable_to_flextable	61

Index	63
--------------	-----------

flextable-package *flextable: Functions for Tabular Reporting*

Description

The flextable package facilitates access to and manipulation of tabular reporting elements from R.

The documentation of functions can be opened with command `help(package = "flextable")`.

To learn more about flextable, start with the vignettes: `browseVignettes(package = "flextable")`.

`flextable()` function is producing flexible tables where each cell can contain several chunks of text with their own set of formatting properties (bold, font color, etc.). Function `compose` lets customise text of cells.

See Also

<https://davidgohe1.github.io/flextable/>, [flextable](#)

add_header_footer *Add a row of labels in header or footer part*

Description

Add a single row of labels in the flextable's header or footer part. It can be inserted at the top or the bottom of the part.

Usage

```
add_header(x, top = TRUE, ...)

add_header_row(x, top = TRUE, values = character(0),
               colwidths = integer(0))

add_footer_row(x, top = TRUE, values = character(0),
               colwidths = integer(0))

add_footer_lines(x, values = character(0), top = FALSE)

add_header_lines(x, values = character(0), top = TRUE)

add_footer(x, top = TRUE, ...)
```

Arguments

x	a flextable object
top	should the row be inserted at the top or the bottom.
...	a named list (names are data colnames) of strings specifying corresponding labels to add.
values	values to add as a character vector
colwidths	the number of columns to merge in the row for each label

Examples

```
ft <- flextable( head( iris ),
  col_keys = c("Species", "Sepal.Length", "Petal.Length", "Sepal.Width", "Petal.Width") )
ft <- add_header(x = ft, Sepal.Length = "length",
  Sepal.Width = "width", Petal.Length = "length",
  Petal.Width = "width", Species = "Species", top = FALSE )
ft <- add_header(ft, Sepal.Length = "Inches",
  Sepal.Width = "Inches", Petal.Length = "Inches",
  Petal.Width = "Inches", Species = "Species", top = TRUE )
```

```

ft <- merge_h(ft, part = "header")
ft <- add_footer(ft, Species = "This is a footnote" )
ft <- merge_at(ft, j = 1:5, part = "footer")
ft
ft <- flextable( head( iris ) )
ft <- add_header_row(ft, values = "blah blah", colwidths = 5)
ft <- add_header_row(ft, values = c("blah", "blah"), colwidths = c(3,2))
ft
ft <- flextable( head( iris ) )
ft <- add_footer_row(ft, values = "blah blah", colwidths = 5)
ft <- add_footer_row(ft, values = c("blah", "blah"), colwidths = c(3,2))
ft
ft <- flextable( head( iris ) )
ft <- add_footer_lines(ft, values = "blah blah")
ft <- add_footer_lines(ft, values = c("blah 1", "blah 2"))
autofit(ft)
ft <- flextable( head( iris ) )
ft <- add_header_lines(ft, values = "blah blah")
ft <- add_header_lines(ft, values = c("blah 1", "blah 2"))
autofit(ft)

```

align

Set text alignment

Description

change text alignment of selected rows and columns of a flextable.

Usage

```
align(x, i = NULL, j = NULL, align = "left", part = "body")
```

```
align_text_col(x, align = "left", header = TRUE, footer = TRUE)
```

```
align_nottext_col(x, align = "right", header = TRUE, footer = TRUE)
```

Arguments

x	a flextable object
i	rows selection
j	columns selection
align	text alignment - a single character value, expected value is one of 'left', 'right', 'center', 'justify'.
part	partname of the table (one of 'all', 'body', 'header', 'footer')
header	should the header be aligned with the body
footer	should the footer be aligned with the body

See Also

Other sugar functions for table style: [bg](#), [bold](#), [color](#), [empty_blanks](#), [fontsize](#), [font](#), [italic](#), [padding](#), [rotate](#), [valign](#)

Other sugar functions for table style: [bg](#), [bold](#), [color](#), [empty_blanks](#), [fontsize](#), [font](#), [italic](#), [padding](#), [rotate](#), [valign](#)

Examples

```
ft <- flextable(mtcars)
ft <- align(ft, align = "center")
ft <- flextable(mtcars)
ft <- align_text_col(ft, align = "left")
ft <- align_nottext_col(ft, align = "right")
ft
```

as_chunk

chunk of text wrapper

Description

The function lets add text within flextable objects with function [compose](#). It should be used inside a call to [as_paragraph](#).

Usage

```
as_chunk(x, props = NULL, formater = format_fun, ...)
```

Arguments

x	text or any element that can be formatted as text with function provided in argument formater.
props	an fp_text object to be used to format the text. If not specified, it will be the default value corresponding to the cell.
formater	a function that will format x as a character vector.
...	additional arguments for formater function.

See Also

Other chunk elements for paragraph: [as_image](#), [hyperlink_text](#), [linerange](#), [minibar](#)

Examples

```
library(officer)

myft <- flextable( head(iris))

myft <- compose( myft, j = "Sepal.Length",
  value = as_paragraph(
    "Sepal.Length value is ",
    as_chunk(Sepal.Length, props = fp_text(color = "red"))
  ),
  part = "body")
myft <- color(myft, color = "gray40", part = "all")
autofit(myft)
```

as_flextable	<i>method to convert object to flextable</i>
--------------	--

Description

This is a convenient function to let users create flextable bindings from any objects.

Usage

```
as_flextable(x, ...)

## S3 method for class 'grouped_data'
as_flextable(x, col_keys = NULL, ...)
```

Arguments

x	object to be transformed as flextable
...	arguments for custom methods
col_keys	columns names/keys to display. If some column names are not in the dataset, they will be added as blank columns by default.

Examples

```
# as_flextable and as_grouped_data -----
if( require("magrittr")){
  library(data.table)
  CO2 <- CO2
  setDT(CO2)
  CO2$conc <- as.integer(CO2$conc)

  data_co2 <- dcast(CO2, Treatment + conc ~ Type,
    value.var = "uptake", fun.aggregate = mean)
  data_co2 <- as_grouped_data(x = data_co2, groups = c("Treatment"))
```

```

zz <- as_flextable( data_co2 ) %>%
  add_footer_lines("dataset C02 has been used for this flextable") %>%
  add_header_lines("mean of carbon dioxide uptake in grass plants") %>%
  set_header_labels(conc = "Concentration") %>%
  autofit() %>%
  width(width = c(1, 1, 1))
zz
}

```

as_grouped_data	<i>grouped data transformation</i>
-----------------	------------------------------------

Description

Repeated consecutive values of group columns will be used to define the title of the groups and will be added as a row title.

Usage

```
as_grouped_data(x, groups, columns = NULL)
```

Arguments

x	dataset
groups	columns names to be used as row separators.
columns	columns names to keep

See Also

[as_flextable](#)

Examples

```

# as_grouped_data -----
library(data.table)
C02 <- C02
setDT(C02)
C02$conc <- as.integer(C02$conc)

data_co2 <- dcast(C02, Treatment + conc ~ Type,
  value.var = "uptake", fun.aggregate = mean)
data_co2
data_co2 <- as_grouped_data(x = data_co2, groups = c("Treatment"))
data_co2

```

as_image	<i>image chunk wrapper</i>
----------	----------------------------

Description

The function lets add images within flextable objects with function [compose](#). It should be used inside a call to [as_paragraph](#).

Usage

```
as_image(src, width = 0.5, height = 0.2, ...)
```

Arguments

src	image filename
width, height	size of the png file in inches
...	unused argument

Note

PowerPoint cannot mix images and text in a paragraph, images are removed when outputting to PowerPoint format.

See Also

[compose](#), [as_paragraph](#)

Other chunk elements for paragraph: [as_chunk](#), [hyperlink_text](#), [linerange](#), [minibar](#)

Examples

```
img.file <- file.path( R.home("doc"), "html", "logo.jpg" )
library(officer)

myft <- flextable( head(iris))

myft <- compose( myft, i = 1:3, j = 1,
  value = as_paragraph(
    as_image(src = img.file, width = .20, height = .15),
    " blah blah ",
    as_chunk(Sepal.Length, props = fp_text(color = "red"))
  ),
  part = "body")

autofit(myft)
```

as_paragraph	<i>concatenate chunks in a flextable</i>
--------------	--

Description

The function is concatenating text and images within paragraphs of a flextable object, this function is to be used with function [compose](#).

Usage

```
as_paragraph(..., list_values = NULL)
```

Arguments

...	chunk elements that are defining paragraph
list_values	a list of chunk elements that are defining paragraph. If specified argument ... is unused.

See Also

[as_chunk](#), [minibar](#), [as_image](#), [hyperlink_text](#)

Examples

```
library(officer)
myft <- flextable( head(iris, n = 10 ) )

myft <- compose( myft, j = 1,
  value = as_paragraph(
    minibar(value = Sepal.Length, max = max(Sepal.Length)),
    " ",
    as_chunk( Sepal.Length, formater = formatC,
      props = fp_text(color = "orange") ),
    " blah blah"
  ),
  part = "body" )

autofit(myft)
```

autofit	<i>Adjusts cell widths and heights</i>
---------	--

Description

compute and apply optimized widths and heights.

Usage

```
autofit(x, add_w = 0.1, add_h = 0.1)
```

Arguments

x	flextable object
add_w	extra width to add in inches
add_h	extra height to add in inches

Examples

```
ft <- flextable(mtcars)
ft <- autofit(ft)
ft
```

bg	<i>Set background color</i>
----	-----------------------------

Description

change background color of selected rows and columns of a flextable.

Usage

```
bg(x, i = NULL, j = NULL, bg, part = "body")
```

Arguments

x	a flextable object
i	rows selection
j	columns selection
bg	color to use as background color
part	partname of the table (one of 'all', 'body', 'header', 'footer')

See Also

Other sugar functions for table style: [align](#), [bold](#), [color](#), [empty_blanks](#), [fontsize](#), [font](#), [italic](#), [padding](#), [rotate](#), [valign](#)

Examples

```
ft <- flextable(mtcars)
ft <- bg(ft, bg = "#DDDDDD", part = "header")
```

body_add_flextable	<i>add flextable into a Word document</i>
--------------------	---

Description

add a flextable into a Word document.

Usage

```
body_add_flextable(x, value, align = "center", pos = "after",
  split = FALSE)
```

```
body_replace_flextable_at_bkm(x, bookmark, value, align = "center",
  split = FALSE)
```

Arguments

x	an rdocx object
value	flextable object
align	left, center (default) or right.
pos	where to add the flextable relative to the cursor, one of "after", "before", "on" (end of line).
split	set to TRUE if you want to activate Word option 'Allow row to break across pages'.
bookmark	bookmark id

body_replace_flextable_at_bkm

Use this function if you want to replace a paragraph containing a bookmark with a flextable. As a side effect, the bookmark will be lost.

Examples

```
library(officer)
ft <- flextable(head(mtcars))
ft <- theme_zebra(ft)
ft <- autofit(ft)
doc <- read_docx()
doc <- body_add_flextable(doc, value = ft)
print(doc, target = "test.docx")
```

bold	<i>Set bold font</i>
------	----------------------

Description

change font weight of selected rows and columns of a flextable.

Usage

```
bold(x, i = NULL, j = NULL, bold = TRUE, part = "body")
```

Arguments

x	a flextable object
i	rows selection
j	columns selection
bold	boolean value
part	partname of the table (one of 'all', 'body', 'header', 'footer')

See Also

Other sugar functions for table style: [align](#), [bg](#), [color](#), [empty_blanks](#), [fontsize](#), [font](#), [italic](#), [padding](#), [rotate](#), [valign](#)

Examples

```
ft <- flextable(mtcars)
ft <- bold(ft, bold = TRUE, part = "header")
```

border	<i>Set cell borders</i>
--------	-------------------------

Description

change borders of selected rows and columns of a flextable.

Usage

```
border(x, i = NULL, j = NULL, border = NULL, border.top = NULL,  
       border.bottom = NULL, border.left = NULL, border.right = NULL,  
       part = "body")
```

Arguments

x	a flextable object
i	rows selection
j	columns selection
border	border (shortcut for top, bottom, left and right)
border.top	border top
border.bottom	border bottom
border.left	border left
border.right	border right
part	partname of the table (one of 'all', 'body', 'header', 'footer')

Note

this function requires careful settings to avoid overlapping borders.

See Also

Other borders management: [border_inner_h](#), [border_inner_v](#), [border_inner](#), [border_outer](#), [border_remove](#), [hline_bottom](#), [hline_top](#), [hline](#), [vline_left](#), [vline_right](#), [vline](#)

Examples

```
library(officer)  
ft <- flextable(mtcars)  
ft <- border(ft, border.top = fp_border(color = "orange") )
```

border_inner	<i>set vertical & horizontal inner borders</i>
--------------	--

Description

The function is applying a vertical and horizontal borders to inner content of one or all parts of a flextable.

Usage

```
border_inner(x, border = NULL, part = "all")
```

Arguments

x	a flextable object
border	border defined by a call to fp_border
part	partname of the table (one of 'all', 'body', 'header', 'footer')

See Also

Other borders management: [border_inner_h](#), [border_inner_v](#), [border_outer](#), [border_remove](#), [border](#), [hline_bottom](#), [hline_top](#), [hline](#), [vline_left](#), [vline_right](#), [vline](#)

Examples

```
library(officer)
std_border = fp_border(color="orange", width = 1)

dat <- iris[c(1:5, 51:55, 101:105),]
ft <- flextable(dat)
ft <- border_remove(x = ft)

# add inner vertical borders
ft <- border_inner(ft, border = std_border )
ft
```

border_inner_h	<i>set inner borders</i>
----------------	--------------------------

Description

The function is applying a border to inner content of one or all parts of a flextable.

Usage

```
border_inner_h(x, border = NULL, part = "body")
```

Arguments

x	a flextable object
border	border defined by a call to fp_border
part	partname of the table (one of 'all', 'body', 'header', 'footer')

See Also

Other borders management: [border_inner_v](#), [border_inner](#), [border_outer](#), [border_remove](#), [border](#), [hline_bottom](#), [hline_top](#), [hline](#), [vline_left](#), [vline_right](#), [vline](#)

Examples

```
library(officer)
std_border = fp_border(color="orange", width = 1)

dat <- iris[c(1:5, 51:55, 101:105),]
ft <- flextable(dat)
ft <- border_remove(x = ft)

# add inner horizontal borders
ft <- border_inner_h(ft, border = std_border )
ft
```

border_inner_v	<i>set vertical inner borders</i>
----------------	-----------------------------------

Description

The function is applying a vertical border to inner content of one or all parts of a flextable.

Usage

```
border_inner_v(x, border = NULL, part = "all")
```

Arguments

x	a flextable object
border	border defined by a call to fp_border
part	partname of the table (one of 'all', 'body', 'header', 'footer')

See Also

Other borders management: [border_inner_h](#), [border_inner](#), [border_outer](#), [border_remove](#), [border](#), [hline_bottom](#), [hline_top](#), [hline](#), [vline_left](#), [vline_right](#), [vline](#)

Examples

```
library(officer)
std_border = fp_border(color="orange", width = 1)

dat <- iris[c(1:5, 51:55, 101:105),]
ft <- flextable(dat)
ft <- border_remove(x = ft)

# add inner vertical borders
ft <- border_inner_v(ft, border = std_border )
ft
```

border_outer	<i>set outer borders</i>
--------------	--------------------------

Description

The function is applying a border to outer cells of one or all parts of a flextable.

Usage

```
border_outer(x, border = NULL, part = "all")
```

Arguments

x	a flextable object
border	border defined by a call to fp_border
part	partname of the table (one of 'all', 'body', 'header', 'footer')

See Also

Other borders management: [border_inner_h](#), [border_inner_v](#), [border_inner](#), [border_remove](#), [border](#), [hline_bottom](#), [hline_top](#), [hline](#), [vline_left](#), [vline_right](#), [vline](#)

Examples

```
library(officer)
big_border = fp_border(color="red", width = 2)

dat <- iris[c(1:5, 51:55, 101:105),]
ft <- flextable(dat)
ft <- border_remove(x = ft)

# add outer borders
ft <- border_outer(ft, part="all", border = big_border )
ft
```

border_remove	<i>remove borders</i>
---------------	-----------------------

Description

The function is deleting all borders of the flextable object.

Usage

```
border_remove(x)
```

Arguments

x a flextable object

See Also

Other borders management: [border_inner_h](#), [border_inner_v](#), [border_inner](#), [border_outer](#), [border](#), [hline_bottom](#), [hline_top](#), [hline](#), [vline_left](#), [vline_right](#), [vline](#)

Examples

```
dat <- iris[c(1:5, 51:55, 101:105),]
ft <- flextable(dat)
ft <- theme_box(ft)
ft

# remove all borders
ft <- border_remove(x = ft)
ft
```

colformat_char	<i>format character columns</i>
----------------	---------------------------------

Description

Format character columns in a flextable.

Usage

```
colformat_char(x, ...)
```

```
## S3 method for class 'flextable'
colformat_char(x, col_keys, na_str = "",
  prefix = "", suffix = "", ...)
```

Arguments

x a flextable object
 ... additional arguments, unused
 col_keys names of the colkeys
 na_str string to be used for NA values
 prefix, suffix string to be used as prefix or suffix

See Also

Other columns formatters: [colformat_int](#), [colformat_lgl](#), [colformat_num](#)

Examples

```
dat <- iris
ft <- flextable(dat)
ft <- colformat_char(
  x = ft, col_keys = "Species", suffix = "!")
autofit(ft)
```

colformat_int *format integer columns*

Description

Format integer columns in a flextable.

Usage

```
colformat_int(x, ...)

## S3 method for class 'flextable'
colformat_int(x, col_keys, big.mark = ",",
  na_str = "", prefix = "", suffix = "", ...)
```

Arguments

x a flextable object
 ... additional arguments, unused
 col_keys names of the colkeys
 big.mark see [formatC](#)
 na_str string to be used for NA values
 prefix string to be used as prefix or suffix
 suffix string to be used as prefix or suffix

See Also

Other columns formatters: [colformat_char](#), [colformat_lgl](#), [colformat_num](#)

Examples

```
dat <- mtcars

ft <- flextable(dat)
colkeys <- c("vs", "am", "gear", "carb")
ft <- colformat_int(x = ft, col_keys = colkeys, prefix = "# ")
autofit(ft)
```

colformat_lgl	<i>format logical columns</i>
---------------	-------------------------------

Description

Format logical columns in a flextable.

Usage

```
colformat_lgl(x, ...)

## S3 method for class 'flextable'
colformat_lgl(x, col_keys, true = "true",
  false = "false", na_str = "", prefix = "", suffix = "", ...)
```

Arguments

x	a flextable object
...	additional arguments, unused
col_keys	names of the colkeys
false, true	string to be used for logical columns
na_str	string to be used for NA values
prefix	string to be used as prefix or suffix
suffix	string to be used as prefix or suffix

See Also

Other columns formatters: [colformat_char](#), [colformat_int](#), [colformat_num](#)

Examples

```
dat <- data.frame(a = c(TRUE, FALSE), b = c(FALSE, TRUE))

ft <- flextable(dat)
ft <- colformat_lgl(x = ft, col_keys = c("a", "b"))
autofit(ft)
```

colformat_num	<i>format numeric columns</i>
---------------	-------------------------------

Description

Format numeric columns in a flextable.

Usage

```
colformat_num(x, ...)

## S3 method for class 'flextable'
colformat_num(x, col_keys, big.mark = ",",
  digits = 2, na_str = "", prefix = "", suffix = "", ...)
```

Arguments

x	a flextable object
...	additional arguments, unused
col_keys	names of the colkeys
big.mark, digits	see formatC
na_str	string to be used for NA values
prefix	string to be used as prefix or suffix
suffix	string to be used as prefix or suffix

See Also

Other columns formatters: [colformat_char](#), [colformat_int](#), [colformat_lgl](#)

Examples

```
dat <- iris
dat[1:4, 1] <- NA
dat[, 2] <- dat[, 2] * 1000000

ft <- flextable(dat)
colkeys = c("Sepal.Length", "Sepal.Width",
  "Petal.Length", "Petal.Width")
ft <- colformat_num(
  x = ft, col_keys = colkeys,
  big.mark="," , digits = 2, na_str = "N/A")
autofit(ft)
```

color	<i>Set font color</i>
-------	-----------------------

Description

change font color of selected rows and columns of a flextable.

Usage

```
color(x, i = NULL, j = NULL, color, part = "body")
```

Arguments

x	a flextable object
i	rows selection
j	columns selection
color	color to use as font color
part	partname of the table (one of 'all', 'body', 'header', 'footer')

See Also

Other sugar functions for table style: [align](#), [bg](#), [bold](#), [empty_blanks](#), [fontsize](#), [font](#), [italic](#), [padding](#), [rotate](#), [valign](#)

Examples

```
ft <- flextable(mtcars)
ft <- color(ft, color = "orange", part = "header")
```

compose	<i>Define flextable displayed values</i>
---------	--

Description

Modify flextable displayed values. Function is handling complex formatting as well as image insertion.

Usage

```
compose(x, i = NULL, j = NULL, value, part = "body")
```

Arguments

x	a flextable object
i	rows selection
j	column selection
value	a call to function as_paragraph .
part	partname of the table (one of 'all', 'body', 'header', 'footer')

Examples

```
library(officer)
ft <- flextable(head( mtcars, n = 10))
ft <- compose(ft, j = "carb", i = ~ drat > 3.5,
  value = as_paragraph("carb is ", as_chunk( sprintf("%.1f", carb)) )
)
ft <- autofit(ft)
```

delete_part

delete flextable part

Description

indicate to not print a part of the flextable, i.e. an header, footer or the body.

Usage

```
delete_part(x, part = "header")
```

Arguments

x	a flextable object
part	partname of the table to delete (one of 'body', 'header' or 'footer').

Examples

```
ft <- flextable( head( iris ) )
ft <- delete_part(x = ft, part = "header")
ft
```

dim.flextable	<i>Get flextable dimensions</i>
---------------	---------------------------------

Description

returns widths and heights for each table columns and rows. Values are inches.

Usage

```
## S3 method for class 'flextable'  
dim(x)
```

Arguments

x	flextable object
---	------------------

dim_pretty	<i>Calculate pretty dimensions</i>
------------	------------------------------------

Description

return minimum estimated widths and heights for each table columns and rows in inches.

Usage

```
dim_pretty(x, part = "all")
```

Arguments

x	flextable object
part	partname of the table (one of 'all', 'body', 'header' or 'footer')

Examples

```
ft <- flextable(mtcars)  
dim_pretty(ft)
```

display	<i>Define flextable displayed values</i>
---------	--

Description

Modify flextable displayed values by specifying a string expression. Function is handling complex formatting as well as image insertion.

Usage

```
display(x, i = NULL, col_key, pattern, formatters = list(),  
        fprops = list(), part = "body")
```

Arguments

x	a flextable object
i	rows selection
col_key	column to modify, a single character
pattern	string to format
formatters	a list of formula, left side for the name, right side for the content.
fprops	a named list of fp_text
part	partname of the table (one of 'all', 'body', 'header', 'footer')

pattern

It defined the template used to format the produced strings. Names enclosed by double braces will be evaluated as R code, the corresponding R code is defined with the argument `formatters`.

formatters

Each compound is specifying the R code to execute to produce strings that will be substituted in the `pattern` argument. An element must be a formula: the left-hand side is a name (matching a name enclosed by double braces in `pattern`) and the right-hand side is an R expression to be evaluated (that will produce the corresponding strings).

The function is designed to work with columns in the dataset provided to `flextable` (the `col_keys`).

fprops

A named list of [fp_text](#). It defines the formatting properties associated to a compound in `formatters`. If not defined for an element of `formatters`, the default formatting properties will be applied.

Note

You should use [compose](#) instead - the function is easier to use.

Examples

```
library(officer)
# Formatting data values example -----
ft <- flextable(head( mtcars, n = 10))
ft <- display(ft, col_key = "carb",
  i = ~ drat > 3.5, pattern = "# {{carb}}",
  formatters = list(carb ~ sprintf("%.1f", carb)),
  fprops = list(carb = fp_text(color="orange") ) )
ft <- autofit(ft)
```

empty_blanks

make blank columns as transparent

Description

blank columns are set as transparent. This is a shortcut function that will delete top and bottom borders, change background color to transparent and display empty content.

Usage

```
empty_blanks(x)
```

Arguments

x a flextable object

See Also

Other sugar functions for table style: [align](#), [bg](#), [bold](#), [color](#), [fontsize](#), [font](#), [italic](#), [padding](#), [rotate](#), [valign](#)

Examples

```
typology <- data.frame(
  col_keys = c( "Sepal.Length", "Sepal.Width", "Petal.Length",
    "Petal.Width", "Species" ),
  what = c("Sepal", "Sepal", "Petal", "Petal", " " ),
  measure = c("Length", "Width", "Length", "Width", "Species"),
  stringsAsFactors = FALSE )
typology

ft <- flextable(head(iris), col_keys = c("Species",
  "break1", "Sepal.Length", "Sepal.Width",
  "break2", "Petal.Length", "Petal.Width" ) )
ft <- set_header_df(ft, mapping = typology, key = "col_keys" )
ft <- merge_h(ft, part = "header")
ft <- theme_vanilla(ft)
ft <- empty_blanks(ft)
ft <- width(ft, j = c(2, 5), width = .1 )
ft
```

fix_border_issues	<i>fix border issues when cell are merged</i>
-------------------	---

Description

When cells are merged, the rendered borders will be those of the first cell. If a column is made of three merged cells, the bottom border that will be seen will be the bottom border of the first cell in the column. From a user point of view, this is wrong, the bottom should be the one defined for cell 3. This function modify the border values to avoid that effect.

Usage

```
fix_border_issues(x, part = "all")
```

Arguments

x	flextable object
part	partname of the table (one of 'all', 'body', 'header', 'footer')

Examples

```
if( require(magrittr) ){
  library(officer)
  ft <- data.frame(a = 1:5, b = 6:10) %>%
    flextable() %>%
    theme_box() %>%
    merge_at(i = 4:5, j = 1, part = "body") %>%
    hline(i = 5, part = "body",
          border = fp_border(color = "red", width = 5) )
  print(ft)
  fix_border_issues(ft) %>% print()
}
```

flextable	<i>flextable creation</i>
-----------	---------------------------

Description

Create a flextable object with function `flextable`.

`flextable` are designed to make tabular reporting easier for R users. Functions are available to let you format text, paragraphs and cells; table cells can be merge vertically or horizontally, row headers can easilly be defined, rows heights and columns widths can be manually set or automatically computed.

Usage

```
flextable(data, col_keys = names(data), cwidth = 0.75,
  cheight = 0.25)
```

```
regulartable(data, col_keys = names(data), cwidth = 0.75,
  cheight = 0.25)
```

Arguments

`data` dataset

`col_keys` columns names/keys to display. If some column names are not in the dataset, they will be added as blank columns by default.

`cwidth, cheight` initial width and height to use for cell sizes in inches.

Details

A flextable is made of 3 parts: header, body and footer.

Most functions have an argument named `part` that will be used to specify what part of the table should be modified.

Examples

```
ft <- flextable(mtcars)
ft
```

<code>font</code>	<i>Set font</i>
-------------------	-----------------

Description

change font of selected rows and columns of a flextable.

Usage

```
font(x, i = NULL, j = NULL, fontname, part = "body")
```

Arguments

`x` a flextable object

`i` rows selection

`j` columns selection

`fontname` string value, the font name.

`part` partname of the table (one of 'all', 'body', 'header', 'footer')

See Also

Other sugar functions for table style: [align](#), [bg](#), [bold](#), [color](#), [empty_blanks](#), [fontsize](#), [italic](#), [padding](#), [rotate](#), [valign](#)

Examples

```
require("gdtools")
fontname <- "Times"

if( !font_family_exists(fontname) ){
  # if Times is not available, we will use the first available
  font_list <- sys_fonts()
  fontname <- as.character(font_list$family[1])
}

ft <- flextable(head(iris))
ft <- font(ft, fontname = fontname, part = "header")
```

fontsize

Set font size

Description

change font size of selected rows and columns of a flextable.

Usage

```
fontsize(x, i = NULL, j = NULL, size = 11, part = "body")
```

Arguments

x	a flextable object
i	rows selection
j	columns selection
size	integer value (points)
part	partname of the table (one of 'all', 'body', 'header', 'footer')

See Also

Other sugar functions for table style: [align](#), [bg](#), [bold](#), [color](#), [empty_blanks](#), [font](#), [italic](#), [padding](#), [rotate](#), [valign](#)

Examples

```
ft <- flextable(mtcars)
ft <- fontsize(ft, size = 14, part = "header")
```

 footers_flextable_at_bkm

add flextable at a bookmark location in document's footer

Description

replace in the footer of a document a paragraph containing a bookmark by a flextable. A bookmark will be considered as valid if enclosing words within a paragraph; i.e., a bookmark along two or more paragraphs is invalid, a bookmark set on a whole paragraph is also invalid, but bookmarking few words inside a paragraph is valid.

Usage

```
footers_flextable_at_bkm(x, bookmark, value)
```

Arguments

x	an rdocx object
bookmark	bookmark id
value	a flextable object

 format.flextable

Encode flextable in a document format.

Description

Encode flextable in a document format, html, docx, pptx.

This function is exported so that users can create their own custom component.

Usage

```
## S3 method for class 'flextable'
format(x, type, ...)
```

Arguments

x	flextable object
type	one of pptx, docx or html.
...	unused

See Also

Other flextable print function: [htmltools_value](#), [knit_print.flextable](#), [print.flextable](#), [save_as_html](#)

Examples

```
ft <- flextable(head(iris, n = 2))
format(ft, type = "html")
```

headers_flextable_at_bkm

add flextable at a bookmark location in document's header

Description

replace in the header of a document a paragraph containing a bookmark by a flextable. A bookmark will be considered as valid if enclosing words within a paragraph; i.e., a bookmark along two or more paragraphs is invalid, a bookmark set on a whole paragraph is also invalid, but bookmarking few words inside a paragraph is valid.

Usage

```
headers_flextable_at_bkm(x, bookmark, value)
```

Arguments

x	an rdocx object
bookmark	bookmark id
value	a flextable object

height	<i>Set flextable rows height</i>
--------	----------------------------------

Description

control rows height.

Usage

```
height(x, i = NULL, height, part = "body")
```

```
height_all(x, height, part = "all")
```

Arguments

x	flextable object
i	rows selection
height	height in inches
part	partname of the table

Examples

```
ft <- flextable(iris)
ft <- height(ft, height = .3)
```

hline	<i>set horizontal borders</i>
-------	-------------------------------

Description

The function is applying an horizontal border to inner content of one or all parts of a flextable. The lines are the bottom borders of selected cells.

Usage

```
hline(x, i = NULL, j = NULL, border = NULL, part = "body")
```

Arguments

x	a flextable object
i	rows selection
j	columns selection
border	border defined by a call to fp_border
part	partname of the table (one of 'all', 'body', 'header', 'footer')

See Also

Other borders management: [border_inner_h](#), [border_inner_v](#), [border_inner](#), [border_outer](#), [border_remove](#), [border](#), [hline_bottom](#), [hline_top](#), [vline_left](#), [vline_right](#), [vline](#)

Examples

```
library(officer)
std_border = fp_border(color="gray")

ft <- flextable(head(iris))
ft <- border_remove(x = ft)

# add horizontal borders
ft <- hline(ft, part="all", border = std_border )
ft
```

hline_bottom	<i>set bottom horizontal border</i>
--------------	-------------------------------------

Description

The function is applying an horizontal border to the bottom of one or all parts of a flextable. The line is the bottom border of selected parts.

Usage

```
hline_bottom(x, j = NULL, border = NULL, part = "body")
```

Arguments

x	a flextable object
j	columns selection
border	border defined by a call to fp_border
part	partname of the table (one of 'all', 'body', 'header', 'footer')

See Also

Other borders management: [border_inner_h](#), [border_inner_v](#), [border_inner](#), [border_outer](#), [border_remove](#), [border](#), [hline_top](#), [hline](#), [vline_left](#), [vline_right](#), [vline](#)

Examples

```
library(officer)
big_border = fp_border(color="orange", width = 3)

ft <- flextable(head(iris))
ft <- border_remove(x = ft)

# add/replace horizontal border on bottom
ft <- hline_bottom(ft, part="body", border = big_border )
ft
```

hline_top	<i>set top horizontal border</i>
-----------	----------------------------------

Description

The function is applying an horizontal border to the top of one or all parts of a flextable. The line is the top border of selected parts.

Usage

```
hline_top(x, j = NULL, border = NULL, part = "body")
```

Arguments

x	a flextable object
j	columns selection
border	border defined by a call to fp_border
part	partname of the table (one of 'all', 'body', 'header', 'footer')

See Also

Other borders management: [border_inner_h](#), [border_inner_v](#), [border_inner](#), [border_outer](#), [border_remove](#), [border](#), [hline_bottom](#), [hline](#), [vline_left](#), [vline_right](#), [vline](#)

Examples

```
library(officer)
big_border = fp_border(color="orange", width = 3)

ft <- flextable(head(iris))
ft <- border_remove(x = ft)

# add horizontal border on top
ft <- hline_top(ft, part="all", border = big_border )
ft
```

htmltools_value	<i>flextable a tag object from htmltools package</i>
-----------------	--

Description

get a `div` from a flextable object. This can be used in a shiny application.

Usage

```
htmltools_value(x)
```

Arguments

x	a flextable object
---	--------------------

See Also

Other flextable print function: [format.flextable](#), [knit_print.flextable](#), [print.flextable](#), [save_as_html](#)

Examples

```
htmltools_value(flextable(iris[1:5,]))
```

hyperlink_text	<i>chunk of text with hyperlink wrapper</i>
----------------	---

Description

The function lets add hyperlinks within flextable objects with function [compose](#). It should be used inside a call to [as_paragraph](#).

Usage

```
hyperlink_text(x, props = NULL, formater = format_fun, url, ...)
```

Arguments

x	text or any element that can be formatted as text with function provided in argument formater.
props	an fp_text object to be used to format the text. If not specified, it will be the default value corresponding to the cell.
formater	a function that will format x as a character vector.
url	url to be used
...	additional arguments for formater function.

See Also

[display](#)

Other chunk elements for paragraph: [as_chunk](#), [as_image](#), [linorange](#), [minibar](#)

Examples

```
dat <- data.frame(
  col = "Google it",
  href = "https://www.google.fr/search?source=hp&q=flextable+R+package",
  stringsAsFactors = FALSE)

ft <- flextable(dat)
ft <- compose( x = ft, j = "col",
  value = as_paragraph(
    "This is a link: ",
    hyperlink_text(x = col, url = href ) ) )
ft
```

<code>italic</code>	<i>Set italic font</i>
---------------------	------------------------

Description

change font decoration of selected rows and columns of a flextable.

Usage

```
italic(x, i = NULL, j = NULL, italic = TRUE, part = "body")
```

Arguments

<code>x</code>	a flextable object
<code>i</code>	rows selection
<code>j</code>	columns selection
<code>italic</code>	boolean value
<code>part</code>	partname of the table (one of 'all', 'body', 'header', 'footer')

See Also

Other sugar functions for table style: [align](#), [bg](#), [bold](#), [color](#), [empty_blanks](#), [fontsize](#), [font](#), [padding](#), [rotate](#), [valign](#)

Examples

```
ft <- flextable(mtcars)
ft <- italic(ft, italic = TRUE, part = "header")
```

<code>knit_print.flextable</code>	<i>Render flextable in rmarkdown</i>
-----------------------------------	--------------------------------------

Description

Function used to render flextable in knitr/rmarkdown documents. HTML, Word and PowerPoint outputs are supported.

Function `htmltools_value` return an HTML version of the flextable, this function is to be used within Shiny applications with `renderUI()`.

Usage

```
## S3 method for class 'flextable'
knit_print(x, ...)
```

Arguments

x a flextable object
... further arguments, not used.

Word chunk options

Result can be aligned with chunk option `ft.align` that accepts values 'left', 'center' and 'right'.

Word option 'Allow row to break across pages' can be activated with chunk option `ft.split` set to TRUE.

PowerPoint chunk options

Position should be defined with options `ft.left` and `ft.top`. These are the top left coordinates of the placeholder that will contain the table. They default to `{r ft.left=1, ft.left=2}`.

Note

For Word (docx) output, if pandoc version ≥ 2.0 is used, a raw XML block with the table code will be inserted. If pandoc version < 2.0 is used, an error will be raised. Insertion of images is not supported with rmarkdown for Word documents. For PowerPoint (pptx) output, if pandoc version < 2.4 is used, an error will be raised.

Author(s)

Maxim Nazarov

See Also

Other flextable print function: [format.flextable](#), [htmltools_value](#), [print.flextable](#), [save_as_html](#)

linorange

mini linorange chunk wrapper

Description

This function is used to insert lineranges into flextable with function [compose](#). It should be used inside a call to [as_paragraph](#)

Usage

```
linorange(value, min = NULL, max = NULL, rangecol = "#CCCCCC",  
          stickcol = "#FF0000", bg = "transparent", width = 1,  
          height = 0.2, raster_width = 30)
```

Arguments

value	values containing the bar size
min	min bar size. Default min of value
max	max bar size. Default max of value
rangecol	bar color
stickcol	jauge color
bg	background color
width, height	size of the resulting png file in inches
raster_width	number of pixels used as width when interpolating value.

Note

PowerPoint cannot mix images and text in a paragraph, images are removed when outputting to PowerPoint format.

See Also

[compose](#), [as_paragraph](#)

Other chunk elements for paragraph: [as_chunk](#), [as_image](#), [hyperlink_text](#), [minibar](#)

Examples

```
myft <- flextable( head(iris, n = 10 ))

myft <- compose( myft, j = 1,
  value = as_paragraph(
    linerange(value = Sepal.Length)
  ),
  part = "body")

autofit(myft)
```

merge_at

Merge flextable cells into a single one

Description

Merge flextable cells into a single one. All rows and columns must be consecutive.

Usage

```
merge_at(x, i = NULL, j = NULL, part = "body")
```

Arguments

x	flextable object
i, j	columns and rows to merge
part	partname of the table where merge has to be done.

See Also

Other flextable merging function: [merge_h_range](#), [merge_h](#), [merge_none](#), [merge_v](#)

Examples

```
ft_merge <- flextable( head( mtcars ), cwidth = .5 )
ft_merge <- merge_at( ft_merge, i = 1:2, j = 1:2 )
ft_merge
```

merge_h	<i>Merge flextable cells horizontally</i>
---------	---

Description

Merge flextable cells horizontally when consecutive cells have identical values.

Usage

```
merge_h(x, i = NULL, part = "body")
```

Arguments

x	flextable object
i	rows where cells have to be merged.
part	partname of the table where merge has to be done.

See Also

Other flextable merging function: [merge_at](#), [merge_h_range](#), [merge_none](#), [merge_v](#)

Examples

```
dummy_df <- data.frame( col1 = letters,
  col2 = letters, stringsAsFactors = FALSE )
ft_merge <- flextable(dummy_df)
ft_merge <- merge_h(x = ft_merge)
ft_merge
```

merge_h_range	<i>rowwise merge of a range of columns</i>
---------------	--

Description

Merge flextable columns into a single one for each selected rows. All columns must be consecutive.

Usage

```
merge_h_range(x, i = NULL, j1 = NULL, j2 = NULL, part = "body")
```

Arguments

x	flextable object
i	selected rows
j1, j2	selected columns that will define the range of columns to merge.
part	partname of the table where merge has to be done.

See Also

Other flextable merging function: [merge_at](#), [merge_h](#), [merge_none](#), [merge_v](#)

Examples

```
ft <- flextable( head( mtcars ), cwidth = .5 )
ft <- merge_h_range( ft, i = ~ cyl == 6, j1 = "am", j2 = "carb" )
ft
```

merge_none	<i>Delete flextable merging informations</i>
------------	--

Description

Delete all merging informations from a flextable.

Usage

```
merge_none(x, part = "all")
```

Arguments

x	flextable object
part	partname of the table where merge has to be done.

See Also

Other flextable merging function: [merge_at](#), [merge_h_range](#), [merge_h](#), [merge_v](#)

Examples

```
typology <- data.frame(
  col_keys = c( "Sepal.Length", "Sepal.Width", "Petal.Length", "Petal.Width", "Species" ),
  what = c("Sepal", "Sepal", "Petal", "Petal", "Species"),
  measure = c("Length", "Width", "Length", "Width", "Species"),
  stringsAsFactors = FALSE )

ft <- flextable( head( iris ) )
ft <- set_header_df(ft, mapping = typology, key = "col_keys" )
ft <- merge_v(ft, j = c("Species"))

ft <- theme_tron_legacy( merge_none( ft ) )
ft
```

merge_v

Merge flextable cells vertically

Description

Merge flextable cells vertically when consecutive cells have identical values.

Usage

```
merge_v(x, j = NULL, part = "body")
```

Arguments

x	flextable object
j	columns names/keys where cells have to be merged.
part	partname of the table where merge has to be done.

See Also

Other flextable merging function: [merge_at](#), [merge_h_range](#), [merge_h](#), [merge_none](#)

Examples

```
ft_merge <- flextable(mtcars)
ft_merge <- merge_v(ft_merge, j = c("gear", "carb"))
ft_merge
```

 minibar

mini barplots chunk wrapper

Description

This function is used to insert bars into flextable with function [compose](#). It should be used inside a call to [as_paragraph](#)

Usage

```
minibar(value, max = NULL, barcol = "#CCCCCC", bg = "transparent",
        width = 1, height = 0.2)
```

Arguments

value	values containing the bar size
max	max bar size
barcol	bar color
bg	background color
width, height	size of the resulting png file in inches

Note

PowerPoint cannot mix images and text in a paragraph, images are removed when outputting to PowerPoint format.

See Also

[compose](#), [as_paragraph](#)

Other chunk elements for paragraph: [as_chunk](#), [as_image](#), [hyperlink_text](#), [linerange](#)

Examples

```
myft <- flextable( head(iris, n = 10 ))

myft <- compose( myft, j = 1,
  value = as_paragraph(
    minibar(value = Sepal.Length, max = max(Sepal.Length))
  ),
  part = "body")

autofit(myft)
```

padding	<i>Set paragraph paddings</i>
---------	-------------------------------

Description

change paddings of selected rows and columns of a flextable.

Usage

```
padding(x, i = NULL, j = NULL, padding = NULL, padding.top = NULL,  
padding.bottom = NULL, padding.left = NULL, padding.right = NULL,  
part = "body")
```

Arguments

x	a flextable object
i	rows selection
j	columns selection
padding	padding (shortcut for top, bottom, left and right)
padding.top	padding top
padding.bottom	padding bottom
padding.left	padding left
padding.right	padding right
part	partname of the table (one of 'all', 'body', 'header', 'footer')

See Also

Other sugar functions for table style: [align](#), [bg](#), [bold](#), [color](#), [empty_blanks](#), [fontsize](#), [font](#), [italic](#), [rotate](#), [valign](#)

Examples

```
ft <- flextable(mtcars)  
ft <- padding(ft, padding.top = 4)
```

ph_with_flextable *add flextable into a PowerPoint slide*

Description

add a flextable as a new shape in the current slide.

Usage

```
ph_with_flextable(x, value, type = "body", index = 1)
```

```
ph_with_flextable_at(x, value, left, top)
```

Arguments

x	an rpptx device
value	flextable object
type	placeholder type
index	placeholder index (integer). This is to be used when a placeholder type is not unique in the current slide, e.g. two placeholders with type 'body'.
left, top	location of flextable on the slide in inches

Note

The width and height of the table can not be set with this function. Use functions [width](#), [height](#), [autofit](#) and [dim_pretty](#) instead. The overall size is resulting from cells, paragraphs and text properties (i.e. padding, font size, border widths).

Examples

```
library(officer)
ft <- flextable(head(mtcars))

doc <- read_pptx()
doc <- add_slide(doc, layout = "Title and Content",
                master = "Office Theme")
doc <- ph_with_flextable(doc, value = ft, type = "body")
doc <- ph_with_flextable_at(doc, value = ft, left = 4, top = 5)
print(doc, target = "test.pptx" )
```

print.flextable	<i>flextable printing</i>
-----------------	---------------------------

Description

print a flextable object to format html, docx, pptx or as text (not for display but for informative purpose). This function is to be used in an interactive context.

Usage

```
## S3 method for class 'flextable'  
print(x, preview = "html", ...)
```

Arguments

x	flextable object
preview	preview type, one of c("html", "pptx", "docx", "log"). When "log" is used, a description of the flextable is printed.
...	unused argument

Note

When argument preview is set to "docx" or "pptx", an external client linked to these formats (Office is installed) is used to edit a document. The document is saved in the temporary directory of the R session and will be removed when R session will be ended.

When argument preview is set to "html", an external client linked to these HTML format is used to display the table. If RStudio is used, the Viewer is used to display the table.

Note also that a print method is used when flextable are used within R markdown documents. See [knit_print.flextable](#).

See Also

Other flextable print function: [format.flextable](#), [htmltools_value](#), [knit_print.flextable](#), [save_as_html](#)

proc_freq	<i>frequency table as flextable</i>
-----------	-------------------------------------

Description

This function compute a two way contingency table and make a flextable with the result.

Usage

```
proc_freq(x, row, col, main = "")
```

Arguments

x	data.frame object
row	character column names for row
col	character column names for column
main	character title

Author(s)

Titouan Robert

Examples

```
proc_freq(mtcars, "vs", "gear")
proc_freq(mtcars, "gear", "vs")
proc_freq(mtcars, "gear", "vs", "My title")
```

rotate	<i>rotate cell text</i>
--------	-------------------------

Description

apply a rotation to cell text

Usage

```
rotate(x, i = NULL, j = NULL, rotation, align = "center",
       part = "body")
```

Arguments

x	a flextable object
i	rows selection
j	columns selection
rotation	one of "lrb", "tbl", "btlr"
align	vertical alignment of paragraph within cell, one of "center" or "top" or "bottom".
part	partname of the table (one of 'all', 'body', 'header', 'footer')

Details

One common case is to rotate text to minimise column space. When rotating, paragraph alignments will remain the same and often right aligned (with an effect of top aligned when rotated). Use `align(..., align = "center")` to center rotated text.

When function `autofit` is used, the rotation will be ignored.

See Also

Other sugar functions for table style: [align](#), [bg](#), [bold](#), [color](#), [empty_blanks](#), [fontsize](#), [font](#), [italic](#), [padding](#), [valign](#)

Examples

```
ft <- flextable(head(iris))
ft <- rotate(ft, rotation = "tbrl", part = "header", align = "center")
ft <- align(ft, align = "center")
ft <- autofit(ft)
ft <- height(ft, height = max(dim_pretty(ft, part = "header")$widths), part = "header")
```

`save_as_html`*save a flextable in an HTML file*

Description

save a flextable in an HTML file. This function has been implemented to help users that do not understand R Markdown. It is highly recommended to use R Markdown instead.

Usage

```
save_as_html(x, path)
```

Arguments

<code>x</code>	a flextable object
<code>path</code>	HTML file to be created

See Also

Other flextable print function: [format.flextable](#), [htmltools_value](#), [knit_print.flextable](#), [print.flextable](#)

Examples

```
ft <- flextable( head( mtcars ) )
tf <- tempfile(fileext = ".html")
save_as_html(ft, tf)
```

set_caption	<i>set caption</i>
-------------	--------------------

Description

set caption value in flextable

Usage

```
set_caption(x, caption)
```

Arguments

x	flextable object
caption	caption value

Note

this will have an effect only when output is HTML.

Examples

```
ft <- flextable( head( iris ) )
ft <- set_caption(ft, "my caption")
ft
```

set_formatter	<i>set column formatter functions</i>
---------------	---------------------------------------

Description

Define formatter functions associated to each column key. Functions have a single argument (the vector) and are returning the formatted values as a character vector.

Usage

```
set_formatter(x, ..., values = NULL, part = "body")

set_formatter_type(x, fmt_double = "%.03f", fmt_integer = "%.0f",
  fmt_date = "%Y-%m-%d", fmt_datetime = "%Y-%m-%d %H:%M:%S",
  true = "true", false = "false", na_str = "")
```


Arguments

x	a flextable object
...	Name-value pairs of functions, names should be existing col_key values
values	a list of name-value pairs of functions, names should be existing col_key values. If values is supplied argument ... is ignored.
part	partname of the table (one of 'body' or 'header' or 'footer')
fmt_double, fmt_integer	arguments used by sprintf to format double and integer columns.
fmt_date, fmt_datetime	arguments used by format to format date and date time columns.
false, true	string to be used for logical columns
na_str	string for NA values

set_formatter_type

set_formatter_type is an helper function to quickly define formatter functions regarding to column types.

Examples

```
ft <- flextable( head( iris ) )
ft <- set_formatter( x = ft,
  Sepal.Length = function(x) sprintf("%.02f", x),
  Sepal.Width = function(x) sprintf("%.04f", x)
)
ft <- theme_vanilla( ft )
ft
```

set_header_footer_df *Set flextable's header or footer rows*

Description

Use a data.frame to specify flextable's header or footer rows.

The data.frame must contain a column whose values match flextable col_keys argument, this column will be used as join key. The other columns will be displayed as header or footer rows. The leftmost column is used as the top header/footer row and the rightmost column is used as the bottom header/footer row.

Usage

```
set_header_df(x, mapping = NULL, key = "col_keys")
```

```
set_footer_df(x, mapping = NULL, key = "col_keys")
```

Arguments

x	a flextable object
mapping	a data.frame specifying for each colname content of the column.
key	column to use as key when joining data_mapping.

Examples

```
typology <- data.frame(
  col_keys = c( "Sepal.Length", "Sepal.Width", "Petal.Length",
               "Petal.Width", "Species" ),
  what = c("Sepal", "Sepal", "Petal", "Petal", "Species"),
  measure = c("Length", "Width", "Length", "Width", "Species"),
  stringsAsFactors = FALSE )
```

```
ft <- flextable( head( iris ) )
ft <- set_header_df(ft, mapping = typology, key = "col_keys" )
ft <- merge_h(ft, part = "header")
ft <- merge_v(ft, j = "Species", part = "header")
ft <- theme_vanilla(ft)
```

```
typology <- data.frame(
  col_keys = c( "Sepal.Length", "Sepal.Width", "Petal.Length",
               "Petal.Width", "Species" ),
  unit = c("(cm)", "(cm)", "(cm)", "(cm)", "" ),
  stringsAsFactors = FALSE )
ft <- set_footer_df(ft, mapping = typology, key = "col_keys" )
ft <- italic(ft, italic = TRUE, part = "footer" )
ft <- theme_booktabs(ft)
ft
```

set_header_labels *Set flextable's headers labels*

Description

This function set labels for specified columns in a single row header of a flextable.

Usage

```
set_header_labels(x, ..., values = NULL)
```

Arguments

x	a flextable object
...	named arguments (names are data colnames), each element is a single character value specifying label to use.
values	a named list (names are data colnames), each element is a single character value specifying label to use. If provided, argument ... will be ignored.

Examples

```
ft_1 <- flextable( head( iris ))
ft_1 <- set_header_labels(ft_1, Sepal.Length = "Sepal length",
  Sepal.Width = "Sepal width", Petal.Length = "Petal length",
  Petal.Width = "Petal width"
)

ft_2 <- flextable( head( iris ))
ft_2 <- set_header_labels(ft_2,
  values = list(Sepal.Length = "Sepal length",
    Sepal.Width = "Sepal width",
    Petal.Length = "Petal length",
    Petal.Width = "Petal width" ) )

ft_2
```

style

Set flextable style

Description

Modify flextable text, paragraphs and cells formatting properties. It allows to specify a set of formatting properties for a selection instead of using multiple functions (i.e bold, italic, bg) that should all be applied to the same selection of rows and columns.

Usage

```
style(x, i = NULL, j = NULL, pr_t = NULL, pr_p = NULL,
  pr_c = NULL, part = "body")
```

Arguments

x	a flextable object
i	rows selection
j	columns selection
pr_t	object(s) of class fp_text
pr_p	object(s) of class fp_par
pr_c	object(s) of class fp_cell
part	partname of the table (one of 'all', 'body', 'header' or 'footer')

Examples

```
library(officer)
def_cell <- fp_cell(border = fp_border(color="#00FFFF"))

def_par <- fp_par(text.align = "center")

ft <- flextable(mtcars)
```

```
ft <- style( ft, pr_c = def_cell, pr_p = def_par, part = "all")
ft <- style(ft, ~ drat > 3.5, ~ vs + am + gear + carb,
  pr_t = fp_text(color="red", italic = TRUE) )

ft
```

theme_alafoli *Apply box theme*

Description

Apply theme box to a flextable

Usage

```
theme_alafoli(x)
```

Arguments

x a flextable object

See Also

Other flextable theme: [theme_booktabs](#), [theme_box](#), [theme_tron_legacy](#), [theme_tron](#), [theme_vader](#), [theme_vanilla](#), [theme_zebra](#)

Examples

```
ft <- flextable(iris)
ft <- theme_alafoli(ft)
```

theme_booktabs *Apply booktabs theme*

Description

Apply theme tron to a flextable

Usage

```
theme_booktabs(x, fontsize = 11)
```

Arguments

x a flextable object
 fontsize font size in pixel

See Also

Other flextable theme: [theme_alafoli](#), [theme_box](#), [theme_tron_legacy](#), [theme_tron](#), [theme_vader](#), [theme_vanilla](#), [theme_zebra](#)

Examples

```
ft <- flextable(iris)
ft <- theme_booktabs(ft)
```

theme_box	<i>Apply box theme</i>
-----------	------------------------

Description

Apply theme box to a flextable

Usage

```
theme_box(x)
```

Arguments

x a flextable object

See Also

Other flextable theme: [theme_alafoli](#), [theme_booktabs](#), [theme_tron_legacy](#), [theme_tron](#), [theme_vader](#), [theme_vanilla](#), [theme_zebra](#)

Examples

```
ft <- flextable(iris)
ft <- theme_box(ft)
```

theme_tron	<i>Apply tron theme</i>
------------	-------------------------

Description

Apply theme tron to a flextable

Usage

```
theme_tron(x)
```

Arguments

x a flextable object

See Also

Other flextable theme: [theme_alafoli](#), [theme_booktabs](#), [theme_box](#), [theme_tron_legacy](#), [theme_vader](#), [theme_vanilla](#), [theme_zebra](#)

Examples

```
ft <- flextable(iris)
ft <- theme_tron(ft)
```

theme_tron_legacy	<i>Apply tron legacy theme</i>
-------------------	--------------------------------

Description

Apply theme tron legacy to a flextable

Usage

```
theme_tron_legacy(x)
```

Arguments

x a flextable object

See Also

Other flextable theme: [theme_alafoli](#), [theme_booktabs](#), [theme_box](#), [theme_tron](#), [theme_vader](#), [theme_vanilla](#), [theme_zebra](#)

Examples

```
ft <- flextable(iris)
ft <- theme_tron_legacy(ft)
```

theme_vader	<i>Apply Sith Lord Darth Vader</i>
-------------	------------------------------------

Description

Apply Sith Lord Darth Vader theme to a flextable

Usage

```
theme_vader(x, fontsize = 11)
```

Arguments

x	a flextable object
fontsize	font size in pixel

See Also

Other flextable theme: [theme_alafoli](#), [theme_booktabs](#), [theme_box](#), [theme_tron_legacy](#), [theme_tron](#), [theme_vanilla](#), [theme_zebra](#)

Examples

```
ft <- flextable(iris)
ft <- theme_vader(ft)
```

theme_vanilla	<i>Apply vanilla theme</i>
---------------	----------------------------

Description

Apply theme vanilla to a flextable

Usage

```
theme_vanilla(x)
```

Arguments

x	a flextable object
---	--------------------

See Also

Other flextable theme: [theme_alafoli](#), [theme_booktabs](#), [theme_box](#), [theme_tron_legacy](#), [theme_tron](#), [theme_vader](#), [theme_zebra](#)

Examples

```
ft <- flextable(iris)
ft <- theme_vanilla(ft)
```

theme_zebra	<i>Apply zebra theme</i>
-------------	--------------------------

Description

Apply theme zebra to a flextable

Usage

```
theme_zebra(x, odd_header = "#CFCFCF", odd_body = "#EFEFEF",
  even_header = "transparent", even_body = "transparent")
```

Arguments

x a flextable object
 odd_header, odd_body, even_header, even_body
 odd/even colors for table header and body

See Also

Other flextable theme: [theme_alafoli](#), [theme_booktabs](#), [theme_box](#), [theme_tron_legacy](#), [theme_tron](#), [theme_vader](#), [theme_vanilla](#)

Examples

```
ft <- flextable(iris)
ft <- theme_zebra(ft)
```

valign	<i>Set vertical alignment</i>
--------	-------------------------------

Description

change vertical alignment of selected rows and columns of a flextable.

Usage

```
valign(x, i = NULL, j = NULL, valign = "center", part = "body")
```


Arguments

x	a flextable object
i	rows selection
j	columns selection
valign	vertical alignment of paragraph within cell, one of "center" or "top" or "bottom".
part	partname of the table (one of 'all', 'body', 'header', 'footer')

See Also

Other sugar functions for table style: [align](#), [bg](#), [bold](#), [color](#), [empty_blanks](#), [fontsize](#), [font](#), [italic](#), [padding](#), [rotate](#)

Examples

```
ft <- flextable(iris[c(1:3, 51:53, 101:103),])
ft <- theme_box(ft)
ft <- merge_v( ft, j = 5)
ft <- valign(ft, j = 5, valign = "top", part = "all")
ft
```

vline *set vertical borders*

Description

The function is applying vertical borders to inner content of one or all parts of a flextable. The lines are the right borders of selected cells.

Usage

```
vline(x, i = NULL, j = NULL, border = NULL, part = "all")
```

Arguments

x	a flextable object
i	rows selection
j	columns selection
border	border defined by a call to fp_border
part	partname of the table (one of 'all', 'body', 'header', 'footer')

See Also

Other borders management: [border_inner_h](#), [border_inner_v](#), [border_inner](#), [border_outer](#), [border_remove](#), [border](#), [hline_bottom](#), [hline_top](#), [hline](#), [vline_left](#), [vline_right](#)

Examples

```
library(officer)
std_border = fp_border(color="orange")

ft <- flextable(head(iris))
ft <- border_remove(x = ft)

# add vertical borders
ft <- vline(ft, border = std_border )
ft
```

vline_left	<i>set flextable left vertical borders</i>
------------	--

Description

The function is applying vertical borders to the left side of one or all parts of a flextable. The line is the left border of selected cells of the first column.

Usage

```
vline_left(x, i = NULL, border = NULL, part = "all")
```

Arguments

x	a flextable object
i	rows selection
border	border defined by a call to fp_border
part	partname of the table (one of 'all', 'body', 'header', 'footer')

See Also

Other borders management: [border_inner_h](#), [border_inner_v](#), [border_inner](#), [border_outer](#), [border_remove](#), [border](#), [hline_bottom](#), [hline_top](#), [hline](#), [vline_right](#), [vline](#)

Examples

```
library(officer)
std_border = fp_border(color="orange")

ft <- flextable(head(iris))
ft <- border_remove(x = ft)

# add vertical border on the left side of the table
ft <- vline_left(ft, border = std_border )
ft
```

vline_right	<i>set flextable right vertical borders</i>
-------------	---

Description

The function is applying vertical borders to the right side of one or all parts of a flextable. The line is the right border of selected cells of the last column.

Usage

```
vline_right(x, i = NULL, border = NULL, part = "all")
```

Arguments

x	a flextable object
i	rows selection
border	border defined by a call to fp_border
part	partname of the table (one of 'all', 'body', 'header', 'footer')

See Also

Other borders management: [border_inner_h](#), [border_inner_v](#), [border_inner](#), [border_outer](#), [border_remove](#), [border](#), [hline_bottom](#), [hline_top](#), [hline](#), [vline_left](#), [vline](#)

Examples

```
library(officer)
std_border = fp_border(color="orange")

ft <- flextable(head(iris))
ft <- border_remove(x = ft)

# add vertical border on the left side of the table
ft <- vline_right(ft, border = std_border )
ft
```

void	<i>Delete flextable content</i>
------	---------------------------------

Description

Set content display as a blank " ".

Usage

```
void(x, j = NULL, part = "body")
```

Arguments

x	flextable object
j	columns selection
part	partname of the table

Examples

```
ft <- flextable(mtcars)
ft <- void(ft, ~ vs + am + gear + carb )
```

width	<i>Set flextable columns width</i>
-------	------------------------------------

Description

control columns width

Usage

```
width(x, j = NULL, width)
```

Arguments

x	flextable object
j	columns selection
width	width in inches

Details

Heights are not used when flextable is been rendered into HTML.

See Also

[flextable](#)

Examples

```
ft <- flextable(iris)
ft <- width(ft, width = 1)
```

xtable_to_flexible *get a flexible from a xtable object*

Description

Get a flexible object from a xtable object.

Usage

```
xtable_to_flexible(x, text.properties = officer::fp_text(),
  format.args = getOption("xtable.format.args", NULL),
  rowname_col = "rowname",
  hline.after = getOption("xtable.hline.after", c(-1, 0, nrow(x))),
  NA.string = getOption("xtable.NA.string", ""),
  include.rownames = TRUE,
  rotate.colnames = getOption("xtable.rotate.colnames", FALSE))
```

Arguments

x	xtable object
text.properties	default text formatting properties
format.args	List of arguments for the formatC function. See argument format.args of print.xtable. Not yet implemented.
rowname_col	colname used for row names column
hline.after	see ?print.xtable.
NA.string	see ?print.xtable.
include.rownames	see ?print.xtable.
rotate.colnames	see ?print.xtable.

Examples

```
library(officer)
if( require("xtable") ){

  data(tli)
  tli.table <- xtable(tli[1:10, ])
  align(tli.table) <- rep("r", 6)
  align(tli.table) <- "|r|r|clr|r|"
  ft <- xtable_to_flexible(
    tli.table,
    rotate.colnames = TRUE,
    include.rownames = FALSE)
  ft <- height(ft, i = 1, part = "header", height = 1)
```

```

ft

Grade3 <- c("A", "B", "B", "A", "B", "C", "C", "D", "A", "B",
           "C", "C", "C", "D", "B", "B", "D", "C", "C", "D")
Grade6 <- c("A", "A", "A", "B", "B", "B", "B", "B", "C", "C",
           "A", "C", "C", "C", "D", "D", "D", "D", "D", "D")
Cohort <- table(Grade3, Grade6)
ft <- xtable_to_flexitable(xtable(Cohort))
ft <- set_header_labels(ft, rowname = "Grade 3")
ft <- autofit(ft)
ft <- add_header(ft, A = "Grade 6")
ft <- merge_at(ft, i = 1, j = seq_len( ncol(Cohort) ) + 1,
              part = "header" )
ft <- bold(ft, j = 1, bold = TRUE, part = "body")
ft <- height_all(ft, part = "header", height = .4)
ft

temp.ts <- ts(cumsum(1 + round(rnorm(100), 0)),
             start = c(1954, 7), frequency = 12)
xtable_to_flexitable(x = xtable(temp.ts, digits = 0),
                    NA.string = "-")
}

```

Index

`add_footer` (`add_header_footer`), 4
`add_footer_lines` (`add_header_footer`), 4
`add_footer_row` (`add_header_footer`), 4
`add_header` (`add_header_footer`), 4
`add_header_footer`, 4
`add_header_lines` (`add_header_footer`), 4
`add_header_row` (`add_header_footer`), 4
`align`, 5, 12, 13, 22, 26, 29, 36, 43, 47, 57
`align_nottxt_col` (`align`), 5
`align_text_col` (`align`), 5
`as_chunk`, 6, 9, 10, 35, 38, 42
`as_flextable`, 7, 8
`as_grouped_data`, 8
`as_image`, 6, 9, 10, 35, 38, 42
`as_paragraph`, 6, 9, 10, 23, 35, 37, 38, 42
`autofit`, 11, 44

`bg`, 6, 11, 13, 22, 26, 29, 36, 43, 47, 57
`body_add_flextable`, 12
`body_replace_flextable_at_bkm`
 (`body_add_flextable`), 12
`bold`, 6, 12, 13, 22, 26, 29, 36, 43, 47, 57
`border`, 14, 15–18, 32–34, 57–59
`border_inner`, 14, 15, 16–18, 32–34, 57–59
`border_inner_h`, 14, 15, 15, 16–18, 32–34, 57–59
`border_inner_v`, 14–16, 16, 17, 18, 32–34, 57–59
`border_outer`, 14–16, 17, 18, 32–34, 57–59
`border_remove`, 14–17, 18, 32–34, 57–59

`colformat_char`, 18, 20, 21
`colformat_int`, 19, 19, 20, 21
`colformat_lgl`, 19, 20, 20, 21
`colformat_num`, 19, 20, 21
`color`, 6, 12, 13, 22, 26, 29, 36, 43, 47, 57
`compose`, 3, 6, 9, 10, 22, 25, 35, 37, 38, 42

`delete_part`, 23
`dim.flextable`, 24
`dim_pretty`, 24, 44
`display`, 25, 35
`div`, 34

`empty_blanks`, 6, 12, 13, 22, 26, 29, 36, 43, 47, 57

`fix_border_issues`, 27
`flextable`, 4, 27, 60
`flextable-package`, 3
`font`, 6, 12, 13, 22, 26, 28, 29, 36, 43, 47, 57
`fontsize`, 6, 12, 13, 22, 26, 29, 29, 36, 43, 47, 57
`footers` (`set_header_footer_df`), 49
`footers_flextable_at_bkm`, 30
`format.flextable`, 30, 34, 37, 45, 47
`formatC`, 19, 21
`fp_border`, 15–17, 32–34, 57–59
`fp_text`, 6, 25, 35

`headers` (`set_header_footer_df`), 49
`headers_flextable_at_bkm`, 31
`height`, 31, 44
`height_all` (`height`), 31
`hline`, 14–18, 32, 33, 34, 57–59
`hline_bottom`, 14–18, 32, 33, 34, 57–59
`hline_top`, 14–18, 32, 33, 33, 57–59
`htmltools_value`, 30, 34, 37, 45, 47
`hyperlink_text`, 6, 9, 10, 35, 38, 42

`italic`, 6, 12, 13, 22, 26, 29, 36, 43, 47, 57

`knit_print.flextable`, 30, 34, 36, 45, 47

`linerange`, 6, 9, 35, 37, 42

`merge_at`, 38, 39–41
`merge_h`, 39, 39, 40, 41
`merge_h_range`, 39, 40, 41
`merge_none`, 39, 40, 40, 41
`merge_v`, 39–41, 41

minibar, [6](#), [9](#), [10](#), [35](#), [38](#), [42](#)

padding, [6](#), [12](#), [13](#), [22](#), [26](#), [29](#), [36](#), [43](#), [47](#), [57](#)

ph_with_flextable, [44](#)

ph_with_flextable_at
 (ph_with_flextable), [44](#)

print.flextable, [30](#), [34](#), [37](#), [45](#), [47](#)

proc_freq, [45](#)

regulartable (flextable), [27](#)

rotate, [6](#), [12](#), [13](#), [22](#), [26](#), [29](#), [36](#), [43](#), [46](#), [57](#)

save_as_html, [30](#), [34](#), [37](#), [45](#), [47](#)

set_caption, [48](#)

set_footer_df (set_header_footer_df), [49](#)

set_formatter, [48](#)

set_formatter_type (set_formatter), [48](#)

set_header_df (set_header_footer_df), [49](#)

set_header_footer_df, [49](#)

set_header_labels, [50](#)

style, [51](#)

theme_alafoli, [52](#), [53–56](#)

theme_booktabs, [52](#), [52](#), [53–56](#)

theme_box, [52](#), [53](#), [53](#), [54–56](#)

theme_tron, [52](#), [53](#), [53](#), [54–56](#)

theme_tron_legacy, [52–54](#), [54](#), [55](#), [56](#)

theme_vader, [52–55](#), [55](#), [56](#)

theme_vanilla, [52–55](#), [55](#), [56](#)

theme_zebra, [52–55](#), [56](#)

valign, [6](#), [12](#), [13](#), [22](#), [26](#), [29](#), [36](#), [43](#), [47](#), [56](#)

vline, [14–18](#), [32–34](#), [57](#), [58](#), [59](#)

vline_left, [14–18](#), [32–34](#), [57](#), [58](#), [59](#)

vline_right, [14–18](#), [32–34](#), [57](#), [58](#), [59](#)

void, [59](#)

width, [44](#), [60](#)

xtable_to_flextable, [61](#)