

# Package ‘hybridModels’

June 15, 2018

**Version** 0.3.5

**Title** Stochastic Hybrid Models in Dynamic Networks

**Date** 2018-06-15

**License** GPL (>= 2)

**Depends** R (>= 3.3.1),

**Imports** doParallel, foreach, ggplot2, GillespieSSA, parallel,  
reshape2, stats, stringr, grid

**Description** Simulates stochastic hybrid models for transmission of infectious diseases in dynamic networks. It is a metapopulation model in which each node in the network is a sub-population and disease spreads within nodes and among them, combining two approaches: stochastic simulation algorithm or its approximations (Gillespie DT (2007) <doi:10.1146/annurev.physchem.58.032806.104637>) and individual-based approach, respectively. Movement among nodes are data based and can be irregular. Equations that models spread within nodes are customizable and there are two link types among nodes: migration and influence (commuting).

**LazyLoad** true

**LazyData** true

**Author** Fernando S. Marques [aut, cre],  
Jose H. H. Grisi-Filho [aut],  
Marcos Amaku [aut]

**Maintainer** Fernando S. Marques <fernandosix@gmail.com>

**URL** <https://github.com/fernandosm/hybridModels>

**BugReports** <https://github.com/fernandosm/hybridModels/issues>

**RoxygenNote** 6.0.1

**NeedsCompilation** no

**Repository** CRAN

**Date/Publication** 2018-06-15 18:59:34 UTC

## R topics documented:

buildModelClass	2
findContactChain	3
hybridModel	4
hybridModels	7
networkSample	8
nodesCensus	8
plot	9
simHM	10
summary	11

<b>Index</b>	<b>13</b>
--------------	-----------

---

buildModelClass	<i>It builds an object of a pre-specified class.</i>
-----------------	--

---

### Description

buildModelClass is generic function that calls a method to create a object base on model's name.

### Usage

```
buildModelClass(x, var.names, init.cond, model.parms, probWeights, emigrRule,
  prop.func = NULL, state.var = NULL, infl.var = NULL,
  state.change.matrix = NULL)
```

### Arguments

x	is an empty object of a class requested.
var.names	a <a href="#">list</a> with variable names of the network: the donor node, the reciever node, the time when each connection between donor to the reciever happened and the weight of these connection. The variables names must be "from", "to", "Time" and "arc", respectively.
init.cond	a named <a href="#">vector</a> with initial conditions.
model.parms	a named <a href="#">vector</a> with model's parameters.
probWeights	a named <a href="#">vector</a> (optinal and for migration type only) mapping state variables to migration probability weights based on state variables. These argument can be used to give weights for sampling individuals from node. They need not sum to one, they should be non-negative and not zero. For more information on the sampling method <a href="#">sample</a> .
emigrRule	a string (optinal and for migration type only) stating how many individual emigrate based on state variables. It requires that the network have weights instead of number of individuals that migrate.
prop.func	a character <a href="#">vector</a> with propensity functions of a generic node. See references for more details

state.var            a character [vector](#) with the state variables of the propensity functions.  
 infl.var            a named [vector](#) mapping state variables to influence variables.  
 state.change.matrix  
                       is a state-change [matrix](#). See references for more details

**Value**

An object of the class requested.

**References**

.

---

findContactChain	<i>Finding elements in contact chains of a dynamic network.</i>
------------------	---

---

**Description**

Parallel function to find outgoing and ingoing contact chain elements.

**Usage**

```
findContactChain(Data, from, to, Time, selected.nodes, type = "size",
  numberOfcores = NULL)
```

**Arguments**

Data	<a href="#">data.frame</a> with network information: node ID, origin node, destination node, and the time in which the link was established.
from	<a href="#">character</a> , variable name (column name) for origin node.
to	<a href="#">character</a> , variable name (column name) for destination node.
Time	<a href="#">character</a> , variable name (column name) for the time in which the link was established between two nodes.
selected.nodes	<a href="#">vector</a> , the function will find the contact chain of the nodes present in the selected.nodes vector.
type	<a href="#">character</a> , of returned result. Type = 'size' (default), will return the size of 'outgoing' and 'ingoing' contact chains. Type = 'chain' will return also the nodes in each chain (might be slow for hugh data sets).
numberOfcores	<a href="#">integer</a> , number of cores used to calculate the contact chain (default is NULL, that will lead the algorithm to use the max number of cores).

**Details**

This is a function that find elements of a contact chain from a dynamic network.

**Value**

a `data.frame` with ingoing and outgoing contact chains size. or `list` with the data frame and elements of ingoing and outgoing chains.

**References**

- [1] K Buttner, J Krieter, and I Traulsen. Characterization of Contact Structures for the Spread of Infectious Diseases in a Pork Supply Chain in Northern Germany by Dynamic Network Analysis of Yearly and Monthly Networks. In: *Transboundary and emerging diseases 2000* (May 2013), pp. 1-12.
- [2] C Dube, C Ribble, D Kelton, et al. Comparing network analysis measures to determine potential epidemic size of highly contagious exotic diseases in fragmented monthly networks of dairy cattle movements in Ontario, Canada. In: *Transboundary and emerging diseases 55.9-10* (Dec. 2008), pp. 382-392.
- [3] C Dube, C Ribble, D Kelton, et al. A review of network analysis terminology and its application to foot-and-mouth disease modelling and policy development. In: *Transboundary and emerging diseases 56.3* (Apr. 2009), pp. 73-85.
- [4] Jenny Frossling, Anna Ohlson, Camilla Bjorkman, et al. Application of network analysis parameters in risk-based surveillance - Examples based on cattle trade data and bovine infections in Sweden. In: *Preventive veterinary medicine 105.3* (July 2012), pp. 202-208. doi: 10.1016/j.prevetmed.2011.12.011.
- [5] Maria Noremark, Nina Ha kansson, Susanna Sternberg Lewerin, et al. Network analysis of cattle and pig movements in Sweden: measures relevant for disease control and risk based surveillance. In: *Preventive veterinary medicine 99.2-4* (2011), pp. 78-90. doi: 10.1016/j.prevetmed.2010.12.009.

**Examples**

```
# Loading data
data(networkSample) # help("networkSample"), for more info.

# contact chain function
selected.nodes <- c(37501, 36811, 36812)
contact.chain <- findContactChain(Data = networkSample, from = 'originID',
                                to = 'destinationID', Time = 'Day', selected.nodes,
                                type = 'chain', numberOfcores = 2)
```

---

hybridModel

*Hybrid model simulation.*


---

**Description**

hybridModel function runs hybrid models simulations.

**Usage**

```
hybridModel(network = stop("undefined 'network'"), var.names = NULL,
  link.type = "migration", model = "custom", probWeights = NULL,
  emigrRule = NULL, init.cond = stop("undefined 'initial conditions'"),
  fill.time = F, model.parms = stop("undefined 'model parameters'"),
  prop.func = NULL, state.var = NULL, infl.var = NULL,
  state.change.matrix = NULL, ssa.method = NULL, nodesCensus = NULL,
  sim.number = 1, pop.correc = TRUE, num.cores = "max")
```

**Arguments**

network	a <a href="#">data.frame</a> with variables that describe the donor node, the receiver node, the time when each connection between donor to the receiver happened and the number of individual or weight of these connection.
var.names	a <a href="#">list</a> with variable names of the network: the donor node, the receiver node, the time when each connection between donor to the receiver happened and the weight of these connection. The variables names must be "from", "to", "Time" and "arc", respectively.
link.type	a <a href="#">character</a> describing the link type between nodes. There are two types: 'migration' and 'influence'. In the migration link type there are actual migration between nodes. In the influence link type individuals does not migrate, just influences another node.
model	a <a href="#">character</a> describing model's name.
probWeights	a named <a href="#">vector</a> (optimal and for migration type only) mapping state variables to migration probability weights based on state variables. These argument can be used to give weights for sampling individuals from node. They need not sum to one, they should be non-negative and not zero. For more information on the sampling method <a href="#">sample</a> .
emigrRule	a string (optimal and for migration type only) stating how many individual emigrate based on state variables. It requires that the network have weights instead of number of individuals that migrate.
init.cond	a named <a href="#">vector</a> with initial conditions.
fill.time	It indicates whether to return all dates or just the dates when nodes get connected.
model.parms	a named <a href="#">vector</a> with model's parameters.
prop.func	a character <a href="#">vector</a> with propensity functions of a generic node. See references for more details
state.var	a character <a href="#">vector</a> with the state variables of the propensity functions.
infl.var	a named <a href="#">vector</a> mapping state variables to influence variables.
state.change.matrix	is a state-change <a href="#">matrix</a> . See references for more details
ssa.method	a <a href="#">list</a> with SSA parameters. The default method is the direct method. See references for more details
nodesCensus	a <a href="#">data.frame</a> with the first column describing nodes' ID, the second column with the number of individuals and the third describing the day of the census.



```

# default plot layout (plot.types: 'pop.mean', 'subpop', or 'subpop.mean')
plot(sim.results, plot.type = 'subpop.mean')

# changing plot layout with ggplot2 (example)
# uncomment the lines below to test new layout exemple
#library(ggplot2)
#plot(sim.results, plot.type = 'subpop') + ggtitle('New Layout') +
# theme_bw() + theme(axis.title = element_text(size = 14, face = "italic"))

# Influence model
# Parameters and initial conditions for an SIS model
# loading the data set
data(networkSample) # help("networkSample"), for more info
networkSample <- networkSample[which(networkSample$Day < "2012-03-20"),]

var.names <- list(from = 'originID', to = 'destinationID', Time = 'Day',
                  arc = 'num.animals')

prop.func <- c('beta * S * (I + i) / (S + I + s + i)', 'gamma * I')
state.var <- c('S', 'I')
infl.var <- c(S = "s", I = "i") # mapping influence
state.change.matrix <- matrix(c(-1, 1, # S
                                1, -1), # I
                              nrow = 2, ncol = 2, byrow = TRUE)

model.parms <- c(beta = 0.1, gamma = 0.01)

init.cond <- rep(100, length(unique(c(networkSample$originID,
                                     networkSample$destinationID))))
names(init.cond) <- paste('S', unique(c(networkSample$originID,
                                     networkSample$destinationID)), sep = '')
init.cond <- c(init.cond, c(I36811 = 10, I36812 = 10)) # adding infection

# running simulations, check num of cores available (num.cores)
# Uncomment to run
# sim.results <- hybridModel(network = networkSample, var.names = var.names,
#                             #
#                             model.parms = model.parms, state.var = state.var,
#                             #
#                             infl.var = infl.var, prop.func = prop.func,
#                             #
#                             init.cond = init.cond,
#                             #
#                             state.change.matrix = state.change.matrix,
#                             #
#                             sim.number = 2, num.cores = 2)

# default plot layout (plot.types: 'pop.mean', 'subpop', or 'subpop.mean')
# plot(sim.results, plot.type = 'subpop.mean')

```

**Description**

The hybridModels package provides functions to simulate stochastic models in dynamics networks, using two processes in different scales: 1 Global scale to simulate the transmission from one node to another 2 Local scale to simulate the transmission inside the node

**Modelling transmission of diseases**

'Framework to run n simulations in dynamic network and plot results'

---

networkSample	<i>Daily record of animal's movement (from 2012 to 2013).</i>
---------------	---

---

**Description**

One dataset containing the number of animals that were moved from one node to another.

**Usage**

networkSample

**Format**

A data frame with 78 rows and 4 variables:

- Day: The day when the movement occurs
- originID: The ID of the origin premises
- destinationID: The ID of the destination premises
- num.animals: The number of animals traded

**Source**

ADAGRO

---

nodesCensus	<i>Information about animal premises (from 2012 to 2013).</i>
-------------	---

---

**Description**

A dataset containing animal premises' identification and census.

**Usage**

nodesCensus



**Format**

A data frame with 507 rows and 2 variables:

- nodes.ID: The ID of the premises
- pop: premises's population size

---

 plot

*Summary plots for hybrid Models*


---

**Description**

plot.HM is a method to plot hybrid models from this package

**Usage**

```
## S3 method for class 'HM'
plot(x, sim = 1, plot.type = "subpop",
     facet.scales = "free_y", ...)
```

**Arguments**

x	HM object
sim	indicates which simulation to plot.
plot.type	plots the mean number of each state variable for the whole population ('pop.mean'), or the subpopulations of a particular simulation ('subpop', default value), or the mean of each subpopulation ('subpop.mean').
facet.scales	should scales be fixed ("free_y", the default), free ("free"), or free in one dimension ("free_x", "free_y"). See ggplot2 package for more details.
...	arguments to be passed to methods.

**Examples**

```
# Parameters and initial conditions for an SIS model
# loading the data set
data(networkSample) # help("networkSample"), for more info
networkSample <- networkSample[which(networkSample$Day < "2012-03-20"),]

var.names <- list(from = 'originID', to = 'destinationID', Time = 'Day',
                 arc = 'num.animals')

prop.func <- c('beta * S * I / (S + I)', 'gamma * I')
state.var <- c('S', 'I')
state.change.matrix <- matrix(c(-1, 1, # S
                               1, -1), # I
                              nrow = 2, ncol = 2, byrow = TRUE)

model.parms <- c(beta = 0.1, gamma = 0.01)
```

```

init.cond <- rep(100, length(unique(c(networkSample$originID,
                                   networkSample$destinationID))))
names(init.cond) <- paste('S', unique(c(networkSample$originID,
                                       networkSample$destinationID)), sep = '')
init.cond <- c(init.cond, c(I36811 = 10, I36812 = 10)) # adding infection

# running simulations, check num of cores available (num.cores)
sim.results <- hybridModel(network = networkSample, var.names = var.names,
                           model.parms = model.parms, state.var = state.var,
                           prop.func = prop.func, init.cond = init.cond,
                           state.change.matrix = state.change.matrix,
                           sim.number = 2, num.cores = 2)

# default plot layout (plot.types: 'pop.mean', 'subpop', or 'subpop.mean')
plot(sim.results, plot.type = 'subpop.mean')

# changing plot layout with ggplot2 (example)
# uncomment the lines below to test new layout example
#library(ggplot2)
#plot(sim.results, plot.type = 'subpop') + ggtitle('New Layout') +
# theme_bw() + theme(axis.title = element_text(size = 14, face = "italic"))

```

---

simHM

*It runs the chosen hybrid model.*


---

## Description

simHM is generic function that calls a method to run the simulation base on object's class

## Usage

```
simHM(x, network, sim.number, num.cores = "max", fill.time)
```

## Arguments

x	of a specific class of model.
network	a <a href="#">data.frame</a> with variables that describe the donor node, the reciever node, the time when each connection between donor to the reciever happened and the number of individual or weight of these connection.
sim.number	Number of repetitions.The default value is 1
num.cores	number of threads/cores that the simulation will use. the default value is num.cores = 'max', the algorithim will use all threads/cores available.
fill.time	It indicates whether to return all dates or just the dates when nodes get connected.

**Value**

A `data.frame` with the number of individuals through time per node, per state and per simulation.

**References**

.

**See Also**

[GillespieSSA](#).

---

summary

*summary for hybrid models*

---

**Description**

`summary.HM` is a method to print a summary with basic description of nodes' states at a specific time (the time must be present in the network data). The default value is `NULL`, that means it prints nodes' final states.

**Usage**

```
## S3 method for class 'HM'
summary(object, at = NULL, stateVars = NULL, nodes = NULL,
        ...)
```

**Arguments**

<code>object</code>	HM object
<code>at</code>	the date (as character) that will be used to print the summary
<code>stateVars</code>	<a href="#">vector</a> containing the state variable to summarize. The default value is <code>NULL</code> , which will print a summary with all states.
<code>nodes</code>	<a href="#">vector</a> containing the nodes of interest. The default value is <code>NULL</code> , which will print a summary with all nodes.
<code>...</code>	arguments to be passed to methods.

**Examples**

```
# Parameters and initial conditions for an SIS model
# loading the data set
data(networkSample) # help("networkSample"), for more info
networkSample <- networkSample[which(networkSample$Day < "2012-03-20"),]

var.names <- list(from = 'originID', to = 'destinationID', Time = 'Day',
                 arc = 'num.animals')

prop.func <- c('beta * S * I / (S + I)', 'gamma * I')
```

```
state.var <- c('S', 'I')
state.change.matrix <- matrix(c(-1, 1, # S
                               1, -1), # I
                              nrow = 2, ncol = 2, byrow = TRUE)

model.parms <- c(beta = 0.1, gamma = 0.01)

init.cond <- rep(100, length(unique(c(networkSample$originID,
                                     networkSample$destinationID))))
names(init.cond) <- paste('S', unique(c(networkSample$originID,
                                     networkSample$destinationID)), sep = '')
init.cond <- c(init.cond, c(I36811 = 10, I36812 = 10)) # adding infection

# running simulations, check num of cores available (num.cores)
sim.results <- hybridModel(network = networkSample, var.names = var.names,
                           model.parms = model.parms, state.var = state.var,
                           prop.func = prop.func, init.cond = init.cond,
                           state.change.matrix = state.change.matrix,
                           sim.number = 4, num.cores = 2)

summary(sim.results, stateVars = c('S', 'I'), nodes = c(36812, 36813))
```

# Index

## \*Topic **datasets**

networkSample, 8  
nodesCensus, 8

buildModelClass, 2

character, 3, 5

data.frame, 3–6, 10, 11

findContactChain, 3

GillespieSSA, 6, 11

hybridModel, 4

hybridModels, 7

hybridModels-package (hybridModels), 7

integer, 3

list, 2, 4, 5

matrix, 3, 5

networkSample, 8

nodesCensus, 8

plot, 9

sample, 2, 5

simHM, 10

summary, 11

vector, 2, 3, 5, 11