

Package ‘pillar’

December 15, 2018

Title Coloured Formatting for Columns

Version 1.3.1

Description Provides a 'pillar' generic designed for formatting columns of data using the full range of colours provided by modern terminals.

License GPL-3

Encoding UTF-8

LazyData true

URL <https://github.com/r-lib/pillar>

BugReports <https://github.com/r-lib/pillar/issues>

Imports cli (>= 1.0.0), crayon (>= 1.3.4), fansi (>= 0.4.0), methods, rlang (>= 0.3.0.1), utf8 (>= 1.1.3)

Suggests knitr (>= 1.19), lubridate (>= 1.7.4), testthat (>= 2.0.0), withr (>= 2.1.2)

RoxygenNote 6.1.1

Collate 'capital.R' 'compat-purrr.R' 'dim.R' 'extent.R' 'multi.R' 'ornament.R' 'pillar-package.R' 'pillar.R' 'rowid-capital.R' 'rowid-data.R' 'rowid-title.R' 'rowid-type.R' 'scientific.R' 'shaft.R' 'shaft-simple.R' 'sigfig.R' 'spark-bar.R' 'spark-line.R' 'strrep.R' 'styles.R' 'testthat.R' 'tick.R' 'title.R' 'type-sum.R' 'type.R' 'utils.R' 'width.R' 'zzz.R'

NeedsCompilation no

Author Kirill Müller [aut, cre],
Hadley Wickham [aut],
RStudio [cph]

Maintainer Kirill Müller <krlmlr+r@mailbox.org>

Repository CRAN

Date/Publication 2018-12-15 17:00:03 UTC

R topics documented:

pillar-package	2
colonnade	3
dim_desc	4
expect_known_display	5
extra_cols	6
format_type_sum	6
get_extent	7
new_ornament	8
new_pillar_shaft	8
new_pillar_title	9
new_pillar_type	10
pillar	10
pillar_shaft	11
style_num	13

Index	15
--------------	-----------

pillar-package	<i>pillar: Coloured Formatting for Columns</i>
----------------	--

Description

Provides a 'pillar' generic designed for formatting columns of data using the full range of colours provided by modern terminals.

Package options

- `pillar.bold`: Use bold font, e.g. for column headers? This currently defaults to `FALSE`, because many terminal fonts have poor support for bold fonts.
- `pillar.subtle`: Use subtle style, e.g. for row numbers and data types? Default: `TRUE`.
- `pillar.subtle_num`: Use subtle style for insignificant digits? Default: `FALSE`, is also affected by the `pillar.subtle` option.
- `pillar.neg`: Highlight negative numbers? Default: `TRUE`.
- `pillar.sigfig`: The number of significant digits that will be printed and highlighted, default: 3. Set the `pillar.subtle` option to `FALSE` to turn off highlighting of significant digits.
- `pillar.min_title_chars`: The minimum number of characters for the column title, default: 15. Column titles may be truncated up to that width to save horizontal space. Set to `Inf` to turn off truncation of column titles.

Author(s)

Maintainer: Kirill Müller <krlmlr+r@mailbox.org>

Authors:

- Hadley Wickham

Other contributors:

- RStudio [copyright holder]

See Also

Useful links:

- <https://github.com/r-lib/pillar>
- Report bugs at <https://github.com/r-lib/pillar/issues>

colonnade

Format multiple vectors in a tabular display

Description

The vectors are formatted to fit horizontally into a user-supplied number of characters per row.

The `squeeze()` function is called by `format()` and `print()` and usually doesn't need to be called manually. It returns an object suitable for printing and formatting at a fixed width with additional information about omitted columns.

Usage

```
colonnade(x, has_row_id = TRUE, width = NULL, ...)
```

```
squeeze(x, width = NULL, ...)
```

Arguments

<code>x</code>	A list of vectors to format. Can contain matrices or data frames. If named, the names will be used as title for the pillars. Non-syntactic names will be escaped.
<code>has_row_id</code>	Include a column indicating row IDs? Pass "*" to mark the row ID column with a star.
<code>width</code>	Default width of the entire output, optional.
<code>...</code>	Ignored

Details

Pillars may be distributed over multiple tiers if `width > getOption("width")`. In this case each tier is at most `getOption("width")` characters wide. The very first step of formatting is to determine how many tiers are shown at most, and the width of each tier.

To avoid unnecessary computation for showing very wide colonnades, a first pass tries to fit all capitals into the tiers. For each pillar whose capital fits, it is then decided in which tier it is shown, if at all, and how much horizontal space it may use (either its minimum or its maximum width). Remaining space is then distributed proportionally to pillars that do not use their desired width.

For fitting pillars in one or more tiers, first a check is made if all pillars fit with their maximum width (e.g., `option(tibble.width = Inf)` or narrow colonnade). If yes, this is the resulting fit, no more work needs to be done. Otherwise, if the maximum width is too wide, the same test is carried out with the minimum width. If this is still too wide, this is the resulting fit. Otherwise, some tiers from the start will contain pillars with their maximum width, and the remaining tiers contain pillars with their minimum width. We determine the cut point where minimum and maximum assignment agree.

Fitting pillars into tiers is very similar to a word-wrapping algorithm. In a loop, new tiers are opened if the current tier overflows. If a column is too wide to fit a single tier, it will never be displayed, and the colonnade will be truncated there. This case should never occur with reasonable display widths larger than 30 characters. Truncation also happens if all available tiers are filled.

The remaining space is distributed from left to right. Each column gains space proportional to the fraction of missing and remaining space, rounded down. Any space remaining after rounding is distributed from left to right, one space per column.

Examples

```
colonnade(list(a = 1:3, b = letters[1:3]))

long_string <- list(paste(letters, collapse = " "))
colonnade(long_string, width = 20)
colonnade(long_string, has_row_id = FALSE, width = 20)

# The width can also be overridden when calling format() or print():
print(colonnade(long_string), width = 20)

# If width is larger than getOption("width"), multiple tiers are created:
colonnade(rep(long_string, 4), width = Inf)
squeeze(colonnade(long_string), width = 20)
```

dim_desc

Format dimensions

Description

Multi-dimensional objects are formatted as `a x b x ...`, for vectors the length is returned.

Usage

```
dim_desc(x)
```

Arguments

x The object to format the dimensions for

Examples

```
dim_desc(1:10)
dim_desc(Titanic)
```

expect_known_display *Test helpers*

Description

Expectation for packages that implement a data type with pillar support. Allows storing the desired result in a file, and comparing the output with the file contents. Note that this expectation sets options that affect the formatting of the pillar, see examples for usage.

Usage

```
expect_known_display(object, file, ..., width = 80L, crayon = TRUE)
```

Arguments

object object to test
file File path where known value/output will be stored.
... Unused.
width The width of the output.
crayon Color the output?

Examples

```
file <- tempfile("pillar", fileext = ".txt")

# The pillar is constructed after options have been set
# (need two runs because reference file doesn't exist during the first run)
suppressWarnings(tryCatch(
  expect_known_display(pillar(1:3), file, crayon = FALSE),
  expectation_failure = function(e) {}
))
expect_known_display(pillar(1:3), file, crayon = FALSE)

# Good: Use tidyeval to defer construction
pillar_quo <- rlang::quo(pillar(1:3))
```

```
expect_known_display(!pillar_quo, file, crayon = FALSE)

## Not run:
# Bad: Options set in the active session may affect the display
integer_pillar <- pillar(1:3)
expect_known_display(integer_pillar, file, crayon = FALSE)

## End(Not run)
```

extra_cols	<i>Retrieve information about columns that didn't fit the available width</i>
------------	---

Description

Formatting a [colonnade](#) object may lead to some columns being omitted due to width restrictions. This method returns a character vector that describes each of the omitted columns.

Usage

```
extra_cols(x, ...)
```

```
## S3 method for class 'squeezed_colonnade'
extra_cols(x, ..., n = Inf)
```

Arguments

x	The result of squeeze() on a colonnade object
...	Unused
n	The number of extra columns to return; the returned vector will always contain as many elements as there are extra columns, but elements beyond n will be NA.

Examples

```
extra_cols(squeeze(colonnade(list(a = 1:3, b = 4:6), width = 8)))
```

format_type_sum	<i>Format a type summary</i>
-----------------	------------------------------

Description

Called on values returned from [type_sum\(\)](#) for defining the description in the capital. Implement this method for a helper class for custom formatting, and return an object of this helper class from your [type_sum\(\)](#) implementation. See examples.

Usage

```
format_type_sum(x, width, ...)
```

```
## Default S3 method:
```

```
format_type_sum(x, width, ...)
```

Arguments

x	A return value from type_sum()
width	The desired total width. If the returned string still is wider, it will be trimmed. Can be NULL.
...	Unused, for extensibility.

Examples

```
format_type_sum(1, NULL)
pillar(1)

type_sum.accel <- function(x) {
  structure("kg m/s^2", width = 8, class = "type_sum_accel")
}
format_type_sum.type_sum_accel <- function(x, width, ...) {
  if (!is.null(width) && width < attr(x, "width")) {
    x <- substr(x, 1, width)
  }
  style_subtle(x)
}
accel <- structure(9.81, class = "accel")
pillar(accel)
```

```
get_extent
```

```
Calculate display width
```

Description

get_extent() calculates the display width for each string in a character vector.

get_max_extent() calculates the maximum display width of all strings in a character vector, zero for empty vectors.

Usage

```
get_extent(x)
```

```
get_max_extent(x)
```

Arguments

x	A character vector.
---	---------------------

Examples

```
get_extent(c("abc", "de"))
get_extent("\u904b\u6c23")
get_max_extent(c("abc", "de"))
```

new_ornament	<i>Helper to define the contents of a pillar</i>
--------------	--

Description

This function is useful if your data renders differently depending on the available width. In this case, implement the `pillar_shaft()` method for your class to return a subclass of "pillar_shaft" and have the `format()` method for this subclass call `new_ornament()`. See the implementation of `pillar_shaft.numeric()` and `format.pillar_shaft_decimal()` for an example.

Usage

```
new_ornament(x, width = NULL, align = NULL)
```

Arguments

x	A character vector with formatting, see crayon
width	An optional width of the resulting pillar, computed from x if missing
align	Alignment, one of "left" or "right"

Examples

```
new_ornament(c("abc", "de"), align = "right")
```

new_pillar_shaft	<i>Constructor for column data</i>
------------------	------------------------------------

Description

The `new_pillar_shaft()` constructor creates objects of the "pillar_shaft" class. This is a virtual or abstract class, you must specify the `subclass` argument. By convention, this should be a string that starts with "pillar_shaft_". See `vignette("extending", package = "tibble")` for usage examples.

`new_pillar_shaft_simple()` provides an implementation of the `pillar_shaft` class suitable for output that has a fixed formatting, which will be truncated with a continuation character (ellipsis or ~) if it doesn't fit the available width. By default, the required width is computed from the natural width of the formatted argument.

Usage

```
new_pillar_shaft(x, ..., width, min_width = width, subclass)

new_pillar_shaft_simple(formatted, ..., width = NULL, align = "left",
  min_width = NULL, na_indent = 0L)
```

Arguments

x	An object
...	Additional attributes
width	The maximum column width.
min_width	The minimum allowed column width, width if omitted.
subclass	The name of the subclass.
formatted	An object coercible to character .
align	Alignment of the column.
na_indent	Indentation of NA values.

Details

The formatted argument may also contain ANSI escapes to change color or other attributes of the text, see [crayon](#).

new_pillar_title	<i>Prepare a column title for formatting</i>
------------------	--

Description

Call [format\(\)](#) on the result to render column titles.

Usage

```
new_pillar_title(x, ...)
```

Arguments

x	A character vector of column titles.
...	Unused.

Examples

```
format(new_pillar_title(names(iris)))
```

<code>new_pillar_type</code>	<i>Prepare a column type for formatting</i>
------------------------------	---

Description

Call `format()` on the result to render column types.

Usage

```
new_pillar_type(x, ...)
```

Arguments

<code>x</code>	A vector for which the type is to be retrieved.
<code>...</code>	Unused.

Examples

```
format(new_pillar_type(iris$Species))
```

<code>pillar</code>	<i>Format a vector suitable for tabular display</i>
---------------------	---

Description

`pillar()` formats a vector using one row for a title (if given), one row for the type, and `length(x)` rows for the data.

Usage

```
pillar(x, title = NULL, width = NULL, ...)
```

Arguments

<code>x</code>	A vector to format
<code>title</code>	An optional title for the column. The title will be used "as is", no quoting will be applied.
<code>width</code>	Default width, optional
<code>...</code>	Other arguments passed to methods

Examples

```
x <- 123456789 * (10 ^ c(-1, -3, -5, NA, -8, -10))
pillar(x)
pillar(-x)
pillar(runif(10))
pillar(rcauchy(20))

# Special values are highlighted
pillar(c(runif(5), NA, NaN, Inf, -Inf))

# Very wide ranges will be displayed in scientific format
pillar(c(1e10, 1e-10), width = 20)
pillar(c(1e10, 1e-10))

x <- c(FALSE, NA, FALSE, FALSE, TRUE, FALSE, FALSE, TRUE, FALSE, TRUE)
pillar(x)

x <- c("This is string is rather long", NA, "?", "Short")
pillar(x)
pillar(x, width = 30)
pillar(x, width = 5)

date <- as.Date("2017-05-15")
pillar(date + c(1, NA, 3:5))
pillar(as.POSIXct(date) + c(30, NA, 600, 3600, 86400))
```

pillar_shaft

Column data

Description

Internal class for formatting the data for a column. `pillar_shaft()` is a coercion method that must be implemented for your data type to display it in a tibble.

This class comes with a default method for `print()` that calls `format()`. If `print()` is called without width argument, the natural width will be used when calling `format()`. Usually there's no need to implement this method for your subclass.

Your subclass must implement `format()`, the default implementation just raises an error. Your `format()` method can assume a valid value for the width argument.

Usage

```
pillar_shaft(x, ...)

## S3 method for class 'pillar_shaft'
print(x, width = NULL, ...)

## S3 method for class 'pillar_shaft'
format(x, width, ...)
```

```

## S3 method for class 'logical'
pillar_shaft(x, ...)

## S3 method for class 'numeric'
pillar_shaft(x, ...,
  sigfig = getOption("pillar.sigfig", 3))

## S3 method for class 'Date'
pillar_shaft(x, ...)

## S3 method for class 'POSIXt'
pillar_shaft(x, ...)

## S3 method for class 'character'
pillar_shaft(x, ..., min_width = 3L)

## S3 method for class 'pillar_vertical'
pillar_shaft(x, ..., min_width = 3L)

## S3 method for class 'list'
pillar_shaft(x, ...)

## S3 method for class 'factor'
pillar_shaft(x, ...)

## S3 method for class 'AsIs'
pillar_shaft(x, ...)

## Default S3 method:
pillar_shaft(x, ...)

```

Arguments

x	A vector to format
...	Unused, for extensibility.
width	Width for printing and formatting.
sigfig	Minimum number of significant figures to display. Numbers larger than 1 will potentially show more significant figures than this but they will be greyed out.
min_width	Minimum number of characters to display, unless the string fits a shorter width.

Details

The default method will currently format via `format()`, but you should not rely on this behavior.

Examples

```
pillar_shaft(1:3)
```

```
pillar_shaft(1.5:3.5)
pillar_shaft(NA)
pillar_shaft(c(1:3, NA))
```

style_num

Styling helpers

Description

Functions that allow implementers of formatters for custom data types to maintain a consistent style with the default data types.

Usage

```
style_num(x, negative, significant = rep_along(x, TRUE))
```

```
style_subtle(x)
```

```
style_subtle_num(x, negative)
```

```
style_bold(x)
```

```
style_na(x)
```

```
style_neg(x)
```

Arguments

`x` The character vector to style.

`negative`, `significant`

Logical vector the same length as `x` that indicate if the values are negative and significant, respectively

Details

`style_subtle()` is affected by the `pillar.subtle` option.

`style_subtle_num()` is affected by the `pillar.subtle_num` option, which is `FALSE` by default.

`style_bold()` is affected by the `pillar.bold` option.

`style_neg()` is affected by the `pillar.neg` option.

See Also

[pillar-package](#) for a list of options

Examples

```
style_num(  
  c("123", "456"),  
  negative = c(TRUE, FALSE)  
)  
style_num(  
  c("123", "456"),  
  negative = c(TRUE, FALSE),  
  significant = c(FALSE, FALSE)  
)  
style_subtle("text")  
style_subtle_num(0.01 * 1:3, c(TRUE, FALSE, TRUE))  
style_bold("Petal.Width")  
style_na("NA")  
style_neg("123")
```

Index

character, [9](#)
colonnade, [3](#), [6](#)
crayon, [8](#), [9](#)

dim_desc, [4](#)

expect_known_display, [5](#)
extra_cols, [6](#)

format(), [3](#), [8–12](#)
format.pillar_shaft (pillar_shaft), [11](#)
format_type_sum, [6](#)

get_extent, [7](#)
get_max_extent (get_extent), [7](#)

new_ornament, [8](#)
new_pillar_shaft, [8](#)
new_pillar_shaft_simple
 (new_pillar_shaft), [8](#)
new_pillar_title, [9](#)
new_pillar_type, [10](#)

pillar, [10](#)
pillar-package, [2](#), [13](#)
pillar_shaft, [11](#)
pillar_shaft(), [8](#)
print(), [3](#), [11](#)
print.pillar_shaft (pillar_shaft), [11](#)

squeeze (colonnade), [3](#)
squeeze(), [6](#)
style_bold (style_num), [13](#)
style_na (style_num), [13](#)
style_neg (style_num), [13](#)
style_num, [13](#)
style_subtle (style_num), [13](#)
style_subtle_num (style_num), [13](#)

type_sum(), [6](#)