

Package ‘r2redux’

February 15, 2023

Title R2 Statistic

Version 1.0.13

Description R2 statistic for significance test. Variance and covariance of R2 values used to assess the 95% CI and p-value of the R2 difference.

License GPL (>= 3)

URL <https://github.com/mommy003/r2redux>

Encoding UTF-8

RoxygenNote 7.1.2

NeedsCompilation no

Depends R (>= 2.10)

LazyData true

Suggests testthat (>= 3.0.0)

Config/testthat/edition 3

Author Hong Lee [aut, cph],
Moksedul Momin [aut, cre, cph]

Maintainer Moksedul Momin <cvasu.momin@gmail.com>

Repository CRAN

Date/Publication 2023-02-15 05:10:02 UTC

R topics documented:

cc_trf	2
dat1	3
dat2	4
olkin12_1	4
olkin12_13	5
olkin12_3	5
olkin12_34	6
olkin1_2	6
olkin_beta1_2	7

olkin_beta_inf	8
olkin_beta_ratio	9
r2_beta_var	10
r2_diff	12
r2_enrich_beta	15
r2_var	17
r_diff	19

Index	23
--------------	-----------

cc_trf	<i>cc_trf function</i>
--------	------------------------

Description

This function transforms the predictive ability (R2) and its standard error (se) between the observed scale and liability scale

Usage

```
cc_trf(R2, se, K, P)
```

Arguments

R2	R2 or coefficient of determination on the observed or liability scale
se	Standard error of R2
K	Population prevalence
P	The ratio of cases in the study samples

Value

This function will transform the R2 and its s.e between observed scale and liability scale. Output from the command is the lists of outcomes.

R21	Transformed R2 on the liability scale
se1	Transformed se on the liability scale
R20	Transformed R2 on the observed scale
se0	Transformed se on the observed scale

References

Lee, S. H., Goddard, M. E., Wray, N. R., and Visscher, P. M. A better coefficient of determination for genetic profile analysis. *Genetic epidemiology*,(2012). 36(3): p. 214-224.

Examples

```
#To get the transformed R2

output=cc_trf(0.06, 0.002, 0.05, 0.05)
output

#output$R2l (transformed R2 on the liability scale)
#0.2679337

#output$se1 (transformed se on the liability scale)
#0.008931123

#output$R20 (transformed R2 on the observed scale)
#0.01343616

#output$se0 (transformed se on the observed scale)
#0.000447872
```

dat1	<i>Phenotypes and 10 sets of PGSs</i>
------	---------------------------------------

Description

A dataset containing phenotypes and multiple PGSs estimated from 10 sets of SNPs according to GWAS p-value thresholds

Usage

```
dat1
```

Format

A data frame with 1000 rows and 11 variables:

- V1** Phenotype, value
- V2** PGS1, for p value threshold ≤ 1
- V3** PGS2, for p value threshold ≤ 0.5
- V4** PGS3, for p value threshold ≤ 0.4
- V5** PGS4, for p value threshold ≤ 0.3
- V6** PGS5, for p value threshold ≤ 0.2
- V7** PGS6, for p value threshold ≤ 0.1
- V8** PGS7, for p value threshold ≤ 0.05
- V9** PGS8, for p value threshold ≤ 0.01
- V10** PGS9, for p value threshold ≤ 0.001
- V11** PGS10, for p value threshold ≤ 0.0001

dat2	<i>Phenotypes and 2 sets of PGSs</i>
------	--------------------------------------

Description

A dataset containing phenotypes and 2 sets of PGSs estimated from 2 sets of SNPs from regulatory and non-regulatory genomic regions

Usage

dat2

Format

A data frame with 1000 rows and 3 variables:

V1 Phenotype

V2 PGS1, regulatory region

V3 PGS2, non-regulatory region

olkin12_1	<i>olkin12_1 function</i>
-----------	---------------------------

Description

olkin12_1 function

Usage

olkin12_1(omat, nv)

Arguments

omat	3 by 3 matrix having the correlation coefficients between y, x1 and x2, i.e. $omat = cor(dat)$ where dat is N by 3 matrix having variables in the order of cbind(y,x1,x2)
------	---

nv	Sample size
----	-------------

Value

This function will be used as source code

`olkin12_13`*olkin12_13 function*

Description

`olkin12_13` function

Usage

```
olkin12_13(omat, nv)
```

Arguments

<code>omat</code>	3 by 3 matrix having the correlation coefficients between y, x1 and x2, i.e. <code>omat=cor(dat)</code> where <code>dat</code> is N by 3 matrix having variables in the order of <code>cbind(y,x1,x2)</code>
<code>nv</code>	Sample size

Value

This function will be used as source code

`olkin12_3`*olkin12_3 function*

Description

`olkin12_3` function

Usage

```
olkin12_3(omat, nv)
```

Arguments

<code>omat</code>	3 by 3 matrix having the correlation coefficients between y, x1 and x2, i.e. <code>omat=cor(dat)</code> where <code>dat</code> is N by 3 matrix having variables in the order of <code>cbind(y,x1,x2)</code>
<code>nv</code>	Sample size

Value

This function will be used as source code

olkin12_34

olkin12_34 function

Description

olkin12_34 function

Usage

olkin12_34(omat, nv)

Arguments

omat	3 by 3 matrix having the correlation coefficients between y, x1 and x2, i.e. omat=cor(dat) where dat is N by 3 matrix having variables in the order of cbind(y,x1,x2)
nv	Sample size

Value

This function will be used as source code

olkin1_2

olkin1_2 function

Description

olkin1_2 function

Usage

olkin1_2(omat, nv)

Arguments

omat	3 by 3 matrix having the correlation coefficients between y, x1 and x2, i.e. omat=cor(dat) where dat is N by 3 matrix having variables in the order of cbind(y,x1,x2)
nv	Sample size

Value

This function will be used as source code

olkin_beta1_2	<i>olkin_beta1_2 function</i>
---------------	-------------------------------

Description

This function derives Information matrix for β_1^2 and β_2^2 where β_1 and β_2 are regression coefficients from a multiple regression model, i.e. $y = x_1 * \beta_1 + x_2 * \beta_2 + e$, where y , x_1 and x_2 are column-standardised, (i.e. in the context of correlation coefficients, see Olkin and Finn 1995).

Usage

```
olkin_beta1_2(omat, nv)
```

Arguments

omat	3 by 3 matrix having the correlation coefficients between y , x_1 and x_2 , i.e. $\text{omat} = \text{cor}(\text{dat})$ where dat is N by 3 matrix having variables in the order of $\text{cbind}(y, x_1, x_2)$
nv	Sample size

Value

This function will give information (variance-covariance) matrix of β_1^2 and β_2^2 . To get information (variance-covariance) matrix of β_1^2 and β_2^2 . Where β_1 and β_2 are regression coefficients from a multiple regression model. The outputs are listed as follows.

info	2x2 information (variance-covariance) matrix
var1	Variance of β_1^2
var2	Variance of β_2^2
var1_2	Variance of difference between β_1^2 and β_2^2

References

Olkin, I. and Finn, J.D. Correlations redux. Psychological Bulletin, 1995. 118(1): p. 155.

Examples

```
#To get information (variance-covariance) matrix of beta1_2 and beta2_2 where
#beta1 and 2 are regression coefficients from a multiple regression model.
dat=dat1
omat=cor(dat)[1:3,1:3]
#omat
#1.0000000 0.1958636 0.1970060
#0.1958636 1.0000000 0.9981003
#0.1970060 0.9981003 1.0000000
```

```

nv=length(dat$V1)
output=olkin_beta1_2(omat,nv)
output

#output$info (2x2 information (variance-covariance) matrix)
#0.04146276 0.08158261
#0.08158261 0.16111124

#output$var1 (variance of beta1_2)
#0.04146276

#output$var2 (variance of beta2_2)
#0.1611112

#output$var1_2 (variance of difference between beta1_2 and beta2_2)
#0.03940878

```

olkin_beta_inf	<i>olkin_beta_inf</i> function
----------------	--------------------------------

Description

This function derives Information matrix for beta1 and beta2 where beta1 and 2 are regression coefficients from a multiple regression model, i.e. $y = x1 * beta1 + x2 * beta2 + e$, where y, x1 and x2 are column-standardised (see Olkin and Finn 1995).

Usage

```
olkin_beta_inf(omat, nv)
```

Arguments

omat	3 by 3 matrix having the correlation coefficients between y, x1 and x2, i.e. $omat = cor(dat)$ where dat is N by 3 matrix having variables in the order of cbind(y,x1,x2)
nv	Sample size

Value

This function will generate information (variance-covariance) matrix of beta1 and beta2. The outputs are listed as follows.

info	2x2 information (variance-covariance) matrix
var1	Variance of beta1
var2	Variance of beta2
var1_2	Variance of difference between beta1 and beta2

References

Olkin, I. and Finn, J.D. Correlations redux. *Psychological Bulletin*, 1995. 118(1): p. 155.

Examples

```
#To get information (variance-covariance) matrix of beta1 and beta2 where
#beta1 and 2 are regression coefficients from a multiple regression model.
dat=dat1
omat=cor(dat)[1:3,1:3]
#omat
#1.0000000 0.1958636 0.1970060
#0.1958636 1.0000000 0.9981003
#0.1970060 0.9981003 1.0000000

nv=length(dat$V1)
output=olkin_beta_inf(omat,nv)
output

#output$info (2x2 information (variance-covariance) matrix)
#0.2531406 -0.2526212
#-0.2526212 0.2530269

#output$var1 (variance of beta1)
#0.2531406

#output$var2 (variance of beta2)
#0.2530269

#output$var1_2 (variance of difference between beta1 and beta2)
#1.01141
```

olkin_beta_ratio *olkin_beta_ratio function*

Description

This function derives variance of β_1^2 / R^2 where β_1 and 2 are regression coefficients from a multiple regression model, i.e. $y = x_1 * \beta_1 + x_2 * \beta_2 + e$, where y , x_1 and x_2 are column-standardised (see Olkin and Finn 1995).

Usage

```
olkin_beta_ratio(omat, nv)
```

Arguments

omat	3 by 3 matrix having the correlation coefficients between y , x_1 and x_2 , i.e. $\text{omat}=\text{cor}(\text{dat})$ where dat is N by 3 matrix having variables in the order of $\text{cbind}(y,x_1,x_2)$
nv	sample size

Value

This function will generate the variance of the proportion, i.e. β_1^2/R^2 . The outputs are listed as follows.

ratio_var Variance of ratio

References

Olkin, I. and Finn, J.D. Correlations redux. Psychological Bulletin, 1995. 118(1): p. 155.

Examples

```
#To get information (variance-covariance) matrix of beta1 and beta2 where
#beta1 and 2 are regression coefficients from a multiple regression model.
dat=dat2
omat=cor(dat)[1:3,1:3]
#omat
#1.0000000 0.1497007 0.136431
#0.1497007 1.0000000 0.622790
#0.1364310 0.6227900 1.000000

nv=length(dat$V1)
output=olkin_beta_ratio(omat,nv)
output

#r2redux output

#output$ratio_var (Variance of ratio)
#0.08042288
```

r2_beta_var

r2_beta_var

Description

This function estimates $\text{var}(\beta_1^2)$ and $\text{var}(\beta_2^2)$, and β_1 and β_2 are regression coefficients from a multiple regression model, i.e. $y = x_1 * \beta_1 + x_2 * \beta_2 + e$, y , x_1 and x_2 are column-standardised (see Olkin and Finn 1995). y is N by 1 matrix having the dependent variable, x_1 is N by 1 matrix having the i th explanatory variable. x_2 is N by 1 matrix having the j th explanatory variable. v_1 and v_2 indicates the i th and j th column in the data (v_1 or v_2 should be a single interger between $1 - M$, see Arguments below).

Usage

```
r2_beta_var(dat, v1, v2, nv)
```

Arguments

dat	N by (M+1) matrix having variables in the order of cbind(y,x)
v1	This can be set as v1=1, v1=2, v1=3 or any value between 1 - M based on combination
v2	This can be set as v2=1, v2=2, v2=3, or any value between 1 - M based on combination
nv	Sample size

Value

This function will estimate the variance of β_1^2 and β_2^2 , and the covariance between β_1^2 and β_2^2 , i.e. the information matrix of squared regression coefficients. β_1 and β_2 are regression coefficients from a multiple regression model, i.e. $y = x_1 * \beta_1 + x_2 * \beta_2 + e$, where y , x_1 and x_2 are column-standardised. The outputs are listed as follows.

beta1_sq	beta1_sq
beta2_sq	beta2_sq
var1	Variance of beta1_sq
var2	Variance of beta2_sq
var1_2	Variance of difference between beta1_sq and beta2_sq
cov	Covariance between beta1_sq and beta2_sq
upper_beta1_sq	upper limit of 95% CI for beta1_sq
lower_beta1_sq	lower limit of 95% CI for beta1_sq
upper_beta2_sq	upper limit of 95% CI for beta2_sq
lower_beta2_sq	lower limit of 95% CI for beta2_sq

References

Olkin, I. and Finn, J.D. Correlations redux. Psychological Bulletin, 1995. 118(1): p. 155.

Examples

```
#To get the 95% CI of beta1_sq and beta2_sq
#beta1 and beta2 are regression coefficients from a multiple regression model,
#i.e.  $y = x_1 * \beta_1 + x_2 * \beta_2 + e$ , where  $y$ ,  $x_1$  and  $x_2$  are column-standardised.
```

```
dat=dat2
nv=length(dat$V1)
v1=c(1)
v2=c(2)
output=r2_beta_var(dat,v1,v2,nv)
output
#r2redux output
#output$beta1_sq (beta1_sq)
#0.01118301
```

```

#output$beta2_sq (beta2_sq)
#0.004980285

#output$var1 (variance of beta1_sq)
#7.072931e-05

#output$var2 (variance of beta2_sq)
#3.161929e-05

#output$var1_2 (variance of difference between beta1_sq and beta2_sq)
#0.000162113

#output$cov (covariance between beta1_sq and beta2_sq)
#-2.988221e-05

#output$upper_beta1_sq (upper limit of 95% CI for beta1_sq)
#0.03037793

#output$lower_beta1_sq (lower limit of 95% CI for beta1_sq)
#-0.00123582

#output$upper_beta2_sq (upper limit of 95% CI for beta2_sq)
#0.02490076

#output$lower_beta2_sq (lower limit of 95% CI for beta2_sq)
#-0.005127546

```

r2_diff

r2_diff function

Description

This function estimates $\text{var}(R^2(y \sim x[,v1]) - R^2(y \sim x[,v2]))$ where R^2 is the R squared value of the model, y is N by 1 matrix having the dependent variable, and x is N by M matrix having M explanatory variables. $v1$ or $v2$ indicates the i th column in the x matrix ($v1$ or $v2$ can be multiple values between $1 - M$, see Arguments below)

Usage

```
r2_diff(dat, v1, v2, nv)
```

Arguments

dat	N by $(M+1)$ matrix having variables in the order of <code>cbind(y,x)</code>
v1	This can be set as <code>v1=c(1)</code> or <code>v1=c(1,2)</code>
v2	This can be set as <code>v2=c(2)</code> , <code>v2=c(3)</code> , <code>v2=c(1,3)</code> or <code>v2=c(3,4)</code>
nv	Sample size

Value

This function will estimate significant difference between two PGS (either dependent or independent and joint or single). To get the test statistics for the difference between $R2(y \sim x[,v1])$ and $R2(y \sim x[,v2])$. (here we define $R2_1=R2(y \sim x[,v1])$ and $R2_2=R2(y \sim x[,v2])$). The outputs are listed as follows.

rsq1	R2_1
rsq2	R2_2
var1	Variance of R2_1
var2	variance of R2_2
var_diff	Variance of difference between R2_1 and R2_2
r2_based_p	two tailed P-value for significant difference between R2_1 and R2_2
r2_based_p_one_tail	one tailed P-value for significant difference
mean_diff	Differences between R2_1 and R2_2
upper_diff	Upper limit of 95% CI for the difference
lower_diff	Lower limit of 95% CI for the difference

Examples

#To get the test statistics for the difference between $R2(y \sim x[,v1])$ and $R2(y \sim x[,v2])$. (here we define $R2_1=R2(y \sim x[,v1])$ and $R2_2=R2(y \sim x[,v2])$)

```
dat=dat1
nv=length(dat$V1)
v1=c(1)
v2=c(2)
output=r2_diff(dat,v1,v2,nv)
output

#r2redux output

#output$rsq1 (R2_1)
#0.03836254

#output$rsq2 (R2_2)
#0.03881135

#output$var1 (variance of R2_1)
#0.0001436128

#output$var2 (variance of R2_2)
#0.0001451358

#output$var_diff (variance of difference between R2_1 and R2_2)
#5.678517e-07

#output$r2_based_p (two tailed p-value for significant difference)
```

```
#0.5514562

#output$r2_based_p_one_tail(one tailed p-value for significant difference)
#0.2757281

#output$mean_diff (differences between R2_1 and R2_2)
#-0.0004488044

#output$upper_diff (upper limit of 95% CI for the difference)
#0.001028172

#output$lower_diff (lower limit of 95% CI for the difference)
#-0.001925781

#To get the test statistics for the difference between  $R2(y \sim x[,v1]+x[,v2])$  and
 $R2(y \sim x[,v2])$ . (here  $R2_1=R2(y \sim x[,v1]+x[,v2])$  and  $R2_2=R2(y \sim x[,v1])$ )

dat=dat1
nv=length(dat$V1)
v1=c(1,2)
v2=c(1)
output=r2_diff(dat,v1,v2,nv)

#r2redux output

#output$rsq1 (R2_1)
#0.03896678

#output$rsq2 (R2_2)
#0.03836254

#output$var1 (variance of R2_1)
#0.0001473686

#output$var2 (variance of R2_2)
#0.0001436128

#output$var_diff (variance of difference between R2_1 and R2_2)
#2.321425e-06

#output$r2_based_p (p-value for significant difference between R2_1 and R2_2)
#0.4366883

#output$mean_diff (differences between R2_1 and R2_2)
#0.0006042383

#output$upper_diff (upper limit of 95% CI for the difference)
#0.00488788

#output$lower_diff (lower limit of 95% CI for the difference)
#-0.0005576171
```

r2_enrich_beta	<i>r2_enrich_beta</i>
----------------	-----------------------

Description

This function estimates $\text{var}(\beta_1^2/R^2)$, β_1 and R^2 are regression coefficient and the coefficient of determination from a multiple regression model, i.e. $y = x_1 * \beta_1 + x_2 * \beta_2 + e$, where y , x_1 and x_2 are column-standardised (see Olkin and Finn 1995). y is N by 1 matrix having the dependent variable, and x_1 is N by 1 matrix having the i th explanatory variables. x_2 is N by 1 matrix having the j th explanatory variables. v_1 and v_2 indicates the i th and j th column in the data (v_1 or v_2 should be a single interger between 1 - M , see Arguments below).

Usage

```
r2_enrich_beta(dat, v1, v2, nv, exp1)
```

Arguments

dat	N by (M+1) matrix having variables in the order of <code>cbind(y,x)</code>
v1	These can be set as $v_1=1$, $v_1=2$, $v_1=3$ or any value between 1 - M based on combination
v2	These can be set as $v_2=1$, $v_2=2$, $v_2=3$, or any value between 1 - M based on combination
nv	Sample size
exp1	The expectation of the ratio (e.g. ratio of # SNPs in genomic partitioning)

Value

This function will estimate $\text{var}(\beta_1^2/R^2)$, β_1 and R^2 are regression coefficient and the coefficient of determination from a multiple regression model, i.e. $y = x_1 * \beta_1 + x_2 * \beta_2 + e$, where y , x_1 and x_2 are column-standardised. The outputs are listed as follows.

beta1_sq	beta1_sq
beta2_sq	beta2_sq
ratio1	beta1_sq/R^2
ratio2	beta2_sq/R^2
ratio_var1	variance of ratio 1
ratio_var2	variance of ratio 2
upper_ratio1	upper limit of 95% CI for ratio 1
lower_ratio1	lower limit of 95% CI for ratio 1
upper_ratio2	upper limit of 95% CI for ratio 2
lower_ratio2	lower limit of 95% CI for ratio 2
enrich_p1	two tailed P-value for beta1_sq/R^2 is significantly different from exp1

```

enrich_p1_one_tail      one tailed P-value for beta1_sq/R^2 is significantly different from exp1
enrich_p2               P-value for beta2_sq/R2 is significantly different from (1-exp1)
enrich_p2_one_tail     one tailed P-value for beta2_sq/R2 is significantly different from (1-exp1)

```

References

Olkin, I. and Finn, J.D. Correlations redux. Psychological Bulletin, 1995. 118(1): p. 155.

Examples

```

#To get the test statistic for the ratio which is significantly
#different from the expectation, this function estimates
#var (beta1^2/R^2), where
#beta1^2 and R^2 are regression coefficients and the
#coefficient of determination from a multiple regression model,
#i.e.  $y = x_1 * \beta_1 + x_2 * \beta_2 + e$ , where  $y$ ,  $x_1$  and  $x_2$  are
#column-standardised.

```

```

dat=dat2
nv=length(dat$V1)
v1=c(1)
v2=c(2)
expected_ratio=0.04
output=r2_enrich_beta(dat,v1,v2,nv,expected_ratio)
output

```

```
#r2redux output
```

```
#output$beta1_sq (beta1_sq)
#0.01118301
```

```
#output$beta2_sq (beta2_sq)
#0.004980285
```

```
#output$ratio1 (beta1_sq/R^2)
#0.4392572
```

```
#output$ratio2 (beta2_sq/R^2)
#0.1956205
```

```
#output$ratio_var1 (variance of ratio 1)
#0.08042288
```

```
#output$ratio_var2 (variance of ratio 2)
#0.0431134
```

```
#output$upper_ratio1 (upper limit of 95% CI for ratio 1)
#0.9950922
```

```
#output$lower_ratio1 (lower limit of 95% CI for ratio 1)
```



```

#-0.1165778

#output$upper_ratio2 (upper limit of 95% CI for ratio 2)
#0.6025904

#output$lower_ratio2 (lower limit of 95% CI for ratio 2)
#-0.2113493

#output$enrich_p1 (two tailed P-value for beta1_sq/R^2 is
#significantly different from exp1)
#0.1591692

#output$enrich_p1_one_tail (one tailed P-value for beta1_sq/R^2
#is significantly different from exp1)
#0.07958459

#output$enrich_p2 (two tailed P-value for beta2_sq/R2 is
#significantly different from (1-exp1))
#0.000232035

#output$enrich_p2_one_tail (one tailed P-value for beta2_sq/R2
#is significantly different from (1-exp1))
#0.0001160175

```

r2_var

r2_var function

Description

This function estimates $\text{var}(R^2(y \sim x[,v1]))$ where R^2 is the R squared value of the model, where R^2 is the R squared value of the model, y is N by 1 matrix having the dependent variable, and x is N by M matrix having M explanatory variables. $v1$ indicates the i th column in the x matrix ($v1$ can be multiple values between $1 - M$, see Arguments below)

Usage

```
r2_var(dat, v1, nv)
```

Arguments

dat	N by $(M+1)$ matrix having variables in the order of <code>cbind(y,x)</code>
v1	This can be set as <code>v1=c(1)</code> , <code>v1=c(1,2)</code> or possibly with more values
nv	Sample size

Value

This function will test the null hypothesis for R^2 . To get the test statistics for $R^2(y \sim x[,v1])$. The outputs are listed as follows.

rsq	R2
var	Variance of R2
r2_based_p	P-value under the null hypothesis, i.e. $R^2=0$
upper_r2	Upper limit of 95% CI for R2
lower_r2	Lower limit of 95% CI for R2

Examples

```
#To get the test statistics for R2(y~x[,v1])
dat=dat1
nv=length(dat$V1)
v1=c(1)
output=r2_var(dat,v1,nv)
output

#r2redux output

#output$rsq (R2)
#0.03836254

#output$var (variance of R2)
#0.0001436128

#output$r2_based_p (P-value under the null hypothesis, i.e. R2=0)
#1.188162e-10

#output$upper_r2 (upper limit of 95% CI for R2)
#0.06433782

#output$lower_r2 (lower limit of 95% CI for R2)
#0.01764252

#To get the test statistic for R2(y~x[,v1]+x[,v2]+x[,v3])

dat=dat1
nv=length(dat$V1)
v1=c(1,2,3)
r2_var(dat,v1,nv)

#r2redux output

#output$rsq (R2)
#0.03836254

#output$var (variance of R2)
#0.0001436128

#output$r2_based_p (R2 based P-value)
#1.188162e-10
```

```

#output$upper_r2 (upper limit of 95% CI for R2)
#0.06433782

#output$lower_r2 (lower limit of 95% CI for R2)
#0.0176425

#When comparing two independent sets of PGSS
#Let's assume dat1$V1 and dat2$V2 are independent for this example
#(e.g. male PGS vs. female PGS)

nv=length(dat1$V1)
v1=c(1)
output1=r2_var(dat1,v1,nv)
nv=length(dat2$V1)
v1=c(1)
output2=r2_var(dat2,v1,nv)

#To get the difference between two independent sets of PGSS
r2_diff_independent=abs(output1$rsq-output2$rsq)

#To get the variance of the difference between two independent sets of PGSS
var_r2_diff_independent= output1$var+output2$var
sd_r2_diff_independent=sqrt(var_r2_diff_independent)

#To get p-value (following eq. 15 in the paper)
chi=r2_diff_independent^2/var_r2_diff_independent
p_value=pchisq(chi,1,lower.tail=FALSE)
#to get 95% CI (following eq. 15 in the paper)
uci=r2_diff_independent+1.96*sd_r2_diff_independent
lci=r2_diff_independent-1.96*sd_r2_diff_independent

```

r_diff

r_diff function

Description

This function estimates $\text{var}(R(y \sim x[,v1]) - R(y \sim x[,v2]))$ where R is the correlation between y and x , y is N by 1 matrix having the dependent variable, and x is N by M matrix having M explanatory variables. $v1$ or $v2$ indicates the i th column in the x matrix ($v1$ or $v2$ can be multiple values between $1 - M$, see Arguments below)

Usage

```
r_diff(dat, v1, v2, nv)
```

Arguments

dat	N by (M+1) matrix having variables in the order of cbind(y,x)
v1	This can be set as v1=c(1) or v1=c(1,2)
v2	This can be set as v2=c(2), v2=c(3), v2=c(1,3) or v2=c(3,4)
nv	Sample size

Value

This function will estimate significant difference between two PGS (either dependent or independent and joint or single). To get the test statistics for the difference between $R(y \sim x[,v1])$ and $R(y \sim x[,v2])$. (here we define $R_1=R(y \sim x[,v1])$ and $R_2=R(y \sim x[,v2])$). The outputs are listed as follows.

r1	R_1
r2	R_2
var1	Variance of R_1
var2	variance of R_2
var_diff	Variance of difference between R_1 and R_2
r2_based_p	P-value for significant difference between R_1 and R_2 for two tailed test
r_based_p_one_tail	P-value for significant difference between R_1 and R_2 for one tailed test
mean_diff	Differences between R_1 and R_2
upper_diff	Upper limit of 95% CI for the difference
lower_diff	Lower limit of 95% CI for the difference

Examples

```
#To get the test statistics for the difference between R(y~x[,v1]) and
#R(y~x[,v2]). (here we define R_1=R(y~x[,v1]) and R_2=R(y~x[,v2]))
```

```
dat=dat1
nv=length(dat$V1)
v1=c(1)
v2=c(2)
output=r_diff(dat,v1,v2,nv)
output

#r2redux output

#output$r1 (R_1)
#0.1958636

#output$r2 (R_2)
#0.197006

#output$var1 (variance of R_1)
#0.0009247466
```

```
#output$var2 (variance of R_1)
#0.0001451358

#output$var_diff (variance of difference between R_1 and R_2)
#3.65286e-06

#output$r_based_p (two tailed p-value for significant difference between R_1 and R_2)
#0.5500319

#output$r_based_p_one_tail (one tailed p-value for significant difference between R_1 and R_2)
#0.2750159

#output$mean_diff
#-0.001142375 (differences between R2_1 and R2_2)

#output$upper_diff (upper limit of 95% CI for the difference)
#0.002603666

#output$lower_diff (lower limit of 95% CI for the difference)
#-0.004888417

#To get the test statistics for the difference between  $R(\tilde{y}[v1]+[v2])$  and
 $R(\tilde{y}[v2])$ . (here  $R_1=R(\tilde{y}[v1]+x[v2])$  and  $R_2=R(\tilde{y}[v1])$ )

nv=length(dat$V1)
v1=c(1,2)
v2=c(2)
output=r_diff(dat,v1,v2,nv)
output

#output$r1
#0.1974001

#output$r2
#0.197006

#output$var1
#0.0009235848

#output$var2
#0.0009238836

#output$var_diff
#3.837451e-06

#output$r2_based_p
#0.8405593

#output$mean_diff
#0.0003940961
```

```
#output$upper_diff  
#0.004233621
```

```
#output$lower_diff  
#-0.003445429
```

Index

- * **R2**
 - cc_trf, 2
 - r2_diff, 12
 - r2_var, 17
 - r_diff, 19
- * **Transformation**
 - cc_trf, 2
- * **and**
 - cc_trf, 2
- * **a**
 - r2_beta_var, 10
 - r2_enrich_beta, 15
- * **beta^2**
 - r2_beta_var, 10
 - r2_enrich_beta, 15
- * **between**
 - cc_trf, 2
 - r2_enrich_beta, 15
- * **context**
 - olkin_beta1_2, 7
 - olkin_beta_inf, 8
 - olkin_beta_ratio, 9
- * **correlation**
 - olkin_beta1_2, 7
 - olkin_beta_inf, 8
 - olkin_beta_ratio, 9
- * **datasets**
 - dat1, 3
 - dat2, 4
- * **from**
 - r2_beta_var, 10
 - r2_enrich_beta, 15
- * **information**
 - olkin_beta1_2, 7
 - olkin_beta_inf, 8
 - olkin_beta_ratio, 9
 - r2_diff, 12
 - r2_var, 17
 - r_diff, 19
- * **in**
 - olkin_beta1_2, 7
 - olkin_beta_inf, 8
 - olkin_beta_ratio, 9
- * **liability**
 - cc_trf, 2
- * **matrix**
 - olkin_beta1_2, 7
 - olkin_beta_inf, 8
 - olkin_beta_ratio, 9
 - r2_diff, 12
 - r2_var, 17
 - r_diff, 19
- * **multiple**
 - r2_beta_var, 10
 - r2_enrich_beta, 15
- * **observed**
 - cc_trf, 2
- * **of**
 - cc_trf, 2
 - olkin_beta1_2, 7
 - olkin_beta_inf, 8
 - olkin_beta_ratio, 9
 - r2_beta_var, 10
 - r2_enrich_beta, 15
- * **ratio**
 - r2_enrich_beta, 15
- * **regression**
 - r2_beta_var, 10
 - r2_enrich_beta, 15
- * **scale**
 - cc_trf, 2
- * **source**
 - olkin12_1, 4
 - olkin12_13, 5
 - olkin12_3, 5
 - olkin12_34, 6
 - olkin1_2, 6
- * **the**

- olkin_beta1_2, 7
- olkin_beta_inf, 8
- olkin_beta_ratio, 9
- * **variance**
 - r2_beta_var, 10
 - r2_diff, 12
 - r2_enrich_beta, 15
 - r2_var, 17
 - r_diff, 19

- cc_trf, 2

- dat1, 3
- dat2, 4

- olkin12_1, 4
- olkin12_13, 5
- olkin12_3, 5
- olkin12_34, 6
- olkin1_2, 6
- olkin_beta1_2, 7
- olkin_beta_inf, 8
- olkin_beta_ratio, 9

- r2_beta_var, 10
- r2_diff, 12
- r2_enrich_beta, 15
- r2_var, 17
- r_diff, 19