

Package ‘rENA’

May 9, 2026

Title Epistemic Network Analysis

Type Package

Author Cody L Marquart [aut, cre] (ORCID:
<<https://orcid.org/0000-0002-3387-6792>>),
Zachari Swiecki [aut],
Wesley Collier [aut],
Brendan Eagan [aut],
Roman Woodward [aut],
David Williamson Shaffer [aut]

Maintainer Cody L Marquart <cody.marquart@wisc.edu>

Version 0.3.1

Description ENA (Shaffer, D. W. (2017) Quantitative Ethnography. ISBN: 0578191687) is a method used to identify meaningful and quantifiable patterns in discourse or reasoning. ENA moves beyond the traditional frequency-based assessments by examining the structure of the co-occurrence, or connections in coded data. Moreover, compared to other methodological approaches, ENA has the novelty of (1) modeling whole networks of connections and (2) affording both quantitative and qualitative comparisons between different network models. Shaffer, D.W., Collier, W., & Ruis, A.R. (2016).

LazyData TRUE

Encoding UTF-8

Depends R (>= 4.1.0)

License GPL-3 | file LICENSE

URL <https://gitlab.com/epistemic-analytics/qe-packages/rENA>

BugReports <https://gitlab.com/epistemic-analytics/qe-packages/rENA/-/issues>

LinkingTo Rcpp, RcppArmadillo

Imports data.table, Rcpp, R6, methods, stats, plotly, doParallel,
parallel, scales, glmnet, tma

Suggests testthat (>= 2.1.0), knitr, rmarkdown

RoxygenNote 7.3.3

NeedsCompilation yes

Repository CRAN

Date/Publication 2026-02-11 16:20:09 UTC

Contents

| | |
|--|----|
| *.ena.matrix | 4 |
| accumulate | 5 |
| add_group | 6 |
| add_network | 7 |
| add_nodes | 9 |
| add_points | 10 |
| add_trajectory | 11 |
| as.ena.co.occurrence | 13 |
| as.ena.matrix | 13 |
| as.ena.metadata | 14 |
| as.matrix.ena.connections | 14 |
| as.matrix.ena.line.weights | 15 |
| as.matrix.ena.matrix | 15 |
| as.matrix.ena.nodes | 16 |
| as.matrix.ena.points | 16 |
| as.matrix.ena.rotation.matrix | 17 |
| as.matrix.row.connections | 17 |
| as.qe.code | 18 |
| as.qe.data | 18 |
| as.qe.horizon | 19 |
| as.qe.metadata | 20 |
| as.qe.unit | 20 |
| as_trajectory | 21 |
| center | 21 |
| check_range | 22 |
| clear | 23 |
| codes | 24 |
| combn_c2 | 25 |
| compute_SB | 25 |
| connection.matrix | 26 |
| define | 26 |
| directed_node_positions | 27 |
| directed_node_positions_with_ground_response_added | 28 |
| ena | 28 |
| ena.accumulate.data | 31 |
| ena.conversations | 33 |
| ena.correlations | 34 |
| ena.group | 35 |
| ena.make.set | 36 |
| ena.plot | 38 |
| ena.plot.group | 39 |
| ena.plot.network | 41 |
| ena.plot.points | 44 |
| ena.plot.trajectory | 47 |
| ena.plotter | 49 |
| ena.rotate.by.generalized | 50 |

| | |
|--|----|
| ena.rotate.by.hena.regression | 51 |
| ena.rotate.by.hena.regression_2 | 51 |
| ena.rotate.by.mean | 52 |
| ena.rotation.h | 53 |
| ena.set.creator | 53 |
| ena.svd | 55 |
| ena.writeup | 56 |
| ENadata | 57 |
| ENApplot | 59 |
| ENARotationSet | 61 |
| ENAsset | 62 |
| ena_correlation | 64 |
| find_binary_cols | 64 |
| find_code_cols | 65 |
| find_dimension_cols | 65 |
| find_meta_cols | 66 |
| fun_cohens.d | 66 |
| fun_skip_sphere_norm | 67 |
| fun_sphere_norm | 67 |
| get_x1_main_effect | 68 |
| gmr | 69 |
| group | 70 |
| horizon | 71 |
| is.qe.code | 72 |
| is.qe.data | 72 |
| is.qe.horizon | 73 |
| is.qe.metadata | 74 |
| is.qe.unit | 74 |
| means_rotate | 75 |
| merge_columns_c | 75 |
| metadata | 76 |
| methods_report | 76 |
| methods_report_stream | 77 |
| model | 78 |
| move_nodes_to_unit_circle | 79 |
| move_nodes_to_unit_circle_with_equal_space | 80 |
| namesToAdjacencyKey | 80 |
| optimize | 81 |
| plot.ena.set | 82 |
| prepare_trajectory_data | 83 |
| print.ena.set | 85 |
| project | 85 |
| project_in | 86 |
| reclassify | 87 |
| remove_meta_data | 87 |
| rENA | 88 |
| rotate | 88 |
| RS.data | 89 |

| | |
|---------------------------|----|
| scale.ENAplot | 89 |
| show | 90 |
| sphere_norm | 90 |
| units | 91 |
| vector_to_ut | 92 |
| with.ena.matrix | 92 |
| with_means | 93 |
| with_trajectory | 93 |
| \$.ena.matrix | 94 |
| \$.ena.metadata | 95 |
| \$.ena.points | 95 |
| \$.line.weights | 96 |

| | |
|--------------|-----------|
| Index | 97 |
|--------------|-----------|

| | |
|--------------|--|
| *.ena.matrix | <i>Multiply ena.matrix objects Element-wise multiplication of dimension columns in an ena.matrix by another ena.matrix or numeric matrix. If e2 is an ena.matrix, it is converted to a standard matrix before multiplication. The multiplication is applied only to the dimension columns of e1, while other columns remain unchanged.</i> |
|--------------|--|

Description

Multiply ena.matrix objects Element-wise multiplication of dimension columns in an ena.matrix by another ena.matrix or numeric matrix. If e2 is an ena.matrix, it is converted to a standard matrix before multiplication. The multiplication is applied only to the dimension columns of e1, while other columns remain unchanged.

Usage

```
## S3 method for class 'ena.matrix'
e1 * e2
```

Arguments

e1 An ena.matrix object whose dimension columns will be multiplied.
e2 An ena.matrix or numeric matrix to multiply with the dimension columns of e1.

Value

An ena.matrix object with the dimension columns of e1 multiplied by e2.

accumulate *Accumulate Connection Counts for ENA*

Description

This function takes a data.frame and accumulates co-occurrences of codes within specified units and conversations (horizon), preparing it for ENA. It's designed to be used with pipes ('|>').

Usage

```
accumulate(
  x,
  units = rENA::units(x),
  codes = rENA::codes(x),
  horizon = rENA::horizon(x),
  ...,
  ordered = FALSE,
  binary = TRUE
)
```

Arguments

| | |
|---------|--|
| x | A data.frame or similar object containing the data to be analyzed. |
| units | A character vector specifying the columns that define the units of analysis. |
| codes | A character vector specifying the columns that contain the codes for co-occurrence analysis. |
| horizon | A character vector specifying the columns that define the conversational boundaries (horizon). |
| ... | Additional arguments passed to underlying accumulation functions. |
| ordered | A logical value. If TRUE, creates ordered networks (A -> B is different from B -> A). Defaults to FALSE. |
| binary | A logical value. If TRUE, connection counts are binarized (0 or 1). Defaults to TRUE. |

Value

An ena.set object containing the accumulated connection counts and metadata.

Examples

```
data(RS.data)

codes <- c("Data", "Technical.Constraints", "Performance.Parameters",
          "Client.and.Consultant.Requests", "Design.Reasoning",
          "Collaboration")
units <- c("Condition", "UserName")
```

```
horizon <- c("Condition", "GroupName")
enaset <- RS.data |>
  accumulate(units, codes, horizon)
```

add_group *Add a group mean to an ENA plot*

Description

This function adds a group mean to an existing ENA plot or ENA set. It supports various input types for the ‘wh’ parameter, including unevaluated expressions and language objects.

Usage

```
add_group(x, wh = NULL, ...)
```

Arguments

| | |
|-----|---|
| x | An ‘ENApLot’ object or an ENA set containing plots. |
| wh | Specifies the group to plot. Can be an unevaluated expression or a language object. |
| ... | Additional parameters passed to the plotting functions. |

Details

The function determines the type of the ‘wh’ parameter and processes it accordingly: - If ‘wh’ is an unevaluated expression, it is captured and evaluated in the parent frame. - If ‘wh’ is a language object, it is processed to extract the relevant group information.

The function updates the plot with the new group mean and stores the updated plot back in the ENA set.

Value

Invisibly returns the modified ENA set.

Examples

```
# Load test data
data(RS.data);

# Define codenames for the test
codenames <- c("Data", "Technical.Constraints", "Performance.Parameters",
  "Client.and.Consultant.Requests", "Design.Reasoning", "Collaboration");

# Standard ENA accumulation
accum <- rENA:::ena.accumulate.data.file(
  RS.data, units.by = c("UserName", "Condition"),
```

```

    conversations.by = c("ActivityNumber", "GroupName"),
    codes = codenames
  );
# Create a standard ENA set
newset <- ena.make.set(accum);

# Simple plot for a set of points, and their mean
newplot <- plot(newset) |>
  add_points(Condition$FirstGame, mean = TRUE, colors = "blue") |>
  add_network();

# Plot a single unit's point and it's line.weights
plot(newset) |>
  add_points(UserName$`steven z`) |>
  add_network();

# Trajectory accumulation and plotting
trajectory_accumulation <- rENA:::ena.accumulate.data.file(
  RS.data, units.by = c("UserName", "Condition"),
  conversations.by = c("ActivityNumber", "GroupName"),
  codes = codenames,
  model = "A"
);
trajectory_model <- ena.make.set(trajectory_accumulation);

newplot3 <- plot(trajectory_model) |>
  add_trajectory(Condition$FirstGame);

```

add_network

Add a network to an ENA plot

Description

Adds a network (set of edges) to an existing ENA plot or ENA set. The network can be specified in several ways, including as an unevaluated expression, a numeric matrix, or a language object. This function is typically used to visualize group means, differences between groups, or custom networks on an ENA plot.

Usage

```

add_network(
  x,
  wh = NULL,
  ...,
  with.mean = F,
  edge.multiplier = 1,
  colors = NULL
)

```

Arguments

| | |
|-----------------|---|
| x | An 'ENApplot' object or an ENA set containing plots. |
| wh | Specifies the network to plot. Can be: <ul style="list-style-type: none"> • An unevaluated expression (e.g., 'Condition\$FirstGame - Condition\$SecondGame') • A numeric matrix or data.frame of edge weights • A language object • NULL (defaults to the mean network) |
| ... | Additional parameters passed to the plotting functions. |
| with.mean | Logical; if 'TRUE', also plots the mean for the points in the network. Default is 'FALSE'. |
| edge.multiplier | Numeric scalar to multiply the edge weights. Useful for scaling the network visualization. Default is 1. |
| colors | Optional vector of colors for the network. If not specified, colors are chosen from the plot palette. |

Details

The function determines the type of the 'wh' parameter and processes it accordingly:

- If 'wh' is an unevaluated expression, it is captured and evaluated in the parent frame. This allows for flexible specification of group means or differences.
- If 'wh' is a numeric matrix or data.frame, it is used directly as the network data.
- If 'wh' is a language object, it is processed to extract the relevant network information.
- If 'wh' is NULL, the mean network is plotted.

The function updates the plot with the new network and returns the modified plot object. The ENA set is not modified in-place.

Value

The modified ENApplot object with the new network added.

Examples

See 'inst/examples/example-plot-piping.R' for usage examples.

| | |
|-----------|---------------------------------|
| add_nodes | <i>Add nodes to an ENA plot</i> |
|-----------|---------------------------------|

Description

This function adds nodes to an existing ENA plot or ENA set. It can be used to customize the nodes displayed on the plot, including their size and other graphical parameters.

Usage

```
add_nodes(x, ..., return_plot = FALSE)
```

Arguments

| | |
|-------------|--|
| x | An ENAplot object or an ENA set containing plots. |
| ... | Additional arguments passed to <code>ena.plot.points</code> , such as <code>nodes</code> , <code>size</code> , and other graphical parameters. |
| return_plot | Logical; if TRUE, returns the modified ENA set. If FALSE (default), returns the modified plot invisibly. |

Details

If `x` is an ENAplot, the function extracts the associated ENA set and plot. Otherwise, it assumes `x` is an ENA set and uses the last plot in the set. The nodes to be added can be specified via the `nodes` argument; otherwise, the default nodes from the set's rotation are used. Node size can be customized via the `size` argument.

The function updates the plot with the new nodes and stores the updated plot back in the ENA set.

Value

Invisibly returns the modified plot or ENA set, depending on the value of `return_plot`.

Examples

```
# Load test data
data(RS.data);

# Define codenames for the test
codenames <- c("Data", "Technical.Constraints", "Performance.Parameters",
  "Client.and.Consultant.Requests", "Design.Reasoning", "Collaboration");

# Standard ENA accumulation
accum <- rENA:::ena.accumulate.data.file(
  RS.data, units.by = c("UserName", "Condition"),
  conversations.by = c("ActivityNumber", "GroupName"),
  codes = codenames
);
# Create a standard ENA set
```

```

newset <- ena.make.set(accum);

# Simple plot for a set of points, and their mean
newplot <- plot(newset) |>
  add_points(Condition$FirstGame, mean = TRUE, colors = "blue") |>
  add_network();

# Plot a single unit's point and it's line.weights
plot(newset) |>
  add_points(UserName$`steven z`) |>
  add_network();

# Trajectory accumulation and plotting
trajectory_accumulation <- rENA:::ena.accumulate.data.file(
  RS.data, units.by = c("UserName", "Condition"),
  conversations.by = c("ActivityNumber", "GroupName"),
  codes = codenames,
  model = "A"
);
trajectory_model <- ena.make.set(trajectory_accumulation);

newplot3 <- plot(trajectory_model) |>
  add_trajectory(Condition$FirstGame);

```

add_points

Add points to an ENA plot

Description

This function adds points to an existing ENA plot or ENA set. It supports various input types for the ‘wh’ parameter, including unevaluated expressions and language objects.

Usage

```
add_points(x, wh = NULL, ..., colors = NULL)
```

Arguments

| | |
|--------|--|
| x | An ‘ENApLot’ object or an ENA set containing plots. |
| wh | Specifies the points to plot. Can be an unevaluated expression or a language object. |
| ... | Additional parameters passed to the plotting functions. |
| colors | A vector of colors for the plotted points. Default is ‘NULL’. |

Details

The function determines the type of the ‘wh’ parameter and processes it accordingly: - If ‘wh’ is an unevaluated expression, it is captured and evaluated in the parent frame. - If ‘wh’ is a language object, it is processed to extract the relevant points information.

The function updates the plot with the new points and stores the updated plot back in the ENA set.

Value

Invisibly returns the modified ENA set.

Examples

```
# Load test data
data(RS.data);

# Define codenames for the test
codenames <- c("Data", "Technical.Constraints", "Performance.Parameters",
  "Client.and.Consultant.Requests", "Design.Reasoning", "Collaboration");

# Standard ENA accumulation
accum <- rENA:::ena.accumulate.data.file(
  RS.data, units.by = c("UserName", "Condition"),
  conversations.by = c("ActivityNumber", "GroupName"),
  codes = codenames
);
# Create a standard ENA set
newset <- ena.make.set(accum);

# Simple plot for a set of points, and their mean
newplot <- plot(newset) |>
  add_points(Condition$FirstGame, mean = TRUE, colors = "blue") |>
  add_network();

# Plot a single unit's point and it's line.weights
plot(newset) |>
  add_points(UserName$`steven z`) |>
  add_network();

# Trajectory accumulation and plotting
trajectory_accumulation <- rENA:::ena.accumulate.data.file(
  RS.data, units.by = c("UserName", "Condition"),
  conversations.by = c("ActivityNumber", "GroupName"),
  codes = codenames,
  model = "A"
);
trajectory_model <- ena.make.set(trajectory_accumulation);

newplot3 <- plot(trajectory_model) |>
  add_trajectory(Condition$FirstGame);
```

 add_trajectory

Add a trajectory to an ENA plot

Description

This function adds a trajectory to an existing ENA plot or ENA set. It supports various input types for the ‘wh’ parameter, including unevaluated expressions and language objects.

Usage

```
add_trajectory(x, wh = NULL, ..., name = "plot")
```

Arguments

| | |
|------|--|
| x | An 'ENApLot' object or an ENA set containing plots. |
| wh | Specifies the trajectory to plot. Can be an unevaluated expression or a language object. |
| ... | Additional parameters passed to the plotting functions. |
| name | A character string specifying the name of the plot. Default is "plot". |

Details

The function determines the type of the 'wh' parameter and processes it accordingly: - If 'wh' is an unevaluated expression, it is captured and evaluated in the parent frame. - If 'wh' is a language object, it is processed to extract the relevant trajectory information.

The function updates the plot with the new trajectory and stores the updated plot back in the ENA set.

Value

Invisibly returns the modified ENA set.

Examples

```
# Load test data
data(RS.data);

# Define codenames for the test
codenames <- c("Data", "Technical.Constraints", "Performance.Parameters",
  "Client.and.Consultant.Requests", "Design.Reasoning", "Collaboration");

# Standard ENA accumulation
accum <- rENA:::ena.accumulate.data.file(
  RS.data, units.by = c("UserName", "Condition"),
  conversations.by = c("ActivityNumber", "GroupName"),
  codes = codenames
);
# Create a standard ENA set
newset <- ena.make.set(accum);

# Simple plot for a set of points, and their mean
newplot <- plot(newset) |>
  add_points(Condition$FirstGame, mean = TRUE, colors = "blue") |>
  add_network();

# Plot a single unit's point and it's line.weights
plot(newset) |>
  add_points(UserName$`steven z`) |>
  add_network();
```

```

# Trajectory accumulation and plotting
trajectory_accumulation <- rENA:::ena.accumulate.data.file(
  RS.data, units.by = c("UserName", "Condition"),
  conversations.by = c("ActivityNumber", "GroupName"),
  codes = codenames,
  model = "A"
);
trajectory_model <- ena.make.set(trajectory_accumulation);

newplot3 <- plot(trajectory_model) |>
  add_trajectory(Condition$FirstGame);

```

as.ena.co.occurrence *Re-class vector as ena.co.occurrence*

Description

Re-class vector as ena.co.occurrence

Usage

```
as.ena.co.occurrence(x)
```

Arguments

x Vector to re-class

Value

re-classed vector

as.ena.matrix *Re-class matrix as ena.matrix*

Description

Re-class matrix as ena.matrix

Usage

```
as.ena.matrix(x, new.class = NULL)
```

Arguments

x data.frame, data.table, or matrix to extend
new.class Additional class to extend the matrix with, default: NULL

Value

Object of same st

| | |
|-----------------|--|
| as.ena.metadata | <i>Re-class matrix as ena.metadata</i> |
|-----------------|--|

Description

Re-class matrix as ena.metadata

Usage

```
as.ena.metadata(x)
```

Arguments

x data.frame, data.table, or matrix to extend

Value

Object of same st

| | |
|---------------------------|------------------------------------|
| as.matrix.ena.connections | <i>ENA Connections as a matrix</i> |
|---------------------------|------------------------------------|

Description

ENA Connections as a matrix

Usage

```
## S3 method for class 'ena.connections'
as.matrix(x, ...)
```

Arguments

x ena.connections object
 ... additional arguments to be passed to or from methods

Value

If square is FALSE (default), a matrix with all metadata columns removed, otherwise a list with square matrices

as.matrix.ena.line.weights
ENA line weights as matrix

Description

ENA line weights as matrix

Usage

```
## S3 method for class 'ena.line.weights'  
as.matrix(x, ..., square = FALSE)
```

Arguments

| | |
|--------|--|
| x | ena.line.weights data.table to covert to matrix |
| ... | additional arguments to be passed to or from methods |
| square | [TBD] |

Value

matrix

as.matrix.ena.matrix *Matrix without metadata*

Description

Matrix without metadata

Usage

```
## S3 method for class 'ena.matrix'  
as.matrix(x, ...)
```

Arguments

| | |
|-----|--|
| x | Object to convert to a matrix |
| ... | additional arguments to be passed to or from methods |

Value

matrix

as.matrix.ena.nodes *ENA nodes as matrix*

Description

ENA nodes as matrix

Usage

```
## S3 method for class 'ena.nodes'  
as.matrix(x, ...)
```

Arguments

x ena.nodes to convert to matrix
... additional arguments to be passed to or from methods

Value

matrix

as.matrix.ena.points *ENA points as matrix*

Description

ENA points as matrix

Usage

```
## S3 method for class 'ena.points'  
as.matrix(x, ...)
```

Arguments

x ena.points to convert to a matrix
... additional arguments to be passed to or from methods

Value

matrix

```
as.matrix.ena.rotation.matrix
      ENA rotations as matrix
```

Description

ENA rotations as matrix

Usage

```
## S3 method for class 'ena.rotation.matrix'
as.matrix(x, ...)
```

Arguments

| | |
|-----|--|
| x | ena.rotation.matrix to conver to matrix |
| ... | additional arguments to be passed to or from methods |

Value

matrix

```
as.matrix.row.connections
      ENA row connections as matrix
```

Description

ENA row connections as matrix

Usage

```
## S3 method for class 'row.connections'
as.matrix(x, ...)
```

Arguments

| | |
|-----|--|
| x | ena.row.connections to conver to a matrix |
| ... | additional arguments to be passed to or from methods |

Value

matrix

| | |
|------------|--|
| as.qe.code | <i>Convert a vector to 'qe.code' class</i> |
|------------|--|

Description

This function converts a vector to the 'qe.code' class. If the vector is a factor, it is first converted to a character vector.

Usage

```
as.qe.code(x)
```

Arguments

x A vector. The vector to be converted to 'qe.code' class.

Value

The modified vector with the 'qe.code' class.

Examples

```
vec <- factor(c("A", "B", "C"))
vec <- as.qe.code(vec)
class(vec) # Should show 'qe.code' along with other classes
```

| | |
|------------|---|
| as.qe.data | <i>Convert an object to 'qe.data' class</i> |
|------------|---|

Description

This function converts an object to the 'qe.data' class. If the object is not a data.frame or matrix, it is first converted to a data.table.

Usage

```
as.qe.data(x)
```

Arguments

x An object. The object to be converted to 'qe.data' class.

Value

The modified object with the 'qe.data' class.

Examples

```
library(data.table)

dt <- data.table(
  ID = 1:5,
  Name = c("Alice", "Bob", "Charlie", "David", "Eve"),
  Age = c(25, 30, 35, 40, 45),
  Score = c(85, 90, 95, 80, 75)
)
dt <- as.qe.data(dt);
class(dt) # Should show 'qe.data' along with other classes
```

as.qe.horizon

Convert a vector to 'qe.horizon' class

Description

This function converts a vector to the 'qe.horizon' class. If the vector is a factor, it is first converted to a character vector.

Usage

```
as.qe.horizon(x)
```

Arguments

x A vector. The vector to be converted to 'qe.horizon' class.

Value

The modified vector with the 'qe.horizon' class.

Examples

```
vec <- factor(c("A", "B", "C"))
vec <- as.qe.horizon(vec)
class(vec) # Should show 'qe.horizon' along with other classes
```

| | |
|----------------|--|
| as.qe.metadata | <i>Convert a vector to 'qe.metadata' class</i> |
|----------------|--|

Description

This function converts a vector to the 'qe.metadata' class. If the vector is a factor, it is first converted to a character vector.

Usage

```
as.qe.metadata(x)
```

Arguments

x A vector. The vector to be converted to 'qe.metadata' class.

Value

The modified vector with the 'qe.metadata' class.

Examples

```
vec <- factor(c("A", "B", "C"))
vec <- as.qe.metadata(vec)
class(vec) # Should show 'qe.metadata' along with other classes
```

| | |
|------------|--|
| as.qe.unit | <i>Convert a vector to 'qe.unit' class</i> |
|------------|--|

Description

This function converts a vector to the 'qe.unit' class. If the vector is a factor, it is first converted to a character vector.

Usage

```
as.qe.unit(x)
```

Arguments

x A vector. The vector to be converted to 'qe.unit' class.

Value

The modified vector with the 'qe.unit' class.

Examples

```
vec <- factor(c("A", "B", "C"))
vec <- as.qe.unit(vec)
class(vec) # Should show 'qe.unit' along with other classes
```

| | |
|---------------|--------------|
| as_trajectory | <i>Title</i> |
|---------------|--------------|

Description

Title

Usage

```
as_trajectory(
  x,
  by = x$_function.params$conversation[1],
  model = c("AccumulatedTrajectory", "SeperateTrajectory"),
  ...
)
```

Arguments

| | |
|-------|-------|
| x | [TBD] |
| by | [TBD] |
| model | [TBD] |
| ... | [TBD] |

Value

[TBD]

| | |
|--------|------------------------|
| center | <i>Center ENA Data</i> |
|--------|------------------------|

Description

This function centers the line weights of an 'ena.set' by subtracting the mean of each connection from all units. This is a standard step in preparing data for rotation.

Usage

```
center(x, add.meta = TRUE)
```

Arguments

| | |
|----------|--|
| x | An 'ena.set' object (typically after 'sphere_norm()') or a numeric matrix. |
| add.meta | A logical value. If 'TRUE' (the default), metadata is preserved. Ignored if 'x' is a matrix. |

Value

If 'x' is an 'ena.set', it returns the modified 'ena.set' with the centered data stored in 'x\$model\$points.for.projection'.
If 'x' is a matrix, it returns a centered matrix.

Examples

```
data(RS.data)

codes <- c("Data", "Technical.Constraints", "Performance.Parameters",
          "Client.and.Consultant.Requests", "Design.Reasoning",
          "Collaboration")
units <- c("Condition", "UserName")
horizon <- c("Condition", "GroupName")
enaset <- RS.data |>
  accumulate(units, codes, horizon) |>
  sphere_norm() |>
  center()
```

| | |
|-------------|--|
| check_range | <i>Updates the axis ranges of an ENA plot based on the plotted data.</i> |
|-------------|--|

Description

This function adjusts the x and y axis ranges of the ENA plot to ensure that all plotted points, networks, and means are visible.

Usage

```
check_range(x)
```

Arguments

| | |
|---|---|
| x | An ENA plot object containing the plotted data and axis configurations. |
|---|---|

Value

The updated ENA plot object with adjusted axis ranges.

| | |
|-------|--|
| clear | <i>Clears specified plots from an ENA set.</i> |
|-------|--|

Description

This function removes the plots specified by their indices from the ‘plots’ field of the ENA set.

Usage

```
clear(x, wh = seq(x$plots))
```

Arguments

| | |
|----|--|
| x | An ENA set object containing the plots. |
| wh | A numeric vector specifying the indices of the plots to clear. Default is all plots. |

Value

Invisibly returns the modified ENA set object with the specified plots removed.

Examples

```
# Load test data
data(RS.data);

# Define codenames for the test
codenames <- c("Data", "Technical.Constraints", "Performance.Parameters",
  "Client.and.Consultant.Requests", "Design.Reasoning", "Collaboration");

# Standard ENA accumulation
accum <- rENA:::ena.accumulate.data.file(
  RS.data, units.by = c("UserName", "Condition"),
  conversations.by = c("ActivityNumber", "GroupName"),
  codes = codenames
);
# Create a standard ENA set
newset <- ena.make.set(accum);

# Simple plot for a set of points, and their mean
newplot <- plot(newset) |>
  add_points(Condition$FirstGame, mean = TRUE, colors = "blue") |>
  add_network();

# Plot a single unit's point and it's line.weights
plot(newset) |>
  add_points(UserName$`steven z`) |>
  add_network();

# Trajectory accumulation and plotting
```

```

trajectory_accumulation <- rENA:::ena.accumulate.data.file(
  RS.data, units.by = c("UserName", "Condition"),
  conversations.by = c("ActivityNumber", "GroupName"),
  codes = codenames,
  model = "A"
);
trajectory_model <- ena.make.set(trajectory_accumulation);

newplot3 <- plot(trajectory_model) |>
  add_trajectory(Condition$FirstGame);

```

| | |
|-------|--|
| codes | <i>Reclassify specified columns as codes or list codes columns in a data.table</i> |
|-------|--|

Description

This function reclassifies specified columns of a `data.table` to the 'qe.code' format if column names are provided. If no column names are provided, it returns the names of columns that are already classified as 'qe.code'.

Usage

```
codes(x, ...)
```

Arguments

| | |
|-----|---|
| x | A <code>data.table</code> . The <code>data.table</code> containing the columns to be reclassified or checked. |
| ... | Additional arguments specifying the names of the columns to be reclassified. |

Value

The modified `data.table` with specified columns reclassified as 'qe.code', or a character vector of column names already classified as 'qe.unit'.

Examples

```

library(data.table)
dt <- data.table(a = 1:5, b = 6:10)
# Reclassify columns 'a' and 'b' as 'qe.code'
dt <- codes(dt, "a", "b")
# List columns classified as 'qe.code'
code_columns <- codes(dt)

```

| | |
|----------|----------------------------|
| combn_c2 | <i>Fast combn choose 2</i> |
|----------|----------------------------|

Description

faster combn alternative

Usage

```
combn_c2(n)
```

Arguments

| | |
|---|-----|
| n | TBD |
|---|-----|

| | |
|------------|---|
| compute_SB | <i>Compute Between-Group Scatter Matrix</i> |
|------------|---|

Description

This function calculates the between-group scatter matrix (SB) for a given numeric matrix and grouping variable.

Usage

```
compute_SB(A, g)
```

Arguments

| | |
|---|--|
| A | A numeric matrix of dimensions $m \times n$, where rows represent observations and columns represent features. |
| g | A grouping variable of length m , either a factor or a character vector, indicating group membership for each observation. |

Details

The function computes the total mean of the matrix A and the mean for each group defined by g . It then calculates the between-group scatter matrix by summing the outer product of the mean differences, weighted by the group sizes.

Value

A numeric matrix representing the between-group scatter matrix (SB).

Examples

```
# Example usage:
A <- matrix(rnorm(20), nrow = 5, ncol = 4)
g <- factor(c("A", "B", "A", "B", "A"))
SB <- rENA:::compute_SB(A, g)
```

connection.matrix *Connection counts as square matrix*

Description

Connection counts as square matrix

Usage

```
connection.matrix(x)
```

Arguments

x ena.set or ena.connections (i.e. set\$connection.counts)

Value

matrix

define *Apply metadata and code transformations to a data.table*

Description

This function applies metadata and code transformations to a data.table if provided. It checks if the metadata and codes are supplied as vectors of column names.

Usage

```
define(
  x,
  metadata_cols = find_meta_cols(x),
  codes_cols = find_binary_cols(x),
  horizon_cols = NULL,
  units_cols = NULL
)
```

Arguments

| | |
|----------------------------|---|
| <code>x</code> | A <code>data.table</code> . The <code>data.table</code> to be transformed. |
| <code>metadata_cols</code> | A vector of column names or <code>NULL</code> . A vector specifying the columns for metadata transformations. |
| <code>codes_cols</code> | A vector of column names or <code>NULL</code> . A vector specifying the columns for code transformations. |
| <code>horizon_cols</code> | A vector of column names or <code>NULL</code> . A vector specifying the columns for horizon transformations. |
| <code>units_cols</code> | A vector of column names or <code>NULL</code> . A vector specifying the columns for unit transformations. |

Value

The modified `data.table` after applying the metadata and code transformations.

Examples

```
library(data.table)
dt <- data.table(a = 1:5, b = 6:10)
dt <- define(dt, metadata = c("a"), codes = c("b"))
```

directed_node_positions

Multiobjective, Component by Component, with Ellipsoidal Scaling, for directed ENA

Description

TBD

Usage

```
directed_node_positions(line_weights, points, numDims)
```

Arguments

| | |
|---------------------------|-----|
| <code>line_weights</code> | TBD |
| <code>points</code> | TBD |
| <code>numDims</code> | TBD |

Details

Multiobjective, Component by Component, with Ellipsoidal Scaling, for directed ENA

directed_node_positions_with_ground_response_added

Node position optimization with ground and response weights/points added

Description

TBD

Usage

```
directed_node_positions_with_ground_response_added(
  line_weights,
  points,
  numDims
)
```

Arguments

| | |
|--------------|-----|
| line_weights | TBD |
| points | TBD |
| numDims | TBD |

Details

Node position optimization with ground and response weights/points added

ena

Wrapper to generate, and optionally plot, an ENA model

Description

Generates an ENA model by constructing a dimensional reduction of adjacency (co-occurrence) vectors as defined by the supplied conversations, units, and codes.

Usage

```
ena(
  data,
  codes,
  units,
  conversation,
  metadata = NULL,
  model = c("EndPoint", "AccumulatedTrajectory", "SeparateTrajectory"),
  weight.by = "binary",
```

```

window = c("MovingStanzaWindow", "Conversation"),
window.size.back = 1,
include.meta = TRUE,
groupVar = NULL,
groups = NULL,
runTest = FALSE,
points = FALSE,
mean = FALSE,
network = TRUE,
networkMultiplier = 1,
subtractionMultiplier = 1,
unit = NULL,
include.plots = T,
print.plots = F,
...
)

```

Arguments

| | |
|-------------------------------|---|
| <code>data</code> | data.frame with containing metadata and coded columns |
| <code>codes</code> | vector, numeric or character, of columns with codes |
| <code>units</code> | vector, numeric or character, of columns representing units |
| <code>conversation</code> | vector, numeric or character, of columns to segment conversations by |
| <code>metadata</code> | vector, numeric or character, of columns with additional meta information for units |
| <code>model</code> | character: EndPoint (default), AccumulatedTrajectory, SeparateTrajectory |
| <code>weight.by</code> | "binary" is default, can supply a function to call (e.g. sum) |
| <code>window</code> | MovingStanzaWindow (default) or Conversation |
| <code>window.size.back</code> | Number of lines in the stanza window (default: 1) |
| <code>include.meta</code> | [TBD] |
| <code>groupVar</code> | vector, character, of column name containing group identifiers. If column contains at least two unique values, will generate model using a means rotation (a dimensional reduction maximizing the variance between the means of the two groups) |
| <code>groups</code> | vector, character, of values of groupVar column used for means rotation, plotting, or statistical tests |
| <code>runTest</code> | logical, TRUE will run a Student's t-Test and a Wilcoxon test for groups defined by the groups argument |
| <code>points</code> | logical, TRUE will plot points (default: FALSE) |
| <code>mean</code> | logical, TRUE will plot the mean position of the groups defined in the groups argument (default: FALSE) |
| <code>network</code> | logical, TRUE will plot networks (default: TRUE) |

```

networkMultiplier      numeric, scaling factor for non-subtracted networks (default: 1)
subtractionMultiplier  numeric, scaling factor for subtracted networks (default: 1)
unit                   vector, character, name of a single unit to plot
include.plots          logical, TRUE will generate plots based on the model (default: TRUE)
print.plots            logical, TRUE will show plots in the Viewer(default: FALSE)
...                    Additional parameters passed to set creation and plotting functions

```

Details

This function generates an `ena.set` object given a `data.frame`, units, conversations, and codes. After accumulating the adjacency (co-occurrence) vectors, computes a dimensional reduction (projection), and calculates node positions in the projected ENA space. Returns location of the units in the projected space, as well as locations for node positions, and normalized adjacency (co-occurrence) vectors to construct network graphs. Includes options for returning statistical tests between groups of units, as well as plots of units, groups, and networks.

Value

`ena.set` object

Examples

```

data(RS.data)

rs = ena(
  data = RS.data,
  units = c("UserName", "Condition", "GroupName"),
  conversation = c("Condition", "GroupName"),
  codes = c('Data',
            'Technical.Constraints',
            'Performance.Parameters',
            'Client.and.Consultant.Requests',
            'Design.Reasoning',
            'Collaboration'),
  window.size.back = 4,
  print.plots = FALSE,
  groupVar = "Condition",
  groups = c("FirstGame", "SecondGame")
)

```

ena.accumulate.data *Accumulate data from a data frame into a set of adjacency (co-occurrence) vectors*

Description

This function initializes an ENAdata object, processing conversations from coded data to generate adjacency (co-occurrence) vectors

Usage

```
ena.accumulate.data(
  units = NULL,
  conversation = NULL,
  codes = NULL,
  metadata = NULL,
  model = c("EndPoint", "AccumulatedTrajectory", "SeparateTrajectory"),
  weight.by = "binary",
  window = c("MovingStanzaWindow", "Conversation"),
  window.size.back = 1,
  window.size.forward = 0,
  mask = NULL,
  include.meta = T,
  as.list = T,
  ...
)
```

Arguments

| | |
|--------------|--|
| units | A data frame where the columns are the properties by which units will be identified |
| conversation | A data frame where the columns are the properties by which conversations will be identified |
| codes | A data frame where the columns are the codes used to create adjacency (co-occurrence) vectors |
| metadata | (optional) A data frame with additional columns of metadata to be associated with each unit in the data |
| model | A character, choices: EndPoint (or E), AccumulatedTrajectory (or A), or SeparateTrajectory (or S); default: EndPoint. Determines the ENA model to be constructed |
| weight.by | (optional) A function to apply to values after accumulation |
| window | A character, choices are Conversation (or C), MovingStanzaWindow (MSW, MS); default MovingStanzaWindow. Determines how stanzas are constructed, which defines how co-occurrences are modeled |

| | |
|----------------------------------|---|
| <code>window.size.back</code> | A positive integer, Inf, or character (INF or Infinite), default: 1. Determines, for each line in the data frame, the number of previous lines in a conversation to include in the stanza window, which defines how co-occurrences are modeled |
| <code>window.size.forward</code> | (optional) A positive integer, Inf, or character (INF or Infinite), default: 0. Determines, for each line in the data frame, the number of subsequent lines in a conversation to include in the stanza window, which defines how co-occurrences are modeled |
| <code>mask</code> | (optional) A binary matrix of size <code>ncol(codes) x ncol(codes)</code> . 0s in the mask matrix row <i>i</i> column <i>j</i> indicates that co-occurrence will not be modeled between code <i>i</i> and code <i>j</i> |
| <code>include.meta</code> | Logical indicating if unit metadata should be attached to the resulting ENAdata object, default is TRUE |
| <code>as.list</code> | R6 objects will be deprecated, but if this is TRUE, the original R6 object will be returned, otherwise a list with class 'ena.set' |
| <code>...</code> | additional parameters addressed in inner function |

Details

ENADdata objects are created using this function. This accumulation receives separate data frames for units, codes, conversation, and optionally, metadata. It iterates through the data to create an adjacency (co-occurrence) vector corresponding to each unit - or in a trajectory model multiple adjacency (co-occurrence) vectors for each unit.

In the default `MovingStanzaWindow` model, co-occurrences between codes are calculated for each line *k* in the data between line *k* and the `window.size.back-1` previous lines and `window.size.forward-1` subsequent lines in the same conversation as line *k*.

In the `Conversation` model, co-occurrences between codes are calculated across all lines in each conversation. Adjacency (co-occurrence) vectors are constructed for each unit *u* by summing the co-occurrences for the lines that correspond to *u*.

Options for how the data is accumulated are `endpoint`, which produces one adjacency (co-occurrence) vector for each until summing the co-occurrences for all lines, and two trajectory models: `AccumulatedTrajectory` and `SeparateTrajectory`. Trajectory models produce an adjacency (co-occurrence) model for each conversation for each unit. In a `SeparateTrajectory` model, each conversation is modeled as a separate network. In an `AccumulatedTrajectory` model, the adjacency (co-occurrence) vector for the current conversation includes the co-occurrences from all previous conversations in the data.

Value

ENADdata object with data [adjacency (co-occurrence) vectors] accumulated from the provided data frames.

See Also

[ENADdata](#), [ena.make.set](#)

ena.conversations *Find conversations by unit*

Description

Find rows of conversations by unit

Usage

```
ena.conversations(  
  set,  
  units,  
  units.by = NULL,  
  codes = NULL,  
  conversation.by = NULL,  
  window = 4,  
  conversation.exclude = c()  
)
```

Arguments

| | |
|----------------------|-------|
| set | [TBD] |
| units | [TBD] |
| units.by | [TBD] |
| codes | [TBD] |
| conversation.by | [TBD] |
| window | [TBD] |
| conversation.exclude | [TBD] |

Details

[TBD]

Value

list containing row indices representing conversations

Examples

```
data(RS.data)  
  
codeNames = c('Data', 'Technical.Constraints', 'Performance.Parameters',  
              'Client.and.Consultant.Requests', 'Design.Reasoning',  
              'Collaboration');
```

```

accum = ena.accumulate.data(
  units = RS.data[,c("Condition", "UserName")],
  conversation = RS.data[,c("Condition", "GroupName")],
  metadata = RS.data[,c("CONFIDENCE.Change", "CONFIDENCE.Pre",
    "CONFIDENCE.Post", "C.Change")],
  codes = RS.data[,codeNames],
  model = "EndPoint",
  window.size.back = 4
);
set = ena.make.set(
  enadata = accum,
  rotation.by = ena.rotate.by.mean,
  rotation.params = list(accum$meta.data$Condition=="FirstGame",
    accum$meta.data$Condition=="SecondGame")
);
ena.conversations(set = RS.data,
  units = c("FirstGame.steven z"), units.by=c("Condition", "UserName"),
  conversation.by = c("Condition", "GroupName"),
  codes=codeNames, window = 4
)

```

 ena.correlations

Calculate the correlations

Description

Calculate both Spearman and Pearson correlations for the provided ENAset

Usage

```
ena.correlations(enaset, dims = c(1:2))
```

Arguments

| | |
|--------|---|
| enaset | ENAset to run correlations on |
| dims | The dimensions to calculate the correlations for. Default: c(1,2) |

Value

Matrix of 2 columns, one for each correlation method, with the corresponding correlations per dimension as the rows.

| | |
|-----------|--|
| ena.group | <i>Compute summary statistic for groupings of units using given method (typically, mean)</i> |
|-----------|--|

Description

Computes summary statistics for groupings (given as vector) of units in ena data using given method (typically, mean); computes summary statistic for point locations and edge weights for each grouping

Usage

```
ena.group(
  enaset = NULL,
  by = NULL,
  method = mean,
  names = as.vector(unique(by))
)
```

Arguments

| | |
|--------|--|
| enaset | An ENASET or a vector of values to group. |
| by | A vector of values the same length as units. Uses rotated points for group positions and normed data to get the group edge weights |
| method | A function that is used on grouped points. Default: mean(). If 'enaset' is an ENASET, enaset\$points.rotated will be groups using 'mean' regardless of 'method' provided |
| names | A vector of names to use for the results. Default: unique(by) |

Value

A list containing names, points, and edge weights for each of the unique groups formed by the function

Examples

```
data(RS.data)

codeNames = c('Data', 'Technical.Constraints', 'Performance.Parameters',
  'Client.and.Consultant.Requests', 'Design.Reasoning', 'Collaboration');

accum = ena.accumulate.data(
  units = RS.data[,c("UserName", "Condition")],
  conversation = RS.data[,c("Condition", "GroupName")],
  metadata = RS.data[,c("CONFIDENCE.Change", "CONFIDENCE.Pre", "CONFIDENCE.Post")],
  codes = RS.data[,codeNames],
  window.size.back = 4
```

```

)

set = ena.make.set(
  enadata = accum
)

means = ena.group(set, "Condition")

```

ena.make.set

Generate ENA Set

Description

Generates an ENA model by constructing a dimensional reduction of adjacency (co-occurrence) vectors in an ENA data object

Usage

```

ena.make.set(
  enadata,
  dimensions = 2,
  norm.by = fun_sphere_norm,
  rotation.by = ena.svd,
  rotation.params = NULL,
  rotation.set = NULL,
  endpoints.only = TRUE,
  center.align.to.origin = TRUE,
  node.position.method = lws.positions.sq,
  as.list = TRUE,
  ...
)

```

Arguments

| | |
|-----------------|--|
| enadata | ENadata that will be used to generate an ENA model |
| dimensions | The number of dimensions to include in the dimensional reduction |
| norm.by | A function to be used to normalize adjacency (co-occurrence) vectors before computing the dimensional reduction, default: <code>sphere_norm_c()</code> |
| rotation.by | A function to be used to compute the dimensional reduction, default: <code>ena.svd()</code> |
| rotation.params | (optional) A character vector containing additional parameters for the function in <code>rotation.by</code> , if needed |
| rotation.set | A previously-constructed <code>ENARotationSet</code> object to use for the dimensional reduction |

| | |
|-------------------------------------|--|
| <code>endpoints.only</code> | A logical variable which determines whether to only show endpoints for trajectory models |
| <code>center.align.to.origin</code> | A logical variable when TRUE (default) determines aligns both point center and centroid center to the origin |
| <code>node.position.method</code> | A function to be used to determine node positions based on the dimensional reduction, default: <code>lws.position.es()</code> |
| <code>as.list</code> | R6 objects will be deprecated, but if this is TRUE, the original R6 object will be returned, otherwise a list with class 'ena.set' |
| <code>...</code> | additional parameters addressed in inner function |

Details

This function generates an ENAset object from an ENAdata object. Takes the adjacency (co-occurrence) vectors from enadata, computes a dimensional reduction (projection), and calculates node positions in the projected ENA space. Returns location of the units in the projected space, as well as locations for node positions, and normalized adjacency (co-occurrence) vectors to construct network graphs

Value

[ENAset](#) class object that can be further processed for analysis or plotting

See Also

[ena.accumulate.data](#), [ENAset](#)

Examples

```
data(RS.data)

codeNames = c('Data','Technical.Constraints','Performance.Parameters',
  'Client.and.Consultant.Requests','Design.Reasoning','Collaboration');

accum = ena.accumulate.data(
  units = RS.data[,c("UserName","Condition")],
  conversation = RS.data[,c("Condition","GroupName")],
  metadata = RS.data[,c("CONFIDENCE.Change","CONFIDENCE.Pre","CONFIDENCE.Post")],
  codes = RS.data[,codeNames],
  window.size.back = 4
)

set = ena.make.set(
  enadata = accum
)

set.means.rotated = ena.make.set(
  enadata = accum,
  rotation.by = ena.rotate.by.mean,
```

```

rotation.params = list(
  accum$meta.data$Condition=="FirstGame",
  accum$meta.data$Condition=="SecondGame"
)
)

```

ena.plot

Generate a plot of an ENAset

Description

Generates an a plot from a given ENA set object

Usage

```

ena.plot(
  enaset,
  title = "ENA Plot",
  dimension.labels = c("", ""),
  font.size = 10,
  font.color = "#000000",
  font.family = c("Arial", "Courier New", "Times New Roman"),
  scale.to = "network",
  ...
)

```

Arguments

| | |
|------------------|---|
| enaset | The ENASET that will be used to generate a plot |
| title | A character used for the title of the plot, default: ENA Plot |
| dimension.labels | A character vector containing labels for the axes, default: c(X, Y) |
| font.size | An integer determining the font size for graph labels, default: 10 |
| font.color | A character determining the color of label font, default: black |
| font.family | A character determining the font type, choices: Arial, Courier New, Times New Roman, default: Arial |
| scale.to | "network" (default), "points", or a list with x and y ranges. Network and points both scale to the c(-max, max) of the corresponding data.frame |
| ... | additional parameters addressed in inner function |

Details

This function defines the axes and other features of a plot for displaying an ENASET; generates an ENAplot object that can used to plot points, network graphs, and other information from an ENASET

Value

[ENApplot](#) used for plotting an ENAset

See Also

[ena.make.set](#), [ena.plot.points](#)

Examples

```
data(RS.data)

codeNames = c('Data', 'Technical.Constraints', 'Performance.Parameters',
  'Client.and.Consultant.Requests', 'Design.Reasoning', 'Collaboration');

accum = ena.accumulate.data(
  units = RS.data[,c("UserName", "Condition")],
  conversation = RS.data[,c("Condition", "GroupName")],
  metadata = RS.data[,c("CONFIDENCE.Change", "CONFIDENCE.Pre", "CONFIDENCE.Post")],
  codes = RS.data[,codeNames],
  window.size.back = 4
)

set = ena.make.set(
  enadata = accum
)

plot = ena.plot(set)

group1.points = set$points.rotated[set$enadata$units$Condition == "FirstGame",]
plot = ena.plot.points(plot, points = group1.points);
print(plot);
```

ena.plot.group

Plot of ENA set groups

Description

Plot a point based on a summary statistic computed from a given method (typically, mean) for a set of points in a projected ENA space

Usage

```
ena.plot.group(
  enaplot,
  points = NULL,
  method = "mean",
  labels = NULL,
  colors = default.colors[1],
```

```

shape = c("square", "triangle-up", "diamond", "circle"),
confidence.interval = c("none", "crosshairs", "box"),
outlier.interval = c("none", "crosshairs", "box"),
label.offset = "bottom right",
label.font.size = NULL,
label.font.color = NULL,
label.font.family = NULL,
show.legend = T,
legend.name = NULL,
...
)

```

Arguments

| | |
|---------------------|--|
| enaplot | ENApplot object to use for plotting |
| points | A matrix or data.frame where columns contain coordinates of points in a projected ENA space |
| method | A function for computing a summary statistic for each column of points |
| labels | A character which will be the label for the group's point |
| colors | A character, determines color of the group's point, default: enaplot\$color |
| shape | A character, determines shape of the group's point, choices: square, triangle, diamond, circle, default: square |
| confidence.interval | A character that determines how the confidence interval is displayed, choices: none, box, crosshair, default: none |
| outlier.interval | A character that determines how outlier interval is displayed, choices: none, box, crosshair, default: none |
| label.offset | character: top left (default), top center, top right, middle left, middle center, middle right, bottom left, bottom center, bottom right |
| label.font.size | An integer which determines the font size for label, default: enaplot\$font.size |
| label.font.color | A character which determines the color of label, default: enaplot\$font.color |
| label.font.family | A character which determines font type, choices: Arial, Courier New, Times New Roman, default: enaplot\$font.family |
| show.legend | Logical indicating whether to show the point labels in the in legend |
| legend.name | Character indicating the name to show above the plot legend |
| ... | Additional parameters |

Details

Plots a point based on a summary statistic for a group (typically, mean)

Value

The `ENApplot` provided to the function, with its plot updated to include the new group point.

See Also

`ena.plot`, `ena.plot.points`

Examples

```

data(RS.data)

codeNames = c('Data', 'Technical.Constraints', 'Performance.Parameters',
              'Client.and.Consultant.Requests', 'Design.Reasoning', 'Collaboration');

accum = ena.accumulate.data(
  units = RS.data[,c("UserName", "Condition")],
  conversation = RS.data[,c("Condition", "GroupName")],
  metadata = RS.data[,c("CONFIDENCE.Change", "CONFIDENCE.Pre", "CONFIDENCE.Post")],
  codes = RS.data[,codeNames],
  window.size.back = 4
)

set = ena.make.set(
  enadata = accum,
  rotation.by = ena.rotate.by.mean,
  rotation.params = list(
    accum$meta.data$Condition=="FirstGame",
    accum$meta.data$Condition=="SecondGame"
  )
)

plot = ena.plot(set)

unitNames = set$enadata$units

### Plot Condition 1 Group Mean
plot = ena.plot.group(plot, as.matrix(set$points$Condition$FirstGame), labels = "FirstGame",
  colors = "red", confidence.interval = "box")

### plot Condition 2 Group Mean
plot = ena.plot.group(plot, as.matrix(set$points$Condition$SecondGame), labels = "SecondGame",
  colors = "blue", confidence.interval = "box")

print(plot);

```

Description

Plot an ENA network: nodes and edges

Usage

```
ena.plot.network(
  enaplot = NULL,
  network = NULL,
  node.positions = enaplot$enaset$rotation$nodes,
  adjacency.key = NULL,
  colors = c(pos = enaplot$palette[1], enaplot$palette[2]),
  edge_type = "line",
  show.all.nodes = T,
  threshold = c(0),
  thin.lines.in.front = T,
  layers = c("nodes", "edges"),
  thickness = c(min(abs(network)), max(abs(network))),
  opacity = thickness,
  saturation = thickness,
  scale.range = c(ifelse(min(network) == 0, 0, 0.1), 1),
  node.size = c(3, 10),
  labels = NULL,
  label.offset = "middle right",
  label.font.size = enaplot$get("font.size"),
  label.font.color = enaplot$get("font.color"),
  label.font.family = enaplot$get("font.family"),
  legend.name = NULL,
  legend.include.edges = F,
  scale.weights = F,
  ...
)
```

Arguments

| | |
|----------------|---|
| enaplot | ENApplot object to use for plotting |
| network | dataframe or matrix containing the edge weights for the network graph; typically comes from ENAset\$line.weights |
| node.positions | matrix containing the positions of the nodes. Defaults to enaplot\$enaset\$node.positions |
| adjacency.key | matrix containing the adjacency key for looking up the names and positions |
| colors | A String or vector of colors for positive and negative line weights. E.g. red or c(pos= red, neg = blue), default: c(pos= red, neg = blue) |
| edge_type | A String representing the type of line to draw, either "line", "dash", or "dot" |
| show.all.nodes | A Logical variable, default: true |
| threshold | A vector of numeric min/max values, default: c(0,Inf) plotting . Edge weights below the min value will not be displayed; edge weights above the max value will be shown at the max value. |

| | |
|----------------------|--|
| thin.lines.in.front | A logical, default: true |
| layers | ordering of layers, default: c("nodes", "edges") |
| thickness | A vector of numeric min/max values for thickness, default: c(min(abs(network)), max(abs(network))) |
| opacity | A vector of numeric min/max values for opacity, default: thickness |
| saturation | A vector of numeric min/max values for saturation, default: thickness |
| scale.range | A vector of numeric min/max to scale from, default: c(0.1,1) or if min(network) is 0, c(0,1) |
| node.size | A lower and upper bound used for scaling the size of the nodes, default c(0, 20) |
| labels | A character vector of node labels, default: code names |
| label.offset | A character vector of representing the positional offset relative to the respective node. Defaults to "middle right" for all nodes. If a single values is provided, it is used for all positions, else the length of the |
| label.font.size | An integer which determines the font size for graph labels, default: enaplot\$font.size |
| label.font.color | A character which determines the color of label font, default: enaplot\$font.color |
| label.font.family | A character which determines font type, choices: Arial, Courier New, Times New Roman, default: enaplot\$font.family |
| legend.name | A character name used in the plot legend. Not included in legend when NULL (Default), if legend.include.edges is TRUE will always be "Nodes" |
| legend.include.edges | Logical value indicating if the edge names should be included in the plot legend. Forces legend.name to be "Nodes" |
| scale.weights | Logical indicating to scale the supplied network |
| ... | Additional parameters |

Details

lots a network graph, including nodes (taken from codes in the ENAplot) and the edges (provided in network)

Value

The ENAplot provided to the function, with its plot updated to include the nodes and provided connecting lines.

See Also

[ena.plot](#), [ena.plot.points](#)

Examples

```

data(RS.data)

codeNames = c('Data','Technical.Constraints','Performance.Parameters',
  'Client.and.Consultant.Requests','Design.Reasoning','Collaboration');

accum = ena.accumulate.data(
  units = RS.data[,c("UserName","Condition")],
  conversation = RS.data[,c("Condition","GroupName")],
  metadata = RS.data[,c("CONFIDENCE.Change","CONFIDENCE.Pre","CONFIDENCE.Post")],
  codes = RS.data[,codeNames],
  window.size.back = 4
)

set = ena.make.set(
  enadata = accum,
  rotation.by = ena.rotate.by.mean,
  rotation.params = list(
    accum$meta.data$Condition=="FirstGame",
    accum$meta.data$Condition=="SecondGame"
  )
)

plot = ena.plot(set)

### Subset rotated points and plot Condition 1 Group Mean
as.matrix(set$points$Condition$FirstGame)

first.game.points = as.matrix(set$points$Condition$FirstGame)
plot = ena.plot.group(plot, first.game.points, labels = "FirstGame",
  colors = "red", confidence.interval = "box")

### Subset rotated points and plot Condition 2 Group Mean
second.game.points = as.matrix(set$points$Condition$SecondGame)
plot = ena.plot.group(plot, second.game.points, labels = "SecondGame",
  colors = "blue", confidence.interval = "box")

### get mean network plots
first.game.lineweights = as.matrix(set$line.weights$Condition$FirstGame)
first.game.mean = colMeans(first.game.lineweights)

second.game.lineweights = as.matrix(set$line.weights$Condition$SecondGame)
second.game.mean = colMeans(second.game.lineweights)

subtracted.network = first.game.mean - second.game.mean
plot = ena.plot.network(plot, network = subtracted.network)
print(plot)

```

Description

Plot all or a subset of the points of an ENAplot using the plotly plotting library

Usage

```
ena.plot.points(
  enaplot,
  points = NULL,
  point.size = enaplot$point.size,
  labels = NULL,
  label.offset = "top left",
  label.group = NULL,
  label.font.size = NULL,
  label.font.color = NULL,
  label.font.family = NULL,
  shape = "circle",
  colors = NULL,
  confidence.interval.values = NULL,
  confidence.interval = c("none", "crosshairs", "box"),
  outlier.interval.values = NULL,
  outlier.interval = c("none", "crosshairs", "box"),
  show.legend = T,
  legend.name = "Points",
  texts = NULL,
  ...
)
```

Arguments

| | |
|-------------------|--|
| enaplot | ENApplot object to use for plotting |
| points | A dataframe of matrix where the first two column are X and Y coordinates |
| point.size | A data.frame or matrix where the first two column are X and Y coordinates of points to plot in a projected ENA space defined in ENAplot |
| labels | A character vector of point labels, length nrow(points); default: NULL |
| label.offset | character: top left (default), top center, top right, middle left, middle center, middle right, bottom left, bottom center, bottom right |
| label.group | A string used to group the labels in the legend. Items plotted with the same label.group will show/hide together when clicked within the legend. |
| label.font.size | An integer which determines the font size for point labels, default: enaplot\$font.size |
| label.font.color | A character which determines the color of label font, default: enaplot\$font.color |
| label.font.family | A character which determines label font type, choices: Arial, Courier New, Times New Roman, default: enaplot\$font.family |

| | |
|----------------------------|---|
| shape | A character which determines the shape of point markers, choices: square, triangle, diamond, circle, default: circle |
| colors | A character vector of the point marker colors; if one given it is used for all, otherwise must be same length as points; default: black |
| confidence.interval.values | A matrix/dataframe where columns are CI x and y values for each point |
| confidence.interval | A character determining markings to use for confidence intervals, choices: none, box, crosshair, default: none |
| outlier.interval.values | A matrix/dataframe where columns are OI x and y values for each point |
| outlier.interval | A character determining markings to use for outlier interval, choices: none, box, crosshair, default: none |
| show.legend | Logical indicating whether to show the point labels in the in legend |
| legend.name | Character indicating the name to show above the plot legend |
| texts | [TBD] |
| ... | additional parameters addressed in inner function |

Value

[ENApplot](#) The ENApplot provided to the function, with its plot updated to include the new points.

See Also

[ena.plot](#), [ENApplot](#), [ena.plot.group](#)

Examples

```

data(RS.data)

codeNames = c('Data','Technical.Constraints','Performance.Parameters',
              'Client.and.Consultant.Requests','Design.Reasoning','Collaboration');

accum = ena.accumulate.data(
  units = RS.data[,c("UserName","Condition")],
  conversation = RS.data[,c("Condition","GroupName")],
  metadata = RS.data[,c("CONFIDENCE.Change","CONFIDENCE.Pre","CONFIDENCE.Post")],
  codes = RS.data[,codeNames],
  window.size.back = 4
)

set = ena.make.set(
  enadata = accum,
  rotation.by = ena.rotate.by.mean,
  rotation.params = list(
    accum$meta.data$Condition=="FirstGame",
    accum$meta.data$Condition=="SecondGame"
  )
)

```

```

    )
  )

  plot = ena.plot(set)

  group1.points = set$points[set$meta.data$Condition == "FirstGame",]
  group2.points = set$points[set$meta.data$Condition == "SecondGame",]
  plot = ena.plot.points(plot, points = group1.points);
  plot = ena.plot.points(plot, points = group2.points);
  print(plot);

```

ena.plot.trajectory *Plot of ENA trajectories*

Description

Function used to plot trajectories

Usage

```

ena.plot.trajectory(
  enaplot,
  points,
  by = NULL,
  labels = NULL,
  labels.show = c("Always", "Hover", "Both"),
  names = NULL,
  label.offset = NULL,
  label.font.size = enaplot$get("font.size"),
  label.font.color = enaplot$get("font.color"),
  label.font.family = c("Arial", "Courier New", "Times New Roman"),
  shape = c("circle", "square", "triangle-up", "diamond"),
  colors = NULL,
  default.hidden = F
)

```

Arguments

| | |
|-------------|---|
| enaplot | ENApplot object to use for plotting |
| points | dataframe of matrix - first two column are X and Y coordinates, each row is a point in a trajectory |
| by | vector used to subset points into individual trajectories, length nrow(points) |
| labels | character vector - point labels, length nrow(points) |
| labels.show | A character choice: Always, Hover, Both. Default: Both |
| names | character vector - labels for each trajectory of points, length length(unique(by)) |

| | |
|-------------------|---|
| label.offset | A numeric vector of an x and y value to offset labels from the coordinates of the points |
| label.font.size | An integer which determines the font size for labels, default: enaplot\$font.size |
| label.font.color | A character which determines the color of label font, default: enaplot\$font.color |
| label.font.family | A character which determines font type, choices: Arial, Courier New, Times New Roman, default: enaplot\$font.family |
| shape | A character which determines the shape of markers, choices: square, triangle, diamond, circle, default: circle |
| colors | A character vector, that determines marker color, default NULL results in alternating random colors. If single color is supplied, it will be used for all trajectories, otherwise the length of the supplied color vector should be equal to the length of the supplied names (i.e a color for each trajectory being plotted) |
| default.hidden | A logical indicating if the trajectories should start hidden (click on the legend to show them) Default: FALSE |

Value

The `ENApplot` provided to the function, with its plot updated to include the trajectories

See Also

[ena.plot](#)

Examples

```

data(RS.data)

codeNames = c('Data', 'Technical.Constraints', 'Performance.Parameters',
              'Client.and.Consultant.Requests', 'Design.Reasoning', 'Collaboration');

accum = ena.accumulate.data(
  units = RS.data[,c("UserName", "Condition")],
  conversation = RS.data[,c("GroupName", "ActivityNumber")],
  metadata = RS.data[,c("CONFIDENCE.Change", "CONFIDENCE.Pre", "CONFIDENCE.Post", "C.Change")],
  codes = RS.data[,codeNames],
  window.size.back = 4,
  model = "A"
);

set = ena.make.set(accum);

### get mean network plots
first.game.lineweights = as.matrix(set$line.weights$Condition$FirstGame)
first.game.mean = colMeans(first.game.lineweights)

second.game.lineweights = as.matrix(set$line.weights$Condition$SecondGame)

```

```

second.game.mean = colMeans(second.game.lineweights)

subtracted.network = first.game.mean - second.game.mean

# Plot dimension 1 against ActivityNumber metadata
dim.by.activity = cbind(
  as.matrix(set$points)[,1],
  set$trajectories$ActivityNumber * .8/14-.4 #scale down to dimension 1
)

plot = ena.plot(set)
plot = ena.plot.network(plot, network = subtracted.network, legend.name="Network")
plot = ena.plot.trajectory(
  plot,
  points = dim.by.activity,
  names = unique(set$model$unit.label),
  by = set$trajectories$ENA_UNIT
);
print(plot)

```

ena.plotter

Wrapper to generate plots of units, groups, and networks

Description

Plots individual units, all units, groups of units, networks, and network subtractions

Usage

```

ena.plotter(
  set,
  groupVar = NULL,
  groups = NULL,
  points = FALSE,
  mean = FALSE,
  network = TRUE,
  networkMultiplier = 1,
  subtractionMultiplier = 1,
  unit = NULL,
  print.plots = F,
  ...
)

```

Arguments

| | |
|----------|---|
| set | an ena.set object |
| groupVar | vector, character, of column name containing group identifiers. |

| | |
|-----------------------|---|
| groups | vector, character, of values of groupVar column you wish to plot. Maxium of two groups allowed. |
| points | logical, TRUE will plot points (default: FALSE) |
| mean | logical, TRUE will plot the mean position of the groups defined in the groups argument (default: FALSE) |
| network | logical, TRUE will plot networks (default: TRUE) |
| networkMultiplier | numeric, scaling factor for non-subtracted networks (default: 1) |
| subtractionMultiplier | numeric, scaling factor for subtracted networks (default: 1) |
| unit | vector, character, name of a single unit to plot |
| print.plots | logical, TRUE will show plots in the Viewer (default: FALSE) |
| ... | Additional parameters passed to set creation and plotting functions |

Details

This function includes options to plots individual units, all units, groups of units, networks, and network subtractions, given an ena.set objects. Plots are stored on the supplied ena.set object.

Value

ena.set object

ena.rotate.by.generalized

ENA Rotate by generalized means rotation (gmr)

Description

ENA Rotate by generalized means rotation (gmr)

Usage

```
ena.rotate.by.generalized(enaset, params)
```

Arguments

| | |
|--------|---|
| enaset | An ENAsset |
| params | list of parameters, may include: x_var: data.frame used for calling gmr() on the first dimension y_var: data.frame used for calling gmr() on the second dimension (optional). |

Value

[ENARotationSet](#)

```
ena.rotate.by.hena.regression
      ENA Rotate by regression
```

Description

This function allows user to provide a regression formula for rotation on x and optionally on y. If regression formula for y is not provide, svd is applied to the residual data deflated by x to get y coordinates. The regression formula uses ENA dimensions are dependent variables. The first predictor has to be two-group categorical, binary, or numerical.

Usage

```
ena.rotate.by.hena.regression(enaset, params)
```

Arguments

| | |
|--------|---|
| enaset | An ENASET |
| params | list of parameters, may include: x_var: Regression formula for x direction, such as "lm(formula=V ~ Condition + GameHalf + Condition : GameHalf)", where V always stands for the ENA points. y_var: Regression formula, similar to x_var, for y direction (optional). |

Value

[ENARotationSet](#)

```
ena.rotate.by.hena.regression_2
      ENA Rotate by regression (second way)
```

Description

This function allows user to provide a regression formula for rotation on x and optionally on y. If regression formula for y is not provide, svd is applied to the residual data deflated by x to get y coordinates. The regression formula should use ENA points as major predictors and a binary or numerical variable as dependent variable. Control and interaction variables are allowed to be included as predictors in the formula.

Usage

```
ena.rotate.by.hena.regression_2(enaset, params)
```

Arguments

| | |
|--------|---|
| enaset | An ENASET |
| params | list of parameters, may include: x_var: Regression formula for x direction, such as "lm(formula= Condition ~ V + GameHalf + Condition : GameHalf)", where V always stands for the ENA points. y_var: Regression formula, similar to x_var for y direction (optional). |

Value

[ENARotationSet](#)

ena.rotate.by.mean *ENA Rotate by mean*

Description

Computes a dimensional reduction from a matrix of points such that the first dimension of the projected space passes through the means of two groups in the original space. Subsequent dimensions of the projected space are computed using `ena.svd`

Usage

```
ena.rotate.by.mean(enaset, groups = NULL, params = groups)
```

Arguments

| | |
|--------|--|
| enaset | An ENASET |
| groups | A list containing two logical vectors of length <code>nrow(ENA.set\$ena.data\$units)</code> , where each vector defines whether a unit is in one of the two groups whose means are used to determine the dimensional reduction |
| params | A list containing two vectors of length <code>nrow(ENA.set\$ena.data\$units)</code> , |

Value

[ENARotationSet](#)

| | |
|----------------|------------------------------|
| ena.rotation.h | <i>hENA rotation for ENA</i> |
|----------------|------------------------------|

Description

hENA rotation function.

Usage

```
ena.rotation.h(enaset, params)
```

Arguments

| | |
|--------|--------------------|
| enaset | ena set |
| params | list of parameters |

Value

ena set

| | |
|-----------------|---|
| ena.set.creator | <i>Wrapper to generate an ENA model</i> |
|-----------------|---|

Description

Generates an ENA model by constructing a dimensional reduction of adjacency (co-occurrence) vectors as defined by the supplied conversations, units, and codes.

Usage

```
ena.set.creator(
  data,
  codes,
  units,
  conversation,
  metadata = NULL,
  model = c("EndPoint", "AccumulatedTrajectory", "SeparateTrajectory"),
  weight.by = "binary",
  window = c("MovingStanzaWindow", "Conversation"),
  window.size.back = 1,
  include.meta = TRUE,
  groupVar = NULL,
  groups = NULL,
  runTest = FALSE,
  ...
)
```

Arguments

| | |
|-------------------------------|---|
| <code>data</code> | data.frame with containing metadata and coded columns |
| <code>codes</code> | vector, numeric or character, of columns with codes |
| <code>units</code> | vector, numeric or character, of columns representing units |
| <code>conversation</code> | vector, numeric or character, of columns to segment conversations by |
| <code>metadata</code> | vector, numeric or character, of columns with additional meta information for units |
| <code>model</code> | character: EndPoint (default), AccumulatedTrajectory, SeparateTrajectory |
| <code>weight.by</code> | "binary" is default, can supply a function to call (e.g. sum) |
| <code>window</code> | MovingStanzaWindow (default) or Conversation |
| <code>window.size.back</code> | Number of lines in the stanza window (default: 1) |
| <code>include.meta</code> | [TBD] |
| <code>groupVar</code> | vector, character, of column name containing group identifiers. If column contains at least two unique values, will generate model using a means rotation (a dimensional reduction maximizing the variance between the means of the two groups) |
| <code>groups</code> | vector, character, of values of groupVar column used for means rotation or statistical tests |
| <code>runTest</code> | logical, TRUE will run a Student's t-Test and a Wilcoxon test for groups defined by the groups argument |
| <code>...</code> | Additional parameters passed to model generation |

Details

This function generates an ena.set object given a data.frame, units, conversations, and codes. After accumulating the adjacency (co-occurrence) vectors, computes a dimensional reduction (projection), and calculates node positions in the projected ENA space. Returns location of the units in the projected space, as well as locations for node positions, and normalized adjacency (co-occurrence) vectors to construct network graphs. Includes options for returning statistical tests between groups of units.

Value

ena.set object

| | |
|---------|----------------|
| ena.svd | <i>ENA SVD</i> |
|---------|----------------|

Description

Computes a dimensional reduction of points in an ENA set using Singular Value Decomposition (SVD).

Usage

```
ena.svd(enaset, params)
```

Arguments

| | |
|--------|---|
| enaset | An ENAset object containing the points to be reduced. |
| params | A list of parameters. Use <code>params\$as_object = TRUE</code> to return an ENARotationSet object, or <code>FALSE</code> (default) to return a list. |

Details

This function computes the SVD of the points in the ENA set and returns either an ENARotationSet object or a list with the rotation matrix, codes, node positions, and eigenvalues, depending on `params$as_object`.

Value

An ENARotationSet object or a list containing:

| | |
|----------------|--|
| rotation | The rotation matrix from SVD |
| codes | The code names used for the matrix |
| node.positions | (Currently NULL) Node positions |
| eigenvalues | The eigenvalues (squared singular values) from SVD |

Examples

```
data(RS.data)
codes <- c("Data", "Technical.Constraints", "Performance.Parameters",
           "Client.and.Consultant.Requests", "Design.Reasoning",
           "Collaboration")
units <- c("Condition", "UserName")
horizon <- c("Condition", "GroupName")
enaset <- RS.data |>
  accumulate(units, codes, horizon) |>
  model()
# SVD as list:
svd_result <- ena.svd(enaset, list(as_object = FALSE))
# SVD as ENARotationSet object:
svd_obj <- ena.svd(enaset, list(as_object = TRUE))
```

 ena.writeup

Calculate the correlations

Description

Calculate both Spearman and Pearson correlations for the provided ENAset

Usage

```
ena.writeup(
  enaset,
  tool = "rENA",
  tool.version = as.character(packageVersion(tool)),
  comparison = NULL,
  comparison.groups = NULL,
  sig.dig = 2,
  output_dir = getwd(),
  type = c("file", "stream"),
  theory = T,
  methods = T,
  params = NULL,
  output_file = NULL,
  output_format = NULL
)
```

Arguments

| | |
|-------------------|--|
| enaset | ENAset to view methods of |
| tool | c("rENA","webENA") |
| tool.version | as.character(packageVersion(tool)) |
| comparison | character string representing the comparison used, c(NULL, "parametric", "non-parametric"). Default NULL |
| comparison.groups | Groups that were used for the comparison |
| sig.dig | Integer for the number of digits to round to |
| output_dir | Where to save the output file |
| type | c("file","stream") File will save to a file in output_dir, Stream returns the contents directly |
| theory | Logical indicating whether to include theory in the writeup |
| methods | Logical indicating whether to include methods in the writeup |
| params | additional parameters for rmarkdown::render |
| output_file | character |
| output_format | character |

Value

String representing the methods used to generate the model

 ENAdata

ENAdata R6class

Description

ENAdata R6class

ENAdata R6class

Public fields

`raw` A data frame constructed from the unit, convo, code, and metadata parameters of `ena.accumulate.data`

`adjacency.vectors` A data frame of adjacency (co-occurrence) vectors by row

`accumulated.adjacency.vectors` A data frame of adjacency (co-occurrence) vectors accumulated per unit

`model` The type of ENA model: EndPoint, Accumulated Trajectory, or Separate Trajectory

`units` A data frame of columns that were combined to make the unique units. Includes column for trajectory selections. (unique)

`unit.names` A vector of unique unit values

`metadata` A data frame of unique metadata for each unit

`trajectories` A list: units - data frame, for a given row tells which trajectory it's a part; step - data frame, where along the trajectory a row sits

`adjacency.matrix` TBD

`adjacency.vectors.raw` TBD

`codes` A vector of code names

`function.call` The string representation of function called and parameters provided

`function.params` A list of all parameters sent to function call Construct ENAdata

Methods**Public methods:**

- [ENAdata\\$new\(\)](#)
- [ENAdata\\$process\(\)](#)
- [ENAdata\\$get\(\)](#)
- [ENAdata\\$add.metadata\(\)](#)
- [ENAdata\\$clone\(\)](#)

Method `new()`:

Usage:

```
ENadata$new(  
  file,  
  units = NULL,  
  units.used = NULL,  
  units.by = NULL,  
  conversations.by = NULL,  
  codes = NULL,  
  model = NULL,  
  weight.by = "binary",  
  window.size.back = 1,  
  window.size.forward = 0,  
  mask = NULL,  
  include.meta = T,  
  ...  
)
```

Arguments:

file TBD
units TBD
units.used TBD
units.by TBD
conversations.by TBD
codes TBD
model TBD
weight.by TBD
window.size.back TBD
window.size.forward TBD
mask TBD
include.meta TBD
... TBD

Returns: Process accumulation

Method process():

Usage:

```
ENadata$process()
```

Returns: ENadata Get property from object

Method get():

Usage:

```
ENadata$get(x = "data")
```

Arguments:

x character key to retrieve from object

Returns: value from object at x Add metadata

Method add.metadata():

Usage:

```
ENadata$add.metadata(merge = F)
```

Arguments:

```
merge logical (default: FALSE)
```

Returns: data.frame

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
ENadata$clone(deep = FALSE)
```

Arguments:

```
deep Whether to make a deep clone.
```

ENApLOT

*ENApLOT Class***Description**

The ENApLOT R6 class provides a structure for visualizing ENAset objects using plotly. It encapsulates the ENAset data, the plotly visualization, and related plotting parameters.

Fields

enaset The [ENAset](#) object from which the ENApLOT was constructed.

plot The plotly object used for data visualization.

axes Axes information for the plot (TBD).

point Point information for the plot (TBD).

palette Color palette used for plotting (TBD).

plotted Indicates whether the plot has been rendered (TBD).

Public fields

`enaset` - The [ENAset](#) object from which the ENApLOT was constructed

`plot` - The plotly object used for data visualization

`axes` A list or object specifying the axes configuration for the ENA plot, such as axis labels, limits, or scaling.

`point` A structure representing the data points to be plotted, including coordinates and visual properties.

`palette` A set of colors or a function defining the color scheme used for plotting elements in the ENA plot.

`plotted` A logical or status indicator showing whether the plot has been rendered or updated.

`showticklabels` Logical. Indicates whether to show tick labels on the axes.

`autosize` Logical. Indicates whether the plot should automatically resize.

`automargin` Logical. Indicates whether the plot should automatically adjust margins.

`axispadding` Numeric. Padding factor for the axes. Create ENApLOT

Methods**Public methods:**

- ENApplot\$new()
- ENApplot\$print()
- ENApplot\$get()
- ENApplot\$clone()

Method new():*Usage:*

```
ENApplot$new(
  enaset = NULL,
  title = "ENA Plot",
  dimension.labels = c("", ""),
  font.size = 14,
  font.color = "#000000",
  font.family = "Arial",
  scale.to = "network",
  ...
)
```

Arguments:

`enaset` An ENA set object containing the data to be plotted.

`title` The title of the plot.

`dimension.labels` Labels for the dimensions shown in the plot.

`font.size` Numeric value specifying the font size for plot text.

`font.color` Color value for the plot text.

`font.family` Font family to use for plot text.

`scale.to` Numeric value to scale the plot axes.

`...` Additional arguments passed to the plotting function. #'

`showticklabels` Logical; whether to display axis tick labels.

`autosize` Logical; whether the plot should automatically size itself.

`automargin` Logical; whether the plot should automatically adjust margins.

`axispadding` Numeric value specifying padding around axes.

Returns: ENApplot Print ENA plot

Method print():*Usage:*

```
ENApplot$print()
```

Returns: Get property from object

Method get():*Usage:*

```
ENApplot$get(x)
```

Arguments:

x character key to retrieve from object

Returns: value from object at x

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
ENAp1ot$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Examples

```
# Example usage:
# enaplot <- ENAp1ot$new(enaset = myENaset)
```

| | |
|----------------|-------------------------------|
| ENARotationSet | <i>ENARotationSet R6class</i> |
|----------------|-------------------------------|

Description

ENARotationSet R6class

ENARotationSet R6class

Public fields

rotation TBD

node.positions TBD

codes TBD

eigenvalues TBD Create ENARotationSet

Methods

Public methods:

- [ENARotationSet\\$new\(\)](#)
- [ENARotationSet\\$clone\(\)](#)

Method new():

Usage:

```
ENARotationSet$new(rotation, codes, node.positions, eigenvalues = NULL)
```

Arguments:

rotation TBD

codes TBD

node.positions TBD

eigenvalues TBD

Returns: ENARotationsSet

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
ENARotationSet$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

ENASET

ENASET R6class

Description

ENASET R6class

ENASET R6class

Public fields

enadata An [ENADATA](#) object originally used to create the set

points.raw A data frame containing accumulated adjacency (co-occurrence) vectors per unit

points.normed.centered A data frame of centered normed accumulated adjacency (co-occurrence) vectors for each unit

points.rotated A data frame of point positions for number of dimensions specified in ena.make.set (i.e., the centered, normed, and rotated data)

line.weights A data frame of connections strengths per unit (Data frame of normed accumulated adjacency (co-occurrence) vectors for each unit)

node.positions - A data frame of positions for each code

codes - A vector of code names

rotation.set - An [ENARotationSet](#) object

variance - A vector of variance accounted for by each dimension specified

centroids - A matrix of the calculated centroid positions

function.call - The string representation of function called

function.params - A list of all parameters sent to function call

rotation_dists TBD

points.rotated.scaled TBD

points.rotated.non.zero TBD

line.weights.unrotated TBD

line.weights.non.zero TBD

correlations A data frame of spearman and pearson correlations for each dimension specified

center.align.to.origin - align point and centroid centers to origin Create ENASET

Methods**Public methods:**

- [ENASET\\$new\(\)](#)
- [ENASET\\$process\(\)](#)
- [ENASET\\$get\(\)](#)
- [ENASET\\$clone\(\)](#)

Method new():*Usage:*

```
ENASET$new(
  enadata,
  dimensions = 2,
  norm.by = fun_sphere_norm,
  rotation.by = ena.svd.R6,
  rotation.params = NULL,
  rotation.set = NULL,
  node.position.method = lws.positions.sq.R6,
  endpoints.only = TRUE,
  center.align.to.origin = TRUE,
  ...
)
```

Arguments:

```
enadata TBD
dimensions TBD
norm.by TBD
rotation.by TBD
rotation.params TBD
rotation.set TBD
node.position.method TBD
endpoints.only TBD
center.align.to.origin TBD
... TBD
```

Returns: ENASET Process ENASET**Method process():***Usage:*

```
ENASET$process()
```

Returns: ENASET Get property from object**Method get():***Usage:*

```
ENASET$get(x = "enadata")
```

Arguments:

x character key to retrieve from object

Returns: value from object at x

Method clone(): The objects of this class are cloneable with this method.

Usage:

ENASet\$clone(deep = FALSE)

Arguments:

deep Whether to make a deep clone.

ena_correlation *Calculate the correlations*

Description

Calculate both Pearson correlations for the provided points and centroids

Usage

```
ena_correlation(points, centroids, conf_level = 0.95)
```

Arguments

| | |
|------------|-----|
| points | TBD |
| centroids | TBD |
| conf_level | TBD |

find_binary_cols *Find Binary Columns*

Description

Identifies columns in a data.frame or data.table that are binary (i.e., contain only two unique values), optionally including logical columns.

Usage

```
find_binary_cols(x, include_logical = FALSE)
```

Arguments

| | |
|-----------------|---|
| x | A data.frame or data.table to search for binary columns. |
| include_logical | Logical. If TRUE, logical columns are also considered binary. Default is FALSE. |

Value

A character vector of column names that are binary, or NULL if none are found.

Examples

```
df <- data.frame(a = c(0, 1, 1), b = c(TRUE, FALSE, TRUE), c = c(1, 2, 3))
find_binary_cols(df)
find_binary_cols(df, include_logical = TRUE)
```

| | |
|----------------|--------------------------|
| find_code_cols | <i>Find code columns</i> |
|----------------|--------------------------|

Description

Find code columns

Usage

```
find_code_cols(x)
```

Arguments

x data.table (or frame) to search for columns of class ena.co.occurrence

Value

logical vector

| | |
|---------------------|-------------------------------|
| find_dimension_cols | <i>Find dimension columns</i> |
|---------------------|-------------------------------|

Description

Find dimension columns

Usage

```
find_dimension_cols(x)
```

Arguments

x data.table (or frame) to search for columns of class ena.dimension

Value

logical vector

find_meta_cols *Find metadata columns*

Description

Find metadata columns

Usage

```
find_meta_cols(x)
```

Arguments

x data.table (or frame) to search for columns of class ena.metadata

Value

logical vector

fun_cohens.d *Cohen's d*

Description

Calculate Cohen's d

Usage

```
fun_cohens.d(x, y)
```

Arguments

x [TBD]

y [TBD]

Details

Cohen's d calculation

[TBD]

Value

numeric Cohen's d calculation

fun_skip_sphere_norm *Row-wise Max-Norm Scaling*

Description

Scales all rows of a numeric dataframe by dividing by the largest row vector length (L2 norm) found in the dataframe. This preserves the relative magnitudes between rows but does not normalize each row to unit length. Useful for analyses where relative scale is important but full normalization is not desired.

Usage

```
fun_skip_sphere_norm(dfM)
```

Arguments

dfM A data.frame or matrix. Each row is treated as a vector to compute its L2 norm.

Details

Row-wise Max-Norm Scaling

This function finds the row with the largest L2 norm (Euclidean length) and divides all entries in the matrix by this value. It does not normalize each row individually.

Value

A numeric matrix with the same dimensions as 'dfM', with all values divided by the largest row L2 norm.

Examples

```
df <- data.frame(a = c(3, 4), b = c(0, 0))
fun_skip_sphere_norm(df)
```

fun_sphere_norm *Row-wise L2 (Sphere) Normalization*

Description

Normalizes each row of a numeric dataframe or matrix to have unit L2 norm (Euclidean length). Each row is divided by its own length, projecting all rows onto the unit hypersphere. Useful for analyses where direction is important but magnitude should be removed.

Usage

```
fun_sphere_norm(dfM)
```

Arguments

dfM A data.frame or matrix. Each row is treated as a vector to compute its L2 norm.

Details

Row-wise L2 (Sphere) Normalization

This function computes the L2 norm (Euclidean length) of each row and divides the row by this value. Rows with zero length are left unchanged.

Value

A numeric matrix with the same dimensions as 'dfM', with each row normalized to unit length (L2 norm = 1), unless the row is all zeros (in which case it remains zeros).

Examples

```
df <- data.frame(a = c(3, 4), b = c(0, 0))
fun_sphere_norm(df)
```

get_x1_main_effect *Extract Main Effect Contribution of the First Predictor Using Elastic Net*

Description

This function fits a multivariate elastic net regression model (using `glmnet`) to estimate the main effect contribution of the first predictor variable (x_1) in the provided data frame X for each response variable in V . The main effect is forced into the model by setting its penalty factor to zero.

Usage

```
get_x1_main_effect(V, X, alpha = 1, lambda = "lambda.min")
```

Arguments

V A numeric matrix of response variables (dimensions: observations x responses).

X A data frame containing all predictor variables. The first column is treated as the target predictor (x_1).

alpha Elastic net mixing parameter (0 = ridge, 1 = lasso). Default is 1.

lambda The value of the regularization parameter to use. Can be "lambda.min", "lambda.1se", or a specific numeric value. Default is "lambda.min".

Details

The function constructs a model matrix including all main effects and two-way interactions. It then fits a multivariate elastic net model using `cv.glmnet`, forcing the inclusion of the main effect of x_1 by setting its penalty factor to zero. The resulting coefficients for x_1 are used to compute its contribution to the fitted values for each response variable.

Value

A numeric matrix of the same dimensions as *V*, where each column contains the estimated main effect contribution of *x1* for the corresponding response variable.

Examples

```
## Not run:
set.seed(123)
V <- matrix(rnorm(100 * 2), ncol = 2)
X <- data.frame(x1 = rnorm(100), x2 = sample(letters[1:3], 100, TRUE))
result <- get_x1_main_effect(V, X)

## End(Not run)
```

*gmr**Generalized Means Rotation (GMR)*

Description

Computes the generalized means rotation for a given set of ENA points and predictor variables.

Usage

```
gmr(V, X)
```

Arguments

| | |
|----------|--|
| <i>V</i> | A matrix containing ENA set points for projection. |
| <i>X</i> | A data frame containing all predictor variables, with the first column as the target variable. |

Details

If *X* has only one column, a linear model is fit between *V* and the single predictor. Otherwise, the main effect of the first predictor is extracted using `get_x1_main_effect`. Singular value decomposition (SVD) is then performed, and the first right singular vector is used to project the data. A linear model is fit to the projected data, and the coefficients are normalized to produce the rotation vector.

Value

A numeric vector representing the rotation.

See Also

[get_x1_main_effect](#)

Examples

```
## Not run:
V <- matrix(rnorm(100), ncol = 5)
X <- data.frame(target = rnorm(20), predictor1 = rnorm(20), predictor2 = rnorm(20))
r <- gmr(V, X)

## End(Not run)
```

| | |
|-------|--------------------------------------|
| group | <i>Add all groups to an ENA plot</i> |
|-------|--------------------------------------|

Description

This function iterates over all unique values of the first metadata column (excluding 'QEUNIT' and 'ENA_UNIT') in the ENA set and adds each group as a set of points to the ENA plot. This is useful for quickly visualizing all groups in a categorical variable on the same plot.

Usage

```
group(x, wh = NULL)
```

Arguments

| | |
|----|---|
| x | An 'ENApplot' object (as returned by 'plot.ena.set'). |
| wh | (Ignored) Included for compatibility with other plotting functions. |

Details

The function finds the first metadata column in the ENA set (excluding 'QEUNIT' and 'ENA_UNIT'), and for each unique value in that column, calls 'add_points()' to add the group's points to the plot.

Value

The modified 'ENApplot' object with all groups added as points.

Examples

```
# Load test data
data(RS.data);

# Define codenames for the test
codenames <- c("Data", "Technical.Constraints", "Performance.Parameters",
  "Client.and.Consultant.Requests", "Design.Reasoning", "Collaboration");

# Standard ENA accumulation
accum <- rENA:::ena.accumulate.data.file(
  RS.data, units.by = c("UserName", "Condition"),
```

```

    conversations.by = c("ActivityNumber", "GroupName"),
    codes = codenames
  );
# Create a standard ENA set
newset <- ena.make.set(accum);

# Simple plot for a set of points, and their mean
newplot <- plot(newset) |>
  add_points(Condition$FirstGame, mean = TRUE, colors = "blue") |>
  add_network();

# Plot a single unit's point and it's line.weights
plot(newset) |>
  add_points(UserName$`steven z`) |>
  add_network();

# Trajectory accumulation and plotting
trajectory_accumulation <- rENA:::ena.accumulate.data.file(
  RS.data, units.by = c("UserName", "Condition"),
  conversations.by = c("ActivityNumber", "GroupName"),
  codes = codenames,
  model = "A"
);
trajectory_model <- ena.make.set(trajectory_accumulation);

newplot3 <- plot(trajectory_model) |>
  add_trajectory(Condition$FirstGame);

```

| | |
|---------|--|
| horizon | <i>Reclassify specified columns as horizon or list horizon columns in a data.table</i> |
|---------|--|

Description

This function reclassifies specified columns of a `data.table` to the `'qe.horizon'` format if column names are provided. If no column names are provided, it returns the names of columns that are already classified as `'qe.horizon'`.

Usage

```
horizon(x, ...)
```

Arguments

| | |
|------------------|---|
| <code>x</code> | A <code>data.table</code> . The <code>data.table</code> containing the columns to be reclassified or checked. |
| <code>...</code> | Additional arguments specifying the names of the columns to be reclassified. |

Value

The modified `data.table` with specified columns reclassified as `'qe.horizon'`, or a character vector of column names already classified as `'qe.horizon'`.

Examples

```
library(data.table)
dt <- data.table(a = 1:5, b = 6:10)
# Reclassify columns 'a' and 'b' as 'qe.horizon'
dt <- horizon(dt, "a", "b")
# List columns classified as 'qe.horizon'
horizon_columns <- horizon(dt)
```

| | |
|------------|---|
| is.qe.code | <i>Check if an object is of class 'qe.code'</i> |
|------------|---|

Description

This function checks if an object is of class 'qe.code'.

Usage

```
is.qe.code(x)
```

Arguments

x An object. The object to be checked.

Value

A logical value. TRUE if the object is of class 'qe.code', otherwise FALSE.

Examples

```
dt <- 1:5
class(dt) <- c("qe.code", class(dt))
is.qe.code(dt) # Should return TRUE
```

| | |
|------------|---|
| is.qe.data | <i>Check if an object is of class 'qe.data'</i> |
|------------|---|

Description

This function checks if an object is of class 'qe.data'.

Usage

```
is.qe.data(x)
```

Arguments

x An object. The object to be checked.

Value

A logical value. TRUE if the object is of class 'qe.data', otherwise FALSE.

Examples

```
library(data.table)

dt <- data.table(ID = 1:5)
class(dt) <- c("qe.data", class(dt))
is.qe.data(dt) # Should return TRUE
```

| | |
|---------------|--|
| is.qe.horizon | <i>Check if an object is of class 'qe.horizon'</i> |
|---------------|--|

Description

This function checks if an object is of class 'qe.horizon'.

Usage

```
is.qe.horizon(x)
```

Arguments

x An object. The object to be checked.

Value

A logical value. TRUE if the object is of class 'qe.horizon', otherwise FALSE.

Examples

```
dt <- 1:5
class(dt) <- c("qe.horizon", class(dt))
is.qe.horizon(dt) # Should return TRUE
```

| | |
|----------------|---|
| is.qe.metadata | <i>Check if an object is of class 'qe.metadata'</i> |
|----------------|---|

Description

This function checks if an object is of class 'qe.metadata'.

Usage

```
is.qe.metadata(x)
```

Arguments

x An object. The object to be checked.

Value

A logical value. TRUE if the object is of class 'qe.metadata', otherwise FALSE.

Examples

```
dt <- 1:5
class(dt) <- c("qe.metadata", class(dt))
is.qe.metadata(dt) # Should return TRUE
```

| | |
|------------|---|
| is.qe.unit | <i>Check if an object is of class 'qe.unit'</i> |
|------------|---|

Description

This function checks if an object is of class 'qe.unit'.

Usage

```
is.qe.unit(x)
```

Arguments

x An object. The object to be checked.

Value

A logical value. TRUE if the object is of class 'qe.unit', otherwise FALSE.

Examples

```
dt <- 1:5
class(dt) <- c("qe.unit", class(dt))
is.qe.unit(dt) # Should return TRUE
```

| | |
|--------------|--------------|
| means_rotate | <i>Title</i> |
|--------------|--------------|

Description

Title

Usage

```
means_rotate(x, on = NULL)
```

Arguments

x [TBD]

on [TBD]

Value

[TBD]

| | |
|-----------------|---------------------------------|
| merge_columns_c | <i>Merge data frame columns</i> |
|-----------------|---------------------------------|

Description

TBD

Usage

```
merge_columns_c(df, cols, sep = "::")
```

Arguments

df Dataframe

cols Vector

sep Character seperator

Details

Merge data frame columns

| | |
|----------|--|
| metadata | <i>Reclassify specified columns as metadata or list metadata columns in a data.table</i> |
|----------|--|

Description

This function reclassifies specified columns of a `data.table` to the `'qe.metadata'` format if column names are provided. If no column names are provided, it returns the names of columns that are already classified as `'qe.metadata'`.

Usage

```
metadata(x, ...)
```

Arguments

`x` A `data.table`. The `data.table` containing the columns to be reclassified or checked.
`...` Additional arguments specifying the names of the columns to be reclassified.

Value

The modified `data.table` with specified columns reclassified as `'qe.metadata'`, or a character vector of column names already classified as `'qe.metadata'`.

Examples

```
library(data.table)
dt <- data.table(a = 1:5, b = 6:10)
# Reclassify columns 'a' and 'b' as 'qe.metadata'
dt <- metadata(dt, "a", "b")
# List columns classified as 'qe.metadata'
metadata_columns <- metadata(dt)
```

| | |
|----------------|-----------------------|
| methods_report | <i>methods_report</i> |
|----------------|-----------------------|

Description

Methods report for rmarkdwon

Usage

```
methods_report(  
  toc = FALSE,  
  toc_depth = 3,  
  fig_width = 5,  
  fig_height = 4,  
  keep_md = FALSE,  
  md_extensions = NULL,  
  pandoc_args = NULL  
)
```

Arguments

| | |
|---------------|-------|
| toc | [TBD] |
| toc_depth | [TBD] |
| fig_width | [TBD] |
| fig_height | [TBD] |
| keep_md | [TBD] |
| md_extensions | [TBD] |
| pandoc_args | [TBD] |

methods_report_stream *methods_report_stream*

Description

Methods report for rmarkdwon

Usage

```
methods_report_stream(  
  toc = FALSE,  
  toc_depth = 3,  
  fig_width = 5,  
  fig_height = 4,  
  keep_md = FALSE,  
  md_extensions = NULL,  
  pandoc_args = NULL  
)
```

Arguments

| | |
|---------------|-------|
| toc | [TBD] |
| toc_depth | [TBD] |
| fig_width | [TBD] |
| fig_height | [TBD] |
| keep_md | [TBD] |
| md_extensions | [TBD] |
| pandoc_args | [TBD] |

 model

Build a Complete ENA Model

Description

This function applies a full ENA modeling pipeline to accumulated data. It is a convenience wrapper that chains together normalization, centering, rotation, projection, and optional optimization. Each step can be customized by supplying an alternative function.

Usage

```

model(
  data,
  ...,
  normalize = sphere_norm,
  center_with = center,
  rotate_with = rotate,
  project_with = project,
  optimize_with = optimize,
  rotate_fun = ena.rotate.by.generalized,
  rotate_params = list()
)

```

Arguments

| | |
|---------------|---|
| data | An ‘ena.set’ object, typically the result of ‘accumulate()’. |
| ... | Additional arguments passed to the rotation function specified by ‘rotate_fun’. |
| normalize | A function to normalize the connection counts. Defaults to ‘sphere_norm’. |
| center_with | A function to center the normalized data. Defaults to ‘center’. |
| rotate_with | A function to perform the rotation (e.g., SVD). Defaults to ‘rotate’. |
| project_with | A function to project the points into the rotated space. Defaults to ‘project’. |
| optimize_with | A function to optimize node positions. Defaults to ‘optimize’. Can be set to ‘NULL’ or ‘FALSE’ to skip. |
| rotate_fun | The specific rotation function to be used by ‘rotate_with’. Defaults to ‘ena.rotate.by.generalized’. |
| rotate_params | A list of additional parameters to pass to the ‘rotate_fun’. |

Value

An 'ena.set' object with a complete ENA model, including projected points and node positions.

Examples

```
data(RS.data)

codes <- c("Data", "Technical.Constraints", "Performance.Parameters",
          "Client.and.Consultant.Requests", "Design.Reasoning",
          "Collaboration")
units <- c("Condition", "UserName")
horizon <- c("Condition", "GroupName")
enaset <- RS.data |>
  accumulate(units, codes, horizon) |>
  model()
```

move_nodes_to_unit_circle
Title

Description

Title

Usage

```
move_nodes_to_unit_circle(  
  set,  
  dimension_name_1 = colnames(as.matrix(set$rotation$nodes))[1],  
  dimension_name_2 = colnames(as.matrix(set$rotation$nodes))[2]  
)
```

Arguments

```
set          TBD  
dimension_name_1  
            TBD  
dimension_name_2  
            TBD
```

Value

TBD

```
move_nodes_to_unit_circle_with_equal_space
```

Title

Description

Title

Usage

```
move_nodes_to_unit_circle_with_equal_space(
  set,
  dimension_name_1 = colnames(as.matrix(set$rotation$nodes))[1],
  dimension_name_2 = colnames(as.matrix(set$rotation$nodes))[2]
)
```

Arguments

```
set          TBD
dimension_name_1
              TBD
dimension_name_2
              TBD
```

Value

TBD

```
namesToAdjacencyKey  Names to Adjacency Key
```

Description

Convert a vector of strings, representing names of a square matrix, to an adjacency

Usage

```
namesToAdjacencyKey(vector, upper_triangle = TRUE)
```

Arguments

```
vector          Vector representing the names of a square matrix
upper_triangle  Not Implemented
```

Details

Returns a matrix of 2 rows by choose(length(vector), 2) columns

| | |
|----------|--|
| optimize | <i>Optimize Node and Centroid Positions in ENA Set</i> |
|----------|--|

Description

This function computes and assigns node positions and centroids for an ENA set object using the current points and rotation information.

Usage

```
optimize(x, weights = NULL)
```

Arguments

| | |
|---------|---|
| x | An ena.set object for which to optimize node and centroid positions. |
| weights | Optional. A numeric matrix of connection weights. If provided, the function will use this matrix instead of the connection counts from the ena.set. |

Value

The input ena.set object with updated node and centroid positions.

Examples

```
# Assuming 'set' is an ena.set object:
data(RS.data)

codes <- c("Data", "Technical.Constraints", "Performance.Parameters",
          "Client.and.Consultant.Requests", "Design.Reasoning",
          "Collaboration")
units <- c("Condition", "UserName")
horizon <- c("Condition", "GroupName")
enaset <- RS.data |>
  accumulate(units, codes, horizon) |>
  sphere_norm() |>
  center() |>
  rotate() |>
  project() |>
  optimize()
```

| | |
|--------------|-------------------------------|
| plot.ena.set | <i>Plot an ena.set object</i> |
|--------------|-------------------------------|

Description

Plot an ena.set object

Usage

```
## S3 method for class 'ena.set'
plot(x, y, ..., empty = TRUE, title = "ENA Plot")
```

Arguments

| | |
|-------|--|
| x | ena.set to plot |
| y | ignored. |
| ... | Additional parameters passed along to ena.plot functions |
| empty | Logical; if TRUE, creates an empty plot without points. Default is TRUE. |
| title | Character; title for the plot. Default is "ENA Plot". |

Value

ena.plot.object

Examples

```
data(RS.data)

codeNames = c('Data', 'Technical.Constraints', 'Performance.Parameters',
              'Client.and.Consultant.Requests', 'Design.Reasoning', 'Collaboration');

accum = ena.accumulate.data(
  units = RS.data[,c("UserName", "Condition")],
  conversation = RS.data[,c("Condition", "GroupName")],
  metadata = RS.data[,c("CONFIDENCE.Change", "CONFIDENCE.Pre", "CONFIDENCE.Post")],
  codes = RS.data[,codeNames],
  window.size.back = 4
)

set = ena.make.set(
  enadata = accum
)

plot(set) |>
  add_points(Condition$FirstGame, colors = "blue", with.mean = TRUE) |>
  add_points(Condition$SecondGame, colors = "red", with.mean = TRUE) |>
  with_means() |>
  add_nodes()
```

```
myENApplot <- plot(set) |>
  add_network(Condition$FirstGame - Condition$SecondGame)

# Add a group mean to an existing ENA plot
add_group(myENApplot, wh = Condition$FirstGame)

# Add a trajectory to an existing ENA plot
add_trajectory(myENApplot, wh = Condition$FirstGame)

# Load test data
data(RS.data);

# Define codenames for the test
codenames <- c("Data", "Technical.Constraints", "Performance.Parameters",
  "Client.and.Consultant.Requests", "Design.Reasoning", "Collaboration");

# Standard ENA accumulation
accum <- rENA:::ena.accumulate.data.file(
  RS.data, units.by = c("UserName", "Condition"),
  conversations.by = c("ActivityNumber", "GroupName"),
  codes = codenames
);
# Create a standard ENA set
newset <- ena.make.set(accum);

# Simple plot for a set of points, and their mean
newplot <- plot(newset) |>
  add_points(Condition$FirstGame, mean = TRUE, colors = "blue") |>
  add_network();

# Plot a single unit's point and it's line.weights
plot(newset) |>
  add_points(UserName$`steven z`) |>
  add_network();

# Trajectory accumulation and plotting
trajectory_accumulation <- rENA:::ena.accumulate.data.file(
  RS.data, units.by = c("UserName", "Condition"),
  conversations.by = c("ActivityNumber", "GroupName"),
  codes = codenames,
  model = "A"
);
trajectory_model <- ena.make.set(trajectory_accumulation);

newplot3 <- plot(trajectory_model) |>
  add_trajectory(Condition$FirstGame);
```

prepare_trajectory_data

Prepares trajectory data for an ENA plot.

Description

This function processes and prepares trajectory data for plotting in an ENA set. It handles rotation, grouping, and filling missing steps in the trajectory.

Usage

```
prepare_trajectory_data(
  x = NULL,
  by = x$`_function.params`$conversation[1],
  rotation_matrix = x$rotation.matrix,
  points = NULL,
  units = points,
  units_by = x$`_function.params`$units,
  steps = NULL
)
```

Arguments

| | |
|------------------------------|--|
| <code>x</code> | An ENA set object. If 'NULL', other parameters must be provided. |
| <code>by</code> | A character vector specifying the grouping variables for the trajectory. Default is the first conversation parameter in the ENA set. |
| <code>rotation_matrix</code> | A matrix used to rotate the points. Default is the rotation matrix from the ENA set. |
| <code>points</code> | A data table of points to be processed. Default is the points from the ENA set. |
| <code>units</code> | A data table of units corresponding to the points. Default is the trajectories or points from the ENA set. |
| <code>units_by</code> | A character vector specifying the unit grouping variables. Default is the unit parameters from the ENA set. |
| <code>steps</code> | A data table specifying the steps for the trajectory. If 'NULL', steps are generated automatically. |

Value

A data table containing the processed trajectory data, including dimensions and metadata.

| | |
|---------------|--------------|
| print.ena.set | <i>Title</i> |
|---------------|--------------|

Description

Title

Usage

```
## S3 method for class 'ena.set'
print(x, ..., plot = FALSE, set = TRUE)
```

Arguments

| | |
|------|-------|
| x | [TBD] |
| ... | [TBD] |
| plot | [TBD] |
| set | [TBD] |

Value

[TBD]

| | |
|---------|--|
| project | <i>Project ENA Points onto Rotated Space</i> |
|---------|--|

Description

This function projects ENA points onto the rotated space using the rotation matrix. Optionally, metadata can be included in the resulting points matrix.

Usage

```
project(x, rotation = NULL, add.meta = TRUE)
```

Arguments

| | |
|----------|---|
| x | An ena.set object containing the points for projection and rotation matrix. |
| rotation | Optional. A rotation matrix to use for projection if x is not an ena.set. |
| add.meta | Logical. If TRUE (default), metadata will be included in the output. |

Value

The input ena.set object with the projected points matrix (and metadata if requested).

Examples

```
# Assuming 'set' is an ena.set object:
data(RS.data)

codes <- c("Data", "Technical.Constraints", "Performance.Parameters",
           "Client.and.Consultant.Requests", "Design.Reasoning",
           "Collaboration")
units <- c("Condition", "UserName")
horizon <- c("Condition", "GroupName")
enaset <- RS.data |>
  accumulate(units, codes, horizon) |>
  sphere_norm() |>
  center() |>
  rotate() |>
  project()
```

| project_in | <i>Title</i> |
|------------|--------------|
|------------|--------------|

Description

Title

Usage

```
project_in(x, by = NULL, ...)
```

Arguments

| | |
|-----|-------|
| x | [TBD] |
| by | [TBD] |
| ... | [TBD] |

Value

[TBD]

| | |
|------------|---|
| reclassify | <i>Reclassify specified columns in a data.table</i> |
|------------|---|

Description

This function reclassifies specified columns of a `data.table` using a provided function.

Usage

```
reclassify(x, v, ...)
```

Arguments

| | |
|------------------|--|
| <code>x</code> | A <code>data.table</code> . The <code>data.table</code> containing the columns to be reclassified. |
| <code>v</code> | A function. The function to apply to each specified column for reclassification. |
| <code>...</code> | Additional arguments specifying the names of the columns to be reclassified. |

Value

The modified `data.table` with specified columns reclassified.

Examples

```
library(data.table)
dt <- data.table(a = 1:5, b = 6:10)
dt <- reclassify(dt, as.qc.code, "a", "b")
```

| | |
|------------------|--|
| remove_meta_data | <i>Remove meta columns from data.table</i> |
|------------------|--|

Description

Remove meta columns from `data.table`

Usage

```
remove_meta_data(x)
```

Arguments

| | |
|----------------|-------|
| <code>x</code> | [TBD] |
|----------------|-------|

Value

`data.table` with columns of class `ena.meta.data` removed

| | |
|------|------------------------------|
| rENA | <i>rENA creates ENA sets</i> |
|------|------------------------------|

Description

rENA is used to create and visualize network models of discourse and other phenomena from coded data using Epistemic Network Analysis (ENA). A more complete description of the methods will be provided with the next release. See also XXXXX

| | |
|--------|------------------------|
| rotate | <i>Rotate ENA Data</i> |
|--------|------------------------|

Description

Rotates ENA data using a specified rotation function (default: SVD), optionally using formulas or grouping variables.

Usage

```
rotate(x, ..., wh = ena.rotate.by.generalized)
```

Arguments

| | |
|-----|---|
| x | An ena.set object to be rotated. |
| ... | Optional formulas or additional arguments for rotation. |
| wh | Function to use for rotation (default: ena.svd). |

Value

The rotated ena.set object with updated rotation matrices.

Examples

```
# Assuming 'set' is an ena.set object:
data(RS.data)

codes <- c("Data", "Technical.Constraints", "Performance.Parameters",
          "Client.and.Consultant.Requests", "Design.Reasoning",
          "Collaboration")
units <- c("Condition", "UserName")
horizon <- c("Condition", "GroupName")
enaset <- RS.data |>
  accumulate(units, codes, horizon) |>
  sphere_norm() |>
  center() |>
  rotate()
```

| | |
|---------|-----------------------------------|
| RS.data | <i>Coded Rescushell Chat Data</i> |
|---------|-----------------------------------|

Description

A dataset containing sample chat data from the Rescushell Virtual Internship

Usage

RS.data

Format

An object of class `data.frame` with 3824 rows and 20 columns.

| | |
|----------------------------|---|
| <code>scale.ENAplot</code> | <i>Scales the points in an ENA set.</i> |
|----------------------------|---|

Description

This function adjusts the scale of the points in the ENA set to match the range of the network.

Usage

```
## S3 method for class 'ENAplot'
scale(x, center = NULL, scale = NULL)
```

Arguments

| | |
|---------------------|--|
| <code>x</code> | An ENAplot object containing the set to scale. |
| <code>center</code> | Unused parameter, included for compatibility. |
| <code>scale</code> | A numeric value specifying the scaling factor. If 'NULL', the function will determine the scale based on the data. |

Value

The modified ENAplot object with scaled points.

| | |
|------|---|
| show | <i>Display and update plot objects within a custom object</i> |
|------|---|

Description

This function updates the plots within the provided object by applying the ‘check_range’ function to each plot. It then prints the updated object using custom print options and returns the object invisibly.

Usage

```
show(x, ...)
```

Arguments

| | |
|-----|--|
| x | An object containing a list of plots in the ‘plots’ field. |
| ... | Additional arguments passed to the ‘print’ method. |

Value

The updated object ‘x’, returned invisibly.

| | |
|-------------|--|
| sphere_norm | <i>Apply Spherical Normalization to ENA Data</i> |
|-------------|--|

Description

This function applies spherical normalization to the connection counts in an ‘ena.set’ object or to a raw matrix of connection counts. Normalization is a key step before centering and rotation in ENA.

Usage

```
sphere_norm(x, add.meta = TRUE)
```

Arguments

| | |
|----------|--|
| x | An ‘ena.set’ object or a numeric matrix of connection counts. |
| add.meta | A logical value. If ‘TRUE’ (the default), metadata from the ‘ena.set’ is preserved and included in the output. This parameter is ignored if ‘x’ is a matrix. |

Value

If ‘x’ is an ‘ena.set’, it returns the modified ‘ena.set’ with a new ‘line.weights’ matrix and an updated ‘centervec’ in the ‘rotation’ object. If ‘x’ is a matrix, it returns a matrix of normalized line weights.

Examples

```

data(RS.data)

codes <- c("Data", "Technical.Constraints", "Performance.Parameters",
          "Client.and.Consultant.Requests", "Design.Reasoning",
          "Collaboration")
units <- c("Condition", "UserName")
horizon <- c("Condition", "GroupName")
enaset <- RS.data |>
  accumulate(units, codes, horizon) |>
  sphere_norm()

```

| | |
|-------|---|
| units | <i>Reclassify specified columns as units or list unit columns in a data.table</i> |
|-------|---|

Description

This function reclassifies specified columns of a `data.table` to the 'qe.unit' format if column names are provided. If no column names are provided, it returns the names of columns that are already classified as 'qe.unit'.

Usage

```
units(x, ...)
```

Arguments

| | |
|-----|---|
| x | A <code>data.table</code> . The <code>data.table</code> containing the columns to be reclassified or checked. |
| ... | Additional arguments specifying the names of the columns to be reclassified. |

Value

The modified `data.table` with specified columns reclassified as 'qe.unit', or a character vector of column names already classified as 'qe.unit'.

Examples

```

library(data.table)
dt <- data.table(a = 1:5, b = 6:10)
# Reclassify columns 'a' and 'b' as 'qe.unit'
dt <- units(dt, "a", "b")
# List columns classified as 'qe.unit'
unit_columns <- units(dt)

```

| | |
|--------------|---------------------------------|
| vector_to_ut | <i>vector to upper triangle</i> |
|--------------|---------------------------------|

Description

TBD

Usage

vector_to_ut(v)

Arguments

v [TBD]

Details

Upper Triangle from Vector

| | |
|-----------------|------------------------|
| with.ena.matrix | <i>with.ena.matrix</i> |
|-----------------|------------------------|

Description

This function sets up a context using the provided data (typically an ENA matrix), allowing the evaluation of an expression ('expr') with access to both the matrix and its metadata. Optionally, a custom matrix 'V' and other arguments can be supplied.

Usage

```
## S3 method for class 'ena.matrix'
with(data, expr, ...)
```

Arguments

| | |
|------|---|
| data | An ENA matrix or data frame containing the data to be used. |
| expr | An R expression to be evaluated within the context of the ENA matrix. |
| ... | Additional arguments, including an optional custom matrix 'V' and other parameters. |

Details

- If a custom matrix 'V' is provided in '...', it will be used; otherwise, 'data' is converted to a matrix. - Metadata columns are coerced to numeric if they are character vectors. - The expression is evaluated with access to both the matrix ('V') and metadata.

Value

The result of evaluating ‘expr’ in the constructed context.

| | |
|------------|--|
| with_means | <i>Adds group means to the ENA plot.</i> |
|------------|--|

Description

This function iterates over the plotted points in the ENA plot and calculates the mean for each group of points. The calculated means are then added to the plot as group means.

Usage

```
with_means(x)
```

Arguments

x An ENA set object containing the plots.

Value

Invisibly returns the modified ENA set object with updated plots.

| | |
|-----------------|--|
| with_trajectory | <i>Adds trajectories to an ENA plot.</i> |
|-----------------|--|

Description

This function generates trajectories for the plotted points in the ENA plot based on the specified grouping variables. It supports options for jittering, animation, and scaling.

Usage

```
with_trajectory(
  x,
  ...,
  by = x$`_function.params`$conversation[1],
  add_jitter = TRUE,
  frame = 1100,
  transition = 1000,
  easing = "circle-in-out"
)
```

Arguments

| | |
|------------|--|
| x | An ENA set object containing the plots. |
| ... | Additional arguments passed to the plotting functions. |
| by | A character vector specifying the grouping variables for the trajectories. Default is the first conversation parameter in the ENA set. |
| add_jitter | Logical; if 'TRUE', adds jitter to the trajectory points. Default is 'TRUE'. |
| frame | Numeric; the duration of each frame in the animation. Default is 1100. |
| transition | Numeric; the duration of the transition between frames. Default is 1000. |
| easing | A character string specifying the easing function for the animation. Default is "circle-in-out". |

Value

Invisibly returns the modified ENA set object with updated plots.

\$.ena.matrix

Extract from ena.matrix easily using metadata

Description

Extract from ena.matrix easily using metadata

Usage

```
## S3 method for class 'ena.matrix'
x$i
```

Arguments

| | |
|---|-------|
| x | [TBD] |
| i | [TBD] |

Value

[TBD]

\$.ena.metadata *Extract metadata easily*

Description

Extract metadata easily

Usage

```
## S3 method for class 'ena.metadata'  
x$i
```

Arguments

x [TBD]
i [TBD]

Value

[TBD]

\$.ena.points *Extract points easily*

Description

Extract points easily

Usage

```
## S3 method for class 'ena.points'  
x$i
```

Arguments

x [TBD]
i [TBD]

Value

[TBD]

\$.line.weights *Extract line.weights easily*

Description

Extract line.weights easily

Usage

```
## S3 method for class 'line.weights'  
x$i
```

Arguments

| | |
|---|-------|
| x | [TBD] |
| i | [TBD] |

Value

[TBD]

Index

* datasets

- RS.data, [89](#)
- *.ena.matrix, [4](#)
- \$.ena.matrix, [94](#)
- \$.ena.metadata, [95](#)
- \$.ena.points, [95](#)
- \$.line.weights, [96](#)

- accumulate, [5](#)
- add_group, [6](#)
- add_network, [7](#)
- add_nodes, [9](#)
- add_points, [10](#)
- add_trajectory, [11](#)
- as.ena.co.occurrence, [13](#)
- as.ena.matrix, [13](#)
- as.ena.metadata, [14](#)
- as.matrix.ena.connections, [14](#)
- as.matrix.ena.line.weights, [15](#)
- as.matrix.ena.matrix, [15](#)
- as.matrix.ena.nodes, [16](#)
- as.matrix.ena.points, [16](#)
- as.matrix.ena.rotation.matrix, [17](#)
- as.matrix.row.connections, [17](#)
- as.qe.code, [18](#)
- as.qe.data, [18](#)
- as.qe.horizon, [19](#)
- as.qe.metadata, [20](#)
- as.qe.unit, [20](#)
- as_trajectory, [21](#)

- center, [21](#)
- check_range, [22](#)
- clear, [23](#)
- codes, [24](#)
- combn_c2, [25](#)
- compute_SB, [25](#)
- connection.matrix, [26](#)

- define, [26](#)

- directed_node_positions, [27](#)
- directed_node_positions_with_ground_response_added, [28](#)

- ena, [28](#)
- ena.accumulate.data, [31, 37](#)
- ena.conversations, [33](#)
- ena.correlations, [34](#)
- ena.group, [35](#)
- ena.make.set, [32, 36, 39](#)
- ena.plot, [38, 41, 43, 46, 48](#)
- ena.plot.group, [39, 46](#)
- ena.plot.network, [41](#)
- ena.plot.points, [39, 43, 44](#)
- ena.plot.trajjectory, [47](#)
- ena.plotter, [49](#)
- ena.rotate.by.generalized, [50](#)
- ena.rotate.by.hena.regression, [51](#)
- ena.rotate.by.hena.regression_2, [51](#)
- ena.rotate.by.mean, [52](#)
- ena.rotation.h, [53](#)
- ena.set.creator, [53](#)
- ena.svd, [55](#)
- ena.writeup, [56](#)
- ena_correlation, [64](#)
- ENAdata, [32, 36, 57, 62](#)
- ENApplot, [39–43, 45–48, 59](#)
- ENARotationSet, [50–52, 61, 62](#)
- ENAsset, [35, 37, 38, 50–52, 59, 62](#)

- find_binary_cols, [64](#)
- find_code_cols, [65](#)
- find_dimension_cols, [65](#)
- find_meta_cols, [66](#)
- fun_cohens.d, [66](#)
- fun_skip_sphere_norm, [67](#)
- fun_sphere_norm, [67](#)

- get_x1_main_effect, [68, 69](#)
- gmr, [69](#)

- group, [70](#)
- horizon, [71](#)
- is.qe.code, [72](#)
- is.qe.data, [72](#)
- is.qe.horizon, [73](#)
- is.qe.metadata, [74](#)
- is.qe.unit, [74](#)
- means_rotate, [75](#)
- merge_columns_c, [75](#)
- metadata, [76](#)
- methods_report, [76](#)
- methods_report_stream, [77](#)
- model, [78](#)
- move_nodes_to_unit_circle, [79](#)
- move_nodes_to_unit_circle_with_equal_space,
[80](#)
- namesToAdjacencyKey, [80](#)
- optimize, [81](#)
- plot.ena.set, [82](#)
- prepare_trajectory_data, [83](#)
- print.ena.set, [85](#)
- project, [85](#)
- project_in, [86](#)
- reclassify, [87](#)
- remove_meta_data, [87](#)
- rENA, [88](#)
- rotate, [88](#)
- RS.data, [89](#)
- scale.ENAplot, [89](#)
- show, [90](#)
- sphere_norm, [90](#)
- units, [91](#)
- vector_to_ut, [92](#)
- with.ena.matrix, [92](#)
- with_means, [93](#)
- with_trajectory, [93](#)