

Package ‘rnetcarto’

August 29, 2016

Type Package

Title Fast Network Modularity and Roles Computation by Simulated Annealing (Rgraph C Library Wrapper for R)

Version 0.2.4

Date 2015-11-11

Maintainer Guilhem Doulcier <guilhem.doulcier@ens.fr>

Description It provides functions to compute the modularity and modularity-related roles in networks. It is a wrapper around the rgraph library (Guimera & Amaral, 2005, doi:10.1038/nature03288).

License GPL (>= 2)

LazyLoad no

SystemRequirements GNU GSL

NeedsCompilation yes

Suggests testthat, knitr, rmarkdown, igraph

VignetteBuilder knitr

Author Guilhem Doulcier [aut, cre] (R bindings, current implementation of the simulated annealing algorithm),
Roger Guimera [ctb] (Author of the original rgraph library),
Daniel B. Stouffer [aut, ths]

Repository CRAN

Date/Publication 2015-11-12 12:58:34

R topics documented:

rnetcarto 2

Index 3

 netcarto

Computes modularity and modularity roles from a network.

Description

Compute modularity and modularity roles for graphs using simulated annealing

Usage

```
netcarto(web, seed = as.integer(floor(runif(1, 1, 100000001))), iterfac = 1,
  coolingfac = 0.995, bipartite = FALSE)
```

Arguments

web	network either as a square adjacency matrix or a list describing E interactions a->b: the first (resp. second) element is the vector of the labels of a (resp. b), the third (optional) is the vector of interaction weights.
seed	Seed for the random number generator: Must be a positive integer.
iterfac	At each temperature of the simulated annealing (SA), the program performs fN^2 individual-node updates (involving the movement of a single node from one module to another) and fN collective updates (involving the merging of two modules and the split of a module). The number "f" is the iteration factor.
coolingfac	Temperature cooling factor.
bipartite	If True use the bipartite definition of modularity.

Value

A list. The first element is a dataframe with the name, module, z-score, and participation coefficient for each row of the input matrix. The second element is the modularity of this partition.

Examples

```
# Generate a simple random network
a = matrix(as.integer(runif(100)<.3), ncol=10)
a[lower.tri(a)] = 0
# Find an optimal partition for modularity using netcarto.
netcarto(a)
```

Index

netcarto (rnetcarto), [2](#)

rnetcarto, [2](#)

rnetcarto-package (rnetcarto), [2](#)