

Package ‘stringstatic’

May 13, 2023

Title Dependency-Free String Operations

Version 0.1.1

Description Provides drop-in replacements for functions from the 'stringr' package, with the same user interface. These functions have no external dependencies and can be copied directly into your package code using the 'staticimports' package.

License CC0

URL <https://github.com/rossellhayes/stringstatic>

BugReports <https://github.com/rossellhayes/stringstatic/issues>

Suggests testthat (>= 3.0.0)

Config/Needs/roxygen wch/staticimports

Config/testthat/edition 3

Encoding UTF-8

RoxygenNote 7.2.3

NeedsCompilation no

Author Alexander Rossell Hayes [aut, cre, cph]
(<<https://orcid.org/0000-0001-9412-0457>>),
Eli Pousson [ctb] (<<https://orcid.org/0000-0001-8280-1706>>, str_pad()
and str_split() functions),
Hadley Wickham [ctb, cph] (stringr package),
RStudio [cph] (stringr package)

Maintainer Alexander Rossell Hayes <alexander@rossellhayes.com>

Repository CRAN

Date/Publication 2023-05-13 06:20:02 UTC

R topics documented:

fixed	2
regex	3
str_c	4

str_count	4
str_detect	5
str_dup	6
str_ends	6
str_extract	7
str_extract_all	8
str_length	8
str_match	9
str_pad	10
str_remove	11
str_remove_all	11
str_replace	12
str_replace_all	13
str_replace_na	13
str_split	14
str_split_fixed	15
str_squish	16
str_starts	16
str_subset	17
str_trim	17
str_which	18
str_width	19

Index	20
--------------	-----------

fixed	<i>Compare literal bytes in the string</i>
-------	--

Description

Compare literal bytes in the string

Usage

```
fixed(pattern, ignore_case = FALSE)
```

Arguments

pattern	Pattern to modify behavior.
ignore_case	Should case differences be ignored in the match?

Value

An integer vector.

Source

Adapted from the `stringr` package.

Dependency-free drop-in alternative for `stringr::fixed()`. This is very fast, but not usually what you want for non-ASCII character sets.

regex

Control regex matching behavior

Description

Dependency-free drop-in alternative for `stringr::regex()`.

Usage

```
regex(  
  pattern,  
  ignore_case = FALSE,  
  multiline = FALSE,  
  comments = FALSE,  
  dotall = FALSE  
)
```

Arguments

<code>pattern</code>	Pattern to modify behavior.
<code>ignore_case</code>	Should case differences be ignored in the match?
<code>multiline</code>	If TRUE, <code>\$</code> and <code>^</code> match the beginning and end of each line. If FALSE, the default, only match the start and end of the input.
<code>comments</code>	If TRUE, white space and comments beginning with <code>#</code> are ignored. Escape literal spaces with <code>\\</code> .
<code>dotall</code>	If TRUE, <code>.</code> will also match line terminators.

Value

An integer vector.

Source

Adapted from the `stringr` package.

str_c	<i>Join multiple strings into a single string</i>
-------	---

Description

Dependency-free drop-in alternative for `stringr::str_c()`.

Usage

```
str_c(..., sep = "", collapse = NULL)
```

Arguments

...	One or more character vectors. Zero length arguments are removed. Short arguments are recycled to the length of the longest. Like most other R functions, missing values are "infectious": whenever a missing value is combined with another string the result will always be missing. Use <code>str_replace_na()</code> to convert NA to "NA"
sep	String to insert between input vectors.
collapse	Optional string used to combine input vectors into single string.

Value

If `collapse = NULL` (the default) a character vector with length equal to the longest input string. If `collapse` is non-NULL, a character vector of length 1.

Source

Adapted from the [stringr](#) package.

str_count	<i>Count the number of matches in a string</i>
-----------	--

Description

Dependency-free drop-in alternative for `stringr::str_count()`.

Usage

```
str_count(string, pattern = "")
```

Arguments

string	Input vector. Either a character vector, or something coercible to one.
pattern	Pattern to look for. The default interpretation is a regular expression, as described in base::regex . Control options with regex() . Match a fixed string (i.e. by comparing only bytes), using fixed() . This is fast, but approximate.

Value

An integer vector.

Source

Adapted from the [stringr](#) package.

str_detect	<i>Detect the presence or absence of a pattern in a string</i>
------------	--

Description

Dependency-free drop-in alternative for `stringr::str_detect()`.

Usage

```
str_detect(string, pattern, negate = FALSE)
```

Arguments

string	Input vector. Either a character vector, or something coercible to one.
pattern	Pattern to look for. The default interpretation is a regular expression, as described in base::regex . Control options with regex() . Match a fixed string (i.e. by comparing only bytes), using fixed() . This is fast, but approximate.
negate	If TRUE, return non-matching elements.

Value

A logical vector.

Source

Adapted from the [stringr](#) package.

str_dup	<i>Duplicate and concatenate strings within a character vector</i>
---------	--

Description

Dependency-free drop-in alternative for `stringr::str_dup()`.

Usage

```
str_dup(string, times)
```

Arguments

string	Input character vector.
times	Number of times to duplicate each string.

Value

A character vector.

Source

Adapted from the [stringr](#) package.

str_ends	<i>Detect the presence or absence of a pattern at the end of a string</i>
----------	---

Description

Dependency-free drop-in alternative for `stringr::str_ends()`.

Usage

```
str_ends(string, pattern, negate = FALSE)
```

Arguments

string	Input vector. Either a character vector, or something coercible to one.
pattern	<p>Pattern to look for.</p> <p>The default interpretation is a regular expression, as described in base::regex. Control options with regex().</p> <p>Match a fixed string (i.e. by comparing only bytes), using fixed(). This is fast, but approximate.</p>
negate	If TRUE, return non-matching elements.

Value

A logical vector.

Source

Adapted from the [stringr](#) package.

str_extract	<i>Extract matching patterns from a string</i>
-------------	--

Description

Dependency-free drop-in alternative for `stringr::str_extract()`.

Usage

```
str_extract(string, pattern)
```

Arguments

string	Input vector. Either a character vector, or something coercible to one.
pattern	Pattern to look for. The default interpretation is a regular expression, as described in base::regex . Control options with regex() . Match a fixed string (i.e. by comparing only bytes), using fixed() . This is fast, but approximate.

Value

A character matrix. The first column is the complete match, followed by one column for each capture group.

Source

Adapted from the [stringr](#) package.

str_extract_all *Extract matching patterns from a string*

Description

Dependency-free drop-in alternative for `stringr::str_extract_all()`.

Usage

```
str_extract_all(string, pattern, simplify = FALSE)
```

Arguments

string	Input vector. Either a character vector, or something coercible to one.
pattern	Pattern to look for. The default interpretation is a regular expression, as described in base::regex . Control options with regex() . Match a fixed string (i.e. by comparing only bytes), using fixed() . This is fast, but approximate.
simplify	If FALSE, the default, returns a list of character vectors. If TRUE returns a character matrix.

Value

A list of character vectors if `simplify = FALSE`, or a character matrix if `simplify = TRUE`.

Source

Adapted from the [stringr](#) package.

str_length *Compute the length of a string*

Description

Dependency-free drop-in alternative for `stringr::str_length()`.

Usage

```
str_length(string)
```

Arguments

string	Input vector. Either a character vector, or something coercible to one.
--------	---

Value

A numeric vector the same length as string.

Source

Adapted from the [stringr](#) package.

str_match	<i>Extract matched groups from a string</i>
-----------	---

Description

Dependency-free drop-in alternative for `stringr::str_match()`.

Usage

```
str_match(string, pattern)
```

Arguments

string	Input vector. Either a character vector, or something coercible to one.
pattern	Pattern to look for. The default interpretation is a regular expression, as described in base::regex . Control options with regex() . Match a fixed string (i.e. by comparing only bytes), using fixed() . This is fast, but approximate.

Value

A character matrix. The first column is the complete match, followed by one column for each capture group.

Source

Adapted from the [stringr](#) package.

`str_pad`*Duplicate and concatenate strings within a character vector*

Description

Dependency-free drop-in alternative for `stringr::str_pad()`.

Usage

```
str_pad(  
  string,  
  width,  
  side = c("left", "right", "both"),  
  pad = " ",  
  use_width = TRUE  
)
```

Arguments

<code>string</code>	Input vector. Either a character vector, or something coercible to one.
<code>width</code>	Minimum width of padded strings.
<code>side</code>	Side on which padding character is added (left, right or both).
<code>pad</code>	Single padding character (default is a space).
<code>use_width</code>	If FALSE, use the length of the string instead of the width; see str_width()/str_length() for the difference.

Value

A character vector.

Author(s)

Eli Pousson <eli.pousson@gmail.com> ([ORCID](#))

Alexander Rossell Hayes <alexander@rossellhayes.com> ([ORCID](#))

Source

Adapted from the [stringr](#) package.

str_remove	<i>Remove matched patterns in a string</i>
------------	--

Description

Dependency-free drop-in alternative for `stringr::str_remove()`.

Usage

```
str_remove(string, pattern)
```

Arguments

string	Input vector. Either a character vector, or something coercible to one.
pattern	Pattern to look for. The default interpretation is a regular expression, as described in base::regex . Control options with regex() . Match a fixed string (i.e. by comparing only bytes), using fixed() . This is fast, but approximate.

Value

A character vector.

Source

Adapted from the [stringr](#) package.

str_remove_all	<i>Remove matched patterns in a string</i>
----------------	--

Description

Dependency-free drop-in alternative for `stringr::str_remove_all()`.

Usage

```
str_remove_all(string, pattern)
```

Arguments

string	Input vector. Either a character vector, or something coercible to one.
pattern	Pattern to look for. The default interpretation is a regular expression, as described in base::regex . Control options with regex() . Match a fixed string (i.e. by comparing only bytes), using fixed() . This is fast, but approximate.

Value

A character vector.

Source

Adapted from the [stringr](#) package.

str_replace	<i>Replace matched patterns in a string</i>
-------------	---

Description

Dependency-free drop-in alternative for `stringr::str_replace()`.

Usage

```
str_replace(string, pattern, replacement)
```

Arguments

string	Input vector. Either a character vector, or something coercible to one.
pattern	Pattern to look for. The default interpretation is a regular expression, as described in base::regex . Control options with regex() . Match a fixed string (i.e. by comparing only bytes), using fixed() . This is fast, but approximate.
replacement	A character vector of replacements. Should be either length one, or the same length as <code>string</code> or <code>pattern</code> . References of the form <code>\1</code> , <code>\2</code> , etc. will be replaced with the contents of the respective matched group (created by <code>()</code>). To replace the complete string with NA, use <code>replacement = NA_character_</code> . Using a function for replacement is not yet supported.

Value

A character vector.

Source

Adapted from the [stringr](#) package.

str_replace_all	<i>Replace matched patterns in a string</i>
-----------------	---

Description

Dependency-free drop-in alternative for `stringr::str_replace_all()`.

Usage

```
str_replace_all(string, pattern, replacement)
```

Arguments

string	Input vector. Either a character vector, or something coercible to one.
pattern	Pattern to look for. The default interpretation is a regular expression, as described in base::regex . Control options with regex() . Match a fixed string (i.e. by comparing only bytes), using fixed() . This is fast, but approximate.
replacement	A character vector of replacements. Should be either length one, or the same length as <code>string</code> or <code>pattern</code> . References of the form <code>\1</code> , <code>\2</code> , etc. will be replaced with the contents of the respective matched group (created by <code>()</code>). To perform multiple replacements in each element of <code>string</code> , pass a named vector (<code>c(pattern1 = replacement1)</code>) to <code>str_replace_all()</code> . To replace the complete string with NA, use <code>replacement = NA_character_</code> . Using a function for replacement is not yet supported.

Value

A character vector.

Source

Adapted from the [stringr](#) package.

str_replace_na	<i>Turn NA into "NA"</i>
----------------	--------------------------

Description

Dependency-free drop-in alternative for `stringr::str_replace_na()`.

Usage

```
str_replace_na(string, replacement = "NA")
```

Arguments

string	Input vector. Either a character vector, or something coercible to one.
replacement	A single string.

Value

A character vector.

str_split	<i>Split up a string into pieces</i>
-----------	--------------------------------------

Description

Dependency-free drop-in alternative for `stringr::str_split()`.

Usage

```
str_split(string, pattern, n = Inf, simplify = FALSE)
```

Arguments

string	Input vector. Either a character vector, or something coercible to one.
pattern	Pattern to look for. The default interpretation is a regular expression, as described in base::regex . Control options with regex() . Match a fixed string (i.e. by comparing only bytes), using fixed() . This is fast, but approximate.
n	Maximum number of pieces to return. Default (Inf) uses all possible split positions. This determines the maximum length of each element of the output.
simplify	A boolean. <ul style="list-style-type: none"> FALSE (the default): returns a list of character vectors. TRUE: returns a character matrix.

Value

A list the same length as `string/pattern` containing character vectors, or if `simplify = FALSE`, a character matrix with `n` columns and the same number of rows as the length of `string/pattern`.

Author(s)

Eli Pousson <eli.pousson@gmail.com> ([ORCID](#))

Alexander Rossell Hayes <alexander@rossellhayes.com> ([ORCID](#))

Source

Adapted from the [stringr](#) package.

str_split_fixed	<i>Split up a string into pieces</i>
-----------------	--------------------------------------

Description

Dependency-free drop-in alternative for `stringr::str_split_fixed()`.

Usage

```
str_split_fixed(string, pattern, n)
```

Arguments

string	Input vector. Either a character vector, or something coercible to one.
pattern	Pattern to look for. The default interpretation is a regular expression, as described in base::regex . Control options with regex() . Match a fixed string (i.e. by comparing only bytes), using fixed() . This is fast, but approximate.
n	Maximum number of pieces to return. This determines the number of columns in the output; if an input is too short, the result will be padded with "".

Value

A character matrix with n columns and the same number of rows as the length of string/pattern.

Author(s)

Eli Pousson <eli.pousson@gmail.com> ([ORCID](#))

Alexander Rossell Hayes <alexander@rossellhayes.com> ([ORCID](#))

Source

Adapted from the [stringr](#) package.

str_squish	<i>Remove whitespace</i>
------------	--------------------------

Description

Dependency-free drop-in alternative for `stringr::str_squish()`.

Usage

```
str_squish(string)
```

Arguments

`string` Input vector. Either a character vector, or something coercible to one.

Value

A character vector the same length as `string`.

Source

Adapted from the [stringr](#) package.

str_starts	<i>Detect the presence or absence of a pattern at the beginning of a string</i>
------------	---

Description

Dependency-free drop-in alternative for `stringr::str_starts()`.

Usage

```
str_starts(string, pattern, negate = FALSE)
```

Arguments

`string` Input vector. Either a character vector, or something coercible to one.

`pattern` Pattern to look for.
 The default interpretation is a regular expression, as described in [base::regex](#).
 Control options with [regex\(\)](#).
 Match a fixed string (i.e. by comparing only bytes), using [fixed\(\)](#). This is fast,
 but approximate.

`negate` If TRUE, return non-matching elements.

Value

A logical vector.

str_subset	<i>Keep strings matching a pattern</i>
------------	--

Description

Dependency-free drop-in alternative for `stringr::str_subset()`.

Usage

```
str_subset(string, pattern, negate = FALSE)
```

Arguments

string	Input vector. Either a character vector, or something coercible to one.
pattern	Pattern to look for. The default interpretation is a regular expression, as described in base::regex . Control options with regex() . Match a fixed string (i.e. by comparing only bytes), using fixed() . This is fast, but approximate.
negate	If TRUE, return non-matching elements.

Value

A character vector.

Source

Adapted from the [stringr](#) package.

str_trim	<i>Remove whitespace</i>
----------	--------------------------

Description

Dependency-free drop-in alternative for `stringr::str_trim()`.

Usage

```
str_trim(string, side = c("both", "left", "right"))
```

Arguments

string	Input vector. Either a character vector, or something coercible to one.
side	Side on which to remove whitespace: "left", "right", or "both", the default.

Value

A character vector the same length as `string`.

Source

Adapted from the `stringr` package.

`str_which`*Find positions of strings matching a pattern*

Description

Dependency-free drop-in alternative for `stringr::str_which()`.

Usage

```
str_which(string, pattern, negate = FALSE)
```

Arguments

<code>string</code>	Input vector. Either a character vector, or something coercible to one.
<code>pattern</code>	Pattern to look for. The default interpretation is a regular expression, as described in base::regex . Control options with regex() . Match a fixed string (i.e. by comparing only bytes), using fixed() . This is fast, but approximate.
<code>negate</code>	If TRUE, return non-matching elements.

Value

An integer vector.

Source

Adapted from the `stringr` package.

str_width	<i>Compute the width of a string</i>
-----------	--------------------------------------

Description

Dependency-free drop-in alternative for `stringr::str_width()`. Results for non-ASCII characters may be inaccurate in R < 4.0.

Usage

```
str_width(string)
```

Arguments

`string` Input vector. Either a character vector, or something coercible to one.

Value

A numeric vector the same length as `string`.

Source

Adapted from the [stringr](#) package.

Index

`base::regex`, [5–9](#), [11–18](#)

`fixed`, [2](#)

`fixed()`, [5–9](#), [11–18](#)

`regex`, [3](#)

`regex()`, [5–9](#), [11–18](#)

`str_c`, [4](#)

`str_count`, [4](#)

`str_detect`, [5](#)

`str_dup`, [6](#)

`str_ends`, [6](#)

`str_extract`, [7](#)

`str_extract_all`, [8](#)

`str_length`, [8](#)

`str_length()`, [10](#)

`str_match`, [9](#)

`str_pad`, [10](#)

`str_remove`, [11](#)

`str_remove_all`, [11](#)

`str_replace`, [12](#)

`str_replace_all`, [13](#)

`str_replace_na`, [13](#)

`str_split`, [14](#)

`str_split_fixed`, [15](#)

`str_squish`, [16](#)

`str_starts`, [16](#)

`str_subset`, [17](#)

`str_trim`, [17](#)

`str_which`, [18](#)

`str_width`, [19](#)

`str_width()`, [10](#)