

Package ‘wildmeta’

February 2, 2022

Title Cluster Wild Bootstrapping for Meta-Analysis

Version 0.1.0

Maintainer Megha Joshi <megha.j456@gmail.com>

Description Conducts single coefficient tests and multiple-contrast hypothesis tests of meta-regression models using cluster wild bootstrapping, based on methods examined in Joshi, Pustejovsky, and Beretvas (2021) <[DOI:10.31222/osf.io/x6uhk](https://doi.org/10.31222/osf.io/x6uhk)>.

URL <https://meghapsimatrix.github.io/wildmeta/index.html>

BugReports <https://github.com/meghapsimatrix/wildmeta/issues>

License GPL-3

Encoding UTF-8

RoxygenNote 7.1.2

Imports clubSandwich (>= 0.5.4), sandwich, robumeta, metafor, stats

Suggests testthat (>= 3.0.0), knitr, rmarkdown, ggplot2, covr, mockery

VignetteBuilder knitr

Config/testthat/edition 3

NeedsCompilation no

Author Megha Joshi [aut, cre] (<<https://orcid.org/0000-0001-7936-076X>>),
James Pustejovsky [aut] (<<https://orcid.org/0000-0003-0591-9465>>),
Sangdon Lim [ctb] (<<https://orcid.org/0000-0002-2988-014X>>),
Pierce Cappelli [ctb]

Repository CRAN

Date/Publication 2022-02-02 08:30:05 UTC

R topics documented:

plot.Wald_test_wildmeta	2
run_cwb	3
Wald_test_cwb	4
Index	7

plot.Wald_test_wildmeta

Plot distribution of bootstrap test statistics

Description

Creates a density plot showing the distribution of bootstrap test statistics.

Usage

```
## S3 method for class 'Wald_test_wildmeta'  
plot(x, ...)
```

Arguments

x	Results from Wald_test_cwb function
...	Any other arguments to be passed to ggplot2::geom_density()

Value

A ggplot2 density plot.

Examples

```
data("SATcoaching", package = "clubSandwich")  
library(clubSandwich)  
library(robumeta)  
  
full_model <- robu(d ~ 0 + study_type + hrs + test,  
                 studynum = study,  
                 var.eff.size = V,  
                 small = FALSE,  
                 data = SATcoaching)  
  
res <- Wald_test_cwb(full_model = full_model,  
                   constraints = constrain_equal(1:3),  
                   R = 99)  
  
plot(res, fill = "darkred", alpha = 0.5)
```

run_cwb	<i>Calculate bootstrap outcomes or test statistics using cluster wild bootstrapping</i>
---------	---

Description

Calculate bootstrap outcomes or test statistics using cluster wild bootstrapping for meta-analytic models fit using `robumeta::robu()` and `metafor::rma.mv()`.

Usage

```
run_cwb(
  model,
  cluster,
  R,
  f = NULL,
  ...,
  auxiliary_dist = "Rademacher",
  adjust = "CR0",
  simplify = FALSE,
  seed = NULL
)
```

Arguments

model	Fitted <code>robumeta::robu()</code> or <code>metafor::rma.mv()</code> model. For cluster wild bootstrapping, a null model is recommended, with null model indicating a model containing all variables except the ones being tested.
cluster	Vector indicating which observations belong to the same cluster.
R	Number of bootstrap replications.
f	Optional function to be used to calculate bootstrap test statistics based on the bootstrapped outcomes. If <code>f</code> is <code>NULL</code> (the default), this function returns a list containing bootstrapped outcomes.
...	Optional arguments to be passed to the function specified in <code>f</code> .
auxiliary_dist	Character string indicating the auxiliary distribution to be used for cluster wild bootstrapping, with available options: "Rademacher", "Mammen", "Webb six", "uniform", "standard normal". The default is set to "Rademacher." We recommend the Rademacher distribution for models that have at least 10 clusters. For models with less than 10 clusters, we recommend the use of "Webb six" distribution.
adjust	Character string specifying which small-sample adjustment should be used to multiply the residuals by. The available options are "CR0", "CR1", "CR2", "CR3", or "CR4", with a default of "CR0".
simplify	Logical, with <code>TRUE</code> indicating the bootstrapped outcomes or F statistics will be simplified to a vector or matrix and <code>FALSE</code> (the default) indicating the results will be returned as a list.

seed Optional seed value to ensure reproducibility.

Value

A list or matrix containing either the bootstrapped outcomes or bootstrapped test statistics.

Examples

```
library(cluster)
library(robustbase)

model <- robu(d ~ 0 + study_type + hrs + test,
             studynum = study,
             var.eff.size = V,
             small = FALSE,
             data = SATcoaching)

bootstraps <- run_cwb(
  model = model,
  cluster = model$data.full$study,
  R = 12,
  adjust = "CR2",
  simplify = FALSE
)

bootstraps
```

Wald_test_cwb	<i>Calculate p-values with cluster wild bootstrapping for meta-regression models.</i>
---------------	---

Description

Calculate p-values for single coefficient and multiple contrast hypothesis tests using cluster wild bootstrapping.

Usage

```
Wald_test_cwb(
  full_model,
  constraints,
  R,
  cluster = NULL,
  auxiliary_dist = "Rademacher",
  adjust = "CR0",
  type = "CR0",
  test = "Naive-F",
```

```

    seed = NULL
  )

```

Arguments

<code>full_model</code>	Model fit using <code>robumeta::robu()</code> and <code>metafor::rma.mv()</code> that includes the full set of moderators in the meta-regression model.
<code>constraints</code>	A $q \times p$ constraint matrix to be tested. Alternately, a function to create such a matrix, specified using <code>clubSandwich::constrain_equal()</code> or <code>clubSandwich::constrain_zero()</code> .
<code>R</code>	Number of bootstrap replications.
<code>cluster</code>	Vector of identifiers indicating which observations belong to the same cluster. If NULL (the default), then the clustering variable will be inferred based on the structure of <code>full_mod</code> .
<code>auxiliary_dist</code>	Character string indicating the auxiliary distribution to be used for cluster wild bootstrapping, with available options: "Rademacher", "Mammen", "Webb six", "uniform", "standard normal". The default is set to "Rademacher." We recommend the Rademacher distribution for models that have at least 10 clusters. For models with less than 10 clusters, we recommend the use of "Webb six" distribution.
<code>adjust</code>	Character string specifying which small-sample adjustment should be used to multiply the residuals by. The available options are "CRO", "CR1", "CR2", "CR3", or "CR4", with a default of "CRO".
<code>type</code>	Character string specifying which small-sample adjustment is used to calculate the Wald test statistic. The available options are "CRO", "CR1", "CR2", "CR3", or "CR4", with a default of "CRO".
<code>test</code>	Character string specifying which (if any) small-sample adjustment is used in calculating the test statistic. Default is "Naive-F", which does not make any small-sample adjustment.
<code>seed</code>	Optional seed value to ensure reproducibility.

Value

A data frame containing the name of the test, the adjustment used for the bootstrap process, the type of variance-covariance matrix used, the type of test statistic, the number of bootstrap replicates, and the bootstrapped p-value.

Examples

```

library(clubSandwich)
library(robumeta)

model <- robu(d ~ 0 + study_type + hrs + test,
             studynum = study,
             var.eff.size = V,
             small = FALSE,
             data = SATcoaching)

C_mat <- constrain_equal(1:3, coefs = coef(model))

```

```
Wald_test_cwb(full_model = model,  
              constraints = C_mat,  
              R = 12)  
  
# Equivalent, using constrain_equal()  
Wald_test_cwb(full_model = model,  
              constraints = constrain_equal(1:3),  
              R = 12)
```

Index

`plot.Wald_test_wildmeta`, [2](#)

`run_cwb`, [3](#)

`Wald_test_cwb`, [4](#)